# INTERNATIONAL STANDARD

ISO 17246

Second edition 2010-06-15

### **Coal** — Proximate analysis

Charbon — Analyse immédiate

### iTeh STANDARD PREVIEW (standards.iteh.ai)



#### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 17246:2010 https://standards.iteh.ai/catalog/standards/sist/7d557ebc-d34d-42f9-bcde-04955b51db1a/iso-17246-2010



#### COPYRIGHT PROTECTED DOCUMENT

#### © ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17246 was prepared by Technical Committee ISO/TC 27, Solid mineral fuels, Subcommittee SC 5, Methods of analysis.

This second edition cancels and replaces the first edition (ISO 17246:2005), of which it constitutes a minor revision. (It also incorporates the Technical corrigendum ISO 17246:2005/Cor.1:2006.)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

### **Coal** — Proximate analysis

#### 1 Scope

This International Standard establishes a practice for the proximate analysis of coal and is intended for general utilization by the coal industry to provide a basis for comparison of coals.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 562, Hard coal and coke — Determination of volatile matter

ISO 589, Hard coal — Determination of total moisture D PREVIEW

ISO 1171, Solid mineral fuels — Determination of ash.iteh.ai)

ISO 1213-2, Solid mineral fuels — Vocabulary — Part 2: Terms relating to sampling, testing and analysis ISO 17246:2010

ISO 11722, Solid mineral fuels and the by drying in nitrogen 04955b51db1a/iso-17246-2010

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1213-2 apply.

#### 4 Principle

Coal is analysed for content of moisture, ash and volatile matter. The fixed carbon is calculated and the results are reported, to the preferred basis, as a proximate analysis.

#### 5 Preparation of sample

Prepare the sample in accordance with the requirements of the various test methods given in Table 1.

#### 6 Test methods

Carry out the determination in accordance with the test methods specified in Table 1.

Table 1 —Standard test methods for proximate analysis

Parameter	Test method
Total moisture (if an "as received" reporting basis is required)	ISO 589
Moisture in air-dried sample	ISO 11722
Ash	ISO 1171
Volatile matter	ISO 562

#### 7 Expression of results

The fixed carbon,  $C_{\text{fix,ad}}$ , calculated to air-dried basis and expressed as a percentage mass fraction, is given by Equation (1):

$$C_{\text{fix,ad}} = 100 - (M_{\text{ad}} + A_{\text{ad}} + V_{\text{ad}})$$
 (1)

where

### iTeh STANDARD PREVIEW

 $M_{\mathrm{ad}}$  is the moisture in the air-dried sample, expressed as a percentage mass fraction;

A<sub>ad</sub> is the ash, calculated to an air-dried basis and expressed as a percentage mass fraction; https://standards.iteh.ai/catalog/standards/sist/7d557ebc-d34d-42f9-bcde-

V<sub>ad</sub> is the volatile matter, calculated to an air-dried basis and expressed as a percentage mass fraction.

The result is reported to the nearest 0,1 % mass fraction.

The fixed carbon may also be calculated to other bases using the equations in Table 2.

Table 2 — Equations for calculating the results to different bases

	Basis of value wanted			
Basis of value given	<b>As received</b> <sup>a</sup> (ar)	<b>Air-dried</b> (ad)	<b>Dry</b> <sup>a</sup> (d)	
Parameter, P (moisture, ash or volatiles)	$P_{\rm ar} = P_{\rm ad} \times \frac{100 - M_{\rm ar}}{100 - M_{\rm ad}}$	_	$P_{\rm d} = P_{\rm ad} \times \frac{100}{100 - M_{\rm ad}}$	
a Where <i>M</i> is the moisture content.				

For further calculations, see ISO 1170.

See Annex A for an example of proximate data reported to different bases.

#### 8 Test report

The test report shall include the following information:

- a) reference to this International Standard, i.e. ISO 17246;
- b) identification of the sample tested;
- c) method or methods used;
- d) results and basis of reporting.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 17246:2010 https://standards.iteh.ai/catalog/standards/sist/7d557ebc-d34d-42f9-bcde-04955b51db1a/iso-17246-2010

© ISO 2010 – All rights reserved

### Annex A

(informative)

### Example of a proximate analysis

Parameter	As received (ar)	Air dried (ad)	<b>Dry</b> (d)
	% mass fraction	% mass fraction	% mass fraction
Total moisture, $M_{\rm ar}$	8,0	_	_
Moisture in air-dried sample, $M_{ad}$	_	3,0	_
Ash, A	9,5	10,0	10,3
Volatile matter, $V$	19,0	20,0	20,6
Fixed carbon, $C_{\rm fix}$	63,5	67,0	69,1
Total	100,0	100,0	100,0

# iTeh STANDARD PREVIEW (standards.iteh.ai)

### **Bibliography**

[1] ISO 1170, Coal and coke — Calculation of analyses to different bases

# iTeh STANDARD PREVIEW (standards.iteh.ai)