



SLOVENSKI STANDARD

SIST ISO 16258-1:2018

01-marec-2018

Zrak na delovnem mestu - Analiza respirabilnega kristaliničnega kremena z uklonom rentgenskih žarkov - 1. del: Neposredna metoda na filtru

Workplace air - Analysis of respirable crystalline silica by X-ray diffraction - Part 1: Direct-on-filter method

iTeh STANDARD PREVIEW

Air des lieux de travail - Fraction alvéolaire de la silice cristalline par diffraction de rayons X - Partie 1: Méthode directe d'analyse sur filtre

[SIST ISO 16258-1:2018](https://standards.iteh.ai/catalog/standards/sist/0f384b55-af68-47c4-9f05-918c111fd198/sist-iso-16258-1-2018)

Ta slovenski standard je istoveten z: ISO 16258-1:2015

ICS:

13.040.30 Kakovost zraka na delovnem mestu Workplace atmospheres

SIST ISO 16258-1:2018

en,fr

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 16258-1:2018

<https://standards.iteh.ai/catalog/standards/sist/0f384fb5-af68-47c4-9f05-9f8e1111d198/sist-iso-16258-1-2018>

INTERNATIONAL STANDARD

ISO
16258-1

First edition
2015-09-15

Workplace air — Analysis of respirable crystalline silica by X-ray diffraction —

Part 1: Direct-on-filter method

iTeh STANDARD PREVIEW
(standards.iteh.ai)
*Air des lieux de travail — Fraction alvéolaire de la silice cristalline
par diffraction de rayons X —
Partie 1: Méthode directe d'analyse sur filtre*

SIST ISO 16258-1:2018

<https://standards.iteh.ai/catalog/standards/sist/0f384fb5-af68-47c4-9f05-9f8e1111d198/sist-iso-16258-1-2018>



Reference number
ISO 16258-1:2015(E)

© ISO 2015

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 16258-1:2018

<https://standards.iteh.ai/catalog/standards/sist/0f384fb5-af68-47c4-9f05-9f8e1111d198/sist-iso-16258-1-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 General definitions	1
3.2 Sampling definitions	2
3.3 Analytical definitions	3
3.4 Statistical terms	4
4 Principle	5
5 Sampling	5
5.1 Sampling equipment	6
5.1.1 Samplers	6
5.1.2 Filters	6
5.1.3 Sampling pumps	7
5.1.4 Flow meters	7
5.1.5 Other equipment required	7
5.2 Sample collection	8
5.3 Transport	9
6 Analytical procedure	9
6.1 Apparatus and equipment	9
6.1.1 X-ray diffraction system	9
6.1.2 Balance	9
6.1.3 Dust cloud generator	9
6.1.4 Standard reference materials	10
6.1.5 Reagents	10
6.1.6 Drift correction sample	11
6.2 Gravimetric analysis for respirable dust	11
6.3 X-ray diffraction analysis	11
6.3.1 Instrumental parameters	11
6.3.2 Scan parameters	11
6.4 Calibration curve	11
6.5 Sample treatment	13
6.6 Sample analysis	13
7 Calculation	13
7.1 Gravimetric analysis	13
7.2 X-ray diffraction analysis	13
7.3 Concentration of RCS	14
8 Performance characteristics	15
8.1 Limit of detection	15
8.2 Minimum detectable value	15
8.3 Limits of quantification	15
8.4 Uncertainty	15
8.5 Differences between samplers	16
8.6 Differences between analytical approaches	16
9 Test report	16
Annex A (informative) Example instrumental conditions	18
Annex B (informative) Data collection parameters	19
Annex C (normative) Corrections for absorption	20

ISO 16258-1:2015(E)

Annex D (informative) Range of typical detection limits	22
Annex E (informative) Typical expanded uncertainty for the direct-on-filter method	23
Annex F (informative) Differences between samplers	24
Bibliography	25

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 16258-1:2018](https://standards.iteh.ai/catalog/standards/sist/0f384fb5-af68-47c4-9f05-9f8e1111d198/sist-iso-16258-1-2018)

<https://standards.iteh.ai/catalog/standards/sist/0f384fb5-af68-47c4-9f05-9f8e1111d198/sist-iso-16258-1-2018>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 146, *Air quality*, Subcommittee SC 2, *Workplace atmospheres*.

ISO 16258 consists of the following parts, under the general title *Workplace air — Analysis of respirable crystalline silica by X-ray diffraction*:

- *Part 1: Direct-on-filter method*
- *Part 2: Method by indirect analysis*

ISO 16258-1:2015(E)**Introduction**

Respirable crystalline silica (RCS) is a hazard to the health of workers in many industries through exposure by inhalation. Industrial hygienists and other public health professionals need to determine the effectiveness of measures taken to control workers' exposure. The collection of samples of air during a work activity and then measuring the amount of respirable crystalline silica are often done to assess an individual's exposure, the effectiveness of controls or their respiratory protection. X-ray diffraction (XRD) analysis of crystalline silica in a sample of respirable dust collected on a filter is the principle technique employed in many countries to measure and estimate exposure to RCS. X-ray diffraction is able to clearly distinguish the polymorphs of crystalline silica.

This part of ISO 16258 specifies the procedure for a method of analysing RCS directly on the air sample filter. A specific requirement of this method is that the filter from the sampling apparatus has a diameter of 25 mm. The method also discusses optimum instrumental parameters, for various types of detectors in common use at the time of publication. This part of ISO 16258 is to be used in conjunction with ISO 24095 which promotes best practice for these analyses.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 16258-1:2018](https://standards.iteh.ai/catalog/standards/sist/0f384fb5-af68-47c4-9f05-9f8e1111d198/sist-iso-16258-1-2018)

<https://standards.iteh.ai/catalog/standards/sist/0f384fb5-af68-47c4-9f05-9f8e1111d198/sist-iso-16258-1-2018>

Workplace air — Analysis of respirable crystalline silica by X-ray diffraction —

Part 1: Direct-on-filter method

1 Scope

This part of ISO 16258 specifies the analysis of respirable crystalline silica (RCS) in samples of air collected on 25 mm-filters by X-ray diffraction, when using an analytical approach where the dust on the air sample filter is directly analysed by the instrument. This part of ISO 16258 includes information on the instrumental parameters, sensitivity of different sampling apparatus, uses of different filters and correction for absorption effects. In this part of ISO 16258, the expression RCS includes the most common polymorphs quartz and cristobalite. The less common polymorphs of crystalline silica, such as tridymite, are not included within the scope of this part of ISO 16258 because a standard reference material is not available. Under certain circumstances (i.e. low filter dust loads, low silica content), the analytical approach described in this method may not fulfil the expanded uncertainty requirements of EN 482. [5] Guidance for calculation of uncertainty for measurements of RCS is given in ISO 24095.

iTeh STANDARD PREVIEW

2 Normative references (standards.iteh.ai)

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies

ISO 7708, *Air quality — Particle size fraction definitions for health-related sampling*

ISO 13137, *Workplace atmospheres — Pumps for personal sampling of chemical and biological agents — Requirements and test methods*

ISO 15767, *Workplace atmospheres — Controlling and characterizing uncertainty in weighing collected aerosols*

ISO 24095, *Workplace air — Guidance for the measurement of respirable crystalline silica*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 General definitions

3.1.1

airborne particles

fine matter, in solid or liquid form, dispersed in air

[SOURCE: EN 1540]

Note 1 to entry: Smoke, fume, mist and fog consist of airborne particles.

ISO 16258-1:2015(E)**3.1.2****aerosol**

airborne particles and the gas (and vapour) mixture in which they are suspended

[SOURCE: EN 1540]

Note 1 to entry: The airborne particles can be in or out of equilibrium with their own vapours.

3.1.3**respirable crystalline silica****RCS**

particles of crystalline silica that penetrate into the unciliated airways according to the respirable convention described in ISO 7708

3.1.4**exposure (by inhalation)**

situation in which a chemical agent is present in air that is inhaled by a person

[SOURCE: EN 1540]

3.1.5**occupational exposure limit value****OELV**

limit of the time-weighted average of the concentration of a chemical agent in the air within the breathing zone of a worker in relation to a specified reference period

[SOURCE: EN 1540]

iTeh STANDARD PREVIEW

(standards.iteh.ai)

Note 1 to entry: Limit values are mostly set for reference periods of 8 h, but can also be set for shorter periods or concentration excursions. Limit values for airborne particles and mixtures of particles and vapours are given in mg/m³ or multiples of that for actual environmental conditions (temperature, pressure) at the workplace.

SIST ISO 16258-1:2018

<https://standards.iteh.ai/catalog/standards/sist/0f384fb5-af68-47c4-9f05-9f8e1111d198/sist-iso-16258-1-2018>

3.1.6**workplace**

designated area or areas in which the work activities are carried out

[SOURCE: EN 1540]

3.2 Sampling definitions**3.2.1****aerosol sampler**

(airborne) particle sampler

(airborne) particulate sampler

sampler that is used to transport airborne particles to a collection substrate

[SOURCE: EN 1540]

3.2.2**collection substrate**

sampling substrate

collection medium

sampling medium

medium on which airborne chemical and/or biological agents are collected for subsequent analysis

[SOURCE: EN 1540]

Note 1 to entry: Filters, polyurethane foams and sampling cassettes are examples of collection substrates for airborne particles.

Note 2 to entry: For the purpose of this part of ISO 16258, the collection substrate is a filter.

3.2.3**laboratory blank**

unused collection substrate, taken from the same batch used for sampling, that does not leave the laboratory

[SOURCE: EN 1540]

Note 1 to entry: The results from the analysis of laboratory blanks are used to correct sample results for contamination with crystalline silica and/or interferences.

3.2.4**field blank**

unused collection substrate, taken from the same batch used for sampling, handled in the same way as a collection substrate that is used for sampling, except it is not used for collecting a sample

[SOURCE: EN 1540]

Note 1 to entry: A field blank is transported to the sampling site, loaded in the sampler, where applicable, and returned to the laboratory in the same way as a sample.

Note 2 to entry: The results from the analysis of field blanks are used to identify contamination of the sample arising from handling in the field and during transport.

3.2.5**breathing zone**

space around the nose and mouth from which a worker's breath is taken

[SOURCE: EN 1540]

Note 1 to entry: Technically the breathing zone corresponds to a hemisphere (generally accepted to be 30 cm in radius) extending in front of the human face, centred on the midpoint of a line joining the ears. The base of the hemisphere is a plane through this line, the top of the head and the larynx. This technical description is not applicable when respiratory protective equipment is used.

3.2.6**personal sampler**

sampler, attached to a person, that collects gases, vapours or airborne particles in the breathing zone to determine exposure to chemical and/or biological agents

[SOURCE: EN 1540]

3.2.7**personal sampling**

process of sampling carried out using a personal sampler

[SOURCE: EN 1540]

3.2.8**sampling train**

apparatus for collecting airborne particles including sampling equipment, pump and connecting tubing.

[SOURCE: ISO 24095]

3.3 Analytical definitions**3.3.1****limit of detection****LOD**

lowest amount of an analyte that is detectable with a given level of confidence

Note 1 to entry: The limit of detection can be calculated as three times the standard deviation of blank measurements. This represents a probability of 50 % that the analyte will not be detected when it is present at the concentration of the LOD.

ISO 16258-1:2015(E)

Note 2 to entry: The LOD can be used as a threshold value to assert the presence of a substance with a known confidence.

Note 3 to entry: Many analysis procedures require laboratories to calculate an LOD by multiplying the standard deviation of measurements of a number of blank samples (~10) by three. Readers should note that there is some doubt about the relationship between signal and the mass when RCS is measured at very low masses and a specific formula to determine the LOD using statistics based on a normal distribution is not given in this guidance. The test samples used for calibration are not matrix matched and reporting an LOD based on three standard deviations of the background noise may give an optimistic impression of the capability of method when analysing 'real' samples. Analysts should take this into consideration when analysing samples for RCS (ISO 24095).

3.3.2

limit of quantification

LOQ

lowest reliable mass of an analyte that is quantifiable with a given level of confidence taking into consideration the matrix effects in the sample

[SOURCE: EN 1540]

Note 1 to entry: The limit of quantification can be calculated as 10 times the standard deviation of blank measurements.

Note 2 to entry: The value LOQ can be used as a threshold value to ensure measurement of a substance accurately.

Note 3 to entry: With LOQ determined from an evaluation experiment based on 10 degrees of freedom, an estimate of an amount at the threshold value LOQ has probability equal to 95 % of falling inside an interval defined as ± 31 % about the true value, with 95 % confidence in the evaluation.

3.4 Statistical terms

(standards.iteh.ai)

3.4.1

accuracy

closeness of agreement between a test result and the accepted reference value

[SOURCE: ISO 3534]

3.4.2

analytical recovery

ratio of the mass of analyte measured when a sample is analysed to the known mass of analyte in that sample

[SOURCE: ISO 24095]

3.4.3

method recovery

ratio of the determined concentration of chemical agent in air to its actual concentration

[SOURCE: EN 1540]

Note 1 to entry: The method recovery incorporates both sampling efficiency and analytical recovery.

3.4.4

bias

difference between the expectation of a test result or measurement result and a true value.

[SOURCE: ISO 6879]

Note 1 to entry: Bias is the total systematic error as contrasted to random error. There may be one or more systematic error components contributing to the bias. A larger systematic difference from the true value is reflected by a larger bias value.