



TECHNICAL SPECIFICATION

**Intelligent Transport Systems (ITS);
Vehicular Communications;
Basic Set of Applications;
Facilities layer protocols and communication requirements
for infrastructure services**

PREVIEW
https://standards.iteh.ai/en/standards/etsi/ts/103/301/v1.3.1/2020-02-4ccf-4b77-91dd-6d5613931c22/

Reference

RTS/ITS-00181

Keywords

application, data, ITS, protocol, requirements

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
Introduction	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	7
3 Definition of terms, symbols and abbreviations.....	8
3.1 Terms.....	8
3.2 Symbols.....	8
3.3 Abbreviations	8
4 Infrastructure services introduction and general requirements.....	10
4.1 Naming convention	10
4.2 Infrastructure services in the ITS communications architecture.....	10
4.3 Infrastructure services in the ITS organizational architecture	11
4.4 Interfaces of the infrastructure services	12
4.4.1 Interface between Application layer and Facilities layer.....	12
4.4.2 Interface between Facilities layer and Management entity.....	12
4.4.3 Interface between Facilities layer and Security entity	12
4.4.4 Interface between Facilities layer and the N&T layer.....	13
4.5 Common protocol requirements for infrastructure services	13
4.5.1 Security for messages used by infrastructure	13
4.5.2 Message payload encapsulation.....	13
4.5.3 Message encoding scheme.....	14
4.6 Protocol version.....	14
4.6.1 Protocol version definition.....	14
4.6.2 Protocol version handling	14
5 Traffic Light Maneuver (TLM) service.....	15
5.1 TLM service overview	15
5.2 TLM service	15
5.3 TLM service message and version	15
5.4 TLM service dissemination	16
5.4.1 TLM service identification	16
5.4.2 TLM service trigger, update, repetition and termination	16
5.4.3 TLM service communication requirements	16
5.4.3.1 TLM service communication overview	16
5.4.3.2 TLM service communication requirements for short range access technologies	16
5.4.3.3 TLM service communication requirements for long range communication	18
6 Road and Lane Topology (RLT) service.....	19
6.1 RLT service overview	19
6.2 RLT service	19
6.3 RLT service message and version	20
6.4 RLT service dissemination	20
6.4.1 RLT service identification	20
6.4.2 RLT service trigger, update, repetition and termination	20
6.4.3 RLT service communication requirements	20
6.4.3.1 RLT service communication overview	20
6.4.3.2 RLT service communication requirements for short range access technologies	20
6.4.3.3 RLT service dissemination parameters for long range communication	22
7 Infrastructure to Vehicle Information (IVI) service	22
7.1 IVI service overview	22

7.2	IVI service	23
7.3	IVI service message and version	23
7.4	IVI service dissemination	23
7.4.1	IVI service identification	23
7.4.2	IVI service trigger, update, repetition and termination	23
7.4.3	IVI service communication requirements	24
7.4.3.1	IVI service communication parameters for short-range communication	24
7.4.3.2	IVI service dissemination parameters for long-range communication	27
8	Traffic Light Control (TLC) service	27
8.1	TLC service overview	27
8.2	TLC service	28
8.3	TLC service message and version	28
8.4	TLC service dissemination	29
8.4.1	TLC service identification	29
8.4.2	TLC service trigger, update, repetition and termination	29
8.4.3	TLC service communication parameters	29
8.4.3.1	TLC service communication overview	29
8.4.3.2	TLC service communication parameters for short range access technologies	29
8.4.3.3	TLC service communication parameters for long range communication	32
9	GNSS positioning correction (GPC) service	33
9.1	GPC service overview	33
9.2	GPC service	33
9.3	GPC service message and version	33
9.4	GPC service dissemination	33
9.4.1	GPC service identification	33
9.4.2	GPC service trigger, update, repetition and termination	33
9.4.3	GPC service communication requirements	33
9.4.3.1	GPC service communication overview	33
9.4.3.2	GPC service communication requirements for short range access technologies	33
9.4.3.3	GPC service dissemination parameters for long range communication	35
10	Basic services running on ITS infrastructure devices	35
10.1	Basic service overview	35
10.2	DEN service on ITS infrastructure devices	36
10.3	CA service on ITS infrastructure devices	36
11	Communication Profiles	36
11.1	Introduction	36
11.2	Basic communication profile settings	36
11.3	CPS_001	37
11.4	CPS_002	37
11.5	CPS_003	38
11.6	CPS_004	38
11.7	CPS_005	39
12	Security Profile	39
Annex A (informative):	ASN.1 specification of SPATEM	40
Annex B (informative):	ASN.1 specification of MAPEM	41
Annex C (informative):	ASN.1 specification of IVIM	42
Annex D (informative):	ASN.1 specification of SREM	43
Annex E (informative):	ASN.1 specification of SSEM	44
Annex F (informative):	ASN.1 specification of RTCMEM	45
History		46

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Intelligent Transport Systems (ITS).

The present document includes the integration of infrastructure based application protocols within the ITS message environment.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The infrastructure services are application support facilities provided by the Facilities layer that construct, manage and process messages distributed from infrastructure to end-users or vice-versa based on payload received from the application. The infrastructure services specified in the present document support infrastructure-based applications in order to achieve communication interoperability, and may be implemented in parallel to other services in an ITS-S.

1 Scope

The present document provides specifications of infrastructure related ITS services to support communication between infrastructure ITS equipment and traffic participants using ITS equipment (e.g. vehicles, pedestrians). It defines services in the Facilities layer for communication between the infrastructure and traffic participants. The specifications cover the protocol handling for infrastructure-related messages as well as requirements to lower layer protocols and to the security entity.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 302 665 (V1.1.1): "Intelligent Transport Systems (ITS); Communications Architecture".
- [2] ETSI TS 102 894-2 (V1.3.1): "Intelligent Transport Systems (ITS); Users and applications requirements; Part 2: Applications and facilities layer common data dictionary".
- [3] ETSI EN 302 636-4-1 (V1.4.1): "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 4: Geographical addressing and forwarding for point-to-point and point-to-multipoint communications; Sub-part 1: Media-Independent Functionality".
- [4] ETSI EN 302 636-5-1 (V2.2.1): "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 5: Transport Protocols; Sub-part 1: Basic Transport Protocol".
- [5] Void.
- [6] ETSI TS 103 097 (V1.3.1): "Intelligent Transport Systems (ITS); Security; Security header and certificate formats".
- [7] CEN ISO/TS 19321-2015: "Intelligent transport systems - Cooperative ITS - Dictionary of in-vehicle information (IVI) data structures".
- [8] CEN ISO/TS 19091: "Intelligent transport systems - Cooperative ITS - Using V2I and I2V communications for applications related to signalized intersections".
- [9] ETSI EN 302 931 (V1.1.1): "Intelligent Transport Systems (ITS); Vehicular Communications; Geographical Area Definition".
- [10] ISO/TS 17427:2014: "Intelligent transport systems - Cooperative systems - Roles and responsibilities in the context of cooperative ITS based on architecture(s) for cooperative systems".
- [11] Recommendation ITU-T X.691/ISO/IEC 8825-2 (1997-12): "Information technology - ASN.1 encoding rules: Specification of Packed Encoding Rules (PER)".
- [12] ETSI EN 302 637-2: "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 2: Specification of Cooperative Awareness Basic Service".

- [13] ETSI EN 302 637-3: "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 3: Specifications of Decentralized Environmental Notification Basic Service".
- [14] ETSI TS 102 965: "Intelligent Transport Systems (ITS); Application Object Identifier (ITS-AID); Registration".
- [15] ETSI TS 103 248 (V1.3.1): "Intelligent Transport Systems (ITS); GeoNetworking; Port Numbers for the Basic Transport Protocol (BTP)".
- [16] ETSI EN 302 663: "Intelligent Transport Systems (ITS); ITS-G5 Access layer specification for Intelligent Transport Systems operating in the 5 GHz frequency band".
- [17] ETSI TS 136 300: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2 (3GPP TS 36.300 version 14.2.0 Release 14)".
- [18] ETSI TS 102 636-4-2: "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 4: Geographical addressing and forwarding for point-to-point and point-to-multipoint communications; Sub-part 2: Media-dependent functionalities for ITS-G5".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Void.
- [i.2] ISO/TS 17423:2014: "Intelligent Transport Systems - Cooperative Systems - Application requirements for selection of communication profiles".
- [i.3] ISO/TS 14823: "Traffic and travel information - Messages via media independent stationary dissemination systems - Graphic data dictionary for pre-trip and in-trip information dissemination systems".
- [i.4] IEEE 802.11TM-2012: "IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks-Specific requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".
- [i.5] ETSI TS 102 723-5 (V1.1.1): "Intelligent Transport Systems (ITS); OSI cross-layer topics; Part 5: Interface between management entity and facilities layer".
- [i.6] IANA Service Name and Transport Protocol Port Number Registry (2016-04-07).

NOTE: Available at <https://www.iana.org/assignments/service-names-port-numbers/service-names-port-numbers.txt>.

- [i.7] IETF RFC 791: "IETF Internet Protocol".
- [i.8] IETF RFC 768: "IETF User Datagram Protocol".
- [i.9] IETF RFC 793: "IETF Transmission Control Protocol".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

destination area: geographic area in which a message is disseminated

NOTE: The definition is compliant to ETSI EN 302 637-3 [13].

driver awareness zone: area in which the driver will be informed about upcoming situations

NOTE: The definition is compliant to CEN ISO/TS 19321 [7].

ITS-G5: access technology to be according to ETSI EN 302 663 [16]

long range: communication with coverage of more than 500 m (e.g. cellular systems)

LTE-V2X sidelink: access technology using V2X sidelink communication according to ETSI TS 136 300 [17]

MAPEM: road/lane topology and traffic maneuver message

NOTE: As defined in Annex B including the corresponding extensions defined in CEN ISO/TS 19091 [8].

minimum dissemination area: minimum area where an information is disseminated by an ITS-S based on application requirements

NOTE: The definition is compliant to CEN ISO/TS 19321 [7].

relevance zone: area where the information is applicable

NOTE: The definition is compliant to CEN ISO/TS 19321 [7].

short range: communication with coverage of approximately 500 m (e.g. WLAN)

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

3GPP	3 rd Generation Partnership Project
AC	Access Category
AC_BE	Access Category Best Effort
AC_BK	Access Category BacKground
AC_VI	Access Category Video
AC_VO	Access Category VOice
ADU	Application Data Unit
AID	Action IDentifier
ASN	Abstract Syntax Notation
BTP	Basic Transport Protocol
CA	Certification Authority
C-ITS	Cooperative ITS
C-ITS-S	Cooperative ITS-Station
DAZ	Driver Awareness Zone
DE	Data Element
DEN	Decentralized Environmental Notification
DENM	DEN Message
E-UTRA	Evolved UTRA

GBC	GeoBroadCast
GN	GeoNetworking
GNSS	Global Navigation Satellite System
GPC	GNSS Positioning Correction
GPCH	General Purpose Channel
IANA	Internet Assigned Numbers Authority
IP	Internet Protocol
ISM	Industrial, Scientific and Medical
ITIS	International Traveller Information Systems
ITS	Intelligent Transport System
ITS-AID	ITS-Application IDentifier
ITS-S	ITS Station
ITU-T	International Telecommunication Union - Telecommunication
IVI	Infrastructure to Vehicle Information
IVIM	Infrastructure to Vehicle Information Message
LTE	Long Term Evolution
LTE-V2X	LTE-Vehicle to Everything
MAPEM	MAP (topology) Extended Message
MDA	Minimum Dissemination Area
MF-SAP	Management Facilities layer SAP
MSB	Most Significant Bit
MTU	Maximum Transmit Unit
PDU	Protocol Data Unit
PER	Packet Encoding Rule
R-ITS-S	Roadside ITS Station
RLT	Road and Lane Topology
RTCM	Radio Technical Commission for Maritime services
RTCMEM	RTCM Extended Message
RTK	Real Time Kinematic
RZ	Relevance Zone
SAP	Service Access Primitive
SCH	Service CHannel
SFCH	SaFety CHannel
SHB	Single Hop Broadcast
SPATEM	Signal Phase And Timing Extended Message
SREM	Signal Request Extended Message
SSEM	Signal request Status Extended Message
SSID	Service Set Identifier
SSP	Service Specific Permissions
TC ID	Traffic Class IDentity
TC	Traffic Class
TCC	Traffic Control Center
TCC	Traffic Control Centre
TCP	Transmission Control Protocol
TCP-IP	Transport Control Protocol - Internet Protocol
TLC	Traffic Light Control
TLM	Traffic Light Maneuver
TS	Technical Specification
UDP	User Datagram Protocol
UTRA	Universal Terrestrial Radio Access
UTRAN	UMTS Terrestrial Radio Access Network
V2X	Vehicle-to-Everything
V-ITS-S	Vehicular and personal ITS Station
WLAN	Wireless Local Area Network

4 Infrastructure services introduction and general requirements

4.1 Naming convention

Within the scope of the present document, the term "message" refers to the Facilities layer PDU; the term "payload" refers to the applications layer ADU. The payload is generated by the application and provided to the corresponding service of the Facilities layer. The Facilities service merges the *ItsPduHeader* with the payload, in order to construct a message. The message is then delivered to the ITS Networking & Transport Layer with a set of communication parameters.

NOTE: In other standards referred by the present document, the term message, payload, data structure may have different meanings e.g. in CEN ISO/TS 19091 [8] and in CEN ISO/TS 19321 [7]. Therefore, the current convention is defined for clarification purposes.

4.2 Infrastructure services in the ITS communications architecture

The infrastructure services refer to Facilities layer entities that manage the generation, transmission and reception of infrastructure-related messages from the infrastructure (C-ITS-S or R-ITS-S) to V-ITS-S or vice-versa. Figure 1 illustrates a high level functional architecture of the infrastructure services within the ITS communication architecture, as specified in ETSI EN 302 665 [1]. The messages are Facilities layer PDUs that are exchanged among ITS-Ss. The payload is generated by ITS applications in the transmitting ITS-S or other connected ITS-S (e.g. a C-ITS-S). At the transmitting ITS-S, the transmission of a message is triggered by applications or by forwarding mechanisms. For this purpose, the applications may connect to other entities of the Facilities layer or to external entities, in order to collect relevant information for the generation of the payload. Once the message is generated, the services may repeat the transmission, until the applications requests the termination of the transmission, or trigger another request to generate updated messages. At the receiving ITS-S, the messages are processed by the services and the content of the message is delivered to applications or to other Facilities layer entity. In one typical application, the message is transmitted by an R-ITS-S and disseminated to V-ITS-S within a target destination area, in which the information included in the message is considered as relevant to traffic participants.

In the scope of the present document, the infrastructure services supports the management of the following message types. As result, the infrastructure services include a set of service entities as listed below:

- SPATEM as defined in Annex A. The corresponding service entity is referred as "Traffic Light Maneuver" - TLM service in the present document. TLM service is specified in clause 5 of the present document.
- MAPEM as defined in Annex B. The corresponding service entity is referred as "Road and Lane Topology" - RLT service in the present document. RLT service is specified in clause 6 of the present document.
- IVIM as defined in Annex C. The corresponding service entity is referred as "Infrastructure to Vehicle Information" - IVI service in the present document. IVI service is specified in clause 7 of the present document.
- SREM as specified in Annex D. The corresponding service entity is referred as "Traffic Light Control" - TLC service in the present document. TLC service is specified in clause 8 of the present document.
- SSEM as specified in Annex E. The corresponding service is referred as "Traffic Light Control" - TLC service in the present document. TLC service is specified in clause 8 of the present document.

NOTE: Other messages may be supported by infrastructure services in the future.




Figure 1: Infrastructure services within the ITS-S architecture

The infrastructure service shall provide at least the following functions.

For the transmission service:

- Message encoding.
- Transmission management.

For the reception service:

- Message decoding.
- Reception management.

4.3 Infrastructure services in the ITS organizational architecture

Within the role "System Operation" as defined in ISO/TS 17427 [10], the following sub roles are relevant for the infrastructure services:

- "Content Provision" is responsible for generating the information that is conveyed in the message. This task is included in any application providing information to the application which generates the payload.
- "Service Provision" is responsible for the generation of the payload and the transmission of the message using an ITS-S. This task is managed by the application making use of the infrastructure services.
- "Service Presentation" is responsible for the reception of the messages and its processing and presentation. This task is managed by the infrastructure services and the application.




Figure 2: Identification of sub-roles of the role system (lifecycle) operation in the ITS organizational architecture

4.4 Interfaces of the infrastructure services

4.4.1 Interface between Application layer and Facilities layer

The infrastructure services within the Facilities layer provide APIs to applications for the processing of the payload at the transmitting ITS-S and the receiving ITS-S. An application may execute requests to the infrastructure services in the Facilities layer to trigger, update or terminate transmission of a message. In addition, a set of Facilities control information is passed as specified in Table 1.

Table 1 presents the Facilities control Information (SAP primitives) contained in an application request.

Table 1: Facilities control information (SAP primitives)

Category	Data	Definition
Data passed from application to infrastructure services	Infrastructure message identification	Identification of the message
	Request type	Trigger, update or ending of transmission
	Dissemination parameter	For more details see the dissemination profile for each service in the clauses 5 to 8
	Traffic class	GN traffic class as defined in ETSI EN 302 636-4-1 [3], if GeoNetworking/BTP is used
	Payload	Information contained in payload
Data returned from I2V service to the requesting application	actionID or other applicable identifier	The infrastructure service returns the message identification or other applicable identifier created by the infrastructure service to the requesting application
	Failure notification	The infrastructure service returns a failure notification to the requesting application

4.4.2 Interface between Facilities layer and Management entity

The infrastructure services may exchange information with the Management entity. This includes the default service communication parameters specified in clauses 5 to 8. The interface MF-SAP may be realized as the MF-SAP ETSI TS 102 723-5 [i.5].

4.4.3 Interface between Facilities layer and Security entity

The infrastructure service may exchange information with the Security entity.