



Designation: D 6938 – 07a

Standard Test Methods for In-Place Density and Water Content of Soil and Soil- Aggregate by Nuclear Methods (Shallow Depth)¹

This standard is issued under the fixed designation D 6938; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method describes the procedures for measuring in-place density and moisture of soil and soil-aggregate by use of nuclear equipment. The density of the material may be measured by direct transmission, backscatter, or backscatter/air-gap ratio methods. Measurements for water (moisture) content are taken at the surface in backscatter mode regardless of the mode being used for density. It is the intent of this subcommittee that this standard replaces D2922 and D3017.

1.1.1 For limitations see Section 5 on Interferences.

1.2 The total or wet density of soil and soil-aggregate is measured by the attenuation of gamma radiation where, in direct transmission, the source is placed at a known depth up to 300 mm (12 in.) and the detector (s) remains on the surface (some gauges may reverse this orientation); or in backscatter or backscatter/air-gap the source and detector (s) both remain on the surface.

1.2.1 The density of the test sample in mass per unit volume is calculated by comparing the detected rate of gamma radiation with previously established calibration data.

1.2.2 The dry density of the test sample is obtained by subtracting the water mass per unit volume from the test sample wet density (Section 11). Most gauges display this value directly.

1.3 The gauge is calibrated to read the water mass per unit volume of soil or soil-aggregate. When divided by the density of water, and then multiplied by 100, the water mass per unit volume is equivalent to the volumetric water content. The water mass per unit volume is determined by the thermalizing or slowing of fast neutrons by hydrogen, a component of water. The neutron source and the thermal neutron detector are both located at the surface of the material being tested. The water content most prevalent in engineering and construction activities is known as the gravimetric water content, w , and is the ratio of the mass of the water in pore spaces to the total mass of solids, expressed as a percentage.

1.4 Two alternative procedures are provided.

1.4.1 *Procedure A* describes the direct transmission method in which the gamma source rod extends through the base of the gauge into a pre-formed hole to a desired depth. The direct transmission is the preferred method.

1.4.2 *Procedure B* involves the use of a dedicated backscatter gauge or the source rod in the backscatter position. This places the gamma and neutron sources and the detectors in the same plane.

1.5 *SI Units*—The values stated in SI units are to be regarded as the standard. The values in inch-pound units (ft – lb units) are provided for information only.

1.6 All observed and calculated values shall conform to the guide for significant digits and rounding established in Practice D 6026.

1.6.1 The procedures used to specify how data are collected, recorded, and calculated in this standard are regarded as the industry standard. In addition, they are representative of the significant digits that should generally be retained. The procedures used do not consider material variation, purpose for obtaining the data, special purpose studies, or any considerations for the user's objectives; and it is common practice to increase or reduce significant digits of reported data to be commensurate with these considerations. It is beyond the scope of this standard to consider significant digits used in analysis methods for engineering design.

1.7 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*²

D 653 Terminology Relating to Soil, Rock, and Contained Fluids

D 698 Test Methods for Laboratory Compaction Characteristics of Soil Using Standard Effort (12 400 ft-lbf/ft³ (600 kN-m/m³))

¹ This test method is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.08 Special and Construction Control Tests.

Current edition approved July 1, 2007. Published July 2007. Originally approved in 2006. Last previous edition approved in 2007 as D 6938–07.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

*A Summary of Changes section appears at the end of this standard.

- D 1556** Test Method for Density and Unit Weight of Soil in Place by the Sand-Cone Method
- D 1557** Test Methods for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000 ft-lbf/ft³ (2,700 kN-m/m³))
- D 2167** Test Method for Density and Unit Weight of Soil in Place by the Rubber Balloon Method
- D 2487** Practice for Classification of Soils for Engineering Purposes (Unified Soil Classification System)
- D 2488** Practice for Description and Identification of Soils (Visual-Manual Procedure)
- D 2216** Test Methods for Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass
- D 2937** Test Method for Density of Soil in Place by the Drive-Cylinder Method
- D 3740** Practice for Minimum Requirements for Agencies Engaged in the Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction
- D 4253** Test Methods for Maximum Index Density and Unit Weight of Soils Using a Vibratory Table
- D 4254** Test Methods for Minimum Index Density and Unit Weight of Soils and Calculation of Relative Density
- D 4643** Test Method for Determination of Water (Moisture) Content of Soil by the Microwave Oven Method
- D 4718** Practice for Correction of Unit Weight and Water Content for Soils Containing Oversize Particles
- D 4944** Test Method for Field Determination of Water (Moisture) Content of Soil by the Calcium Carbide Gas Pressure Tester
- D 4959** Test Method for Determination of Water (Moisture) Content of Soil By Direct Heating
- D 6026** Practice for Using Significant Digits in Geotechnical Data
- D 7013** Guide for Nuclear Surface Moisture and Density Gauge Calibration Facility Setup

3. Terminology

3.1 Definitions - See Terminology **D 653** for general definitions.

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *Nuclear Gauge*—A device containing one or more radioactive sources used to measure certain properties of soil and soil-aggregates.

3.2.2 *Wet Density*—Same as bulk density (as defined in Terminology **D 653**); the total mass (solids plus water) per total volume of soil or soil-aggregate.

3.2.3 *Dry Density*—Same as density of dry soil or rock (as defined in Terminology **D 653**); the mass of solid particles per the total volume of soil or soil-aggregate.

3.2.4 *Gamma (Radiation) Source*—A sealed source of radioactive material that emits gamma radiation as it decays.

3.2.5 *Neutron (Radiation) Source*—A sealed source of radioactive material that emits neutron radiation as it decays.

3.2.6 *Compton Scattering*—The interaction between a gamma ray (photon) and an orbital electron where the gamma ray loses energy and rebounds in a different direction.

3.2.7 *Detector*—A device to detect and measure radiation.

3.2.8 *Probe* —A metal rod attached to a nuclear gauge in which a radioactive source or a detector is housed. The rod can

be lowered to specified depths for testing. Probes containing only a radioactive source are commonly referred to as “Source Rods”.

3.2.9 *Thermalization*—The process of “slowing down” fast neutrons by collisions with light-weight atoms, such as hydrogen.

3.2.10 *Water Content*—The ratio of the mass of water contained in the pore spaces of soil or soil-aggregate, to the solid mass of particles in that material, expressed as a percentage (*this is sometimes referred to in some scientific fields as gravimetric water content to differentiate it from volumetric water content*).

3.2.11 *Volumetric Water Content*—the volume of water as a percent of the total volume of soil or rock material.

3.2.12 *Test Count, N*—The measured output of a detector for a specific type of radiation for a given test.

3.2.13 *Prepared Blocks*—Blocks prepared of soil, solid rock, concrete, and engineered materials, that have characteristics of various degrees of reproducible uniformity.

4. Significance and Use

4.1 The test method described is useful as a rapid, nondestructive technique for in-place measurements of wet density and water content of soil and soil-aggregate and the determination of dry density.

4.2 The test method is used for quality control and acceptance testing of compacted soil and soil-aggregate mixtures as used in construction and also for research and development. The non-destructive nature allows repetitive measurements at a single test location and statistical analysis of the results.

4.3 *Density*—The fundamental assumptions inherent in the methods are that Compton scattering is the dominant interaction and that the material is homogeneous.

4.4 *Water Content*—The fundamental assumptions inherent in the test method are that the hydrogen ions present in the soil or soil-aggregate are in the form of water as defined by the water content derived from Test Methods **D 2216**, and that the material is homogeneous. (See **5.2**)

NOTE 1—The quality of the result produced by this standard test method is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice **D 3740** are generally considered capable of competent and objective testing/sampling/inspection, and the like. Users of this standard are cautioned that compliance with Practice **D 3740** does not in itself assure reliable results. Reliable results depend on many factors; Practice **D 3740** provides a means of evaluating some of those factors.

5. Interferences

5.1 *In-Place Density Interferences*

5.1.1 Measurements may be affected by the chemical composition of the material being tested.

5.1.2 Measurements may be affected by non-homogeneous soils and surface texture (see **10.2**).

5.1.3 Measurements in the Backscatter Mode are influenced more by the density and water content of the material in close proximity to the surface.

5.1.4 Measurements in the Direct Transmission mode are an average of the density from the bottom of the probe in the soil or soil aggregate back up to the surface of the gauge.

5.1.5 Oversize particles or large voids in the source-detector path may cause higher or lower density measurements. Where lack of uniformity in the soil due to layering, aggregate or voids is suspected, the test site should be excavated and visually examined to determine if the test material is representative of the in-situ material in general and if an oversize correction is required in accordance with Practice **D 4718**.

5.1.6 The measured volume is approximately 0.0028 m³ (0.10 ft³) for the Backscatter Mode and 0.0057 m³ (0.20 ft³) for the Direct Transmission Mode when the test depth is 150 mm (6 in.). The actual measured volume is indeterminate and varies with the apparatus and the density of the material.

5.1.7 Other radioactive sources must not be within 9 m (30 ft.) of equipment in operation.

5.2 *In-Place Water (Moisture) Content Interferences*

5.2.1 The chemical composition of the material being tested can affect the measurement and adjustments may be necessary (see Section **10.6**). Hydrogen in forms other than water and carbon will cause measurements in excess of the true value. Some chemical elements such as boron, chlorine, and cadmium will cause measurements lower than the true value.

5.2.2 The water content measured by this test method is not necessarily the average water content within the volume of the sample involved in the measurement. Since this measurement is by backscatter in all cases, the value is biased by the water content of the material closest to the surface. The volume of soil and soil-aggregate represented in the measurement is indeterminate and will vary with the water content of the material. In general, the greater the water content of the material, the smaller the volume involved in the measurement. Approximately 50 % of the typical measurement results from the water content of the upper 50 to 75 mm (2 to 3 in.).

5.2.3 Other neutron sources must not be within 9 m (30 ft) of equipment in operation.

6. Apparatus

6.1 *Nuclear Density / Moisture Gauge*—While exact details of construction of the apparatus may vary, the system shall consist of:

6.1.1 *Gamma Source*—A sealed source of high-energy gamma radiation such as cesium or radium.

6.1.2 *Gamma Detector*—Any type of gamma detector such as a Geiger-Mueller tube(s).

6.1.3 *Fast Neutron Source*—A sealed mixture of a radioactive material such as americium, radium and a target material such as beryllium, or a neutron emitter such as californium-252.

6.1.4 *Slow Neutron Detector*—Any type of slow neutron detector such as boron trifluoride or helium-3 proportional counter.

6.2 *Reference Standard*—A block of material used for checking instrument operation, correction of source decay, and to establish conditions for a reproducible reference count rate.

6.3 *Site Preparation Device*—A plate, straightedge, or other suitable leveling tool that may be used for planing the test site

to the required smoothness, and in the Direct Transmission Method, guiding the drive pin to prepare a perpendicular hole.

6.4 *Drive Pin*—A pin of slightly larger diameter than the probe in the Direct Transmission Instrument used to prepare a hole in the test site for inserting the probe.

6.4.1 *Drive Pin Guide*—A fixture that keeps the drive pin perpendicular to the test site. Generally part of the site preparation device.

6.5 *Hammer*—Heavy enough to drive the pin to the required depth without undue distortion of the hole.

6.6 *Drive Pin Extractor*—A tool that may be used to remove the drive pin in a vertical direction so that the pin will not distort the hole in the extraction process.

6.7 *Slide Hammer*, with a drive pin attached, may also be used both to prepare a hole in the material to be tested and to extract the pin without distortion to the hole.

7. Hazards

7.1 These gauges utilize radioactive materials that may be hazardous to the health of the users unless proper precautions are taken. Users of these gauges must become familiar with applicable safety procedures and government regulations.

7.2 Effective user instructions, together with routine safety procedures and knowledge of and compliance with Regulatory Requirements, are a mandatory part of the operation and storage of these gauges.

8. Calibration

8.1 Calibration of the gauge will be in accordance with **Annex A1 and Annex A2**.

8.2 For further reference on gauge calibration, see Guide **D 7013**, Standard Guide for Nuclear Surface Moisture and Density Gauge Calibration Facility Setup.

9. Standardization

9.1 Nuclear moisture density gauges are subject to long-term aging of the radioactive sources, which may change the relationship between count rates and the material density and water content. To correct for this aging effect, gauges are calibrated as a ratio of the measurement count rate to a count rate made on a reference standard or to an air-gap count (for the backscatter/air-gap ratio method).

9.2 Standardization of the gauge shall be performed at the start of each day's use, and a record of these data should be retained for the amount of time required to ensure compliance with either subsection **9.2.2** or **9.2.3**, whichever is applicable. Perform the standardization with the gauge located at least 9 m (30 ft) away from other nuclear moisture density gauges and clear of large masses of water or other items which can affect the reference count rates.

9.2.1 Turn on the gauge and allow for stabilization according to the manufacturer's recommendations. If the gauge is to be used either continuously or intermittently during the day, it is best to leave it in the "power on" condition to prevent having to repeat the stabilization (refer to manufacturer's recommendations). This will provide more stable, consistent results.

9.2.2 Using the reference standard, take at least four repetitive readings at the normal measurement period and obtain the

mean. If available on the gauge, one measurement at four or more times the normal measurement period is acceptable. This constitutes one standardization check.

Use the procedure recommended by the gauge manufacturer to establish the compliance of the standard measurement to the accepted range. Without specific recommendations from the gauge manufacturer, use the procedure in 9.2.3.

9.2.3 If the value of the current standardization count is outside the limits set by Eq 1, repeat the standardization check. If the second standardization check satisfies Eq 1, the gauge is considered in satisfactory operating condition. If the second standardization check does not satisfy Eq 1, the gauge calibration should be checked and verified according to **Annex A1 and Annex A2**, Sections **A1.2 and A2.2**. If the verification shows that the gauge meets the requirements of both **Annex A1 and Annex A2**, Sections **A1.2 and A2.2**, then, a new reference standard count, N_o , should be established.

If the verification check shows that the gauge fails to meet the requirements of both **Annex A1 and Annex A2**, Section **A1.2 and A2.2**, then repair and recalibrate the gauge.

$$N_s = N_o + 1.96 \sqrt{(N_o / F)} \quad (1)$$

where:

N_s = value of current standardization count,

N_o = average of the past four values of N_s taken for prior usage.

F = factory pre-scale factor. The pre-scale value (F) is a divisor which reduces the actual value for the purpose of display. The manufacturer will supply this value if other than 1.0. Some instruments may have provisions to compute and display this value

9.2.3.1 If a gauge has not had a standard count taken for three months or more, the user should repeat the standardization procedure in this section or follow the recommendations of the manufacturer. If for any reason the measured density becomes suspect during the day's use, perform another standardization check.

10. Procedure

10.1 When possible, select a test location where the gauge will be placed at least 600 mm (24.0 in) away from any object sitting on or projecting above the surface of the test location, when the presence of this object has the potential to modify gauge response. Any time a measurement must be made at a specific location and the aforementioned clearance cannot be achieved, such as in a trench, follow the gauge manufacturer's correction procedure(s).

10.2 *Prepare the test site in the following manner:*

10.2.1 Remove all loose and disturbed material and additional material as necessary to expose the true surface of the material to be tested.

10.2.2 Prepare a horizontal area sufficient in size to accommodate the gauge by grading or scraping the area to a smooth condition so as to obtain maximum contact between the gauge and material being tested.

10.2.3 The depth of the maximum void beneath the gauge shall not exceed 3 mm (1/8 in.). Use native fines or fine sand to fill the voids and smooth the surface with a rigid straight edge

or other suitable tool. The depth of the filler should not exceed approximately 3 mm (1/8 in.).

10.2.4 The placement of the gauge on the surface of the material to be tested is critical to accurate density measurements. The optimum condition is total contact between the bottom surface of the gauge and the surface of the material being tested. The total area filled should not exceed approximately 10 percent of the bottom area of the gauge.

10.3 Turn on and allow the gauge to stabilize (warm up) according to the manufacturer's recommendations (see Section 9.2.1).

10.4 *Procedure A - The Direct Transmission Procedure:*

10.4.1 Select a test location where the gauge in test position will be at least 150 mm (6 in.) away from any vertical projection

10.4.2 Make a hole perpendicular to the prepared surface using the rod guide and drive pin. The hole should be a minimum of 50 mm (2 inches) deeper than the desired measurement depth and of an alignment that insertion of the probe will not cause the gauge to tilt from the plane of the prepared area.

10.4.3 Mark the test area to allow the placement of the gauge over the test site and to align the source rod to the hole. Follow the manufacturer's recommendations if applicable.

10.4.4 Remove the hole-forming device carefully to prevent the distortion of the hole, damage to the surface, or loose material to fall into the hole.

NOTE 2—Care must be taken in the preparation of the access hole in uniform cohesionless granular soils. Measurements can be affected by damage to the density of surrounding materials when forming the hole.

10.4.5 Place the gauge on the material to be tested, ensuring maximum surface contact as described previously in 10.2.4.

10.4.6 Lower the probe into the hole to the desired test depth. Pull the gauge gently toward the back, or detector end, so that the back side of the probe is in intimate contact with the side of the hole in the gamma measurement path.

NOTE 3—As a safety measure, it is recommended that a probe containing radioactive sources not be extended out of its shielded position prior to placing it into the test site. When possible, align the gauge so as to allow placing the probe directly into the test hole from the shielded position.

10.4.7 Keep all other radioactive sources at least 9 m (30 feet) away from the gauge to avoid any effect on the measurement.

10.4.8 If the gauge is so equipped, set the depth selector to the same depth as the probe.

10.4.9 Secure and record one or more one-minute density and water content readings. Read the in-place wet density directly or determine one by use of the calibration curve or table previously established.

10.4.10 Read the water content directly or determine the water content by use of the calibration curve or table previously established.

10.5 *Procedure B -The Backscatter or Backscatter/Air-Gap Ratio Procedure:*

10.5.1 Seat the gauge firmly (see Note 2).

10.5.2 Keep all other radioactive sources at least 9m (30 ft) away from the gauge to avoid affecting the measurement.

10.5.3 Set the gauge into the Backscatter (BS) position.

10.5.4 Secure and record one or more set(s) of one-minute density and water content readings. When using the backscatter/air-gap ratio mode, follow the manufacturer's instructions regarding gauge setup. Take the same number of readings for the normal measurement period in the air-gap position as in the standard backscatter position. Calculate the air-gap ratio by dividing the counts per minute obtained in the air-gap position by the counts per minute obtained in the standard position. Many gauges have built-in provisions for automatically calculating the air-gap ratio and wet density.

10.5.5 Read the in-place wet density or determine one by use of the calibration curve or table previously established.

10.5.6 Read the water content or determine one by use of the calibration curve or previously established table (see Section 10.6).

10.6 Water Content Correction and Oversize Particle Correction

10.6.1 For proper use of the gauge and accurate values of both water content and dry density, both of these corrections need to be made when applicable.

Prior to using the gauge-derived water content on any new material, the value should be verified by comparison to another ASTM method such as Test Methods **D 2216**, **D 4643**, **D 4944**, or **D 4959**. As part of a user developed procedure, occasional samples should be taken from beneath the gauge and comparison testing done to confirm gauge-derived water content values. All gauge manufacturers have a procedure for correcting the gauge-derived water content values.

10.6.2 When oversize particles are present, the gauge can be rotated about the axis of the probe to obtain additional readings as a check. When there is any uncertainty as to the presence of these particles it is advisable to sample the material beneath the gauge to verify the presence and the relative proportion of the oversize particles. A rock correction can then be made for both water content and wet density by the method in Practice **D 4718**.

10.6.3 When sampling for water content correction or oversize particle correction, the sample should be taken from a zone directly under the gauge. The size of the zone is approximately 200 mm (8 in.) in diameter and a depth equal to the depth setting of the probe when using the direct transmission mode; or approximately 75 mm (3 in.) in depth when using the backscatter mode.

11. Calculation of Results

11.1 Determine the Wet Density

11.1.1 On most gauges read the value directly in kg/m³ (lbm/ft³). If the density reading is in "counts", determine the in-place wet density by use of this reading and the previously established calibration curve or table for density.

11.1.2 Record the density to the nearest 1 kg/m³ (0.1 lbm/ft³).

11.2 Water Content

11.2.1 Use the gauge reading for w if the gauge converts to that value.

11.2.2 If the gauge determines water mass per unit volume in kg/m³ (lbm / ft³), calculate w using the formula:

$$w = \frac{M_m \times 100}{\rho_d} \quad (2)$$

or,

$$w = \frac{M_m \times 100}{\rho - M_m} \quad (3)$$

where:

w = water content

ρ_d = dry density in kg/m³ or (lbm/ft³),

ρ = wet density in kg/m³ or (lbm/ft³), and

M_m = water mass per unit volume in kg/m³ or (lbm/ft³)

11.2.3 If the water content reading was in "counts", determine the water mass per unit volume by use of this reading and previously established calibration curve or table. Then convert to gravimetric water content as per 11.2.2.

11.2.4 Record water content to the nearest 0.1 %.

11.3 Determine the Dry Density of the soil by one of the following methods:

11.3.1 If the water content is obtained by nuclear methods, use the gauge readings directly for dry density in kg/m³ (lbm/ft³). The value can also be calculated from:

$$\rho_d = \rho - M_m \quad (4)$$

11.3.2 If the water content is to be determined from a sample of soil taken as prescribed in (10.6.3), follow the procedures and perform the calculations of the chosen Test Method (**D 2216**, **D 4643**, **D 4944**, or **D 4959**).

11.3.3 With a water content value from 11.3.2 calculate the dry density from:

$$\rho_d = \frac{100 \times \rho}{100 + w} \quad (5)$$

11.3.4 Report the dry density to the nearest 1 kg/m³ (0.1 lbm/ft³).

11.4 Determine the Percent Compaction:

11.4.1 It may be desired to express the in-place dry density as a percentage of a laboratory density such as Test Methods **D 698**, **D 1557**, **D 4253**, or **D 4254**. This relationship can be calculated by dividing the in-place dry density by the laboratory maximum dry density and multiplying by 100. Procedures for calculating relative density are provided in Test Method **D 4254** which requires that Test Method **D 4253** also be performed. Corrections for oversize material, if required, should be performed in accordance with Practice **D 4718**.

12. Report: Test Data Sheet(s)/Form(s)/Final Report(s)

12.1 The Field Data Records shall include, as a minimum, the following:

12.1.1 Test Number or Test Identification.

12.1.2 Location of test (e.g.-Station number or GPS or Coordinates or other identifiable information).

12.1.3 Visual description of material tested.

12.1.4 Lift number or elevation or depth.

12.1.5 Name of the operator(s).

12.1.6 Make, model and serial number of the test gauge

12.1.7 Test mode, Method A (direct transmission and test depth), or Method B (backscatter, backscatter/air-gap),

12.1.8 Standardization and adjustment data for the date of the tests.

12.1.9 Any corrections made in the reported values and reasons for these corrections (i.e. over-sized particles, water content)

12.1.10 Maximum laboratory density value in kg/m³ or lbm/ft³.

12.1.11 Dry density in kg/m³ or lbm/ft³.

12.1.12 Wet density in kg/m³ or lbm/ft³.

12.1.13 Water content in percent

12.1.14 Percent Compaction.

12.2 *Final Report (minimum required information):*

12.2.1 Test Number.

12.2.2 Gauge Serial number.

12.2.3 Location of test (eg.-Station number or GPS or Coordinates or other identifiable information).

12.2.4 Lift number or elevation or depth.

12.2.5 Moisture (Water) content as a percent.

12.2.6 Maximum laboratory density value in kg/m³ or lbm/ft³.

12.2.7 Dry Density result in kg/m³ or lbm/ft³.

12.2.8 Percent Compaction.

12.2.9 Name of Operator(s).

13. Precision and Bias

13.1 *Precision:*

13.1.1 *Precision – Wet Density*—Criteria for judging the acceptability of wet density test results obtained by this test method are given in **Table 1**. The figure in column three represents the standard deviations that have been found to be appropriate for the materials tested in column one. The figures

given in column four are the limits that should not be exceeded by the difference between the results of two properly conducted tests. The figures given are based upon an interlaboratory study in which five test sites containing soils, with wet densities as shown in column two were tested by eight different nuclear gauges and operators. The wet density of each test site was measured three times by each device.

13.1.2 *Precision – Water Content*—Criteria for judging the acceptability of the water content results obtained by this test method are given in **Table 2**. The value in column two is in the units actually reported by the nuclear gauge. The figures in column three represent the standard deviations that have been found to be appropriate for the materials tested in column one. The figures given in column four are the limits that should not be exceeded by the difference between the results of two properly conducted tests. The figures given are based upon an inter-laboratory study in which five test sites containing soils, with water content as shown in column two were tested by eight different nuclear gauges and operators. The water content of each test site was measured three times by each device.

13.2 *Bias:*

13.2.1 There are no accepted reference values for these test methods, therefore, bias cannot be determined

14. Keywords

14.1 Compaction test; acceptance testing; construction control; quality control; field density; in-place density; wet density; water content; dry density; nuclear methods, nuclear gauge

TABLE 1 Results of Statistical Analysis (Wet Density)^A

Precision and Soil Type ^B	Average kg/m ³ or (lbm/ft ³)	Standard Deviation kg/m ³ or (lbm/ft ³)	Acceptable Range ^C of Two Results kg/m ³ or (lbm/ft ³)
Single Operator Precision:			
Direct Transmission:			
CL	1837 (114.7)	5.4 (0.3)	15.1 (0.9)
SP	1937 (120.9)	4.3 (0.3)	11.8 (0.7)
ML	2084 (130.1)	7.4 (0.5)	20.5 (1.3)
Backscatter:			
ML	1996 (124.6)	19.4 (1.2)	54.3 (3.4)
Multi-laboratory Precision:			
Direct Transmission:			
CL	1837 (114.7)	10.6 (0.7)	29.8 (1.9)
SP	1937 (120.9)	10.9 (0.7)	30.6 (1.9)
ML	2084 (130.1)	12.3 (0.8)	34.4 (2.1)
Backscatter:			
ML	1996 (124.6)	38.1 (2.4)	106.8 (6.7)

^AThe data used to establish this precision statement is contained in a Research Report available from ASTM Headquarters. Request RR: D18-1004.

^BFor definitions of soil types see Practices **D 2487** and **2488**.

^CTwo separate readings at a singular site with constant gauge orientation and settings.