

---

---

**Fasteners — Hexalobular socket  
countersunk head screws, high head**

*Éléments de fixation — Vis à tête fraisée à six lobes internes, tête haute*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 14582:2013

<https://standards.iteh.ai/catalog/standards/sist/0b43bfea-179c-4978-a4cf-e0c605d36d80/iso-14582-2013>



Reference number  
ISO 14582:2013(E)

© ISO 2013

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 14582:2013

<https://standards.iteh.ai/catalog/standards/sist/0b43bfea-179c-4978-a4cf-e0c605d36d80/iso-14582-2013>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Dimensions</b> .....	<b>2</b>
<b>4 Requirements and reference International Standards</b> .....	<b>6</b>
<b>5 Marking</b> .....	<b>6</b>
<b>6 Designation</b> .....	<b>6</b>
<b>Bibliography</b> .....	<b>7</b>

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 14582:2013

<https://standards.iteh.ai/catalog/standards/sist/0b43bfea-179c-4978-a4cf-e0c605d36d80/iso-14582-2013>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. [www.iso.org/directives](http://www.iso.org/directives)

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. [www.iso.org/patents](http://www.iso.org/patents)

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

The committee responsible for this document is ISO/TC 2, *Fasteners*, Subcommittee SC 11, *Fasteners with metric external thread*.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 14582:2013](https://standards.iteh.ai/catalog/standards/sist/0b43bfea-179c-4978-a4cf-e0c605d36d80/iso-14582-2013)

<https://standards.iteh.ai/catalog/standards/sist/0b43bfea-179c-4978-a4cf-e0c605d36d80/iso-14582-2013>

# Fasteners — Hexalobular socket countersunk head screws, high head

## 1 Scope

This International Standard specifies hexalobular socket countersunk head bolts and screws with high head (full loadability), of product grade A, and thread diameters from M3 up to and including M10 and property classes 4.8, 8.8 and 10.9.

NOTE 1 In comparison with ISO common countersunk head, the height of the head has been slightly increased in order to have screws with full loadability, in conformity with the mechanical properties specified in ISO 898-1.

This International Standard also specifies gauge dimensions for the control of the head dimensions.

NOTE 2 Because of the increased head height, these screws are not fully interchangeable with other countersunk ISO metric screws. The assembled parts also need a slightly deeper countersink than those specified in ISO 15065.

If, in special cases, specifications other than those listed in this International Standard are required, they can be selected from existing International Standards, for example ISO 261, ISO 888, ISO 898-1, ISO 965-2 and ISO 4759-1.

## 2 Normative references (standards.iteh.ai)

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 225, *Fasteners — Bolts, screws, studs and nuts — Symbols and descriptions of dimensions*

ISO 261, *ISO general purpose metric screw threads — General plan*

ISO 898-1, *Mechanical properties of fasteners made of carbon steel and alloy steel — Part 1: Bolts, screws and studs with specified property classes — Coarse thread and fine pitch thread*

ISO 965-2, *ISO general purpose metric screw threads — Tolerances — Part 2: Limits of sizes for general purpose external and internal screw threads — Medium quality*

ISO 3269, *Fasteners — Acceptance inspection*

ISO 4042, *Fasteners — Electroplated coatings*

ISO 4759-1, *Tolerances for fasteners — Part 1: Bolts, screws, studs and nuts — Product grades A, B and C*

ISO 6157-1, *Fasteners — Surface discontinuities — Part 1: Bolts, screws and studs for general requirements*

ISO 8992, *Fasteners — General requirements for bolts, screws, studs and nuts*

ISO 10664, *Hexalobular internal driving feature for bolts and screws*

ISO 10683, *Fasteners — Non-electrolytically applied zinc flake coatings*

ISO 10684, *Fasteners — Hot dip galvanized coatings*


### 3 Dimensions

See [Figures 1](#) and [2](#) and [Table 1](#). Symbols and descriptions of dimensions are specified in ISO 225.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 14582:2013

<https://standards.iteh.ai/catalog/standards/sist/0b43bfea-179c-4978-a4cf-e0c605d36d80/iso-14582-2013>



a Incomplete thread  $u \leq 2P$ .

b  $d_s$  applies if values of  $l_{s,min}$  are specified.

c Point is to be chamfered or, for sizes  $\leq M4$ , "as rolled" in conformity with ISO 4753.


d Edge of the head flat or rounded.

e  $a_{max} \leq 2P$ .

f  $a_{max} \leq 2,5P$ .

g Any shape or size of the reinforcing feature is at the discretion of the manufacturer and shall not exceed  $d$ .

**Figure 1 — Hexalobular socket countersunk head screw, high head**




**Key**

- 1  $d_{k \text{ theoretical,max}}$
- 2  $d_{k \text{ actual,max}}$
- 3  $d_{k \text{ actual,min}}$
- $F$  flushness tolerance of the gauge (see Table 1)

**Figure 2 — Countersunk head configuration**

For gauging of the head and for dimensions of the gauge allowing the control of the head dimensions see Figure 3 and Table 1. The top surface of the screw shall be located between the gauge surfaces A and B.

Tolerances in millimetres



**Key**

- $F$  flushness tolerance of the gauge (see Table 1)
- a  $D = d_{k \text{ theoretical,max}}$

**Figure 3 — Flushness gauge**



Table 1 — Dimensions for hexalobular socket countersunk head screws, high head

Dimensions in millimetres

Thread, <i>d</i>			M3	M4	M5	M6	M8	M10							
<i>p</i> <sub>a</sub>			0,5	0,7	0,8	1	1,25	1,5							
<i>b</i>	ref.		18	20	22	24	28	32							
<i>d</i> <sub>a</sub>	max.		3,30	4,40	5,50	6,60	8,54	10,62							
	min. <sup>b</sup>		3,20	4,30	5,40	6,50	8,44	10,52							
<i>d</i> <sub>k</sub>	theoretical	max.	7,40	10,02	12,00	14,44	19,38	23,00							
	actual	max.	6,57	9,02	10,90	13,20	17,90	21,30							
		min.	6,17	8,52	10,27	12,46	17,09	20,49							
<i>d</i> <sub>s</sub>	max.		3,00	4,00	5,00	6,00	8,00	10,00							
	min.		2,86	3,82	4,82	5,82	7,78	9,78							
<i>F</i> <sup>c</sup>	max.		0,25	0,25	0,30	0,35	0,40	0,40							
<i>k</i> <sup>d</sup>	max.		2,20	3,01	3,50	4,22	5,69	6,50							
<i>r</i>	min.		0,10	0,20	0,20	0,25	0,40	0,40							
Hexalobular socket	Socket No.		10	20	25	30	45	50							
	<i>A</i>	ref.	2,8	3,95	4,5	5,6	7,93	8,95							
	<i>t</i>	max.	1,18	1,69	1,89	2,22	2,99	3,30							
		min.	0,92	1,30	1,50	1,83	2,60	2,91							
ITech STANDARD PREVIEW (standards.iteh.ai)															
<i>l</i> <sup>e</sup>			<i>l</i> <sub>s</sub> and <i>l</i> <sub>g</sub>												
nom. <sup>f</sup>	min.	max.	<i>l</i> <sub>s</sub> min.	<i>l</i> <sub>g</sub> max.	<i>l</i> <sub>s</sub> min.	<i>l</i> <sub>g</sub> max.	<i>l</i> <sub>s</sub> min.	<i>l</i> <sub>g</sub> max.	<i>l</i> <sub>s</sub> min.	<i>l</i> <sub>g</sub> max.	<i>l</i> <sub>s</sub> min.	<i>l</i> <sub>g</sub> max.	<i>l</i> <sub>s</sub> min.	<i>l</i> <sub>g</sub> max.	
8	7,71	8,29													
10	9,71	10,29			ISO 14582:2013										
12	11,65	12,35	standards.iteh.ai/catalog/standards/sist/0b43bfea-179c-4978-a4cf-e0c695d36d80/iso-14582-2013												
(14)	13,65	14,35													
16	15,65	16,35													
20	19,58	20,42													
25	24,58	25,42													
30	29,58	30,42	9,5	12	6,5	10									
35	34,5	35,5			11,5	15	9	13							
40	39,5	40,5			16,5	20	14	18	11	16					
45	44,5	45,5					19	23	16	21					
50	49,5	50,5					24	28	21	26	15,75	22			
55	54,4	55,6							26	31	20,75	27	15,5	23	
60	59,4	60,6							31	36	25,75	32	20,5	28	
65	64,4	65,6									30,75	37	25,5	33	
70	69,4	70,6									35,75	42	30,5	38	
80	79,4	80,6									45,75	52	40,5	48	
90	89,3	90,7											50,5	58	
100	99,3	100,7											60,5	68	

a *P* is the pitch of the thread.

b Values for *d<sub>a,min</sub>* are based on a radius *r* = 0,25*d*.

c The flushness tolerance of the gauge, *F*, has the tolerance  $0 - 0,01$ .

d The dimensions of the gauges defined in ISO 7721 are not adapted to this countersunk head.

e Preferred lengths are between the bold, stepped lines. Lengths above the discontinuous, stepped line are threaded to the head within 3*P*. Lengths below the discontinuous, stepped line have values of *l<sub>g</sub>* and *l<sub>s</sub>* in accordance with the following formulae:

$$l_{g,max} = l_{nom} - b$$

$$l_{s,min} = l_{g,max} - 5P$$

f Dimensions in parentheses should be avoided.