

ETSI EN 300 392-3-14 V1.2.1 (2020-04)



Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D);

Part 3: Interworking at the Inter-System Interface (ISI);

Sub-part 14: Transport layer independent

Additional Network Feature

Short Data Service (ANF-ISISDS)

**Industrial Trunked Radio (TETRA);
Voice plus Data (V+D);
Working at the Inter-System Interface
14: Transport layer independence;
Additional Network Feature
with Data Service (ANF-ISIDS)**

Reference

REN/TCCE-03262

Keywords

ANF, interworking, SDS, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definition of terms, symbols and abbreviations.....	10
3.1 Terms.....	10
3.2 Symbols.....	10
3.3 Abbreviations	10
4 ANF-ISISDS stage 1 specification.....	10
4.1 Description	10
4.2 Overview of operation.....	10
4.3 Security concerns	11
4.4 Procedures	11
4.4.1 Provision/withdrawal	11
4.4.2 Normal procedures.....	11
4.4.2.1 Activation/deactivation/registration/interrogation	11
4.4.2.2 Invocation and operation.....	11
4.4.3 Exceptional procedures.....	12
4.4.3.1 Activation/deactivation/registration/interrogation	12
4.4.3.2 Invocation and operation.....	12
4.5 The generic ANF-ISISDS stage 1 service model.....	12
4.5.1 Introduction.....	12
4.5.2 Primitive definitions	13
4.5.3 Parameter description	14
5 ANF-ISISDS stage 2 specification.....	16
5.1 Overview of functional entities	16
5.1.1 Introduction.....	16
5.1.2 Roles of the functional entities	16
5.1.3 Relationships between FEs.....	16
5.2 Information flow	16
5.2.1 Definitions of information flows	16
6 ANF-ISISDS stage 3 specification.....	17
6.1 General on ANF-ISISDS	17
6.2 TETRA ANF-ISISDS PDUs	17
6.2.1 TETRA information encoding	17
6.2.2 ISISDS-UNITDATA PDU	18
6.2.3 Information element encoding	18
6.2.3.1 Called party extension.....	18
6.2.3.2 Called party external subscriber number.....	18
6.2.3.3 Called party SSI	18
6.2.3.4 Calling party extension	19
6.2.3.5 Calling party external subscriber number	19
6.2.3.6 Calling party external subscriber number parameters	19
6.2.3.7 Calling party SSI.....	19
6.2.3.8 Hop count.....	20
6.2.3.9 ISISDS Subtype	20
6.2.3.10 Length of user defined data-4.....	20
6.2.3.11 MSISDN present as external subscriber number.....	20
6.2.3.12 Number of digits in called party external subscriber number	20
6.2.3.13 Number of digits in calling party external subscriber number	20

6.2.3.14	PDU type.....	20
6.2.3.15	Pre-coded status	21
6.2.3.16	Security level at the calling user air interface	21
6.2.3.17	Selected area number	21
6.2.3.18	Short data type identifier	21
6.2.3.19	User defined data-1	21
6.2.3.20	User defined data-2	21
6.2.3.21	User defined data-3	21
6.2.3.22	User defined data-4	21

Annex A (normative): Interaction with other TETRA supplementary services and ANFs.....22

A.1	Calling Line Identification Presentation (SS-CLIP).....	22
A.2	Connected Line Identification Presentation (SS-COLP).....	22
A.3	Calling/Connected Line Identification Restriction (SS-CLIR)	22
A.4	Connected Name Identification Presentation (SS-CONP)	22
A.5	Completion of Calls of Busy Subscriber (SS-CCBS)	22
A.6	Completion of Calls on No Reply (SS-CCNR).....	22
A.7	Call Forward Unconditional (SS-CFU).....	22
A.8	Call Forwarding Busy (SS-CFB)	22
A.9	Call Forwarding No Reply (SS-CFNR)	23
A.10	Call Report (SS-CR).....	23
A.11	Talking Party Identification (SS-TPI)	23
A.12	List Search Call (SS-LSC)	23
A.13	Call Authorized by Dispatcher (SS-CAD)	23
A.14	Short Number Addressing (SS-SNA).....	23
A.15	Area Selection (SS-AS).....	23
A.16	Access Priority (SS-AP).....	23
A.17	Priority Call (SS-PC).....	23
A.18	Call Waiting (SS-CW).....	23
A.19	Call Hold (SS-HOLD).....	24
A.20	Late Entry (SS-LE).....	24
A.21	Transfer of Control (SS-TC)	24
A.22	Pre-emptive Priority Call (SS-PPC)	24
A.23	Include Call (SS-IC)	24
A.24	Barring of Outgoing Calls (SS-BOC)	24
A.25	Barring of Incoming Calls (SS-BIC).....	24
A.26	Discreet Listening (SS-DL).....	24
A.27	Ambience Listening (SS-AL).....	24
A.28	Dynamic Group Number Assignment (SS-DGNA)	24
A.29	Call Retention (SS-CRT).....	24
A.30	ISI Individual Call (ANF-ISIIC)	25
A.31	ISI group call (ANF-ISIGC).....	25

A.32 ISI Mobility Management (ANF-ISIMM)	25
Annex B (informative): Change Requests.....	26
History	27

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/b9d1033b-39b3-4371-8d90-97198e84e519/etsi-en-300-392-3-14-v1.2.1-2020-04>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee TETRA and Critical Communications Evolution (TCCE).

The present document is part 3, sub-part 14 of a multi-part deliverable covering the Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D), as identified below:

Part 1: "General network design";

Part 2: "Air Interface (AI)";

Part 3: "Interworking at the Inter-System Interface (ISI)":

Sub-part 1: "General design";

Sub-part 2: "Additional Network Feature Individual Call (ANF-ISIIC)";

Sub-part 3: "Additional Network Feature Group Call (ANF-ISIGC)";

Sub-part 4: "Additional Network Feature Short Data Service (ANF-ISISDS)";

Sub-part 5: "Additional Network Feature for Mobility Management (ANF-ISIMM)";

Sub-part 6: "Speech format implementation for circuit mode transmission";

Sub-part 7: "Speech Format Implementation for Packet Mode Transmission";

Sub-part 8: "Generic Speech Format Implementation";

Sub-part 9: "Transport layer independent, General design";

Sub-part 10: "General design, PSS1 over E.1";

Sub-part 11: "General design, SIP/IP";

Sub-part 12: "Transport layer independent Additional Network Feature Individual Call (ANF-ISIIC)";

Sub-part 13: "Transport layer independent Additional Network Feature Group Call (ANF-ISIGC)";

Sub-part 14: "Transport layer independent Additional Network Feature Short Data Service (ANF-ISISDS)";

Sub-part 15: "Transport layer independent Additional Network Feature, Mobility Management (ANF-ISIMM)";

Part 4: "Gateways basic operation";

Part 5: "Peripheral Equipment Interface (PEI)";

Part 7: "Security";

Part 9: "General requirements for supplementary services";

Part 10: "Supplementary services stage 1";

Part 11: "Supplementary services stage 2";

Part 12: "Supplementary services stage 3";

Part 13: "SDL model of the Air Interface (AI)";

Part 14: "Protocol Implementation Conformance Statement (PICS) proforma specification";

Part 15: "TETRA frequency bands, duplex spacings and channel numbering";

Part 16: "Network Performance Metrics";

Part 17: "TETRA V+D and DMO specifications";

Part 18: "Air interface optimized applications";

Part 19: "Interworking between TETRA and Broadband systems".

NOTE 1: Part 3, sub-parts 6 and 7 (Speech format implementation), part 4, sub-part 3 (Data networks gateway), part 10, sub-part 15 (Transfer of control), part 13 (SDL) and part 14 (PICS) of this multi-part deliverable are in status "historical" and are not maintained.

NOTE 2: Some parts are also published as Technical Specifications such as ETSI TS 100 392-2 and those may be the latest version of the document.

The present document is based on ETSI EN 300 392-3-4 [i.1]. The main changes are:

- Removal of any reference to the bearer protocol.

For all subparts in the TETRA specification ETSI EN 300 392-3, "Interworking at the Inter-System Interface (ISI)" the terms ISI and TETRA ISI are equivalent.

National transposition dates	
Date of adoption of this EN:	13 November 2019
Date of latest announcement of this EN (doa):	31 July 2020
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2021
Date of withdrawal of any conflicting National Standard (dow):	31 January 2021

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are NOT allowed in ETSI deliverables except when used in direct citation.

1 Scope

The TETRA V+D interworking - at the Inter-System Interface (ISI) part defines the interworking between TETRA networks over the corresponding interface: the Inter-System Interface (ISI). It comprises the following sub-parts:

- Transport layer independent General design [3];
- General Design, PSS1 over E.1 [i.2];
- General Design, SIP/IP [i.3];
- Transport layer independent Additional Network Feature - ISI Individual Call (ANF-ISIIC) [i.4];
- Transport layer independent Additional Network Feature - ISI Group Call (ANF-ISIGC) [2];
- Transport layer independent Additional Network Feature - ISI Short Data service (ANF-ISISDS) (the present document);
- Transport layer independent Additional Network Feature - ISI Mobility Management (ANF-ISIMM) [i.5];
- Generic Speech Format Implementation [i.6].

The present document specifies the Additional Network Function (ANF) - Inter-System Interface (ISI) Short Data service (ANF-ISISDS) which is part of the Interworking at the Inter-System Interface (ISI) of the Terrestrial Trunked Radio system (TETRA) supporting Voice and Data (V+D). This service comprises of:

- TETRA short message transmission over the ISI to individual and group addresses;
- TETRA pre-defined status message transmission over the ISI to individual and group addresses.

ANF-ISISDS enables short data and status messages to be transferred between a user registered in one TETRA network to another user registered in another TETRA network, operating at the ISI of both SwMIs.

Like all other Additional Network Feature (ANF) specifications, those of ANF-ISISDS are produced in three stages, according to the method described in Recommendation ITU-T I.130 [4]. The present document contains the stage 1 and 2 descriptions of ANF-ISIIC, and stage 3 description. The stage 1 description specifies the ANF as seen by its users, which are essentially the CMCE SDS entities in both TETRA networks. The stage 2 description identifies the functional entities involved in the ANF and the information flows between them. The stage 3 description of ANF-ISISDS specifies its protocol.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE 1: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

NOTE 2: Note that for the TETRA standards, the reference is always to a European Standard (ETSI EN 300 xxx) if such has been published, but the latest version of that standard can be either an EN or a Technical Specification (ETSI TS 100 xxx), even if this is not visible in the reference list.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [2] ETSI EN 300 392-3-13: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 13: Transport layer independent Additional Network Feature Group Call (ANF-ISIGC)".
- [3] ETSI EN 300 392-3-9: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 9: Transport layer independent, General design".
- [4] Recommendation ITU-T I.130: "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [5] ETSI EN 300 392-12-8: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 8: Area Selection (AS)".
- [6] ETSI EN 300 392-9: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 9: General requirements for supplementary services".
- [7] ISO/IEC 11571 (1998): "Information technology -- Telecommunications and information exchange between systems -- Private Integrated Services Networks -- Addressing".
- [8] Recommendation ITU-T E.164: "The international public telecommunication numbering plan".
- [9] Recommendation ITU-T X.121: "International numbering plan for public data networks".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE 1: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

NOTE 2: Note that for the TETRA standards, the reference is always to a European Standard (ETSI EN 300 xxx) if such has been published, but the latest version of that standard can be either an EN or a Technical Specification (ETSI TS 100 xxx), even if this is not visible in the reference list.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EN 300 392-3-4: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 4: Additional Network Feature Short Data Service (ANF-ISISDS)".
- [i.2] ETSI EN 300 392-3-10: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 10: General design, PSS1 over E.1".
- [i.3] ETSI EN 300 392-3-11: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 11: General design, SIP/IP".
- [i.4] ETSI EN 300 392-3-12: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 12: Transport Layer Independent Additional Network Feature Individual Call (ANF-ISIIC)".
- [i.5] ETSI EN 300 392-3-15: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 15: Transport layer independent Additional Network Feature, Mobility Management (ANF-ISIMM)".

- [i.6] ETSI EN 300 392-3-8: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 8: Generic Speech Format Implementation".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in ETSI EN 300 392-2 [1] and ETSI EN 300 392-3-9 [3] apply.

NOTE: In the present document the term visited SwMI follows the definition of the Air Interface standard ETSI EN 300 392-2 [1]: TETRA network which MNI is not equal to the user's MNI.

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 300 392-2 [1], ETSI EN 300 392-3-9 [3] and ETSI EN 300 392-3-13 [2] apply.

4 ANF-ISISDS stage 1 specification

4.1 Description

ANF-ISISDS provides support of the SDS service described in ETSI EN 300 392-2 [1], clause 13, across the ISI connection between 2 SwMIs. In addition the present document supports the embedded SDS-TL service described in ETSI EN 300 392-2 [1].

NOTE: The interpretation of all status code values contained in predefined status or short message services are not defined in the TETRA suite of standards. The consistent interpretation of these code values in user equipment will not be made by the ANF-ISISDS service but will be left to end-users to co-ordinate codeset interpretation.

4.2 Overview of operation

ANF-ISISDS shall transparently take the SDS message as presented by the originating SwMI and transport it to the peer ANF-ISISDS entity in the destination SwMI.

There shall be a single invocation of ANF-ISISDS per SDS transfer. Each message therefore is considered as independent. Group addressed SDS shall be sent to the group (linking) controlling SwMI only for further distribution by that SwMI to each participating SwMI.

ANF-ISISDS assumes that an equivalent to the TNSDS-SAP defined in ETSI EN 300 392-2 [1], clause 13 exists in the SwMI that provides an equivalent set of primitives.

For outgoing SDS messages the SwMI shall have received an equivalent to the TNSDS-UNITDATA indication primitive with those extensions required to indicate area selection. It shall then determine the destination SwMI. ANF-ISISDS shall only be invoked if the destination is on another SwMI.

For incoming SDS ANF-ISISDS shall deliver the SDS message to the SwMI in like manner to any internal SwMI device.