



**Fixed Short Range Devices (SRD) in data networks;
Radio equipment to be used in the 870 MHz to 876 MHz
frequency range with power levels
ranging up to 500 mW e.r.p.;
Harmonised Standard for access to the radio spectrum**

From STANDARDS PREVIEW
<https://standards.iteh.ai/en/standards/etsi-en-303-204-v3-1-0-2020-12-49a8-9acd-14334590463/>

Reference

REN/ERM-TG28-555

Keywords

harmonised standard, radio, SRD, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	14
Foreword.....	14
Modal verbs terminology.....	14
Introduction	15
1 Scope	19
2 References	20
2.1 Normative references	20
2.2 Informative references.....	20
3 Definition of terms, symbols and abbreviations.....	21
3.1 Terms.....	21
3.2 Symbols.....	23
3.3 Abbreviations	23
4 Technical requirements specifications	24
4.1 Environmental profile.....	24
4.2 Conformance requirements	24
4.2.1 General requirements.....	24
4.2.2 Performance criteria.....	24
4.2.3 Signal threshold	25
4.2.4 Disregard time	25
4.2.5 Transmission bandwidth	25
4.2.6 Fixed frequency operating	25
4.3 Requirements for transmitters	25
4.3.1 Frequency drift.....	25
4.3.1.1 Applicability.....	25
4.3.1.2 Description	25
4.3.1.3 Limits	25
4.3.1.4 Conformance.....	26
4.3.2 Operating frequencies and channel spacing.....	26
4.3.2.1 Applicability.....	26
4.3.2.2 Description	26
4.3.2.3 Limits	26
4.3.2.4 Conformance.....	27
4.3.3 Effective radiated power	27
4.3.3.1 Applicability.....	27
4.3.3.2 Description	27
4.3.3.3 Limits	27
4.3.3.4 Conformance.....	27
4.3.4 Transient power	28
4.3.4.1 Applicability.....	28
4.3.4.2 Description	28
4.3.4.3 Limits	28
4.3.4.4 Conformance.....	28
4.3.5 Occupied bandwidth	28
4.3.5.1 Applicability.....	28
4.3.5.2 Description	28
4.3.5.3 Limits	28
4.3.5.4 Conformance.....	29
4.3.6 Unwanted emissions in the out-of-band domain.....	29
4.3.6.1 Applicability.....	29
4.3.6.2 Description	29
4.3.6.3 Limits	30
4.3.6.4 Conformance.....	30
4.3.7 Unwanted emissions in the spurious domain	30
4.3.7.1 Applicability.....	30

4.3.7.2	Description	31
4.3.7.3	Limits	31
4.3.7.4	Conformance	31
4.3.8	Frequency stability under low-voltage conditions	31
4.3.8.1	Applicability	31
4.3.8.2	Description	31
4.3.8.3	Limits	32
4.3.8.4	Conformance	32
4.3.9	Duty cycle and transmission timing	32
4.3.9.1	Applicability	32
4.3.9.2	Description	32
4.3.9.3	Long term behaviour	32
4.3.9.4	Short term behaviour	33
4.3.9.5	Limits	33
4.3.9.6	Conformance	33
4.3.10	Automatic/adaptive power control	33
4.3.10.1	Applicability	33
4.3.10.2	Description	33
4.3.10.3	Limits	34
4.3.10.4	Conformance	34
4.4	Requirements for receivers	34
4.4.1	Receiver sensitivity	34
4.4.1.1	Applicability	34
4.4.1.2	Description	34
4.4.1.3	Limits	34
4.4.1.4	Conformance	34
4.4.2	Receiver maximum input signal level	34
4.4.2.1	Applicability	34
4.4.2.2	Description	35
4.4.2.3	Limits	35
4.4.2.4	Conformance	35
4.4.3	Clear channel assessment threshold	35
4.4.3.1	Applicability	35
4.4.3.2	Description	35
4.4.3.3	Limits	35
4.4.3.4	Conformance	35
4.4.4	Co-channel rejection	35
4.4.4.1	Applicability	35
4.4.4.2	Description	35
4.4.4.3	Limits	36
4.4.4.4	Conformance	36
4.4.5	Adjacent channel selectivity	36
4.4.5.1	Applicability	36
4.4.5.2	Description	36
4.4.5.3	Limits	36
4.4.5.4	Conformance	36
4.4.6	Blocking	36
4.4.6.1	Applicability	36
4.4.6.2	Description	36
4.4.6.3	Limits	37
4.4.6.4	Conformance	37
4.4.7	Receiver spurious response rejection	37
4.4.7.1	Applicability	37
4.4.7.2	Description	37
4.4.7.3	Limits	37
4.4.7.4	Conformance	37
4.4.8	Receiver intermodulation rejection	37
4.4.8.1	Applicability	37
4.4.8.2	Description	37
4.4.8.3	Limits	38
4.4.8.4	Conformance	38
4.4.9	Receiver spurious emissions	38

4.4.9.1	Applicability.....	38
4.4.9.2	Description.....	38
4.4.9.3	Limits.....	38
4.4.9.4	Conformance.....	38
4.5	Requirements for polite spectrum access	38
4.5.1	Listen before talk	38
4.5.1.1	Applicability.....	38
4.5.1.2	Description.....	38
4.5.1.3	Limits.....	39
4.5.1.4	Conformance.....	39
4.5.2	Short control signalling transmissions.....	39
4.5.2.1	Applicability.....	39
4.5.2.2	Description.....	39
4.5.2.3	Limits.....	40
4.5.2.4	Conformance.....	41
4.6	Functional requirements	41
4.6.1	General considerations.....	41
4.6.2	Network access point.....	41
4.6.2.1	Applicability.....	41
4.6.2.2	Description.....	41
4.6.2.3	Limits.....	41
4.6.2.4	Conformance.....	41
5	Testing for compliance with technical requirements.....	42
5.1	Environmental conditions for testing	42
5.2	General conditions for testing	42
5.2.1	General considerations.....	42
5.2.2	Presentation of equipment for testing purposes.....	42
5.2.2.1	General Considerations	42
5.2.2.2	Choice of model for testing.....	42
5.2.2.2.1	General considerations	42
5.2.2.2.2	EUT with an external RF connector.....	42
5.2.2.2.3	EUT without an external RF connector.....	43
5.2.2.3	Testing of modular equipment	43
5.2.2.4	Transmitter shut-off facility	43
5.2.2.5	Battery saving circuit	43
5.2.2.6	Test power source	44
5.2.2.6.1	General considerations.....	44
5.2.2.6.2	External test power source.....	44
5.2.2.6.3	Internal test power source.....	44
5.2.3	Normal and extreme test conditions.....	44
5.2.3.1	Normal temperature and humidity	44
5.2.3.2	Extreme temperatures.....	44
5.2.3.2.1	Procedure for tests at extreme temperatures	44
5.2.3.2.2	Procedure for equipment designed for continuous operation	45
5.2.3.2.3	Procedure for equipment designed for intermittent operation	45
5.2.3.2.4	Extreme temperature ranges	45
5.2.3.3	Normal test power source.....	45
5.2.3.3.1	Mains voltage	45
5.2.3.3.2	Regulated lead-acid battery power sources	45
5.2.3.3.3	Other power sources	45
5.2.3.4	Extreme test source voltages.....	46
5.2.3.4.1	Mains voltage	46
5.2.3.4.2	Regulated lead-acid battery power sources	46
5.2.3.4.3	Power sources using other types of batteries.....	46
5.2.3.4.4	Other power sources	46
5.2.4	Conducted measurements	46
5.2.4.1	Artificial antenna.....	46
5.2.4.2	Voltage Standing Wave Ratio (VSWR).....	46
5.2.5	Radiated measurements	46
5.2.6	Measuring receiver	47
5.2.6.1	General considerations	47

5.2.6.2	Reference Bandwidth	47
5.2.7	Transmitter test signals	47
5.2.8	Applicable measurement methods	48
5.2.9	Modes of operation	49
5.2.9.1	Test mode	49
5.2.9.2	Transmitter operation	49
5.2.9.3	Testing of multi-frequency or channel agile equipment	50
5.2.9.4	Non-uniform maximum transmit power	50
5.3	Conformance methods of measurement for transmitters	50
5.3.1	Frequency drift	50
5.3.1.1	Test conditions	50
5.3.1.2	Measurement procedure	51
5.3.2	Operating frequencies	52
5.3.2.1	Test conditions	52
5.3.2.2	Measurement procedure	52
5.3.3	Effective radiated power	53
5.3.3.1	Test conditions	53
5.3.3.2	Radiated measurement procedure	53
5.3.3.3	Conducted measurement procedure	55
5.3.4	Transient power	55
5.3.4.1	Test conditions	55
5.3.4.2	Measurement procedure	56
5.3.5	Occupied bandwidth	57
5.3.5.1	Test conditions	57
5.3.5.2	Measurement procedure	57
5.3.6	Unwanted emissions in the out-of-band domain	59
5.3.6.1	Test conditions	59
5.3.6.2	Measurement procedure	60
5.3.7	Unwanted emissions in the spurious domain	61
5.3.7.1	Test conditions	61
5.3.7.2	Radiated measurement	62
5.3.7.3	Cabinet radiation measurement	62
5.3.7.4	Conducted measurement	62
5.3.7.5	Measurement procedure	62
5.3.7.5.1	Conducted measurement	62
5.3.7.5.2	Radiated measurement	63
5.3.8	Frequency stability under low-voltage conditions	64
5.3.8.1	Test conditions	64
5.3.8.2	Measurement procedure	64
5.3.9	Duty cycle and transmission timing	65
5.3.9.1	Long term behaviour	65
5.3.9.1.1	Test conditions	65
5.3.9.1.2	Measurement procedure	65
5.3.9.2	Short term behaviour	66
5.3.9.2.1	Test conditions	66
5.3.9.2.2	Measurement procedure	66
5.3.10	Automatic/adaptive power control	67
5.3.10.1	Test conditions	67
5.3.10.2	Conducted measurement procedure	67
5.3.10.3	Radiated measurement procedure	68
5.3.10.4	Measurement procedure	68
5.4	Conformance test suites for receivers	69
5.4.1	Receiver sensitivity	69
5.4.1.1	Test conditions	69
5.4.1.2	Radiated measurement	69
5.4.1.3	Conducted measurement	72
5.4.1.4	Measurement procedure	72
5.4.2	Receiver maximum input signal level	73
5.4.2.1	Test conditions	73
5.4.2.2	Radiated measurement	73
5.4.2.3	Conducted measurement	73
5.4.2.4	Measurement procedure	74

5.4.3	Clear channel assessment threshold	74
5.4.3.1	Test conditions	74
5.4.3.2	Radiated measurement	75
5.4.3.3	Conducted measurement	75
5.4.3.4	Measurement procedure	76
5.4.4	Co-channel rejection	77
5.4.4.1	Test conditions	77
5.4.4.2	Measurement procedure	77
5.4.5	Adjacent channel selectivity	78
5.4.5.1	Test conditions	78
5.4.5.2	Measurement procedure	78
5.4.6	Blocking and spurious response rejection.....	79
5.4.6.1	Test conditions	79
5.4.6.2	Measurement procedure	79
5.4.7	Intermodulation rejection.....	80
5.4.7.1	Test conditions	80
5.4.7.2	Radiated measurement procedure	81
5.4.7.3	Conducted measurement procedure	82
5.4.7.4	Measurement procedure	83
5.4.8	Receiver spurious emissions	83
5.4.8.1	Test conditions	83
5.4.8.2	Radiated measurement	84
5.4.8.3	Cabinet radiation measurement.....	84
5.4.8.4	Conducted measurement	84
5.4.8.5	Measurement procedure	84
5.4.8.5.1	Conducted measurement.....	84
5.4.8.5.2	Radiated measurement.....	85
5.5	Conformance test suites for polite spectrum access.....	85
5.5.1	Listen before talk	85
5.5.1.1	Test conditions	85
5.5.1.2	Measurement procedure	86
5.5.2	Short control signalling transmissions.....	87
5.5.2.1	Test conditions	87
5.5.2.2	Measurement procedure	87
5.6	Conformance test suites for functional requirements	88
5.6.1	General test conditions.....	88
5.6.2	Network access point.....	88
5.6.2.1	Test conditions	88
5.6.2.2	Measurement Procedure.....	89

Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU91

A.0	General information	91
A.1	Equipment Type 1a terminal nodes.....	91
A.2	Equipment Type 1b network nodes.....	92
A.3	Equipment Type 1c network access points	93

Annex B (normative): Test sites and arrangements for radiated measurement95

B.1	General considerations	95
B.2	Radiation test sites.....	95
B.2.1	Open Area Test Site (OATS)	95
B.2.2	Semi Anechoic Room.....	96
B.2.3	Fully Anechoic Room (FAR).....	97
B.2.4	Measurement Distance	98
B.3	Antennae.....	99
B.3.1	General considerations	99
B.3.2	Measurement antenna.....	99

B.3.3	Substitution antenna	99
B.4	Guidance on the use of radiation test sites	100
B.4.1	General considerations	100
B.4.2	Power supplies for the battery powered EUT	100
B.4.3	Site preparation	100
B.5	Coupling of signals.....	101
B.5.1	General	101
B.5.2	Data signals	101
B.6	Measurement procedures for radiated measurement	101
B.6.1	General considerations	101
B.6.2	Radiated measurements in an OATS or SAR.....	101
B.6.3	Radiated measurements in a FAR	102
B.6.4	Substitution measurement	102
B.6.5	Radiated measurement methods for receivers	103
Annex C (normative):	Test fixture	104
C.1	General considerations	104
C.2	Validation of the test-fixture in the temperature chamber.....	105
C.3	Mode of use.....	106
Annex D (informative):	Maximum measurement uncertainty	107
Annex E (normative):	Transmission bandwidth.....	108
Annex F (normative):	T_{On} time measurements	109
F.1	Measurement procedure	109
F.2	T _{Disregard} procedure	109
Annex G (normative):	General receiver test case procedure	111
G.1	Test procedure	111
G.1.0	General requirements	111
G.1.1	Radiated measurement	111
G.1.2	Conducted measurement	112
G.1.3	Minimum wanted signal level setup	112
G.1.4	High wanted signal level setup.....	112
Annex H (normative):	General transmitter test case procedure.....	113
H.1	Test procedure where use of a test fixture is permitted.....	113
H.1.0	General requirements	113
H.1.1	Radiated measurement	113
H.1.2	Conducted measurement	113
H.1.3	Alternate conducted measurement	113
H.2	Test procedure where use of a test fixture is not permitted.....	113
H.2.0	General requirements	113
H.2.1	Radiated measurement	113
H.2.2	Conducted measurement	114
Annex I (informative):	Selection of receiver parameters.....	115
I.1	Receiver parameters as listed in ETSI EG 203 336 (V1.1.1).....	115
I.1.1	Receiver sensitivity	115
I.1.2	Adjacent channel selectivity.....	115
I.1.3	Blocking	115
I.1.4	Co-channel rejection.....	115
I.1.5	Spurious response rejection.....	115
I.1.6	Intermodulation	115

I.1.7	Dynamic range	116
I.1.8	Reciprocal mixing	116
I.1.9	Desensitisation	116
I.1.10	Signal interferer handling	116
I.2	Other receiver parameters	116
I.2.1	CCA threshold.....	116
Annex J (informative):	Properties of equipment under test.....	117
Annex K (informative):	Bibliography.....	118
Annex L (informative):	Change History	119
History		120

iTeh STANDARD PREVIEW
 (standards.iteh.ai)
 Full standard:
<https://standards.iteh.ai/catalog/standards/sist/8e5696b7-86fb-49a8-9acd-143345904634/etsi-en-303-204-v3.1.0-2020-12>

List of figures

Figure 1: Adjacent channel definitions.....	21
Figure 2: Signal Occupied Bandwidth	22
Figure 3: Transmission definitions.....	23
Figure 4: Out-of-band domain for operating channel.....	29
Figure 5: Out-of-band domain for operating frequency band.....	30
Figure 6: Spectrum mask for unwanted emissions in the spurious domain.....	31
Figure 7: SCS dialog timing constraints.....	40
Figure 8: APC conducted measurement setup.....	68
Figure 9: APC radiated measurement setup	68
Figure 10: Conducted clear channel assessment threshold measurement arrangement.....	75
Figure 11: Radiated clear channel assessment threshold measurement arrangement.....	75
Figure 12: Receiver intermodulation rejection radiated measurement arrangement	81
Figure 13: Receiver intermodulation rejection conducted measurement arrangement.....	82
Figure 14: SCS transmissions measurement arrangement.....	87
Figure 15: Network access point analyser arrangement.....	89
Figure B.1: A typical Open Area Test Site.....	96
Figure B.2: A typical Semi Anechoic Room.....	97
Figure B.3: A typical Fully Anechoic Room.....	98
Figure B.4: Measurement arrangement No.1	102
Figure C.1: Test fixture	104
Figure C.2: Validation of test set-up without EUT	105
Figure C.3: Validation of test set-up with EUT in place	106
Figure C.4: Test of EUT.....	106
Figure F.1: Power samples reference timing.....	109
Figure F.2: $T_{\text{Disregard}}$	109
Figure G.1: Conducted test measurement arrangement.....	111
Figure G.2: Radiated test measurement arrangement.....	111

List of tables

Table 1: Operating frequency bands.....	19
Table 2: Frequency drift limits	26
Table 3: Operating frequency and channel spacing error limits	27
Table 4: Channel spacing limits	27
Table 5: Effective radiated power limits	27
Table 6: Transmitter transient power limits	28
Table 7: Occupied bandwidth limits.....	28
Table 8: Emission limits in the out-of-band domain	30
Table 9: Spurious domain emission limits	31
Table 10: Frequency stability under low voltage conditions limits.....	32
Table 11: Duty cycle parameters.....	32
Table 12: Transmission timing parameters	32
Table 13: Duty cycle limits	33
Table 14: Transmission timing limits.....	33
Table 15: APC power limit	34
Table 16: Limits for receiver sensitivity	34
Table 17: Limits for receiver maximum input signal level	35
Table 18: CCA threshold limit	35
Table 19: Co-channel rejection limit.....	36
Table 20: Adjacent channel selectivity limit.....	36
Table 21: Limits for receiver blocking.....	37
Table 22: Receiver spurious response rejection limits	37
Table 23: Receiver intermodulation rejection limits	38
Table 24: Receiver spurious emission limits.....	38
Table 25: Limits for listen before talk requirement.....	39
Table 26: Limits for SCS transmissions	41
Table 27: Network access point limits	41
Table 28: Resolution bandwidth for the measuring receiver.....	47
Table 29: Permitted test signals.....	48
Table 30: Applicable test methods	49
Table 31: Specific test procedures.....	50
Table 32: Information recorded in the test report for frequency drift	51
Table 33: Test parameters for operating frequencies measurement	52

Table 34: Information recorded in the test report for operating frequencies	52
Table 35: Test parameters for effective radiated power measurement	53
Table 36: Information recorded in the test report for effective radiated power under normal test conditions	54
Table 37: Information recorded in the test report for effective radiated power under extreme test conditions.....	55
Table 38: Information recorded in the test report for effective radiated power.....	55
Table 39: Measurement offsets & RBW for transient power measurement	56
Table 40: Test parameters for transient power measurement	56
Table 41: Information recorded in the test report for transmitter transient power	57
Table 42: Test parameters for occupied bandwidth measurement	57
Table 43: Information recorded in the test report for occupied bandwidth	58
Table 44: Information recorded in the test report for occupied bandwidth	59
Table 45: Test parameters for upper out-of-band measurement.....	60
Table 46: Test parameter setting for lower out-of-band measurement.....	60
Table 47: Information recorded in the test report for OOB emissions	60
Table 48: Test parameter setting for intermediate out-of-band measurement	61
Table 49: Information recorded in the test report for OOB emissions	61
Table 50: Conducted spurious radiations measurement frequency range	62
Table 51: Radiated spurious radiations measurement frequency range.....	63
Table 52: Information recorded in the test report for unwanted emissions in the spurious domain.....	64
Table 53: Test parameters for frequency stability under low voltage conditions measurement.....	64
Table 54: Information recorded in the test report for frequency stability under low voltage conditions	65
Table 55: Test parameters settings for long term behaviour measurement	65
Table 56: Information recorded in the test report for long term behaviour	66
Table 57: Test parameters settings for short term behaviour measurement	66
Table 58: Information recorded in the test report for short term behaviour	67
Table 59: Test parameters settings for automatic/adaptive power control measurement	68
Table 60: Information recorded in the test report for automatic/adaptive power control.....	69
Table 61: Information recorded in the test report for sensitivity under normal test conditions.....	70
Table 62: Information recorded in the test report for sensitivity under extreme test conditions	72
Table 63: Information recorded in the test report for sensitivity	73
Table 64: Information recorded in the test report for maximum input signal level.....	74
Table 65: Test parameters settings for CCA threshold measurement.....	76
Table 66: Information recorded in the test report for CCA threshold	77
Table 67: Information recorded in the test report for co-channel rejection.....	78
Table 68: Information recorded in the test report for adjacent channel selectivity	78

Table 69: Information recorded in the test report for spurious response rejection	80
Table 70: Information recorded in the test report for blocking	80
Table 71: Test parameters settings for receiver intermodulation measurement	81
Table 72: Information recorded in the test report for receiver intermodulation rejection	83
Table 73: Receiver spurious emissions measurement frequency range - conducted	84
Table 74: Information recorded in the test report for receiver spurious emissions	85
Table 75: Receiver spurious emissions measurement frequency range - radiated	85
Table 76: Test parameters settings for listen before talk measurement	86
Table 77: Information recorded in the test report for LBT	87
Table 78: Information recorded in the test report for SCS transmissions	88
Table 79: Test parameters settings for NAP observations	89
Table 80: Information recorded in the test report for NAP	90
Table A.1: Relationship between the present document equipment Type 1a and the essential requirements of Directive 2014/53/EU	91
Table A.2: Relationship between the present document equipment Type 1b and the essential requirements of Directive 2014/53/EU	92
Table A.3: Relationship between the present document equipment Type 1c and the essential requirements of Directive 2014/53/EU	93
Table D.1: Maximum measurement uncertainty	107
Table E.1: TBW for values of OBW	108