



SLOVENSKI STANDARD SIST EN 300 113 V3.1.1:2020

01-september-2020

Storitev kopenskih mobilnih komunikacij - Radijska oprema za prenos podatkov (oziroma govora), ki uporablja modulacijo s konstantno ali nekonstantno ovojnico in ima antenski priključek

Land Mobile Service - Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 113 V3.1.1:2020](https://standards.iteh.ai/catalog/standards/sist/bc100e83-be38-4479-b595-c8925503493e/sist-en-300-113-v3-1-1-2020)

[https://standards.iteh.ai/catalog/standards/sist/bc100e83-be38-4479-b595-](https://standards.iteh.ai/catalog/standards/sist/bc100e83-be38-4479-b595-c8925503493e/sist-en-300-113-v3-1-1-2020)

[c8925503493e/sist-en-300-113-v3-1-1-2020](https://standards.iteh.ai/catalog/standards/sist/bc100e83-be38-4479-b595-c8925503493e/sist-en-300-113-v3-1-1-2020)

Ta slovenski standard je istoveten z: ETSI EN 300 113 V3.1.1 (2020-06)

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.070.01	Mobilni servisi na splošno	Mobile services in general

SIST EN 300 113 V3.1.1:2020 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 113 V3.1.1:2020](https://standards.iteh.ai/catalog/standards/sist/bc100e83-be38-4479-b595-c8925503493e/sist-en-300-113-v3-1-1-2020)

<https://standards.iteh.ai/catalog/standards/sist/bc100e83-be38-4479-b595-c8925503493e/sist-en-300-113-v3-1-1-2020>

ETSI EN 300 113 V3.1.1 (2020-06)



**Land Mobile Service;
Radio equipment intended for the transmission of data
(and/or speech) using constant or non-constant
envelope modulation and having an antenna connector**

SIST EN 300 113 V3.1.1:2020
<https://standards.iteh.ai/catalog/standards/sist/bc100e83-be38-4479-b595-c8925503493e/sist-en-300-113-v3-1-1-2020>

Reference

REN/ERM-TGDMR-377

Keywordsantenna, data, mobile, PMR, radio, regulation,
speech, TDD, TDMA**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Important notice

<https://standards.iteh.ai/catalog/standards/sist/bc100e83-be38-4479-b595-c02531349e/sist-en-300-113-v3-1-1-2020>
The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	10
3 Definition of terms, symbols and abbreviations.....	10
3.1 Terms.....	10
3.2 Symbols.....	12
3.3 Abbreviations	12
4 General and operational requirements.....	13
4.1 General	13
4.1.1 Environmental profile	13
4.1.2 Choice of model for testing	13
4.2 Mechanical and electrical design.....	13
4.2.1 General.....	13
4.2.2 Controls	13
4.2.3 Transmitter shut-off facility.....	14
4.3 Testing using bit streams or messages.....	14
4.4 Measuring continuous mode equipment.....	14
4.5 Measuring discontinuous mode equipment.....	14
4.6 Constant and non-constant envelope modulation.....	14
4.7 Combined full bandwidth analogue speech/full bandwidth digital equipment.....	14
5 Test conditions, power sources and ambient temperatures.....	15
5.1 Normal and extreme test conditions.....	15
5.2 Test power source.....	15
5.3 Normal test conditions.....	16
5.3.1 Normal temperature and humidity	16
5.3.2 Normal test power source	16
5.3.2.1 Mains voltage	16
5.3.2.2 Regulated lead-acid battery power sources used on vehicles.....	16
5.3.2.3 Other power sources.....	16
5.4 Extreme test conditions	16
5.4.1 Extreme temperatures	16
5.4.2 Extreme test source voltages.....	17
5.4.2.1 Mains voltage.....	17
5.4.2.2 Regulated lead-acid battery power sources used on vehicles.....	17
5.4.2.3 Power sources using other types of batteries.....	17
5.4.2.4 Other power sources.....	17
5.5 Procedure for tests at extreme temperatures.....	17
5.5.0 Thermal balance.....	17
5.5.1 Procedure for equipment designed for continuous transmission.....	17
5.5.2 Procedure for equipment designed for intermittent transmission	18
5.5.3 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment).....	18
6 General conditions of measurement	18
6.1 Arrangements for test signals applied to the receiver input.....	18
6.2 Receiver mute or squelch facility	18
6.3 Normal test signals (wanted and unwanted signals).....	18
6.3.1 Equipment measured as constant envelope angle modulation equipment	18
6.3.2 Equipment measured as non-constant envelope modulation equipment.....	19
6.4 Encoder for receiver measurements	20

6.5	Transceiver data interface.....	20
6.6	Impedance	20
6.7	Artificial antenna.....	20
6.8	Tests of equipment with a duplex filter	20
6.9	Facilities for access	21
6.9.1	Analogue access.....	21
6.9.2	Test points for bit stream measurements.....	21
6.9.3	Coupling arrangements	21
6.9.3.0	General	21
6.9.3.1	Arrangements for measurements with continuous bit streams	21
6.9.3.2	Arrangements for measurements with messages.....	21
6.10	Test site and general arrangements for measurements involving the use of radiated fields	22
6.11	Modes of operation of the transmitter for constant envelope equipment	22
6.12	Multi-rate equipment	22
7	Technical characteristics of the transmitter	22
7.1	Frequency error	22
7.1.0	General.....	22
7.1.1	Definition.....	22
7.1.2	Method of measurement	22
7.1.3	Limits.....	23
7.2	Transmitter power (conducted)	23
7.2.1	Definitions	23
7.2.1.1	Equipment measured as constant envelope angle modulation equipment.....	23
7.2.1.2	Equipment measured as non-constant envelope modulation equipment	23
7.2.2	Method of measurement	24
7.2.2.1	Equipment measured as constant envelope angle modulation equipment.....	24
7.2.2.2	Equipment measured as non-constant envelope modulation equipment	24
7.2.3	Limits.....	24
7.3	Maximum Effective radiated power	25
7.3.1	Definition.....	25
7.3.1.0	General	25
7.3.1.1	Equipment measured as constant envelope angle modulation equipment.....	25
7.3.1.2	Equipment measured as non-constant envelope modulation equipment	25
7.3.2	Methods of measurement	25
7.3.2.0	General	25
7.3.2.1	Equipment measured as constant envelope angle modulation equipment.....	27
7.3.2.2	Equipment measured as non-constant envelope modulation equipment	28
7.3.3	Limits.....	29
7.4	Adjacent and alternate channel power	30
7.4.1	Definition.....	30
7.4.2	Method of measurement	30
7.4.3	Limits.....	31
7.5	Unwanted emissions in the spurious domain.....	32
7.5.1	Definition.....	32
7.5.2	Method of measuring the power level	32
7.5.2.0	General	32
7.5.2.1	Equipment measured as constant envelope angle modulation equipment.....	33
7.5.2.2	Equipment measured as non-constant envelope modulation equipment	33
7.5.3	Method of measuring the effective radiated power.....	33
7.5.3.0	General	33
7.5.3.1	Equipment measured as constant envelope angle modulation equipment.....	34
7.5.3.2	Equipment measured as non-constant envelope modulation equipment	34
7.5.4	Limits.....	36
7.6	Intermodulation attenuation.....	37
7.6.1	Definition.....	37
7.6.2	Method of measurement	37
7.6.3	Limits.....	38
7.7	Transmitter attack time.....	38
7.7.1	Definition.....	38
7.7.2	Method of measurement	39
7.7.3	Limit	39

7.8	Transmitter release time	39
7.8.1	Definition	39
7.8.2	Method of measurement	40
7.8.3	Limits	40
7.9	Transient behaviour of the transmitter	40
7.9.1	Definitions	40
7.9.2	Timings, frequencies and powers	41
7.9.3	Methods of measurement	45
7.9.3.0	General	45
7.9.3.1	Time domain measurements of power and frequency	45
7.9.3.2	Test arrangement and characteristics of the FM modulation meter	46
7.9.3.3	Adjacent channel transient power measurements	46
7.9.3.3.1	Definition	46
7.9.3.3.2	Measurement method for constant envelope angle modulation equipment	46
7.9.3.3.3	Measurement method for non-constant envelope modulation equipment	47
7.9.3.3.4	Alternative measurement method using a spectrum analyser	48
7.9.3.4	Characteristics of the adjacent channel transient power measuring device	49
7.9.4	Limits	49
7.9.4.0	General	49
7.9.4.1	Time domain analysis of power and frequency for constant envelope transmissions	50
7.9.4.2	Adjacent and alternate channel transient power	50
7.9.4.2.1	Equipment measured as constant envelope angle modulation equipment	50
7.9.4.2.2	Equipment measured as non-constant envelope modulation equipment	50
8	Technical characteristics of the receiver	51
8.1	Maximum usable sensitivity (conducted)	51
8.1.1	Definition	51
8.1.2	Method of measurement	51
8.1.2.1	Method of measurement with continuous bit streams	51
8.1.2.2	Method of measurement with messages	52
8.1.2.3	Method of measurement with packets	52
8.1.3	Limits	53
8.2	Average usable sensitivity (field strength)	53
8.2.1	Definition	53
8.2.2	Method of measurement	53
8.2.3	Limits	54
8.3	Level of the wanted signal for the degradation measurements	55
8.4	Error behaviour at high input levels	55
8.4.1	Definition	55
8.4.2	Method of measurement	56
8.4.2.1	Method of measurement with continuous bit streams	56
8.4.2.2	Method of measurement with messages	56
8.4.2.3	Method of measurement with packets	57
8.4.3	Limits	57
8.5	Co-channel rejection	57
8.5.1	Definition	57
8.5.2	Method of measurement	57
8.5.2.1	Method of measurement with continuous bit streams	57
8.5.2.2	Method of measurement with messages	58
8.5.2.3	Method of measurement with packets	59
8.5.3	Limits	60
8.6	Adjacent channel selectivity	60
8.6.1	Definition	60
8.6.2	Method of measurement	61
8.6.2.1	Method of measurement with continuous bit streams	61
8.6.2.2	Method of measurement with messages	62
8.6.2.3	Method of measurement with packets	63
8.6.3	Limits	64
8.7	Spurious response rejection	64
8.7.1	Definition	64
8.7.2	Introduction to the method of measurement	64
8.7.3	Method of search over the "limited frequency range"	65

8.7.4	Method of measurement with continuous bit streams.....	66
8.7.5	Method of measurement with messages	66
8.7.6	Method of measurement with packets	67
8.7.7	Limits.....	68
8.8	Intermodulation response rejection	68
8.8.1	Definition.....	68
8.8.2	Method of measurement	68
8.8.2.1	Method of measurement with continuous bit streams	68
8.8.2.2	Method of measurement with messages.....	69
8.8.2.3	Method of measurement with packets.....	70
8.8.3	Limits.....	71
8.9	Blocking or desensitization	71
8.9.1	Definition.....	71
8.9.2	Method of measurement	71
8.9.2.1	Method of measurement with continuous bit streams	71
8.9.2.2	Method of measurement with messages.....	72
8.9.2.3	Method of measurement with packets.....	73
8.9.3	Limits.....	74
8.10	Spurious radiations	74
8.10.1	Definition.....	74
8.10.2	Method of measuring the power level	74
8.10.3	Method of measuring the effective radiated power.....	75
8.10.4	Limits.....	76
9	Duplex operation	77
9.1	Receiver desensitization (with simultaneous transmission and reception).....	77
9.1.1	Definition.....	77
9.1.2	Desensitization measured with continuous bit streams.....	78
9.1.2.1	Method of measurement when the equipment has a duplex filter.....	78
9.1.2.2	Method of measurement when the equipment has to operate with two antennas.....	79
9.1.3	Limits.....	80
9.2	Receiver spurious response rejection (with simultaneous transmission and reception)	80
9.2.1	Definition.....	80
9.2.2	Method of measurement	81
9.2.3	Limits.....	82
10	Testing for compliance with technical requirements.....	82
10.1	Test conditions, power supply and ambient temperatures	82
10.2	Interpretation of the measurement results	83
Annex A (informative):	Void	84
Annex B (normative):	Radiated measurement.....	85
B.1	Test sites and general arrangements for measurements involving the use of radiated fields	85
B.1.0	General	85
B.1.1	Anechoic chamber.....	85
B.1.2	Anechoic chamber with a conductive ground plane.....	86
B.1.3	Open Area Test Site (OATS)	87
B.1.4	Test antenna.....	88
B.1.5	Substitution antenna	88
B.1.6	Measuring antenna	89
B.2	Guidance on the use of radiation test sites	89
B.2.0	General	89
B.2.1	Verification of the test site	89
B.2.2	Preparation of the EUT.....	89
B.2.3	Power supplies to the EUT.....	89
B.2.4	Volume control setting for analogue speech tests	89
B.2.5	Range length.....	90
B.2.6	Site preparation	90
B.3	Coupling of signals.....	91
B.3.0	General	91

B.3.1	Data signals	91
B.3.2	Speech and analogue signals	91
B.3.2.0	General.....	91
B.3.2.1	Acoustic coupler description.....	91
B.3.2.2	Calibration	92
Annex C (normative): Specification for some particular measurement arrangements.....		93
C.1	Power measuring receiver specification.....	93
C.1.0	General	93
C.1.1	IF filter	93
C.1.2	Attenuation indicator.....	94
C.1.3	RMS value indicator.....	94
C.1.4	Oscillator and amplifier.....	94
C.2	Spectrum analyser specification.....	95
C.2.1	Adjacent and alternate channel power measurement.....	95
C.2.2	Unwanted emissions measurement.....	95
C.3	Integrating and power summing device	95
History		96

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 113 V3.1.1:2020](https://standards.iteh.ai/catalog/standards/sist/bc100e83-be38-4479-b595-c8925503493e/sist-en-300-113-v3-1-1-2020)

<https://standards.iteh.ai/catalog/standards/sist/bc100e83-be38-4479-b595-c8925503493e/sist-en-300-113-v3-1-1-2020>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

(standards.iteh.ai)

National transposition dates	
Date of adoption of this EN:	9 June 2020
Date of latest announcement of this EN (doa):	30 September 2020
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2021
Date of withdrawal of any conflicting National Standard (dow):	31 May 2022

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document covers the technical requirements for radio transmitters and receivers used in stations in the Private Mobile Radio (PMR) service.

It applies to use in the land mobile service, operating on radio frequencies between 30 MHz and 1 GHz, with channel separations of 12,5 kHz, 20 kHz and 25 kHz, intended for speech and/or data.

Table 1: Radiocommunications service frequency bands

	Radiocommunications service frequency bands
Transmit	30 MHz to 1 000 MHz
Receive	30 MHz to 1 000 MHz

It applies to equipment for continuous and/or discontinuous transmission of data and/or digital speech.

The equipment comprises a transmitter and associated encoder and modulator and/or a receiver and associated demodulator and decoder.

The types of equipment covered by the present document are as follows:

- 1) base station (equipment fitted with an antenna connector, intended for use in a fixed location);
- 2) mobile station (equipment fitted with an antenna connector, normally used in a vehicle or as a transportable); and
- 3) those handportable stations:
 - a) fitted with an antenna connector; or
 - b) without an external antenna connector, but fitted with a permanent internal or a temporary internal 50 Ω Radio Frequency (RF) connector which allows access to the transmitter output and the receiver input.

Handportable equipment without an external or internal RF connector and without the possibility of having a temporary internal 50 Ω RF connector is not covered by the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 086 (V2.1.2) (08-2016): "Land Mobile Service; Radio equipment with an internal or external RF connector intended primarily for analogue speech; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
- [2] ETSI EN 300 390 (V2.1.1) (03-2016): "Land Mobile Service; Radio equipment intended for the transmission of data (and speech) and using an integral antenna; Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".

- [3] Void.
- [4] Recommendation ITU-T O.153 (10/1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [5] IEEE/ANSI C63.5 (2017): "American National Standard for Electromagnetic Compatibility -- Radiated Emission Measurements in Electromagnetic Interference (EMI) Control -- Calibration and Qualification of Antennas (9 kHz to 40 GHz)".
- [6] Void.
- [7] CEPT/ERC/Recommendation 74-01E: "Unwanted emissions in the spurious domain" (Siófok 1998, Nice 1999, Sesimbra 2002, Hradec Kralove 2005).
- [8] Void.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 102 273 (V1.2.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement of Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.2] Void. <https://standards.iteh.ai/catalog/standards/sist/bc100e83-be38-4479-b595-38925504f95c/sist-en-300-113-v3-1-1-2020>
- [i.3] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.4] ETSI EN 300 793 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Presentation of equipment for type testing".
- [i.5] ETSI TR 100 028 (V1.4.1) (12-2001) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.6] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.7] IEC 60489-3 (1988): "Methods of measurement for radio equipment used in the mobile services. Part 3: Receivers for A3E or F3E emissions".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

50 Ω: 50 ohm non-reactive impedance

adaptive bit rate equipments: equipments that change bit rate such that a bit rate that is compliant with the present document is always selected if communication is not possible at other bit rates

adjacent channels: channel offset from the wanted channel by the channel spacing (see figure 1)

alternate channels: two channels offset from the wanted channel by double the channel spacing (see figure 1)




Figure 1: Adjacent and alternate channel definitions

angle modulation: either phase modulation or frequency modulation

base station: equipment fitted with an antenna connector, for use with an external antenna, and intended for use in a fixed location

bit: binary digit

block: smallest quantity of information that is sent over the radio channel

NOTE: A constant number of useful bits are always sent together with the corresponding redundancy bits.

burst or transmission (physical): one or several packets transmitted between power on and power off of a particular transmitter

conducted measurements: measurements which are made using direct 50 Ω connection to the equipment under test

data transmission systems: systems which transmit and/or receive data and/or digitized voice

handportable station: equipment either fitted with an antenna connector or integral antenna, or both, normally used on a stand-alone basis, to be carried on a person or held in the hand

integral antenna: antenna designed to be connected to the equipment without the use of a 50 Ω external connector and considered to be part of the equipment

NOTE: An integral antenna may be fitted internally or externally to the equipment.

manufacturer: any natural or legal person who manufactures radio equipment or has radio equipment designed or manufactured, and markets that equipment under his name or trade mark

message: user data to be transferred in one or more packets in a session

mobile station: mobile equipment fitted with an antenna connector, for use with an external antenna, normally used in a vehicle or as a transportable station

multi-rate equipment: equipment that supports multiple (i.e. two or more) on-air bit rates or symbol rates

packet: one block or a contiguous stream of blocks sent by one (logical) transmitter to one particular receiver or one particular group of receivers

Peak Envelope Power (PEP): mean power delivered to the artificial antenna during a radio frequency cycle at the highest crest of the modulation envelope

radiated measurements: measurements which involve the absolute measurement of a radiated field

session: set of inter-related exchange of packets occupying one or several windows or part thereof (if applicable)

NOTE: Corresponds to a complete interactive procedure for interchanging data between users, comprising initiation, data transmission and termination procedures. The session can be short (e.g. 2 packets), or long (e.g. one full page of text).

switching range: maximum frequency range, as specified by the manufacturer, over which the receiver or the transmitter can be operated within the alignment range without reprogramming or realignment

window: set of inter-related transmissions which may be limited in time by an appropriate access protocol and corresponding occupation rules

3.2 Symbols

For the purposes of the present document, the following symbols apply:

D-M0, D-M1, etc. names of signals defined in clause 6.3.1 and clause 6.3.2

NOTE: The symbols used in the clauses relating to transients and timings can be found in clause 7.9.1.

f_{I1}	1 st intermediate frequency
f_{I2}	2 nd intermediate frequency
f_{In}	n th intermediate frequency
f_l	frequency of the limited frequency range
f_{LO}	Local oscillator frequency
T_{max}	Maximum extreme test temperature
T_{min}	Minimum extreme test temperature
V_{max}	Maximum extreme test voltage
V_{min}	Minimum extreme test voltage

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ac	alternating current
BW	BandWidth
CBW	Channel BandWidth
CEPT	European Conference of Postal and Telecommunications administrations
CSP	Channel SeParation
CW	Continuous Wave
dB	decibel
dBc	decibels relative to the carrier power
dBm	dB relative to 1 mW in 50 ohms
dc	direct current
emf	electromotive force
EU	European Union
EUT	Equipment Under Test
FM	Frequency Modulation
FSK	Frequency Shift Keying
GMSK	Gaussian Minimum Shift Keying
IEC	International Electrotechnical Commission
IF	Intermediate Frequency
ITU-T	International Telecommunication Union - Telecommunication standardization sector
OATS	Open Area Test Site

PEP	Peak Envelope Power
PLL	Phase Locked Loop
PMR	Private Mobile Radio
PN	Pseudo Noise
RBW	Relative BandWidth
RF	Radio Frequency
rms	root mean square
Rx	Receiver
SINAD	Signal, Noise And Distortion
sr	switching range
Tx	Transmitter
VSWR	Voltage Standing Wave Ratio

4 General and operational requirements

4.1 General

4.1.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer, but as a minimum, shall be that specified in the test conditions contained in the present document.

4.1.2 Choice of model for testing

Stand-alone equipment shall be complete with any ancillary equipment needed for testing.

If an equipment has several optional features, considered not to affect the RF parameters, then the tests need only be performed on the equipment configured with the combination of features considered to be the most complex.

Where practicable, equipment to be tested shall provide a 50 Ω connector for conducted RF power level measurements.

In the case of integral antenna equipment, if the equipment does not have an internal permanent 50 Ω connector then it is permissible to use a second sample of the equipment with a temporary antenna connector fitted to facilitate testing. Any such modified sample shall not be used for any radiated measurements, except as noted in clause 5.5.3.

The performance of the equipment to be tested shall be representative of the performance of the corresponding production model.

Guidance on the presentation of equipment is also given in ETSI EN 300 793 [i.4].

4.2 Mechanical and electrical design

4.2.1 General

The equipment should be designed, constructed and manufactured in accordance with good engineering practice, and with the aim of avoiding harmful interference to other equipment and services.

4.2.2 Controls

Those controls, which if maladjusted, might increase the interfering potentialities of the equipment shall not be accessible for adjustment by the user.