

ETSI TS 151 021 V13.7.0 (2018-10)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Base Station System (BSS) equipment specification;
Radio aspects
(3GPP TS 51.021 version 13.7.0 Release 13)**



ReferenceRTS/TSGR-0651021vd70

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	9
1 Scope	10
2 References	10
3 Definitions, abbreviations, frequency bands and channels.....	12
3.1 Definitions	12
3.2 Abbreviations	14
3.3 Frequency bands and channels	15
3.3.1 Frequency bands	15
3.3.2 Channels and channel numbering	15
4 General test conditions and declarations	16
4.1 Output power and determination of power class	16
4.2 Specified frequency range	17
4.3 Frequency hopping	17
4.4 RF power control.....	18
4.5 Downlink discontinuous transmission (DTX)	18
4.6 Test environments	18
4.6.1 Normal test environment	18
4.6.2 Extreme test environment	18
4.6.2.1 Extreme temperature	19
4.6.3 Vibration.....	19
4.6.4 Power supply	19
4.7 Acceptable uncertainty of measurement equipment.....	19
4.8 Interpretation of measurement results	23
4.9 Selection of configurations for testing.....	24
4.10 BTS Configurations.....	24
4.10.1 Receiver diversity	24
4.10.2 Duplexers	24
4.10.3 Power supply options.....	25
4.10.4 Ancillary RF amplifiers	25
4.10.5 BSS using antenna arrays	25
4.10.6 BTS supporting 8-PSK modulation	26
4.10.7 BTS supporting additional modulations in EGPRS2	27
4.10.8 Supported Symbol Rate.....	27
4.10.9 Support of RTTI and/or FANR	27
4.10.10 Multicarrier BTS.....	27
4.10.11 Support of EC-GSM-IoT	28
5 Format and interpretation of tests.....	29
6 Transmitter	29
6.1 Static Layer 1 functions.....	30
6.1.1 Test purpose.....	30
6.1.2 Test case	30
6.1.3 Void	30
6.1.4 Conformance requirement	30
6.1.5 Requirement reference	30
6.2 Modulation accuracy	30
6.2.1 Test purpose.....	30
6.2.2 Test case	31
6.2.3 Void	32
6.2.4 Conformance requirement	32
6.2.5 Requirement reference	33

6.3	Mean transmitted RF carrier power and equivalent combined power	33
6.3.1	Test purpose	33
6.3.2	Test case	33
6.3.3	Void	35
6.3.4	Conformance requirement	35
6.3.5	Requirement reference	36
6.4	Transmitted RF carrier power versus time	36
6.4.1	Test purpose	36
6.4.2	Test case	36
6.4.3	Void	37
6.4.4	Conformance requirement	37
6.4.5	Requirement reference	41
6.5	Adjacent channel power	41
6.5.1	Spectrum due to modulation and wideband noise	42
6.5.1.1	Test purpose	42
6.5.1.2	Test case	42
6.5.1.3	Void	42
6.5.1.4	Conformance requirement	43
6.5.1.4.1	Normal BTS Minimum requirement	43
6.5.1.4.2	Multicarrier BTS Minimum requirement	43
6.5.1.4.3	Micro and Pico-BTS Minimum requirement	44
6.5.1.5	Requirement reference	45
6.5.2	Switching transients spectrum	45
6.5.2.1	Test purpose	45
6.5.2.2	Test case	45
6.5.2.3	Void	47
6.5.2.4	Conformance requirement	47
6.5.2.5	Requirement reference	47
6.6	Spurious emissions from the transmitter antenna connector	47
6.6.1	Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band	47
6.6.1.1	Test Purpose	47
6.6.1.2	Test Case	47
6.6.1.3	Void	48
6.6.1.4	Conformance requirement	48
6.6.1.5	Requirement Reference	48
6.6.2	Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band	48
6.6.2.1	Applicability (Phase 2)	48
6.6.2.1.1	Test Purpose	48
6.6.2.1.2	Test Case	48
6.6.2.1.3	Void	49
6.6.2.1.4	Conformance requirement	49
6.6.2.1.5	Requirement Reference	50
6.6.2.2	Applicability (Phase 2+)	50
6.6.2.2.1	Test Purpose	50
6.6.2.2.2	Test Case	50
6.6.2.2.3	Void	51
6.6.2.2.4	Conformance requirement	51
6.6.2.2.5	Requirement Reference	52
6.6.2.3	Applicability (Release 1999 and later releases GSM 400, GSM 900 and DCS 1800)	52
6.6.2.3.1	Test Purpose	52
6.6.2.3.2	Test Case	52
6.6.2.3.3	Void	53
6.6.2.3.4	Conformance requirement	53
6.6.2.3.5	Requirement Reference	53
6.6.2.4	Applicability (Release 4 and later releases GSM 700, GSM 850 and PCS 1900)	53
6.6.2.4.1	Test Purpose	53
6.6.2.4.2	Test Case	53
6.6.2.4.3	Void	54
6.6.2.4.4	Conformance requirement	54
6.6.2.4.5	Requirement Reference	54
6.6.2.5	Applicability (Release 7 and later releases GSM 400, T-GSM 810, GSM 900 and DCS 1800)	54

6.6.2.5.1	Test Purpose	54
6.6.2.5.2	Test Case	55
6.6.2.5.3	Void	56
6.6.2.5.4	Conformance requirement	56
6.6.2.5.5	Requirement Reference	56
6.6.2.5a	Applicability (Release 7 and later releases GSM 700, GSM 850 and PCS 1900)	56
6.6.2.5a.1	Test Purpose	57
6.6.2.5a.2	Test Case	57
6.6.2.5a.3	Void	57
6.6.2.5a.4	Conformance requirement	57
6.6.2.5a.5	Requirement Reference	58
6.6.2.6	Applicability (Release 8 and later releases GSM 400, T-GSM 810, GSM 900 and DCS 1800).....	58
6.6.2.6.1	Test Purpose	58
6.6.2.6.2	Test Case	58
6.6.2.6.3	Void	59
6.6.2.6.4	Conformance requirement	59
6.6.2.6.5	Requirement Reference	60
6.6.2.7	Applicability (Release 8 and later releases GSM 700, GSM 850 and PCS 1900)	60
6.6.2.7.1	Test Purpose	61
6.6.2.7.2	Test Case	61
6.6.2.7.3	Void	62
6.6.2.7.4	Conformance requirement	62
6.6.2.7.5	Requirement Reference	63
6.6.2.8	Applicability (Release 8 and later releases GSM 400, GSM 900 and DCS 1800).....	63
6.6.2.8.1	Test Purpose	63
6.6.2.8.2	Test Case	64
6.6.2.8.3	Void	65
6.6.2.8.4	Complete conformance.....	65
6.6.2.8.5	Requirement Reference	65
6.6.2.9	Applicability (Release 12 and later releases GSM 400, T-GSM 810, GSM 900, ER-GSM 900 and DCS 1800).....	65
6.6.2.9.1	Test Purpose	65
6.6.2.9.2	Test Case	65
6.6.2.9.3	Void	66
6.6.2.9.4	Conformance requirement	67
6.6.2.9.5	Requirement Reference	67
6.6.2.10	Applicability (Release 12 and later releases GSM 400, T-GSM 810, GSM 900 and DCS 1800).....	67
6.6.2.10.1	Test Purpose	67
6.6.2.10.2	Test Case	68
6.6.2.10.3	Void	69
6.6.2.10.4	Conformance requirement	69
6.6.2.10.5	Requirement Reference	70
6.6.2.11	Applicability (Release 12 and later releases GSM 400, GSM 900, ER-GSM 900 and DCS 1800).....	70
6.6.2.11.1	Test Purpose	70
6.6.2.11.2	Test Case	71
6.6.2.11.3	Void	72
6.6.2.11.4	Conformance requirement	72
6.6.2.11.5	Requirement Reference	72
6.7	Intermodulation attenuation (GSM 400, GSM 900, ER-GSM 900 and DCS 1800).....	72
6.7.1	Test purpose.....	72
6.7.2	Test case	72
6.7.3	Void	74
6.7.4	Conformance requirement	74
6.7.5	Requirement reference.....	75
6.8	Intra Base Station System intermodulation attenuation.....	76
6.8.1	Test purpose.....	76
6.8.2	Test case	76
6.8.3	Void	77
6.8.4	Conformance requirement	77
6.8.5	Requirement reference.....	77
6.9	Intra Base Station System intermodulation attenuation, MXM 850 and MXM 1900	78
6.9.1	Test purpose.....	78

6.9.2	Test cases	78
6.9.2.1	200 kHz carriers-only	78
6.9.2.2	200 kHz and ANSI-136 30 kHz carriers	78
6.9.3	Void	78
6.9.4	Conformance requirement	78
6.9.5	Requirement reference	79
6.10	Intra Base Station System intermodulation attenuation, PCS 1900, GSM 850 and GSM 700	79
6.10.1	Test purpose	79
6.10.2	Test case	79
6.10.3	Void	80
6.10.4	Conformance requirement	80
6.10.5	Requirement reference	80
6.11	Intermodulation attenuation (GSM 700, GSM 850, MXM 850, PCS 1900 and MXM 1900)	80
6.11.1	Test purpose	80
6.11.2	Test case	80
6.11.3	Void	82
6.11.4	Conformance requirement	82
6.11.5	Requirement reference	83
6.12	Wideband noise and intra BSS intermodulation attenuation in multicarrier operation	83
6.12.1	Test purpose	83
6.12.2	Test case	83
6.12.3	Void	86
6.12.4	Conformance requirement	86
6.12.5	Requirement reference	87
7	Receivers	88
7.1	Static Layer 1 receiver functions (nominal error ratios)	88
7.1.1	Test Purpose	88
7.1.2	Test Case	88
7.1.3	Void	92
7.1.4	Conformance requirement	92
7.1.5	Requirement Reference	92
7.2	Erroneous Frame Indication Performance	93
7.2.1	Test Purpose	93
7.2.2	Test Case	93
7.2.3	Void	94
7.2.4	Conformance requirement	94
7.2.5	Requirement reference	94
7.3	Static Reference Sensitivity Level	94
7.3.1	Test Purpose	94
7.3.2	Test Case	94
7.3.3	Void	100
7.3.4	Conformance requirement	100
7.3.5	Requirements Reference	105
7.4	Multipath Reference Sensitivity Level	105
7.4.1	Test Purpose	105
7.4.2	Test Case	105
7.4.3	Void	118
7.4.4	Conformance requirement	119
7.4.5	Requirement Reference	129
7.5	Reference interference level	129
7.5.1	Test Purpose	129
7.5.2	Test Case	129
7.5.3	Void	148
7.5.4	Conformance requirement	149
7.5.5	Requirements Reference	165
7.6	Blocking Characteristics	165
7.6.1	Test Purpose	165
7.6.2	Test Case	165
7.6.3	Void	172
7.6.4	Conformance requirement	173
7.6.5	Requirements reference	174

7.7	Intermodulation characteristics	174
7.7.1	Test Purpose.....	174
7.7.2	Test Case.....	174
7.7.3	Void	176
7.7.4	Conformance requirement	176
7.7.5	Requirement Reference.....	177
7.8	AM suppression.....	177
7.8.1	Test Purpose.....	177
7.8.2	Test Case.....	177
7.8.3	Void	179
7.8.4	Conformance requirement	179
7.8.5	Requirement Reference.....	180
7.9	Spurious emissions from the receiver antenna connector.....	180
7.9.1	Test Purpose.....	180
7.9.2	Test Case.....	180
7.9.3	Void	181
7.9.4	Conformance requirement	181
7.9.5	Requirement Reference.....	181
8	Radiated spurious emissions	181
8.1	Test Purpose	181
8.2	Test Case	182
8.3	Void.....	184
8.4	Conformance requirement.....	184
8.5	Requirement reference	184
9	Radio link management.....	185
9.1	General	185
9.2	Synchronization.....	185
9.2.1	Timing Tolerance.....	185
9.2.1.1	Test purpose	185
9.2.1.2	Test case.....	185
9.2.1.3	Void.....	186
9.2.1.4	Conformance requirement.....	186
9.2.1.5	Requirement reference	186
9.3	Frame structure.....	186
9.3.1	BCCH Multiframe	186
9.3.1.1	Test purpose	186
9.3.1.2	Test case.....	186
9.3.1.2a	Test case for EC-GSM-IoT.....	186
9.3.1.3	Void.....	187
9.3.1.4	Conformance requirement.....	187
9.3.1.5	Requirement reference	187
9.3.2	TDMA-frame structure	187
9.3.2.1	Test purpose	187
9.3.2.2	Test case.....	187
9.3.2.3	Void.....	187
9.3.2.4	Conformance requirement.....	187
9.3.2.5	Requirement reference	188
9.4	Radio link measurements	188
9.4.1	Signal Strength.....	188
9.4.1.1	Measurement Accuracy.....	188
9.4.1.1.1	Test purpose	188
9.4.1.1.2	Test case	188
9.4.1.1.3	Void.....	188
9.4.1.1.4	Conformance requirement	189
9.4.1.1.5	Requirement reference.....	190
9.4.1.2	Selectivity of signal strength measurements	190
9.4.1.2.1	Test purpose	190
9.4.1.2.2	Test case	190
9.4.1.2.3	Void.....	191
9.4.1.2.4	Conformance requirement	191

9.4.1.2.5	Requirement reference.....	191
9.4.2	Signal quality.....	191
9.4.2.1	Test purpose.....	191
9.4.2.2	Test case.....	191
9.4.2.3	Void.....	192
9.4.2.4	Conformance requirement.....	192
9.4.2.5	Requirement reference.....	193
9.4.3	Idle channel signal level.....	193
9.4.3.1	Test purpose.....	193
9.4.3.2	Test case.....	193
9.4.3.3	Void.....	194
9.4.3.4	Conformance requirement.....	194
9.4.3.5	Requirement reference.....	194
9.5	Adaptive frame alignment.....	194
9.5.1	Test purpose.....	194
9.5.2	Test case.....	194
9.5.3	Void.....	195
9.5.4	Conformance requirement.....	195
9.5.5	Requirement reference.....	196
Annex A (informative):	Testing of statistical parameters.....	197
A.1	General theoretical methodology.....	197
A.2	Detailed theoretical methodology.....	199
A.3	Limitations and corrections to the theoretical methodology.....	200
A.3.1	Independent errors.....	200
A.3.2	Gaussian distribution.....	200
A.3.3	Stationary random processes.....	200
A.3.4	Low error ratios.....	201
A.3.5	Total corrections.....	201
A.4	Alternative experimental methodology.....	201
A.5	Detailed definition of error events.....	202
Annex B (informative):	Description of special test equipment.....	203
B.1	Base Station System Test Equipment (BSSTE).....	203
B.1.1	Fading and multipath propagation simulator.....	203
B.2	Measurement set ups for TX intermodulation.....	203
B.2.1	Test set-up for Intermodulation Attenuation (6.7.).....	203
B.2.1.1	RX-Band.....	204
B.2.1.2	Outside RX Band.....	204
B.2.2	Test set-up for Intra BSS Intermodulation Attenuation (6.8.).....	204
B.2.2.1	RX-Band.....	205
B.2.2.2	TX-Band.....	205
Annex C (informative):	Number of samples needed for statistical testing.....	206
C.1	GSM 900; Number of samples for testing.....	206
C.2	DCS 1800; Number of Samples for Testing.....	226
Annex D (informative):	Change history.....	247
History.....		255

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

ETSI STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/3137cf0d-6844-4cc8-a485-69d5308242/etsi-ts-151-021-v13.7.0-2018-10>

1 Scope

The present document specifies the Radio Frequency (RF) test methods and conformance requirements for GSM 400, GSM 700, T-GSM 810, GSM 900, ER-GSM 900 and DCS 1800, PCS 1900, GSM 850, MXM 850 and MXM 1900 Base Station Systems (BSS)s. These have been derived from, and are consistent with, the core GSM specifications specified in the requirements reference subclause of each test with the exception that requirements expressed as a reference to regulatory documents (e.g. FCC) have not been included in the present document.

The present document is applicable to BSS meeting the requirements of either GSM Phase 2 or GSM Phase 2+. Unless otherwise stated, all tests are applicable to BSS meeting Phase 2 and/or Phase 2+ GSM requirements, because the requirements of the Phase 2 and Phase 2+ core GSM specifications which are referenced in the test are consistent. Most differences between Phase 2 and Phase 2+ requirements represent Phase 2+ features which are optional for the BSS to support.

Conformance requirements may be tested to verify all aspects of the performance of a BSS. These minimum requirements are intended to be used by manufacturers and operators to allow conformance and acceptance testing to be performed in a consistent manner; the tests to be performed should be agreed between the parties.

In some tests there are separate requirements for micro-BTS and BTS. If there is no separate requirement for a micro-BTS, the requirements for the BTS apply to a micro-BTS.

In Rel-7, higher symbol rate is introduced for EGPRS2-B. EGPRS2-A and all other channels use normal symbol rate. For definition of normal and higher symbol rate see 3GPP TS 45.004. All tests and requirements apply to both symbol rates except otherwise stated in the test.

In some tests there are separate requirements for multicarrier BTS, that apply for all classes of multicarrier BTS (Wide Area, Medium Range and Local Area, cf. [22]) unless otherwise stated. If there is no separate requirement for a multicarrier BTS class, the requirement designated for BTS and normal BTS apply to that multicarrier BTS class.

In Rel-12, BTS operating in the ER-GSM 900 band is introduced. In some tests there are separate requirements for BTS operating in the ER-GSM 900 band. If there is no separate requirement, the requirements for normal BTS apply.

In Rel-13, BTS support of a low-complexity, low data throughput service in environments experiencing high propagation attenuation as indoors in basements etc. is introduced. This service, based on EGPRS, with extended coverage is called EC-GSM-IoT. The requirements for EGPRS apply in case no specific requirement is explicitly stated for EC-GSM-IoT.

In the present document, the reference point for RF connections (except for the measurement of mean transmitted RF carrier power) is the antenna connector, as defined by the manufacturer. The present document does not apply to repeaters or RF devices which may be connected to an antenna connector of a BSS, except as specified in subclause 4.10.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TR 21.905: " Vocabulary for 3GPP Specifications ".

[2] GSM 04.22: "Digital cellular telecommunications system (Phase 2+); Radio Link Protocol (RLP) for data and telematic services on the Mobile Station - Base Station System (MS - BSS) interface and the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".

- [3] GSM 05.01: "Digital cellular telecommunications system (Phase 2); Physical layer on the radio path; General description".
- [4] GSM 05.02 (ETS 300 574): "Digital cellular telecommunications system (Phase 2); Multiplexing and multiple access on the radio path".
- [5] GSM 05.03 (ETS 300 575): "Digital cellular telecommunications system (Phase 2); Channel coding".
- [6] GSM 05.04 (ETS 300 576): "Digital cellular telecommunications system (Phase 2); Modulation".
- [7] GSM 05.05 (ETS 300 577): "Digital cellular telecommunications system (Phase 2); Radio transmission and reception".
- [8] GSM 05.08 (ETS 300 578): "Digital cellular telecommunications system (Phase 2); Radio subsystem link control".
- [9] GSM 05.10 (ETS 300 579): "Digital cellular telecommunications system (Phase 2); Radio subsystem synchronization".
- [10] 3GPP TS 08.20: "Digital cellular telecommunications system (Phase 2); Rate adaption on the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [11] ETSI EN 300 019-1: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment Part 1-0: Classification of environmental conditions Introduction".
- [12] IEC 60 068-2: "Basic environmental testing procedures; Part 2: Tests".
- [13] IEC 60 721: "Classification of environmental conditions".
- [14] ETSI ETR 027: "Radio and Equipment Systems; methods of measurement for mobile radio equipment".
- [15] ETSI ETR 028: "Radio and Equipment Systems; Uncertainties in the measurement of mobile radio equipment characteristics".
- [16] ITU-R Rec. SM.329-7: "Spurious emissions"
- [17] 3GPP TS 05.05: "Digital cellular telecommunications system (Phase 2+); Radio transmission and reception".
- [18] 3GPP TS 45.001: "Physical layer on the radio path; General description".
- [19] 3GPP TS 45.002: "Multiplexing and multiple access on the radio path".
- [20] 3GPP TS 45.003: "Channel coding".
- [21] 3GPP TS 45.004: "Modulation".
- [22] 3GPP TS 45.005: "Radio transmission and reception".
- [23] 3GPP TS 45.008: "Radio subsystem link control".
- [24] 3GPP TS 45.010: "Radio subsystem synchronization".
- [25] TIA/EIA-136-C: "TDMA Third Generation Wireless".
- [26] EN 300 019-1-3: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment Part 1-3; Classification of environmental conditions, Stationary use at weather-protected locations".
- [27] EN 300 019-1-4: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment Part 1-4; Classification of environmental conditions, Stationary use at non-weather-protected locations".
- [28] IEC 60 721-3-3 "Stationary use at weather protected locations".

- [29] IEC 60 721-3-4 "Stationary use at non weather protected locations".
- [30] 3GPP TS 24.022 "Radio Link Protocol (RLP) for circuit switched bearer and teleservices".
- [31] 3GPP TS 48.020 "Rate adaption on the Base Station System - Mobile services Switching Centre (BSS - MSC) interface".
- [32] 3GPP TS 25.113 "Base Station (BS) and repeater ElectroMagnetic Compatibility (EMC)".
- [33] 3GPP TS 36.113 "E-UTRA - Base Station (BS) and repeater ElectroMagnetic Compatibility (EMC)".

3 Definitions, abbreviations, frequency bands and channels

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply.

8-PSK: modulation type as defined 3GPP TS 45.004 clause 3.

Carrier Frequency: centre of the ARFCN under test.

GMSK: modulation type as defined by 3GPP TS 45.004 clause 2.

GSM: unless otherwise specified, references to GSM include GSM 400, GSM 700, T-GSM 810, GSM 850, GSM 900, ER-GSM 900, DCS 1800, PCS 1900, MXM 850 and MXM 1900.

GSM 900: unless otherwise specified, references to GSM 900 include P-GSM, E-GSM and R-GSM.

BSS: in the present document, the term BSS (or base station subsystem) applies to both a BTS and integrated BSS. If a separate BSC is required to perform tests on a BTS, the BSC may be regarded as test equipment and the environmental conditions of the BSC need not be controlled.

pico-BTS: as defined in 3GPP TS 45.005. In the present document, this also includes a BSS which incorporates a pico-BTS.

micro-BTS: as defined in 3GPP TS 05.05 and 3GPP TS 45.005. In the present document, this also includes a BSS which incorporates a micro-BTS.

Multicarrier BTS: defined as BTS, characterized by the ability to, in addition to single carrier operation, process two or more carriers in common active components simultaneously.

Wide Area (WA) multicarrier BTS: defined as a class of multicarrier BTS, characterized by requirements derived from macro cell scenarios. The class has either multicarrier transmitter only, or both multicarrier transmitter and receiver.

Medium Range (MR) multicarrier BTS: defined as a class of multicarrier BTS, characterized by requirements derived from micro cell scenarios. The class has both multicarrier transmitter and multicarrier receiver.

Local Area (LA) multicarrier BTS: defined as a class of multicarrier BTS, characterized by requirements derived from pico cell scenarios. The class has both multicarrier transmitter and multicarrier receiver.

MXM: mixed Mode system. Mixed-mode is defined as a network that deploys both 30 kHz RF carriers and 200 kHz RF carriers in geographic regions where the Federal Communications Commission (FCC) or similar regulations are applied. In the present document MXM 850 and MXM 1900 are defined.

normal BTS: any BTS or BSS as defined by 3GPP TS 05.05 and 3GPP TS 45.005 which is not a micro-BTS, pico-BTS or multicarrier BTS.

BSSTE: base Station System Test Equipment; see annex B.

manufacturer: in the present document, a reference to a manufacturer shall also apply to an agent of the manufacturer.