

ETSI TS 151 021 V15.1.0 (2018-10)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Base Station System (BSS) equipment specification;
Radio aspects
(3GPP TS 51.021 version 15.1.0 Release 15)**



ReferenceRTS/TSGR-0651021vf10

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.

All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and LTE™ are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	9
1 Scope	10
2 References	10
3 Definitions, abbreviations, frequency bands and channels.....	12
3.1 Definitions	12
3.2 Abbreviations	14
3.3 Frequency bands and channels	15
3.3.1 Frequency bands	15
3.3.2 Channels and channel numbering	15
4 General test conditions and declarations	16
4.1 Output power and determination of power class	16
4.2 Specified frequency range	17
4.3 Frequency hopping	17
4.4 RF power control.....	18
4.5 Downlink discontinuous transmission (DTX)	18
4.6 Test environments	18
4.6.1 Normal test environment	18
4.6.2 Extreme test environment	19
4.6.2.1 Extreme temperature	19
4.6.3 Vibration.....	19
4.6.4 Power supply	19
4.7 Acceptable uncertainty of measurement equipment.....	20
4.8 Interpretation of measurement results	24
4.9 Selection of configurations for testing.....	24
4.10 BTS Configurations.....	24
4.10.1 Receiver diversity	25
4.10.2 Duplexers	25
4.10.3 Power supply options.....	25
4.10.4 Ancillary RF amplifiers	25
4.10.5 BSS using antenna arrays	26
4.10.6 BTS supporting 8-PSK modulation	27
4.10.7 BTS supporting additional modulations in EGPRS2	27
4.10.8 Supported Symbol Rate.....	27
4.10.9 Support of RTTI and/or FANR	27
4.10.10 Multicarrier BTS.....	27
4.10.11 Support of EC-GSM-IoT	28
4.10.12 Support of Multilateration	29
5 Format and interpretation of tests.....	29
6 Transmitter	30
6.1 Static Layer 1 functions.....	30
6.1.1 Test purpose.....	30
6.1.2 Test case	31
6.1.3 Void	31
6.1.4 Conformance requirement	31
6.1.5 Requirement reference	31
6.2 Modulation accuracy	31
6.2.1 Test purpose.....	31
6.2.2 Test case	31
6.2.3 Void	32
6.2.4 Conformance requirement	32

6.2.5	Requirement reference	34
6.3	Mean transmitted RF carrier power and equivalent combined power	34
6.3.1	Test purpose	34
6.3.2	Test case	34
6.3.3	Void	36
6.3.4	Conformance requirement	36
6.3.5	Requirement reference	37
6.4	Transmitted RF carrier power versus time	37
6.4.1	Test purpose	37
6.4.2	Test case	37
6.4.3	Void	38
6.4.4	Conformance requirement	38
6.4.5	Requirement reference	42
6.5	Adjacent channel power	42
6.5.1	Spectrum due to modulation and wideband noise	43
6.5.1.1	Test purpose	43
6.5.1.2	Test case	43
6.5.1.3	Void	43
6.5.1.4	Conformance requirement	44
6.5.1.4.1	Normal BTS Minimum requirement	44
6.5.1.4.2	Multicarrier BTS Minimum requirement	44
6.5.1.4.3	Micro and Pico-BTS Minimum requirement	45
6.5.1.5	Requirement reference	46
6.5.2	Switching transients spectrum	46
6.5.2.1	Test purpose	46
6.5.2.2	Test case	46
6.5.2.3	Void	48
6.5.2.4	Conformance requirement	48
6.5.2.5	Requirement reference	48
6.6	Spurious emissions from the transmitter antenna connector	48
6.6.1	Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band	48
6.6.1.1	Test Purpose	48
6.6.1.2	Test Case	48
6.6.1.3	Void	49
6.6.1.4	Conformance requirement	49
6.6.1.5	Requirement Reference	49
6.6.2	Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band	49
6.6.2.1	Applicability (Phase 2)	49
6.6.2.1.1	Test Purpose	49
6.6.2.1.2	Test Case	49
6.6.2.1.3	Void	50
6.6.2.1.4	Conformance requirement	50
6.6.2.1.5	Requirement Reference	51
6.6.2.2	Applicability (Phase 2+)	51
6.6.2.2.1	Test Purpose	51
6.6.2.2.2	Test Case	51
6.6.2.2.3	Void	52
6.6.2.2.4	Conformance requirement	52
6.6.2.2.5	Requirement Reference	53
6.6.2.3	Applicability (Release 1999 and later releases GSM 400, GSM 900 and DCS 1800)	53
6.6.2.3.1	Test Purpose	53
6.6.2.3.2	Test Case	53
6.6.2.3.3	Void	54
6.6.2.3.4	Conformance requirement	54
6.6.2.3.5	Requirement Reference	54
6.6.2.4	Applicability (Release 4 and later releases GSM 700, GSM 850 and PCS 1900)	54
6.6.2.4.1	Test Purpose	54
6.6.2.4.2	Test Case	54
6.6.2.4.3	Void	55
6.6.2.4.4	Conformance requirement	55
6.6.2.4.5	Requirement Reference	55

6.6.2.5	Applicability (Release 7 and later releases GSM 400, T-GSM 810, GSM 900 and DCS 1800).....	55
6.6.2.5.1	Test Purpose	55
6.6.2.5.2	Test Case	56
6.6.2.5.3	Void	57
6.6.2.5.4	Conformance requirement	57
6.6.2.5.5	Requirement Reference	57
6.6.2.5a	Applicability (Release 7 and later releases GSM 700, GSM 850 and PCS 1900)	57
6.6.2.5a.1	Test Purpose	58
6.6.2.5a.2	Test Case	58
6.6.2.5a.3	Void	58
6.6.2.5a.4	Conformance requirement	58
6.6.2.5a.5	Requirement Reference	59
6.6.2.6	Applicability (Release 8 and later releases GSM 400, T-GSM 810, GSM 900 and DCS 1800).....	59
6.6.2.6.1	Test Purpose	59
6.6.2.6.2	Test Case	59
6.6.2.6.3	Void	60
6.6.2.6.4	Conformance requirement	60
6.6.2.6.5	Requirement Reference	61
6.6.2.7	Applicability (Release 8 and later releases GSM 700, GSM 850 and PCS 1900)	61
6.6.2.7.1	Test Purpose	62
6.6.2.7.2	Test Case	62
6.6.2.7.3	Void	63
6.6.2.7.4	Conformance requirement	63
6.6.2.7.5	Requirement Reference	64
6.6.2.8	Applicability (Release 8 and later releases GSM 400, GSM 900 and DCS 1800).....	64
6.6.2.8.1	Test Purpose	64
6.6.2.8.2	Test Case	65
6.6.2.8.3	Void	66
6.6.2.8.4	Complete conformance	66
6.6.2.8.5	Requirement Reference	66
6.6.2.9	Applicability (Release 12 and later releases GSM 400, T-GSM 810, GSM 900, ER-GSM 900 and DCS 1800).....	66
6.6.2.9.1	Test Purpose	66
6.6.2.9.2	Test Case	66
6.6.2.9.3	Void	67
6.6.2.9.4	Conformance requirement	68
6.6.2.9.5	Requirement Reference	68
6.6.2.10	Applicability (Release 12 and later releases GSM 400, T-GSM 810, GSM 900 and DCS 1800).....	68
6.6.2.10.1	Test Purpose	68
6.6.2.10.2	Test Case	69
6.6.2.10.3	Void	70
6.6.2.10.4	Conformance requirement	70
6.6.2.10.5	Requirement Reference	71
6.6.2.11	Applicability (Release 12 and later releases GSM 400, GSM 900, ER-GSM 900 and DCS 1800).....	71
6.6.2.11.1	Test Purpose	71
6.6.2.11.2	Test Case	72
6.6.2.11.3	Void	73
6.6.2.11.4	Conformance requirement	73
6.6.2.11.5	Requirement Reference	73
6.7	Intermodulation attenuation (GSM 400, GSM 900, ER-GSM 900 and DCS 1800).....	73
6.7.1	Test purpose.....	73
6.7.2	Test case	73
6.7.3	Void	75
6.7.4	Conformance requirement	75
6.7.5	Requirement reference	76
6.8	Intra Base Station System intermodulation attenuation.....	77
6.8.1	Test purpose.....	77
6.8.2	Test case	77
6.8.3	Void	78
6.8.4	Conformance requirement	78
6.8.5	Requirement reference	78
6.9	Intra Base Station System intermodulation attenuation, MXM 850 and MXM 1900	79

6.9.1	Test purpose.....	79
6.9.2	Test cases	79
6.9.2.1	200 kHz carriers-only.....	79
6.9.2.2	200 kHz and ANSI-136 30 kHz carriers	79
6.9.3	Void	79
6.9.4	Conformance requirement	79
6.9.5	Requirement reference	80
6.10	Intra Base Station System intermodulation attenuation, PCS 1900, GSM 850 and GSM 700.....	80
6.10.1	Test purpose.....	80
6.10.2	Test case	80
6.10.3	Void	81
6.10.4	Conformance requirement	81
6.10.5	Requirement reference	81
6.11	Intermodulation attenuation (GSM 700, GSM 850, MXM 850, PCS 1900 and MXM 1900)	81
6.11.1	Test purpose.....	81
6.11.2	Test case	81
6.11.3	Void	83
6.11.4	Conformance requirement	83
6.11.5	Requirement reference.....	84
6.12	Wideband noise and intra BSS intermodulation attenuation in multicarrier operation	84
6.12.1	Test purpose.....	84
6.12.2	Test case	84
6.12.3	Void	87
6.12.4	Conformance requirement	87
6.12.5	Requirement reference	88
7	Receivers	89
7.1	Static Layer 1 receiver functions (nominal error ratios).....	89
7.1.1	Test Purpose.....	89
7.1.2	Test Case.....	89
7.1.3	Void	93
7.1.4	Conformance requirement	93
7.1.5	Requirement Reference	93
7.2	Erroneous Frame Indication Performance	94
7.2.1	Test Purpose.....	94
7.2.2	Test Case.....	94
7.2.3	Void	95
7.2.4	Conformance requirement	95
7.2.5	Requirement reference	95
7.3	Static Reference Sensitivity Level.....	95
7.3.1	Test Purpose.....	95
7.3.2	Test Case.....	95
7.3.3	Void	102
7.3.4	Conformance requirement	102
7.3.5	Requirements Reference	106
7.4	Multipath Reference Sensitivity Level	106
7.4.1	Test Purpose.....	106
7.4.2	Test Case.....	106
7.4.3	Void	123
7.4.4	Conformance requirement	123
7.4.5	Requirement Reference.....	133
7.5	Reference interference level	133
7.5.1	Test Purpose.....	133
7.5.2	Test Case.....	133
7.5.3	Void	156
7.5.4	Conformance requirement	156
7.5.5	Requirements Reference	173
7.6	Blocking Characteristics.....	173
7.6.1	Test Purpose.....	173
7.6.2	Test Case.....	173
7.6.3	Void	180
7.6.4	Conformance requirement	181

7.6.5	Requirements reference	182
7.7	Intermodulation characteristics	182
7.7.1	Test Purpose.....	182
7.7.2	Test Case.....	182
7.7.3	Void	184
7.7.4	Conformance requirement	184
7.7.5	Requirement Reference.....	185
7.8	AM suppression.....	185
7.8.1	Test Purpose.....	185
7.8.2	Test Case.....	185
7.8.3	Void	187
7.8.4	Conformance requirement	187
7.8.5	Requirement Reference.....	188
7.9	Spurious emissions from the receiver antenna connector.....	188
7.9.1	Test Purpose.....	188
7.9.2	Test Case.....	188
7.9.3	Void	189
7.9.4	Conformance requirement	189
7.9.5	Requirement Reference.....	189
8	Radiated spurious emissions	189
8.1	Test Purpose	189
8.2	Test Case	190
8.3	Void.....	192
8.4	Conformance requirement.....	192
8.5	Requirement reference	192
9	Radio link management.....	193
9.1	General	193
9.2	Synchronization.....	193
9.2.1	Timing Tolerance.....	193
9.2.1.1	Test purpose	193
9.2.1.2	Test case.....	193
9.2.1.3	Void.....	194
9.2.1.4	Conformance requirement.....	194
9.2.1.5	Requirement reference	194
9.3	Frame structure.....	194
9.3.1	BCCH Multiframe	194
9.3.1.1	Test purpose	194
9.3.1.2	Test case.....	194
9.3.1.2a	Test case for EC-GSM-IoT	194
9.3.1.3	Void.....	195
9.3.1.4	Conformance requirement.....	195
9.3.1.5	Requirement reference	195
9.3.2	TDMA-frame structure	195
9.3.2.1	Test purpose	195
9.3.2.2	Test case.....	195
9.3.2.3	Void.....	195
9.3.2.4	Conformance requirement.....	195
9.3.2.5	Requirement reference	196
9.4	Radio link measurements	196
9.4.1	Signal Strength.....	196
9.4.1.1	Measurement Accuracy.....	196
9.4.1.1.1	Test purpose	196
9.4.1.1.2	Test case	196
9.4.1.1.3	Void.....	196
9.4.1.1.4	Conformance requirement	197
9.4.1.1.5	Requirement reference.....	198
9.4.1.2	Selectivity of signal strength measurements	198
9.4.1.2.1	Test purpose	198
9.4.1.2.2	Test case	198
9.4.1.2.3	Void.....	199

9.4.1.2.4	Conformance requirement	199
9.4.1.2.5	Requirement reference	199
9.4.2	Signal quality	199
9.4.2.1	Test purpose	199
9.4.2.2	Test case	199
9.4.2.3	Void	200
9.4.2.4	Conformance requirement	200
9.4.2.5	Requirement reference	201
9.4.3	Idle channel signal level	201
9.4.3.1	Test purpose	201
9.4.3.2	Test case	201
9.4.3.3	Void	202
9.4.3.4	Conformance requirement	202
9.4.3.5	Requirement reference	202
9.5	Adaptive frame alignment	202
9.5.1	Test purpose	202
9.5.2	Test case	202
9.5.3	Void	203
9.5.4	Conformance requirement	203
9.5.5	Requirement reference	204
Annex A (informative): Testing of statistical parameters.....		205
A.1	General theoretical methodology	205
A.2	Detailed theoretical methodology	207
A.3	Limitations and corrections to the theoretical methodology	208
A.3.1	Independent errors	208
A.3.2	Gaussian distribution	208
A.3.3	Stationary random processes	208
A.3.4	Low error ratios	209
A.3.5	Total corrections	209
A.4	Alternative experimental methodology	209
A.5	Detailed definition of error events	210
Annex B (informative): Description of special test equipment.....		211
B.1	Base Station System Test Equipment (BSSTE)	211
B.1.1	Fading and multipath propagation simulator	211
B.2	Measurement set ups for TX intermodulation	211
B.2.1	Test set-up for Intermodulation Attenuation (6.7.)	211
B.2.1.1	RX-Band	212
B.2.1.2	Outside RX Band	212
B.2.2	Test set-up for Intra BSS Intermodulation Attenuation (6.8.)	212
B.2.2.1	RX-Band	213
B.2.2.2	TX-Band	213
Annex C (informative): Number of samples needed for statistical testing.....		214
C.1	GSM 900; Number of samples for testing	214
C.2	DCS 1800; Number of Samples for Testing	234
Annex D (informative): Change history		255
History		263

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/5376e57c-7664-4c73-8ac9-ca89b72bc4f4/etsi-ts-151-021-v15.1.0-2018-10>

1 Scope

The present document specifies the Radio Frequency (RF) test methods and conformance requirements for GSM 400, GSM 700, T-GSM 810, GSM 900, ER-GSM 900 and DCS 1800, PCS 1900, GSM 850, MXM 850 and MXM 1900 Base Station Systems (BSS)s. These have been derived from, and are consistent with, the core GSM specifications specified in the requirements reference subclause of each test with the exception that requirements expressed as a reference to regulatory documents (e.g. FCC) have not been included in the present document.

The present document is applicable to BSS meeting the requirements of either GSM Phase 2 or GSM Phase 2+. Unless otherwise stated, all tests are applicable to BSS meeting Phase 2 and/or Phase 2+ GSM requirements, because the requirements of the Phase 2 and Phase 2+ core GSM specifications which are referenced in the test are consistent. Most differences between Phase 2 and Phase 2+ requirements represent Phase 2+ features which are optional for the BSS to support.

Conformance requirements may be tested to verify all aspects of the performance of a BSS. These minimum requirements are intended to be used by manufacturers and operators to allow conformance and acceptance testing to be performed in a consistent manner; the tests to be performed should be agreed between the parties.

In some tests there are separate requirements for micro-BTS and BTS. If there is no separate requirement for a micro-BTS, the requirements for the BTS apply to a micro-BTS.

In Rel-7, higher symbol rate is introduced for EGPRS2-B. EGPRS2-A and all other channels use normal symbol rate. For definition of normal and higher symbol rate see 3GPP TS 45.004. All tests and requirements apply to both symbol rates except otherwise stated in the test.

In some tests there are separate requirements for multicarrier BTS, that apply for all classes of multicarrier BTS (Wide Area, Medium Range and Local Area, cf. [22]) unless otherwise stated. If there is no separate requirement for a multicarrier BTS class, the requirement designated for BTS and normal BTS apply to that multicarrier BTS class.

In Rel-12, BTS operating in the ER-GSM 900 band is introduced. In some tests there are separate requirements for BTS operating in the ER-GSM 900 band. If there is no separate requirement, the requirements for normal BTS apply.

In Rel-13, BTS support of a low-complexity, low data throughput service in environments experiencing high propagation attenuation as indoors in basements etc. is introduced. This service, based on EGPRS, with extended coverage is called EC-GSM-IoT. The requirements for EGPRS apply in case no specific requirement is explicitly stated for EC-GSM-IoT.

In the present document, the reference point for RF connections (except for the measurement of mean transmitted RF carrier power) is the antenna connector, as defined by the manufacturer. The present document does not apply to repeaters or RF devices which may be connected to an antenna connector of a BSS, except as specified in subclause 4.10.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TR 21.905: " Vocabulary for 3GPP Specifications ".

[2] GSM 04.22: "Digital cellular telecommunications system (Phase 2+); Radio Link Protocol (RLP) for data and telematic services on the Mobile Station - Base Station System (MS - BSS) interface and the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".

- [3] GSM 05.01: "Digital cellular telecommunications system (Phase 2); Physical layer on the radio path; General description".
- [4] GSM 05.02 (ETS 300 574): "Digital cellular telecommunications system (Phase 2); Multiplexing and multiple access on the radio path".
- [5] GSM 05.03 (ETS 300 575): "Digital cellular telecommunications system (Phase 2); Channel coding".
- [6] GSM 05.04 (ETS 300 576): "Digital cellular telecommunications system (Phase 2); Modulation".
- [7] GSM 05.05 (ETS 300 577): "Digital cellular telecommunications system (Phase 2); Radio transmission and reception".
- [8] GSM 05.08 (ETS 300 578): "Digital cellular telecommunications system (Phase 2); Radio subsystem link control".
- [9] GSM 05.10 (ETS 300 579): "Digital cellular telecommunications system (Phase 2); Radio subsystem synchronization".
- [10] 3GPP TS 08.20: "Digital cellular telecommunications system (Phase 2); Rate adaption on the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [11] ETSI EN 300 019-1: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment Part 1-0: Classification of environmental conditions Introduction".
- [12] IEC 60 068-2: "Basic environmental testing procedures; Part 2: Tests".
- [13] IEC 60 721: "Classification of environmental conditions".
- [14] ETSI ETR 027: "Radio and Equipment Systems; methods of measurement for mobile radio equipment".
- [15] ETSI ETR 028: "Radio and Equipment Systems; Uncertainties in the measurement of mobile radio equipment characteristics".
- [16] ITU-R Rec. SM.329-7: "Spurious emissions"
- [17] 3GPP TS 05.05: " Digital cellular telecommunications system (Phase 2+); Radio transmission and reception "
- [18] 3GPP TS 45.001: "Physical layer on the radio path; General description".
- [19] 3GPP TS 45.002: "Multiplexing and multiple access on the radio path".
- [20] 3GPP TS 45.003: "Channel coding".
- [21] 3GPP TS 45.004: "Modulation".
- [22] 3GPP TS 45.005: "Radio transmission and reception".
- [23] 3GPP TS 45.008: "Radio subsystem link control".
- [24] 3GPP TS 45.010: "Radio subsystem synchronization".
- [25] TIA/EIA-136-C: "TDMA Third Generation Wireless".
- [26] EN 300 019-1-3: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment Part 1-3; Classification of environmental conditions, Stationary use at weather-protected locations".
- [27] EN 300 019-1-4: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment Part 1-4; Classification of environmental conditions, Stationary use at non-weather-protected locations".
- [28] IEC 60 721-3-3 "Stationary use at weather protected locations".

- [29] IEC 60 721-3-4 "Stationary use at non weather protected locations".
- [30] 3GPP TS 24.022 "Radio Link Protocol (RLP) for circuit switched bearer and teleservices".
- [31] 3GPP TS 48.020 "Rate adaption on the Base Station System - Mobile services Switching Centre (BSS - MSC) interface".
- [32] 3GPP TS 25.113 "Base Station (BS) and repeater ElectroMagnetic Compatibility (EMC)".
- [33] 3GPP TS 36.113 "E-UTRA - Base Station (BS) and repeater ElectroMagnetic Compatibility (EMC)".
- [34] 3GPP TS 43.059 "Functional stage 2 description of Location Services (LCS) in GERAN".
- [35] 3GPP TS 49.031 "Base Station System Application Part LCS Extension (BSSAP-LE)".
- [36] 3GPP TS 44.018 " Mobile radio interface layer 3 specification; GSM/EDGE Radio Resource Control (RRC) protocol".
- [37] 3GPP TS 45.010 "Radio subsystem synchronization".

3 Definitions, abbreviations, frequency bands and channels

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply.

8-PSK: modulation type as defined 3GPP TS 45.004 clause 3.

Carrier Frequency: centre of the ARFCN under test.

GMSK: modulation type as defined by 3GPP TS 45.004 clause 2.

GSM: unless otherwise specified, references to GSM include GSM 400, GSM 700, T-GSM 810, GSM 850, GSM 900, ER-GSM 900, DCS 1800, PCS 1900, MXM 850 and MXM 1900.

GSM 900: unless otherwise specified, references to GSM 900 include P-GSM, E-GSM and R-GSM.

BSS: in the present document, the term BSS (or base station subsystem) applies to both a BTS and integrated BSS. If a separate BSC is required to perform tests on a BTS, the BSC may be regarded as test equipment and the environmental conditions of the BSC need not be controlled.

pico-BTS: as defined in 3GPP TS 45.005. In the present document, this also includes a BSS which incorporates a pico-BTS.

micro-BTS: as defined in 3GPP TS 05.05 and 3GPP TS 45.005. In the present document, this also includes a BSS which incorporates a micro-BTS.

Multicarrier BTS: defined as BTS, characterized by the ability to, in addition to single carrier operation, process two or more carriers in common active components simultaneously.

Wide Area (WA) multicarrier BTS: defined as a class of multicarrier BTS, characterized by requirements derived from macro cell scenarios. The class has either multicarrier transmitter only, or both multicarrier transmitter and receiver.

Medium Range (MR) multicarrier BTS: defined as a class of multicarrier BTS, characterized by requirements derived from micro cell scenarios. The class has both multicarrier transmitter and multicarrier receiver.

Local Area (LA) multicarrier BTS: defined as a class of multicarrier BTS, characterized by requirements derived from pico cell scenarios. The class has both multicarrier transmitter and multicarrier receiver.