

ETSI TS 123 283 V15.2.0 (2018-10)



TECHNICAL SPECIFICATION

LTE;
**Mission Critical Communication Interworking with Land Mobile
Radio Systems**
(3GPP TS 23.283 version 15.2.0 Release 15)

*Full PDF preview
https://standards.iteh.ai/catalog/standards/sist/662a3fa4-mbb-4f7a-9658-1ba3555e620e/etsi-ts-123-283-v15-2-0-2018-10*



Reference

RTS/TSGS-0623283vf20

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	8
1 Scope	9
2 References	9
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Abbreviations	10
4 Introduction	10
5 Assumptions and architectural requirements.....	10
5.1 Key management.....	10
5.2 Packet format.....	11
6 Involved business relationships.....	11
7 Functional model	11
7.1 General	11
7.2 Functional model description	11
7.3 Functional entities description.....	12
7.3.1 IWF.....	12
7.4 Reference points	12
7.4.1 Reference point IWF-1 (between the IWF and the MCPTT server).....	12
7.4.2 Reference point IWF-2 (between the IWF and the MCData server)	12
7.4.3 Reference point IWF-3 (between the IWF and the group management server).....	13
8 Identities	13
8.1 Identity mapping	13
9 Application of functional model to deployments	13
10 Procedures and information flows.....	13
10.1 Affiliation.....	13
10.1.1 Information flows for affiliation	13
10.1.1.1 General	13
10.1.1.2 IWF group affiliation request	13
10.1.1.3 IWF group affiliation response	14
10.1.1.4 IWF group de-affiliation request.....	14
10.1.1.5 IWF group de-affiliation response	14
10.1.2 Affiliation procedures	15
10.1.2.1 General	15
10.1.2.2 Group affiliation to a group defined in the MC system.....	16
10.1.2.3 Group de-affiliation from a group defined in the MC system.....	17
10.1.2.4 Group affiliation to group defined in the LMR system.....	17
10.1.2.5 Group de-affiliation from a group defined in the LMR system	19
10.2 Group management	20
10.2.1 Information flows for group management	20
10.2.1.1 General	20
10.2.1.2 IWF group regroup teardown notification.....	20
10.2.1.3 IWF group regroup teardown notification response.....	20
10.2.1.4 IWF group regroup request	20
10.2.1.5 IWF group regroup response	20
10.2.1.6 IWF group regroup notification	20
10.2.1.7 IWF group regroup notification response	21
10.2.1.8 IWF group information request.....	21

10.2.1.9	IWF group information response	21
10.2.1.10	IWF group information provision request.....	21
10.2.1.11	IWF group information provision response	22
10.2.1.12	IWF group information subscribe request.....	22
10.2.1.13	IWF group information subscribe response	22
10.2.1.14	IWF group information notify request	22
10.2.1.15	IWF group information notify response.....	23
10.2.2	Group regrouping.....	23
10.2.2.1	General	23
10.2.2.2	MC system initiates the group regroup	23
10.2.2.3	IWF initiates the group regroup	25
10.2.2.4	Ownership of the group regroup	26
10.2.2.5	Simultaneous group regroup requests from each side of the IWF-1 interface	26
10.2.2.6	Resolution of vocoder and encryption mode for the group regroup.....	26
10.2.3	Group configuration for interworking.....	26
10.2.3.1	Overview.....	26
10.2.3.2	MC system provides group configuration to the IWF.....	26
10.2.3.3	IWF requests group configuration from the MC system.....	27
10.2.3.4	IWF provides group configuration to the MC system.....	28
10.2.3.5	MC system requests group configuration from the IWF.....	29
10.2.3.6	IWF subscribes to group configuration.....	29
10.2.3.7	MC system notifies group configuration.....	30
10.2.3.8	MC system subscribes to group configuration	30
10.2.3.9	IWF notifies group configuration.....	31
10.3	Group call.....	31
10.3.1	General.....	31
10.3.2	Information flows for group call over interworking group	32
10.3.2.1	General	32
10.3.2.2	IWF group call request.....	32
10.3.2.3	IWF group call response (IWF – MCPTT server).....	32
10.3.2.4	IWF Group-broadcast group call setup request.....	32
10.3.2.5	IWF Group-broadcast group call setup response	33
10.3.2.6	IWF Group-broadcast group call release request	33
10.3.2.7	IWF group-broadcast group call release response.....	33
10.3.2.8	IWF group join request	34
10.3.2.9	IWF group join response.....	34
10.3.2.10	IWF group call leave request.....	34
10.3.2.11	IWF group call leave response.....	35
10.3.2.12	IWF group call release request.....	35
10.3.2.13	IWF group call release response	35
10.3.3	Pre-arranged group call.....	35
10.3.3.1	General	35
10.3.3.2	Group call setup initiated by MCPTT user on an interworking group defined in MCPTT system.....	36
10.3.3.3	Group call setup initiated by LMR user on an interworking group defined in MCPTT system.	37
10.3.3.4	Group call setup initiated by MCPTT user on an interworking group defined in the LMR system.....	38
10.3.3.5	Group call setup initiated by LMR user on an interworking group defined in the LMR system.	40
10.3.3.6	Encrypted group call with transcoding.....	41
10.3.3.7	Late Entry.....	43
10.3.3.7.1	General	43
10.3.3.7.2	Group call late entry on an interworking group defined in the MCPTT system.....	43
10.3.3.7.3	Group call late entry on an interworking group defined in the LMR system	44
10.3.3.8	Interworking group call release.....	45
10.3.3.8.1	General	45
10.3.3.8.2	Group call release on an interworking group defined in the MCPTT system.....	46
10.3.3.8.3	Group call release on an interworking group defined in the LMR system	47
10.3.4	Group broadcast.....	48
10.3.4.1	General	48
10.3.4.2	Group-broadcast group call procedure with an interworking group where the group-broadcast group is defined in the MCPTT system.....	48
10.3.4.3	Group-broadcast group call procedure with an interworking group where the group-broadcast group is defined in the LMR system	51

10.3.4.4	Group-broadcast group call release with an interworking group procedure where the group-broadcast group is defined in the MCPTT system	53
10.3.4.5	Group-broadcast group call release with an interworking group procedure where the group-broadcast group is defined in the LMR system	55
10.3.5	Chat group call.....	56
10.3.5.1	General	56
10.3.5.2	MCPTT user initiated chat group call in an interworking group defined in LMR system	56
10.3.5.3	LMR user initiated chat group call in an interworking group defined in MCPTT system	57
10.3.5.4	Release chat group call on an interworking group defined in the LMR system.....	58
10.3.5.5	Release chat group call on an interworking group defined in the MCPTT system	59
10.3.5.6	void	60
10.3.5.7	void	60
10.3.6	Exiting group call due to de-affiliation	60
10.3.6.1	General	60
10.3.6.2	Exiting group call defined in the LMR system due to de-affiliation	60
10.3.6.3	Exiting group call defined in the MCPTT system due to de-affiliation	61
10.4	Private call.....	61
10.4.1	Information flows for private calls	61
10.4.1.1	General	61
10.4.1.2	IWF private call request	62
10.4.1.3	IWF private call response.....	62
10.4.1.4	IWF ringing.....	62
10.4.1.5	IWF call end request	63
10.4.1.6	IWF call end response.....	63
10.4.2	Private call setup in automatic commencement mode	63
10.4.2.1	MCPTT user initiating an MCPTT private call.....	63
10.4.2.2	LMR user initiating a private call with MCPTT user.....	65
10.4.3	Private call setup in manual commencement mode	66
10.4.3.1	MCPTT user is initiating an MCPTT private call.....	66
10.4.3.2	LMR user initiating a private call with MCPTT user.....	68
10.4.4	Private call release	69
10.4.4.1	MCPTT client initiated	69
10.4.4.2	MCPTT server initiated.....	70
10.4.4.3	LMR user initiated	71
10.4.5	Encryption of private calls	72
10.5	Floor control.....	72
10.5.1	General.....	72
10.5.2	Information flows for floor control.....	73
10.5.2.1	General	73
10.5.2.2	IWF floor request	73
10.5.2.3	IWF floor granted.....	73
10.5.2.4	IWF floor rejected.....	73
10.5.2.5	IWF floor request cancel	73
10.5.2.6	IWF floor request cancel response	74
10.5.2.7	IWF floor request cancel notify	74
10.5.2.8	IWF floor idle.....	74
10.5.2.9	IWF floor release	74
10.5.2.10	IWF floor taken	75
10.5.2.11	IWF floor revoked.....	75
10.5.2.12	IWF floor acknowledgement.....	75
10.5.2.13	IWF queue position request.....	75
10.5.2.14	IWF queue position info.....	76
10.5.2.15	IWF unicast media stop request	76
10.5.2.16	IWF unicast media resume request	76
10.5.3	Interworking floor control	76
10.5.4	Floor override without using floor revoked on an interworking group.....	77
10.5.5	Floor control on an interworking group homed in the LMR system.....	78
10.5.6	Floor control on an interworking group homed in the MCPTT system.....	80
10.5.7	Floor control without local filtering on an interworking group defined in the LMR system.....	81
10.5.8	Floor control without local filtering on an interworking group defined in the MCPTT system	82
10.6	Emergency and imminent peril	84
10.6.1	Information flows for emergency and imminent peril	84

10.6.1.1	IWF emergency group call request	84
10.6.1.2	IWF emergency group call response	84
10.6.1.3	IWF imminent peril group call request	84
10.6.1.4	IWF imminent peril group call response	84
10.6.1.5	IWF in-progress imminent peril group state cancel request	85
10.6.1.6	IWF in-progress imminent peril group state cancel response	85
10.6.1.7	IWF emergency alert request	85
10.6.1.8	IWF emergency alert response	85
10.6.1.9	IWF emergency alert cancel request	86
10.6.1.10	IWF emergency alert cancel response	86
10.6.1.11	IWF in-progress emergency group state cancel request	86
10.6.1.12	IWF in-progress emergency group state cancel response	87
10.6.2	Emergency calls	87
10.6.2.1	General	87
10.6.2.2	Emergency group call	87
10.6.2.2.1	Emergency group call setup initiated by a user in the LMR system on an interworking group defined in the MCPTT system	87
10.6.2.2.2	Emergency group call setup initiated by a user in the MCPTT system on an interworking group defined in MCPTT system	89
10.6.2.2.3	Emergency group call setup initiated by a user in the LMR system on an interworking group defined in the LMR system	91
10.6.2.2.4	Emergency group call setup initiated by a user in the MCPTT system to an interworking group defined in the LMR system	92
10.6.2.3	In-progress emergency group state cancel of an interworking group	94
10.6.2.3.1	LMR user initiated in-progress emergency group state cancel of an interworking group defined in the MCPTT system	94
10.6.2.3.2	MCPTT user initiated in-progress emergency group state cancel of an interworking group defined in the MCPTT system	95
10.6.2.3.3	LMR user initiated in-progress emergency group state cancel of an interworking group defined in an LMR system	96
10.6.2.3.4	MCPTT user initiated in-progress emergency group state cancel of an interworking group defined in an LMR system	97
10.6.2.4	Losing audio	98
10.6.2.5	Default emergency group	99
10.6.2.6	Emergency private call	99
10.6.2.7	LMR systems that do not track group emergencies	99
10.6.3	Imminent peril calls	99
10.6.3.1	General	99
10.6.3.2	Imminent peril group call initiated by an MCPTT user on an interworking group	99
10.6.3.3	Group call initiated by a user in the LMR system on an interworking group in imminent peril state	101
10.6.3.4	In-progress imminent peril state cancel on an interworking group	102
10.6.4	Emergency alerts	104
10.6.4.1	Emergency alert initiated by LMR user	104
10.6.4.2	Emergency alert initiated by MC service user	106
10.6.5	Emergency alert cancellation	107
10.6.5.1	Emergency alert cancellation of an LMR user	107
10.6.5.2	Emergency alert cancellation of an MC service user	108
10.7	Codec	110
10.7.1	Information flows for codec	110
10.7.1.1	IWF codec reconciliation request	110
10.7.1.2	IWF codec reconciliation response	110
10.7.2	IWF transcoding	110
10.7.3	Codec negotiation by the LMR system	110
10.7.3.1	Description	110
10.8	MCDData short data service	111
10.8.1	General	111
10.8.2	Information flows for the short data service	112
10.8.2.1	General	112
10.8.2.2	IWF MCDData standalone data request	112
10.8.2.3	IWF MCDData data disposition notification	112
10.8.2.4	IWF MCDData group standalone data request (IWF – MCDData server)	113

10.8.2.5	IWF MCDATA group standalone data request (MCDATA server - IWF).....	113
10.8.2.6	IWF MCDATA data disposition notification(s) (MCDATA server to IWF).....	113
10.8.2.7	IWF MCDATA group standalone data request (IWF – MCDATA server).....	114
10.8.2.8	IWF MCDATA group standalone data request (MCDATA server – IWF).....	114
10.8.2.9	IWF MCDATA group standalone data response.....	115
10.8.3	Behaviour at the MCDATA Client.....	115
10.8.4	Behaviour at the IWF.....	115
10.8.5	Behaviour at the MCDATA server.....	115
10.8.6	MCDATA user one-to-one SDS request to an LMR user.....	115
10.8.6.1	Signalling control plane.....	115
10.8.6.2	Media plane.....	116
10.8.7	LMR user one-to-one SDS request to an MCDATA user.....	116
10.8.7.1	Signalling control plane.....	116
10.8.7.2	Media plane.....	116
10.8.8	MCDATA user group SDS request to an MCDATA group including LMR users.....	116
10.8.8.1	Signalling control plane.....	116
10.8.8.2	Media plane.....	116
10.8.9	LMR user group SDS request to an MCDATA group.....	116
10.8.9.1	Signalling control plane.....	116
10.8.9.2	Media plane.....	116
10.9	IWF as a security gateway.....	117
10.9.1	Support for transcoding with encrypted speech.....	117
10.10	Simultaneous interworked calls (on-network).....	117
10.10.1	General.....	117
10.11	Location.....	117
10.11.1	Location of current talker.....	117
10.11.2	Location of current talker (MCPTT server to IWF).....	117
10.11.3	Location of current talker (IWF to MCPTT server).....	118
10.12	LMR security transport.....	119
10.12.1	Information flows for LMR security transport.....	119
10.12.1.1	Non-3GPP security message request.....	119
10.12.1.2	Non-3GPP security message response.....	119
10.12.2	LMR key management messages.....	120
10.12.2.1	General.....	120
10.12.2.2	MC service client initiated.....	120
10.12.2.3	IWF initiated.....	120
Annex A (informative): Change history.....		122
History.....		123

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

PREVIEW
iTech STANDARD
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/662a3fa4-fbbf-4f7a-9658-1ba3555e620e/etsi-ts-123-283-v15.2.0-2018-10>

1 Scope

The objective of this technical specification is to specify interworking between MC systems and LMR systems that satisfy the MCPTT requirements in 3GPP TS 22.179 [3], MCCoRe requirements in 3GPP TS 22.280 [2] and the MCDATA requirements (SDS only) in 3GPP TS 22.282 [4].

The present document refers to an InterWorking Function (IWF). The structure and functionality of the IWF is out of scope of the present document. The definition of reference points between the IWF and MC systems and the interactions between the IWF and MC systems are in scope of the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications"
- [2] 3GPP TS 22.280: "Mission Critical Services Common Requirements (MCCoRe); Stage 1".
- [3] 3GPP TS 22.179: "Mission Critical Push to Talk (MCPTT); Stage 1".
- [4] 3GPP TS 22.282: "Mission Critical Data services".
- [5] 3GPP TS 23.280: "Common functional architecture to support mission critical services; Stage 2".
- [6] 3GPP TS 23.282: "Functional architecture and information flows to support Mission Critical Data (MCDATA); Stage 2".
- [7] 3GPP TS 23.379: "Functional architecture and information flows to support Mission Critical Push To Talk (MCPTT); Stage 2".
- [8] 3GPP TS 33.180: "Security of the mission critical service"

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

End-to-End Encryption: encryption that is applied by an originating terminal or client and is decrypted only by chosen terminating terminals or clients.

Interworking: a means of communication between mission critical systems and LMR systems whereby MC users obtaining service from a mission critical system can communicate with LMR users who are obtaining service from one or more LMR systems.

Interworking function: adapts LMR Systems to mission critical systems via the IWF interface and supports interworking between LMR systems and mission critical systems.

Interworking group: a group, which is composed of group members from the MC system and the LMR system and defined in the MC system or the LMR system.

LMR system: the collection of applications, services, and enabling capabilities providing a land mobile radio service offering group and private communications.

LMR user: a user of a device which allows participation in an LMR system.

NOTE: The term LMR user is defined for discussion purposes only and is out of scope of the present document.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

E2EE	End-to-End Encryption
IWF	InterWorking Function
KEK	Key Encryption Key (TETRA)
KMS	Key Management Service
MC	Mission Critical
MCPTT	Mission Critical Push To Talk
LMR	Land Mobile Radio
OTAK	Over-The-Air-Key Management (TETRA)
OTAR	Over-The-Air Rekeying (P25)
P25	Project 25
SDS	Short Data Service
TETRA	TErrestrial Trunked Radio
UE	User Equipment
UKEK	Unique Key Encryption Key (P25)
URI	Uniform Resource Identifier

4 Introduction

Mission critical users currently employ a wide range of LMR mission critical Push To Talk services, and associated data capabilities where available.

The present document describes the architecture to support the interworking between the MC system and the LMR system to satisfy interworking requirements specified in 3GPP TS 22.179 [3] and 3GPP TS 22.282 [4]. Other LMR technologies may interwork as long as they conform to the present document.

The IWF, along with its LMR system, will appear as a peer interconnected MC system. This is meant as an approach for defining interactions on the IWF interface but is not intended to specify the functionality of the IWF nor meant to mandate a deployment model.

5 Assumptions and architectural requirements

5.1 Key management

Interworking requirements for key management for encrypted interworking include:

- a mechanism to securely (i.e. authenticity, integrity, confidentiality) share an LMR E2EE traffic key for a private call sessions between a party in an MCPTT system and a party in the LMR system;
- a mechanism to securely convey to group members, the LMR E2EE key or set of LMR E2EE keys associated with an MC service group or set of MC service groups, to be used for encryption of interworking group calls spanning the multiple systems;
- a mechanism to securely share with temporary group members in MC systems, the LMR E2EE key(s) associated with a temporary MC service group to be used in interworking group calls spanning the multiple systems;

- d) key management solutions shall not preclude the ability of an IWF to allow one or more individual Mission Critical Organizations from having sole control over and sole access to LMR E2EE traffic keys used for the entity's media traffic and users' key encryption keys (UKEKs or KEKs);
- e) key management solutions shall support the ability of the IWF to decrypt/reencrypt the media traffic for zero or more groups; and,
- f) for deployments where Mission Critical Organizations wish to use LMR E2EE mechanisms when interworking with LMR users:
 - i) a mechanism to securely provision an MC service client with the user's UKEK or KEK; and,
 - ii) a mechanism to convey LMR OTAR or OTAK message contents.

5.2 Packet format

Each LMR technology defines its own packet format for voice media transmission. For interworking sessions, there might be cases where LMR formatted media is required to be transferred between the IWF and LMR aware MCPTT clients. An example of such a case is where E2EE is used and thus the IWF is not able to decrypt the media. In such cases, media that is sent over the IWF-1 interface needs to be routed within MCPTT systems to/from LMR aware MCPTT clients using methods described in 3GPP TS 23.379 [7].

Requirements for media transmission across the IWF-1 interface include:

- a) media transmission to carry the LMR formatted media between the IWF and LMR aware MCPTT clients; and
- b) the MCPTT system, along with the IWF, may choose to encrypt the LMR formatted media using 3GPP mechanisms.

NOTE: The contents of the LMR formatted media is out of scope of the present document.

6 Involved business relationships

No business relationships have been identified.

7 Functional model

7.1 General

7.2 Functional model description

Figure 7.2-1 shows the functional model for the application plane for interworking between MC systems and LMR systems. Functional entities and interfaces depicted on the right-hand side of the IWF-x interfaces are defined in 3GPP TS 23.280 [5], 3GPP TS 23.379 [7], and 3GPP TS 23.282 [6].




Figure 7.2-1: Functional model for application plane for interworking

7.3 Functional entities description

7.3.1 IWF

The IWF supports most of the functionality of peer MCPTT and MCData systems, with some differences, as specified in the present document. The IWF supports any necessary protocol translation and identity mapping between the MC systems and the IWF. The internal function of the IWF is out of scope of the present document.

7.4 Reference points

7.4.1 Reference point IWF-1 (between the IWF and the MCPTT server)

The IWF-1 reference point, which exists between the IWF and the MCPTT server, provides peer to peer interconnection between an LMR system and the MCPTT system. IWF-1 supports a subset of MCPTT-3 as defined in 3GPP TS 23.379 [7], with some differences, as specified in the present document. The IWF-1 interface is supported by the same signalling plane protocol(s) as defined for MCPTT-3 except as specified in the present document.

7.4.2 Reference point IWF-2 (between the IWF and the MCData server)

The IWF-2 reference point, which exists between the IWF and the MCData server, provides SDS interconnection between an LMR system and the MCData system. IWF-2 supports a subset of the functionality of MCData-SDS-1 and MCData-SDS-2, as defined in 3GPP TS 23.282 [6] with some differences, as specified in the present document. The IWF-2 interface is supported by the same signalling plane protocol(s) as defined for MCData-3 except as specified in the present document.