

ISO/TC 188/SC 1

Secretariat: DIN

Voting begins on:
2020-04-30

Voting terminates on:
2020-06-25

Personal flotation devices —

Part 9: Evaluation

*Équipements individuels de flottabilité —
Partie 9: Évaluation*

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/26521402-0ecc-4e2d-bb9b-27cf0cd6c095/iso-fdis-12402-9.2>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

ISO/CEN PARALLEL PROCESSING



Reference number
ISO/FDIS 12402-9.2:2020(E)

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/26524e02-0ecd-4e2d-bb9b-27cf0cd6c095/iso-fdis-12402-9.2>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	v
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Classification of personal flotation devices	4
5 Test methods	4
5.1 General	4
5.2 Sampling and conditioning	4
5.2.1 Sampling	4
5.2.2 Conditioning	4
5.3 Criteria	4
5.4 Magnetic properties testing	5
5.5 Mechanical properties tests	5
5.5.1 General	5
5.5.2 Rotating shock bin test	7
5.5.3 Temperature cycling test	8
5.5.4 Horizontal and vertical load tests	10
5.5.5 Lifting loop test	11
5.5.6 Buddy line test	12
5.5.7 Collar handles	17
5.5.8 Body strap hardware secureness test	18
5.5.9 Inflation tests	18
5.5.10 Measurement of buoyancy of the whole device	19
5.5.11 Uninflated buoyancy test	20
5.5.12 Buoyancy test for inherently buoyant material	21
5.5.13 Test of the resistance to burning	21
5.5.14 Overpressure test	23
5.5.15 Strength test of attachment points	24
5.5.16 Test of the resistance to inadvertent inflation	24
5.6 Human subject performance tests	26
5.6.1 General	26
5.6.2 Donning test	31
5.6.3 Water entry test	33
5.6.4 Self-righting and stability test	34
5.6.5 Measurement of freeboard	36
5.6.6 In-water stability test for lifejackets	37
5.6.7 Boarding test	37
5.6.8 Oral inflation	38
5.7 Tests using manikins	39
5.7.1 General	39
5.7.2 Test order	39
5.7.3 Fall from a height	40
5.7.4 Mouth freeboard	41
5.7.5 Self-righting and stability	43
Annex A (informative) Classification of personal flotation devices	44
Annex B (normative) Adult reference vest for test subject disqualification	46
Annex C (normative) Child reference vest for test subject disqualification and test subject group validation (body mass from 25 kg to 40 kg)	60
Annex D (normative) Reference vest for test subject disqualification and test subject group validation (body mass less than 25 kg)	69

Annex E (normative) Manikin	78
Bibliography	83

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/26524e02-0ecd-4e2d-bb9b-27cf0cd6c095/iso-fdis-12402-9.2>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 188, *Small craft*, Subcommittee SC 1, *Personal safety equipment*.

This second edition cancels and replaces the first edition (ISO 12402-9:2006), which has been technically revised. It also incorporates the Amendment ISO 12402-9:2006/Amd 1:2010.

The main changes compared to the previous edition are as follows:

- a) amendment of title to make clear the need of this part for the fulfilment of the requirements in ISO 12402-2 to ISO 12402-6 to make visible the interaction and relation of the different parts of ISO 12402, and with this, its need of harmonization;
- b) new [Table 1](#) (A) Mechanical properties test for inherently buoyant PFDs (see [5.5.1](#));
- c) new [Table 2](#) (B) Mechanical properties test for inflatable PFDs (see [5.5.1](#));
- d) horizontal and vertical load test amended ([5.5.4](#));
- e) requirements on collar handles added (see [5.5.7](#));
- f) temperature cycling test amended (see [5.5.3](#));
- g) over-pressure test amended (see [5.5.14](#));
- h) air retention test deleted;
- i) requirement for the colour deleted;
- j) measurement of buoyancy of the whole device amended (see [5.5.9](#));
- k) inflation tests amended (see [5.5.13](#));
- l) strength of attachment test for inflatable chambers added (see [5.5.15](#));

ISO/FDIS 12402-9.2:2020(E)

- m) human subject performance tests amended (see [5.6](#));
- n) performance levels amended (see [A.2](#));
- o) [Figures B.15](#) to [B.17](#) added.

A list of all parts in the ISO 12402 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/26524e02-0ecd-4e2d-bb9b-27cf0cd6c095/iso-fdis-12402-9.2>

Introduction

ISO 12402 (all parts):2020 deals with personal floatation devices (PFDs) for persons engaged in activities, whether in relation to their work or their leisure, in or near water. PFDs manufactured, selected, and maintained to this International Standard give a reasonable assurance of safety from drowning to a person who is immersed in water. ISO 12402 (all parts):2020 does not include the following:

- requirements for lifejackets on seagoing ships, which are regulated by the International Maritime Organization (IMO¹) under the International Convention for the Safety of Life at Sea (SOLAS);
- throwable devices and flotation cushions.

ISO 12402 (all parts):2020 allows for the buoyancy of a PFD to be provided by a variety of materials or designs, some of which can require preparation before entering the water (e.g. inflation of chambers by gas from a cylinder or blown in orally). PFDs can be divided into the following two main classes:

- those which provide face up in-water support to the user regardless of physical conditions (lifejackets), and
- those which require the user to make swimming and other postural movements to position the user with the face out of the water (buoyancy aids).

Within these main two classes there are a number of levels of support, types of buoyancy, activation methods for inflatable devices, and auxiliary items (such as location aids), which all affect the user's probability of survival. Within the different types of buoyancy allowed, inflatable PFDs either provide full buoyancy without any user intervention other than arming (i.e. PFDs inflated by a fully automatic method) or require the user to initiate the inflation. Hybrid PFDs always provide some buoyancy but rely on the same methods as inflatable PFDs to achieve full buoyancy. With inherently buoyant PFDs, the user only needs to put the PFD on to achieve the performance of its class.

PFDs that do not require intervention (automatically operating PFDs) are suited to activities where persons are likely to enter the water unexpectedly; whereas PFDs requiring intervention (e.g. manually inflated PFDs) are only suitable for use if the user believes there will be sufficient time to produce full buoyancy, if automatic operation would result in entrapment, or if help is close at hand. In every circumstance, the user should ensure that the operation of the PFD is suited to the specific application. The conformity of a PFD to this part of the ISO 12402 series:2020 does not imply that it is suitable for all circumstances. The relative amount of required inspection and maintenance is another factor of paramount importance in the choice and application of specific PFDs.

ISO 12402 (all parts):2020 is intended to serve as a guide to manufacturers, purchasers, and users of such safety equipment in ensuring that the equipment provides an effective standard of performance in use. Equally essential is the need for the designer to encourage the wearing of the equipment by making it comfortable and attractive for continuous wear on or near water, rather than for it to be stored in a locker for emergency use. The primary function of a PFD is to support the user in reasonable safety in the water. Within the two classes, alternative attributes make some PFDs better suited to some circumstances than others or make them easier to use and care for than others. Important alternatives provided by ISO 12402 (all parts):2020 are the following:

- to provide higher levels of support (levels 100, 150, or 275) that generally float the user with greater water clearance, when required for increasingly severe conditions; or to provide lighter or less bulky PFDs (levels 50 or 100);
- to provide the kinds of flotation (inherently buoyant foam, hybrid, and inflatable) that accommodate the sometimes conflicting needs of reliability and durability, in-water performance, and continuous wear;

1) The International Maritime Organization (IMO) is an institution with domicile in London issuing regulations which are then published as laws by its Member States.

- to provide automatically operating (inherently buoyant or automatically inflated) PFDs that float users without any intervention on their part, except in initially donning the PFD (and regular inspection and rearming of inflatable types), or to provide user control of the inflatable PFD's buoyancy by manual and oral operation; and
- to assist in detection (location aids) and recovery of the user.

PFDs provide various degrees of buoyancy in garments that are light in weight and only as bulky and restrictive as needed for their intended use. They need to be secure when worn, in order to provide positive support in the water and to allow users to swim or actively assist themselves or others. The PFD selected ensures that the user is supported with the mouth and nose clear of the water under the expected conditions of use and the user's ability to assist.

Under certain conditions (such as rough water and waves), the use of watertight and multilayer clothing, which provide (intentionally or otherwise) additional buoyancy, or the use of equipment with additional weight (such as tool belts) can alter the performance of the PFD. Users, owners and employers need to ensure that this is taken into account when selecting a PFD. Similarly, it is possible that PFDs do not perform as well in extremes of temperature, although meeting ISO 12402 (all parts):2020 requirements. PFDs can also be affected by other conditions of use, such as chemical exposure and welding, and can require additional protection to meet the specific requirements of use. Taking a PFD into such conditions necessitates the assurance that the PFD will not be adversely affected. ISO 12402 (all parts):2020 also allows a PFD to be an integral part of a safety harness designed to conform to ISO 12401:2009, or an integral part of a garment with other uses, for example to provide thermal protection during immersion, in which case the complete assembly as used is expected to conform to ISO 12402 (all parts):2020.

In compiling the attributes required of a PFD, consideration has also been given to the potential length of service that the user might expect. Whilst a PFD needs to be of substantial construction and material, its potential length of service often depends on the conditions of use and storage, which are the responsibility of the owner, user and/or employer. Furthermore, whilst the performance tests included are believed to assess relevant aspects of performance in real-life use, they do not accurately simulate all conditions of use. For example, the fact that a device passes the self-righting tests in swimming attire, as described herein, does not guarantee that it will self-right an unconscious user wearing clothing; neither can it be expected to completely protect the airway of an unconscious person in rough water. Waterproof clothing can trap air and further impair the self-righting action of a lifejacket.

It is essential that owners, users and employers choose those PFDs that meet the correct standards for the circumstances in which they will be used.

The characteristics of the product properties, alternative choices and the limitations to normal use are to be explained to potential buyers by manufacturers and distributors of PFDs prior to purchase.

Similarly, it is advised that regulators regarding the use of these garments consider carefully which class and performance levels are most appropriate for the foreseeable conditions of use, allowing for the higher risk circumstances. These higher risk circumstances should account for the highest probabilities of occurrence of accidental immersion and expected consequences. Requirements and recommendations for the correct selection and application of PFDs are given in ISO 12402-10:2020.

Personal flotation devices —

Part 9: Evaluation

1 Scope

This document specifies the processes for evaluation of personal flotation devices for fulfilment of the requirements in ISO 12402-2:2020 to ISO 12402-6:2020, with which this document is intended to be used.

The classification of PFDs used in the ISO 12402 series:2020 is given in [Annex A](#) for information.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 139:2005+Amd.1:2011, *Textiles — Standard atmospheres for conditioning and testing*

ISO 2768-1:1989, *General tolerances — Part 1: Tolerances for linear and angular dimensions without individual tolerance indications*

ISO 3386-1:1986+Amd.1:2010, *Polymeric materials, cellular flexible — Determination of stress-strain characteristics in compression — Part 1: Low-density materials*

ISO 12401:2009, *Small craft — Deck safety harness and safety line — Safety requirements and test methods*

ISO 12402-2:2020, *Personal flotation devices — Part 2: Lifejackets, performance level 275 — Safety requirements*

ISO 12402-3:2020, *Personal flotation devices — Part 3: Lifejackets, performance level 150 — Safety requirements*

ISO 12402-4:2020, *Personal flotation devices — Part 4: Lifejackets, performance level 100 — Safety requirements*

ISO 12402-5:2020, *Personal flotation devices — Part 5: Buoyancy aids (level 50) — Safety requirements*

ISO 12402-6:2020, *Personal flotation devices — Part 6: Special purpose lifejackets and buoyancy aids — Safety requirements and additional test methods*

ISO 12402-7:2020, *Personal flotation devices — Part 7: Materials and components — Safety requirements and test methods*

ISO 12402-8:2020, *Personal flotation devices — Part 8: Accessories — Safety requirements and test methods*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <http://www.electropedia.org/>

**3.1
personal flotation device**

PFD

garment or device which, when correctly worn and used in water, provides the user with a specific amount of buoyancy which increases the likelihood of survival

**3.2
inherently buoyant**

permanently less dense than water

**3.3
automatic inflation**

inflation of the *PFD* (3.1) without the user carrying out any action at the time of water immersion

**3.4
manual inflation**

inflation of the *PFD* (3.1) resulting from the user operating a mechanism

**3.5
oral inflation**

inflation resulting from the user blowing air into the *PFD* (3.1) by mouth

**3.6
PFD with secondary donning**

PFD (3.1) for which additional donning or adjustment is needed to place the PFD in its functioning position from the position it is normally worn

**3.7
vest-type PFD**

PFD (3.1) covering the upper trunk of the user like a vest

**3.8
yoke-type PFD**

PFD (3.1) in a style worn around the back of the neck and secured by a waist strap

**3.9
buddy line**

length of cord which can be tied or otherwise fixed to another person or to that person's *PFD* (3.1) or other objects, so as to keep a user in the vicinity of that person or object with a view to making location and thus rescue easier

**3.10
lifting loop**

device which facilitates manual recovery of a person from water

**3.11
whistle**

device which, when blown by mouth, produces an audible sound which can aid in the location of the user

**3.12
hybrid PFD**

PFD (3.1) of combined buoyancy types, i.e. inherent and inflatable

**3.13
sheltered waters**

water with protection from significant breaking waves, current, or strong winds, where the possibility of being blown or carried away from shore or place of safety is minimal

3.14**offshore**

water that is unprotected and influenced by threat conditions such as waves, tide, currents, or wind, at sea or on inland waters

3.15**primary means of inflation**

means of inflating an inflation chamber that meets the applicable PFD performance requirements and that requires the least amount of intervention by the user, generally according to the following order of precedence: automatic (easiest), manual (second), and oral (most difficult)

3.16**primary chamber**

inflation chamber associated with the *primary means of inflation* (3.15) that alone meets the applicable PFD (3.1) performance requirements

3.17**back-up chamber**

inflation chamber other than the *primary chamber(s)* (3.16) or *supplemental chamber* (3.18) that, when used alone, provides performance in case the primary chamber fails to function

3.18**supplemental chamber**

inflation chamber other than a *primary chamber* (3.16) or *back-up chamber* (3.17) that is intended for deployment after stabilization in the water, and provides enhanced performance such as higher freeboard, improved head support, additional stability, splash protection, location, detection

3.19**status indicator**

part or parts of an inflation system which provide user feedback to assist in keeping an inflatable PFD in an armed and ready condition

3.20**adult lifejacket**

PFD (3.1) intended for users with a body mass greater than 40 kg

3.21**infant lifejacket**

lifejacket intended for users with a body mass less than or equal to 15 kg

3.22**child lifejacket**

lifejacket intended for users with a body mass greater than 15 kg and less than or equal to 40 kg

3.23**child buoyancy aid**

buoyancy aid intended for users with a body mass greater than 25 kg and less than or equal to 40 kg

3.24**collar handle**

device on the upper back of a PFD (3.1) which facilitates getting hold of the wearer

3.25**test panel**

group of persons, experienced in testing PFDs (3.1), who observes the *test subjects* (3.26) undergoing the tests

3.26**test subject**

human selected to be an integral part of a test

4 Classification of personal flotation devices

An overview of this classification is given in [Annex A](#) for information.

5 Test methods

5.1 General

PFDs/devices that aim to fulfil the requirements and essential requirements of ISO 12402-2:2020 to ISO 12402-6:2020 shall pass the applicable procedures and sequences as specified in the following order in this part.

Unless otherwise specified, a new sample of the PFD to be tested may be used for each of the tests.

The tests shall be performed in a sequence in accordance with [Table 1](#) for inherently buoyant PFDs and [Table 2](#) for inflatable PFDs. The temperature cycling test in [5.5.3](#), and the rotating shock bin test in [5.5.2](#) shall be carried out prior to all other tests.

A combination of a PFD and accessories shall not impair the performance of either item. This shall be proved by testing the PFD and accessories in combination. If necessary, the test sequence has to be arranged accordingly. Requirements and test methods for accessories are specified in ISO 12402-8:2020.

The human subject performance tests shall be carried out under the direction of a test panel. The test panel shall consist of 2 persons.

If there is any question about the performance observed, the test shall be repeated with an additional person. The panel is to be qualified by having experience of observing or conducting the specific test (see Note 1) on at least 3 occasions.

NOTE 1 Specific test means, for instance, that experience with stability testing would not qualify for self-righting testing or that experience with self-righting testing of inherently buoyant PFDs would not qualify as experience with similar testing of inflatable PFDs.

NOTE 2 It is recommended that the test panel have at least one member regularly participating in experience exchanges and round robin tests.

5.2 Sampling and conditioning

5.2.1 Sampling

One sample of each size of the device to be tested shall be provided, unless otherwise specified in this document.

5.2.2 Conditioning

Prior to testing, the samples shall be conditioned for $(24 \pm 0,1)$ h under the appropriate standard atmosphere as defined in ISO 139:2005+Amd.1:2011 according to the specific fabric used for the PFD.

If testing under wet conditions is required, the sample shall be soaked for (5 ± 1) min in fresh water, or as specified by the test procedure itself.

5.3 Criteria

All required samples of the PFD shall pass all tests specified in [5.5](#) for the entire device to meet the requirements of the relevant parts of the ISO 12402 series:2020.

5.4 Magnetic properties testing

Place a direct-reading magnetic compass in an undisturbed magnetic area (i.e. an area in which magnetic items and d.c. electrical cables are not continually moved or switched). Check the compass to ensure that it has negligible pivot friction. This can be done by deflecting the compass card by 10° by means of a magnet and then removing the deflecting force, when the card should return to within 0,5° of its original position.

Present all metal components (with any hooks closed) individually to the compass on an approximately east-to-west line, to a position where the nearest point of the component is (500 ± 10) mm horizontally from the centre of the compass. Lightly tap the compass to eliminate the effect of friction. Record the angle, in degrees, of any deflection of the compass from its position before the metal components were brought near the compass.

5.5 Mechanical properties tests

5.5.1 General

The mechanical properties of the PFD shall be tested to determine if the device:

- provides resistance against wear and tear;
- remains functional after extreme temperatures;
- remains functional after external loads are applied; and
- remains functional after exposed to flames.

The mechanical properties tests shall be conducted in the sequence in accordance with [Table 1](#) or [Table 2](#) on device(s) of the required size(s). The samples in [Tables 1](#) and [Table 2](#) shall follow the test sequence defined.