



Designation: E729 – 96(Reapproved 2007)

Standard Guide for Conducting Acute Toxicity Tests on Test Materials with Fishes, Macroinvertebrates, and Amphibians¹

This standard is issued under the fixed designation E729; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This guide (1)² describes procedures for obtaining laboratory data concerning the adverse effects (for example, lethality and immobility) of a test material added to dilution water, but not to food, on certain species of freshwater and saltwater fishes, macroinvertebrates, and amphibians during 2 to 8-day exposures, depending on the species. These procedures will probably be useful for conducting acute toxicity tests with many other aquatic species, although modifications might be necessary.

1.2 Other modifications of these procedures might be justified by special needs or circumstances. Although using appropriate procedures is more important than following prescribed procedures, results of tests conducted using unusual procedures are not likely to be comparable to results of many other tests. Comparison of results obtained using modified and unmodified versions of these procedures might provide useful information concerning new concepts and procedures for conducting acute tests.

1.3 This guide describes tests using three basic exposure techniques: static, renewal, and flow-through. Selection of the technique to use in a specific situation will depend on the needs of the investigator and on available resources. Tests using the static technique provide the most easily obtained measure of acute toxicity, but conditions often change substantially during static tests; therefore, static tests should not last longer than 96 h, and test organisms should not be fed during such tests. Static tests should probably not be conducted on materials that have a high oxygen demand, are highly volatile, are rapidly transformed biologically or chemically in aqueous solution, or are removed from test solutions in substantial quantities by the test chambers or organisms during the test. Because the pH and

concentrations of dissolved oxygen and test material are maintained at desired levels and degradation and metabolic products are removed, tests using renewal and flow-through methods are preferable and may last longer than 96 h; test organisms may be fed during renewal and flow-through tests. Although renewal tests might be more cost-effective, flow-through tests are generally preferable.

1.4 Acute tests may be performed to meet regulatory data requirements or to obtain time-independent estimates of toxicity.

1.4.1 If the objective is to obtain data to meet regulatory requirements, it may be necessary to limit the number of observation times based on stipulations of the regulatory agency and cost considerations.

1.4.2 If the objective of an acute toxicity test is to determine a time-independent (that is, incipient, threshold, or asymptotic) toxicity level, an appropriate number of observations must be taken over an exposure duration of sufficient length to establish the shape of the toxicity curve or allow the direct or mathematically estimated determination of a time-independent toxicity value (1), or both.

1.5 In the development of these procedures, an attempt was made to balance scientific and practical considerations and to ensure that the results will be sufficiently accurate and precise for the applications for which they are commonly used. A major consideration was that the common uses of the results of acute toxicity tests do not require or justify stricter requirements than those set forth herein. Although the tests may be improved by using more organisms, longer acclimation times, and so forth, the requirements presented herein should usually be sufficient.

1.6 Results of acute toxicity tests should usually be reported in terms of an LC50 (median lethal concentration) or EC50 (median effective concentration) at the end of the test, but it is desirable to provide information concerning the dependence of adverse effects on both time and concentration. Thus, when feasible, flow-through and renewal tests should be conducted so that LC50s or EC50s can be reported from 6 h to an asymptotic (time-independent, threshold, incipient) value, if one exists. In some situations, it might only be necessary to

¹ This guide is under the jurisdiction of ASTM Committee E50 on Environmental Assessment, Risk Management and Corrective Action and is the direct responsibility of Subcommittee E50.47 on Biological Effects and Environmental Fate.

Current edition approved Oct. 1, 2007. Published October 2007. Originally approved in 1980. Last previous edition approved in 2002 as E729 – 96(2002). DOI: 10.1520/E0729-96R07.

² The boldface numbers in parentheses refer to the list of references at the end of this standard.

determine whether a specific concentration is acutely toxic to the test species or whether the LC50 or EC50 is above or below a specific concentration.

1.7 This guide is arranged as follows:

	Section
Referenced Documents	2
Terminology	3
Summary of Guide	4
Significance and Use	5
Apparatus	6
Facilities	6.1
Special Requirements	6.2
Construction Materials	6.3
Metering System	6.4
Test Chambers	6.5
Cleaning	6.6
Acceptability	6.7
Hazards	7
Dilution Water	8
Requirements	8.1
Source	8.2
Treatment	8.3
Characterization	8.4
Test Material	9
General	9.1
Stock Solution	9.2
Test Concentration(s)	9.3
Test Organisms	10
Species	10.1
Age	10.2
Source	10.3
Care and Handling	10.4
Feeding	10.5
Disease Treatment	10.6
Holding	10.7
Acclimation	10.8
Quality	10.9
Procedure	11
Experimental Design	11.1
Dissolved Oxygen	11.2
Temperature	11.3
Loading	11.4
Beginning the Test	11.5
Feeding	11.6
Duration of Test	11.7
Biological Data	11.8
Other Measurements	11.9
Analytical Methodology	12
Acceptability of Test	13
Calculation of Results	14
Report	15

1.8 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.9 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* Specific hazard statements are given in Section 7.

2. Referenced Documents

2.1 ASTM Standards:³

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

E724 Guide for Conducting Static Acute Toxicity Tests Starting with Embryos of Four Species of Saltwater Bivalve Molluscs

E943 Terminology Relating to Biological Effects and Environmental Fate

E1023 Guide for Assessing the Hazard of a Material to Aquatic Organisms and Their Uses

E1191 Guide for Conducting Life-Cycle Toxicity Tests with Saltwater Mysids

E1192 Guide for Conducting Acute Toxicity Tests on Aqueous Ambient Samples and Effluents with Fishes, Macroinvertebrates, and Amphibians

E1203 Practice for Using Brine Shrimp Nauplii as Food for Test Animals in Aquatic Toxicology (Withdrawn 2013)⁴

E1563 Guide for Conducting Static Acute Toxicity Tests with Echinoid Embryos

E1604 Guide for Behavioral Testing in Aquatic Toxicology

IEEE/ASTM SI 10 Standard for Use of the International System of Units (SI) (the Modernized Metric System)

3. Terminology

3.1 Acute toxicity tests are generally used to determine the concentration of test material that produces a specific adverse effect on a specified percentage of test organisms during a short exposure. Because death is an obviously important adverse effect and is easily detected for many species, the most common acute toxicity test is the acute lethality test. Experimentally, effect on 50 % of a group of test organisms is the most reproducible and easily determined measure of toxicity, and 96 h is often a convenient, useful exposure duration. Therefore, the measure of acute toxicity most often used with fishes, macroinvertebrates, and amphibians is the 96-h LC50. However, because immobilization is a severe effect and is not easy to distinguish from death for some species, the measure of acute toxicity most often used with daphnids and midge larvae is the 48-h EC50 based on death plus immobilization. The terms LC50 and EC50 are consistent with the widely used toxicological terms LD50 (median lethal dose) and ED50 (median effective dose), respectively. The terms LC50 and EC50 should be used whenever results are calculated based on the concentration of test material in dilution water, whereas the terms LD50 and ED50 should be used whenever results are calculated based on the quantity of test material that enters or is applied directly to test organisms. For toxic agents or tests for which neither concentration nor dose is appropriate, such as tests on temperature or with poorly water-soluble materials, the terms LL50 (median lethal level) and EL50 (median effective level) should be used, if the effect is dichotomous. For tests in which the effect is expressed as a percent inhibition compared to the control, for example, a percent inhibition in growth, and not as the percentage of the individual organisms that were affected, the term IC50 should be used to denote the concentration that causes a 50 % inhibition compared to the control.

3.2 Acute toxicity tests in which test organisms are exposed to test solutions containing a test material can be conducted by at least four techniques:

⁴ The last approved version of this historical standard is referenced on www.astm.org.

3.2.1 In the static technique, test solutions and organisms are placed in chambers and kept there for the duration of the test.

3.2.2 The recirculation technique is like the static technique except that each test solution is continuously circulated through an apparatus designed to maintain water quality, and possibly remove degraded, but not undegraded, test material by such means as aeration, filtration, and sterilization and then returned to the test chamber.

3.2.3 The renewal technique is like the static technique except that test organisms are periodically exposed to fresh test solution of the same composition, usually once every 24 h, either by transferring the organisms from one test chamber to another or by replacing nearly all the test solution.

3.2.4 In the flow-through technique, test solution flows through the test chamber on a once-through basis throughout the test.

3.2.4.1 Two procedures may be used. In the first a large volume of each test solution is prepared before the beginning of the test, and these solutions flow through the respective chambers. In the second and more common procedure, fresh test solutions are prepared continuously or every few minutes just before they enter the respective test chambers. In both procedures a metering system controls the flow of test solution, and in the latter procedure the test solutions are prepared by the metering system. Both of the procedures may be used to conduct continuous-flow tests. Many tests conducted using the second procedure, however, are intermittent-flow tests because the metering system cycles and delivers test solution every few minutes.

3.2.5 With any of these techniques a pump or stirrer can be used to create a current in the test chamber to accommodate particular species, but the current will often increase both aeration and volatilization.

3.3 In flow-through tests a “volume addition” is the introduction into the test chamber of a volume of test solution equal to the volume of solution in the chamber.

3.4 For the purposes of 8.4.1, the term “organophosphorus pesticides” refers to chlorpyrifos, demeton, diazinon, disulfoton, fenitrothion, malathion, methyl parathion, and parathion; the term “organochlorine pesticides” refers to aldrin, chlordane, DDD, DDE, DDT, dieldrin, endosulfan, endrin, heptachlor, heptachlor epoxide, lindane, methoxychlor, mirex, and toxaphene; and the term “chlorinated phenoxy herbicides” refers to the free acids, salts, and esters of 2,4-D, dicamba, silvex, and 2,4,5-T. The term “organic chlorine” refers to chlorine that would be detected if, when samples are prepared for gas chromatographic analysis for polychlorinated biphenyls (PCBs) and the organochlorine pesticides listed above, a chloride detector is used instead of an electron capture detector to measure compounds that elute from just before lindane to just after mirex on the gas chromatograph being used. Organic chlorine does not refer only to chlorine associated with organochlorine pesticides and PCBs; it refers to all chlorine that elutes within the specified period.

3.5 *reconstituted water*—a dilution water that is prepared by adding sea salt or appropriate amounts of selected chemicals to

water, which is usually prepared using deionization, distillation, or reverse osmosis, so that the concentrations and ratios of the major ions in the dilution water are similar to those in comparable natural surface waters.

3.6 The words “must,” “should,” “may,” “can,” and “might” have very specific meanings in this guide. “Must” is used to express an absolute requirement, that is, to state that the test ought to be designed to satisfy the specified condition, unless the purpose of the test requires a different design. “Must” is only used in connection with factors that directly relate to the acceptability of the test (see 13.1). “Should” is used to state that the specified condition is recommended and ought to be met if possible. Although violation of one “should” is rarely a serious matter, violation of several will often render the results questionable. Terms such as “is desirable,” “is often desirable,” and “might be desirable” are used in connection with less important factors. “May” is used to mean “is (are) allowed to,” “can” is used to mean “is (are) able to,” and “might” is used to mean “could possibly.” Thus the classic distinction between “may” and “can” is preserved, and “might” is never used as a synonym for either “may” or “can.”

3.7 *IC50*—a statistically or graphically estimated concentration of test material that is expected to cause a 50 % inhibition of one or more specified biological processes (such as growth or reproduction), for which the data are not dichotomous, under specified conditions.

3.8 For definitions of other terms used in this guide, refer to Terminology E943 and Guide E1023. For an explanation of units and symbols, refer to Standard IEEE/ASTM SI 10.

4. Summary of Guide

4.1 In each of two or more treatments, test organisms of one species are maintained for 2 to 8 days in one or more test chambers. In each of the one or more control treatments, the organisms are maintained in dilution water to which no test material has been added in order to provide (1) a measure of the acceptability of the test by giving an indication of the quality of the test organisms and the suitability of the dilution water, test conditions, handling procedures, and so forth, and (2) the basis for interpreting data obtained from the other treatments. In each of the one or more other treatments, the organisms are maintained in dilution water to which a selected concentration of test material has been added. Data concerning effects on the organisms in each test chamber are usually obtained periodically during the test and analyzed to determine LC50s, EC50s, or IC50s for various lengths of exposure.

5. Significance and Use

5.1 An acute toxicity test is conducted to obtain information concerning the immediate effects on test organisms of a short-term exposure to a test material under specific experimental conditions. An acute toxicity test does not provide information about whether delayed effects will occur, although a post-exposure observation period, with appropriate feeding, if necessary, might provide such information.

5.2 Results of acute toxicity tests might be used to predict acute effects likely to occur on aquatic organisms in field

situations as a result of exposure under comparable conditions, except that (1) motile organisms might avoid exposure when possible, and (2) toxicity to benthic organisms might be dependent on sorption or settling of the test material onto the substrate.

5.3 Results of acute tests might be used to compare the acute sensitivities of different species and the acute toxicities of different test materials, and to study the effects of various environmental factors on results of such tests.

5.4 Results of acute toxicity tests might be an important consideration when assessing the hazards of materials to aquatic organisms (see Guide E1023) or when deriving water quality criteria for aquatic organisms (2).

5.5 Results of acute toxicity tests might be useful for studying the biological availability of, and structure-activity relationships between, test materials.

5.6 Results of acute toxicity tests will depend on the temperature, composition of the dilution water, condition of the test organisms, exposure technique, and other factors.

6. Apparatus

6.1 *Facilities*—Although some small organisms can be held and acclimated in static or renewal systems, most organisms are held, acclimated, and cultured in flow-through systems. Test chambers should be in a constant-temperature room, incubator, or recirculating water bath. For static and renewal tests a dilution-water tank, which may be used to prepare reconstituted water, is often elevated so that dilution water can be gravity fed into holding and acclimation tanks and test chambers. For flow-through tests an elevated headbox is often desirable so that dilution water can be gravity fed into holding and acclimation tanks and into the metering system (see 6.4), which prepares the test solutions and delivers them to the test chambers. Strainers and air traps should be included in the water-supply system. Headboxes and holding, acclimation, culture, and dilution-water tanks should be equipped for temperature control and aeration (see 8.3.1). Air used for aeration should be free of fumes, oil, and water; filters to remove oil and water are desirable. Filtration of air through a 0.22- μm bacterial filter might be desirable (3). The facility should be well-ventilated and free of fumes. To further reduce the possibility of contamination by test materials and other substances, especially volatile ones, holding, acclimation, and culture tanks should not be in a room in which toxicity tests are conducted, stock solutions or test solutions are prepared, or equipment is cleaned. Organisms should be shielded from disturbances with curtains or partitions to prevent unnecessary stress during holding, acclimation, culture, and testing. A timing device should be used to provide a 16-h light and 8-h dark photoperiod. A 15 to 30-min transition period (4) when the lights go on might be desirable to reduce the possibility of organisms being stressed by large, sudden increases in light intensity. A transition period when the lights go off might also be desirable.

6.2 *Special Requirements*—Some organisms require special conditions during holding, acclimation, and testing. For example, burrowing mayfly nymphs should be provided a

substrate suitable for burrowing (5) or artificial burrows (6, 7); immature stream insects should be provided with a current (6) or mild aeration, or both (7); and crabs, shrimp, and bottom-dwelling fish should be provided a silica sand substrate. Because cannibalism might occur among many species of decapod crustaceans, the claws of crabs and crayfish should be banded, or the individuals should be physically isolated by such means as screened compartments.

6.3 *Construction Materials*—Equipment and facilities that contact stock solutions, test solutions, or any water into which test organisms will be placed should not contain substances that can be leached or dissolved by aqueous solutions in amounts that adversely affect test organisms. In addition, equipment and facilities that contact stock solutions or test solutions should be chosen to minimize sorption of test materials from water. Glass, Type 316 stainless steel, nylon, and fluorocarbon plastics should be used whenever possible to minimize dissolution, leaching, and sorption, except that stainless steel should not be used in tests on metals in salt water. Concrete and rigid plastics may be used for holding, acclimation, and culture tanks in the water-supply system, but these materials should be soaked, preferably in flowing dilution water, for a week or more before use (7). Cast iron pipe should not be used with salt water and probably should not be used in a freshwater-supply system because colloidal iron will probably be added to the dilution water, and strainers will be needed to remove rust particles. A specially designed system is usually necessary to obtain salt water from a natural water source (8). Brass, copper, lead, galvanized metal, and natural rubber should not contact dilution water, stock solutions, or test solutions before or during the test. Items made of neoprene rubber or other materials not previously mentioned should not be used unless it has been shown that either (1) unfed individuals of a sensitive aquatic species (see 8.1.1.1 and 8.1.1.2) do not show more signs of stress, such as discoloration, unusual behavior, or death, when held for at least 48 h in static dilution water in which the item is soaking than when held in static dilution water that does not contain the item, or (2) their use will not adversely affect survival, growth, or reproduction of a sensitive species.

6.4 Metering System:

6.4.1 For flow-through tests, the metering system should be designed to accommodate the type and concentration(s) of the test material and the necessary flow rates of test solutions. The system should permit the mixing of test material with dilution water immediately before entrance to the test chambers and permit the supply of the selected concentration(s) of test material (see 9.3 and 11.9.3.4) in a reproducible fashion. Various metering systems, using different combinations of syringes, “dipping birds,” siphons, pumps, saturators, solenoids, valves, and so forth, have been used successfully to control the concentrations of test material in, and the flow rates of, test solutions (9). Proportional diluters (10) use an intermittent flow design and various devices for metering the test material (11). Continuous-flow metering systems are also available, as are systems that prepare the different test solutions independently of each other (9).

6.4.2 The metering system should be calibrated before and after the test by determining the flow rate through each test chamber and by measuring either the concentration of test material in each test chamber or the volume of solution used in each portion of the metering system. The general operation of the metering system should be visually checked daily in the morning and afternoon throughout the test. The metering system should be adjusted during the test if necessary.

6.4.3 The flow rate through each test chamber should be at least five-volume additions per 24 h. It is usually desirable to construct the metering system so that it can provide at least ten-volume additions per 24 h, if desired, in case (1) the loading is high (see 11.4) or (2) there is rapid loss of test material due to microbial degradation, hydrolysis, oxidation, photolysis, reduction, sorption, or volatilization (see 11.9.3.4). In shell deposition tests with saltwater bivalve molluscs, the minimum necessary flow rate might also depend on the amount of food available in the dilution water (see 10.5.3). At any particular time during the test, the flow rates through any two test chambers should not differ by more than 10 %.

6.5 Test Chambers:

6.5.1 In a toxicity test with aquatic organisms, test chambers are defined as the smallest physical units between which no water connections exist. However, screens, cups, and so forth, may be used to create two or more compartments within each chamber. Therefore, the test solution can flow from one compartment to another within a test chamber, but, by definition, cannot flow from one chamber to another. Because the solution can flow from one compartment to another in the same test chamber, the temperature, concentration of test material, and levels of pathogens and extraneous contaminants are likely to be more similar between compartments in the same test chamber than between compartments in different test chambers in the same treatment. Chambers should be covered to keep out extraneous contaminants and, especially in static and renewal tests, to reduce evaporation of test solution and test material. Also, chambers filled to within 150 mm of the top sometimes need to be covered to prevent organisms from jumping out. All chambers (and compartments) in a test must be identical.

6.5.2 Test chambers may be constructed by welding, but not soldering, stainless steel or by gluing double-strength or stronger window glass with clear silicone adhesive. Stoppers and silicone adhesive sorb some organochlorine and organophosphorus pesticides, which are then difficult to remove. Therefore, as few stoppers and as little adhesive as possible should be in contact with test solution. If extra beads of adhesive are needed for strength, they should be on the outside of chambers rather than on the inside. Especially in static and renewal tests, the size and shape of the test chamber might affect the results of tests on materials that volatilize or sorb onto the chambers in substantial quantities.

6.5.3 The minimum acceptable dimensions of test chambers and the minimum depth of test solution depend on the size of the individual test organisms and the loading (see 11.4). The smallest horizontal dimension of the test chambers should be at least three times the largest horizontal dimension of the largest test organism. The depth of the test solution should be at least

three times the height of the largest test organism. In addition, the test solution should be at least 150 mm deep for organisms over 0.5 g (wet weight) each, and at least 50 mm deep for smaller organisms. Use of excessively large volumes of solution in test chambers will probably unnecessarily increase the amount of dilution water and test material used, and, in flow-through tests, increase the average retention time.

6.5.4 For static and renewal tests, organisms weighing more than 0.5 g (wet weight) each are often exposed in 19-L (5-gal) wide-mouth soft-glass bottles (12) containing 15 L of solution or in 300 by 600 by 300-mm deep all-glass test chambers. Smaller organisms are often exposed in 500-mL to 1-L glass beakers containing 200 to 800 mL of solution. Daphnids and midge larvae are often exposed in 100-mL beakers containing 50 mL of solution.

6.5.5 For flow-through tests, chambers may be constructed by modifying glass bottles, battery jars, or beakers to provide screened overflow holes, standpipes, or V-shaped notches. Organisms weighing more than 0.5 g (wet weight) each are often exposed in 30 L of solution in 300 by 600 by 300-mm deep all-glass test chambers. Smaller organisms are often exposed in 2 to 4 L of solution. In tests with daphnids and other small species, the test chambers or metering system, or both, should be constructed so that the organisms are not stressed by turbulence (13).

6.5.6 Embryos are often exposed in glass cups with stainless steel or nylon screen bottoms or cups constructed by welding stainless steel screen or gluing nylon screen with clear silicone adhesive. The cups should be suspended in the test chambers in such a way as to ensure that the embryos are always submerged and that test solution regularly flows into and out of the cups without creating too much turbulence.

6.6 *Cleaning*—The metering system, test chambers, and equipment used to prepare and store dilution water, stock solutions, and test solutions should be cleaned before use. New items should be washed with detergent and rinsed with water, a water-miscible organic solvent, water, acid (such as 10 % concentrated hydrochloric acid (HCl)), and rinsed at least twice with deionized, distilled, or dilution water. Reagent grade solvents are recommended. If lesser grades are used, possible contaminants should be considered with respect to the purpose of the test. (Some lots of some organic solvents might leave a film that is insoluble in water.) A dichromate-sulfuric acid cleaning solution may be used in place of both the organic solvent and the acid, but it might attack silicone adhesive. At the end of the test, all items that are to be used again should be immediately (1) emptied, (2) rinsed with water, (3) cleaned by a procedure appropriate for removing the test material (for example, acid to remove metals and bases, detergent, organic solvent, or activated carbon to remove organic chemicals), and (4) rinsed at least twice with deionized, distilled, or dilution water. Acid is often used to remove mineral deposits, and 200 mg of hypochlorite (ClO^-)/L is often used to remove organic matter and for disinfection. (A solution containing about 200 mg of ClO^- /L may be prepared by adding 6 mL of liquid household chlorine bleach to 1 L of water. However, ClO^- is quite toxic to many aquatic animals (14) and is difficult to remove from some construction materials. It is often removed

by soaking in a sodium thiosulfate, sodium sulfite, or sodium bisulfite solution, by autoclaving in distilled water for 20 min, or by drying the item and letting it sit for at least 24 h before use. An item cleaned or disinfected with hypochlorite should not be used unless it has been demonstrated at least once that unfed individuals of a sensitive aquatic species (see 8.1.1.1 and 8.1.1.2) do not show more signs of stress, such as discoloration, unusual behavior, or death, when held for at least 48 h in static dilution water in which the item is soaking than when held in static dilution water containing a similar item that was not treated with ClO₂. The metering system and test chambers should be rinsed with dilution water just before use.

6.7 *Acceptability*—The acceptability of new holding, acclimation, and testing facilities should be demonstrated with a sensitive species (see 8.1.1.1 and 8.1.1.2) before use.

7. Hazards

7.1 Many materials can affect humans adversely if precautions are inadequate. Therefore, skin contact with all test materials and solutions of them should be minimized by such means as wearing appropriate protective gloves (especially when washing equipment or putting hands in test solutions), laboratory coats, aprons, and glasses, and by using dip nets, forceps, or tubes to remove organisms from test solutions. Special precautions, such as covering test chambers and ventilating the area surrounding the chambers, should be taken when conducting tests on volatile materials. Information on toxicity to humans (15), recommended handling procedures (16), and biological, chemical, and physical properties of the test material should be studied before a test is begun. (See Appendixes X2, X3, and X4 of Guide E1023.) Special procedures might be necessary with radiolabeled test materials (17) and with test materials that are, or are suspected of being, carcinogenic (18).

7.2 Although disposal of stock solutions, test solutions, and test organisms poses no special problems in most cases, health and safety precautions and applicable regulations should be considered before beginning a test. Removal or degradation of test material might be desirable before disposal of stock and test solutions.

7.3 Cleaning of equipment with a volatile solvent such as acetone should be performed only in a well-ventilated area in which no smoking is allowed and no open flame, such as a pilot light, is present.

7.4 An acidic solution should not be mixed with a hypochlorite solution because hazardous fumes might be produced.

7.5 To prepare dilute acid solutions, concentrated acid should be added to water, not vice versa. Opening a bottle of concentrated acid and adding concentrated acid to water should be performed only in a fume hood.

7.6 Because dilution water and test solutions are usually good conductors of electricity, use of ground fault systems and leak detectors should be considered to help prevent electrical shocks. Salt water is such a good conductor that protective devices are strongly recommended.

7.7 To protect hands from being cut by sharp edges of shells, cotton work gloves should be worn (over appropriate

protective gloves (see 7.1) if necessary) when juvenile and adult bivalve molluscs are handled.

8. Dilution Water

8.1 *Requirements*—The dilution water should (1) be available in adequate supply, (2) be acceptable to the test organisms, (3) be of uniform quality, and (4) except as stated in 8.1.4, not unnecessarily affect results of the test.

8.1.1 The minimal requirement for an acceptable dilution water for acute toxicity tests is that healthy test organisms survive in it through acclimation and testing without showing signs of stress, such as discoloration, unusual behavior, or death. A better criterion for an acceptable dilution water is that at least one species of aquatic animal (preferably of the one being tested or one taxonomically similar) will survive, grow, and reproduce satisfactorily in it.

8.1.1.1 *Fresh Water*—Because daphnids are more acutely sensitive to some test materials than many other aquatic animal species, water in which daphnids (less than 24-h old) will survive for 48 h without showing signs of stress is probably acceptable for acute tests with most freshwater animal species. Water in which daphnids will survive, grow, and reproduce satisfactorily in a life-cycle test is probably an acceptable dilution water for tests with most freshwater animal species.

8.1.1.2 *Salt Water*—Because *Acartia tonsa*, mysids (less than 24-h post-release from the brood sac), and bivalve mollusc larvae are more acutely sensitive to many test materials than many other saltwater animal species, water in which they will survive for 48 h without showing signs of stress is probably acceptable for acute tests with most saltwater animal species. Water in which *Acartia tonsa* or mysids will survive, grow, and reproduce satisfactorily in a life-cycle test is probably an acceptable dilution water for tests with most saltwater animal species.

8.1.2 The quality of the dilution water should be uniform so that the test organisms are cultured or acclimated and the test conducted in water of the same quality. In fresh water, the range of hardness should be less than 5 mg/L or 10 % of the average, whichever is higher. In salt water, the range of salinity should be less than 2 g/kg or 20 % of the average, whichever is higher.

8.1.3 The dilution water should not unnecessarily affect the results of an acute test because of such things as sorption or complexation of test material. Except as in accordance with 8.1.4, it is desirable for the purpose of reducing interlaboratory variability that the concentrations of both total organic carbon (TOC) and particulate matter should be less than 20 mg/L for shell deposition tests with saltwater bivalve molluscs (see 10.5.2) and less than 5 mg/L for all other tests.

8.1.4 If it is desired to study the effect of an environmental factor such as TOC, particulate matter, or dissolved oxygen on the results of an acute test, it will be necessary to use a water that is naturally or artificially high in TOC or particulate matter or low in dissolved oxygen. If such a water is used, it is important that adequate analyses be performed to characterize the water and that a comparable test be available or be conducted in a more usual dilution water to facilitate interpretation of the results in the special water.

8.2 Source:

8.2.1 Reconstituted Water:

8.2.1.1 If a reconstituted water is used for tests with freshwater species, the soft reconstituted water described in Table 1 should be used whenever possible, although some problems have been encountered with daphnids in this water. The other reconstituted fresh waters (Tables 1 and 2) may be used for studying the effects of water quality on results of toxicity tests. However, the buffers used in Table 2 might react chemically with some test materials. Because these waters might be deficient in some trace nutrients, addition of about 2 µg of selenium(IV) and 1 µg of crystalline vitamin B₁₂/L might be desirable (20), especially if daphnids are cultured in these waters.

8.2.1.2 If a reconstituted water is used for tests with saltwater species, the reconstituted water described in Table 3 should be used whenever possible. If desired, a reconstituted water may be prepared using a commercially obtained sea salt. However, because quality may differ among commercial brands, tests to determine the acceptability of the water (8.1.1) may be necessary. The reconstituted water should be used at a salinity of 34 g/kg and pH = 8.0 for tests with true marine stenohaline species, and at a salinity of 17 g/kg and pH = 7.7 with euryhaline species. Other salinities may be used for studying the effects of water quality on results of toxicity tests. It might be difficult to provide saltwater bivalve molluscs with an adequate amount of acceptable food (see 10.5.3) if reconstituted water is used for shell deposition tests.

8.2.1.3 Reconstituted water is prepared by adding a sea salt or specified amounts of reagent grade⁵ chemicals to high-quality water with (1) conductivity less than 1 µΩ/cm and (2) either total organic carbon (TOC) less than 2 mg/L or chemical oxygen demand (COD) less than 5 mg/L. Acceptable water can usually be prepared using properly operated deionization, distillation, or reverse osmosis units. Conductivity should be measured on each batch and TOC or COD should be measured at least twice a year and whenever substantial changes might be expected. If the water is prepared from a surface water, TOC or COD should be measured on each batch. The reconstituted water should be intensively aerated before use, except that the buffered soft fresh waters (Table 2) should be aerated before, but not after, addition of buffers. Problems have been encountered

TABLE 2 Quantities of Reagent Grade⁵ Chemicals to Be Added to Aerated Soft Reconstituted Fresh Water to Buffer pH (19)

NOTE 1—The solutions should not be aerated after addition of these chemicals.

pH ^A	Millilitres of Solution to Add to 15 L of Soft Water		
	1.0 N NaOH Solution	1.0 M KH ₂ PO ₄ Solution ^B	0.5 M H ₃ BO ₃ Solution ^B
6.0	1.3	80.0	...
6.5	5.0	30.0	...
7.0	19.0	30.0	...
7.5
8.0	19.0	20.0	...
8.5	6.5	...	40.0
9.0	8.8	...	30.0
9.5	11.0	...	20.0
10.0	16.0	...	18.0

^A Approximate equilibrium pH with fish in water.

^B Buffers containing ions such as phosphate and borate should not be used when conducting tests on metals unless it has been shown that the buffers do not affect the toxicity of the metal to the test species.

TABLE 3 Reconstituted Salt Water (21)

Add the following reagent grade⁵ chemicals in the amounts and order listed to 890 mL of water. Each chemical must be dissolved before the next is added.^A

Chemical	Amount
NaF	3 mg
SrCl ₂ ·6H ₂ O	20 mg
H ₃ BO ₃	30 mg
KBr	100 mg
KCl	700 mg
CaCl ₂ ·2H ₂ O	1.47 g
Na ₂ SO ₄	4.00 g
MgCl ₂ ·6H ₂ O	10.78 g
NaCl	23.50 g
Na ₂ SiO ₃ ·9H ₂ O	20 mg
Na ₄ EDTA ^B	1 mg
NaHCO ₃	200 mg

^A If the resulting solution is diluted to 1 L, the salinity should be 34 ± 0.5 g/kg and the pH should be 8.0 ± 0.2. The desired test salinity is attained by dilution at time of use.

^B Tetrasodium ethylenediaminetetraacetate. This should be omitted when toxicity tests are conducted on metals. When tests are conducted with fish or bivalve mollusc larvae, zooplankton, or crustaceans, the EDTA should be omitted and the reconstituted salt water stripped of trace metals (22).

tered with some species in some fresh and salt reconstituted waters, but sometimes these problems have been overcome by aging the reconstituted water for one or more weeks.

8.2.2 Natural Dilution Water:

TABLE 1 Quantities of Reagent Grade⁵ Chemicals Required to Prepare Reconstituted Fresh Waters (19) and the Resulting Water Qualities

Name	Salts Required, mg/L				pH ^A	pH ^B	Hardness ^C	Alkalinity ^C
	NaHCO ₃	CaSO ₄ ·2H ₂ O	MgSO ₄	KCl				
Very soft	12	7.5	7.5	0.5	6.7–6.8	6.4–6.9	10–13	10–13
Soft	48	30.0	30.0	2.0	7.3–7.5	7.2–7.6	40–48	30–35
Hard	192	120.0	120.0	8.0	7.8–8.0	7.6–8.0	160–180	110–120
Very hard	384	240.0	240.0	16.0	8.0–8.2	8.0–8.4	280–320	225–245

^A Approximate equilibrium pH after aeration.

^B Approximate equilibrium pH after aeration and with fish in water.

^C Expressed as mg CaCO₃/L.

8.2.2.1 If a natural dilution water is used, it should be obtained from an uncontaminated, uniform quality source. The quality of water from a well or spring is usually more uniform than that of water from a surface water. If a surface water is used as a source of fresh or salt water, the intake should be positioned (for example, about one metre below the surface) to minimize fluctuations in quality and the possibility of contamination, and to maximize the concentration of dissolved oxygen to help ensure that the concentrations of sulfide and iron are not high.

8.2.2.2 For shell deposition tests with saltwater bivalve molluscs, it might be desirable to position the intake to maximize the amount of phytoplankton that will support growth and survival (see 10.5.3).

8.2.2.3 The hardness, salinity, pH, and so forth, of a water may be adjusted, if desired, by addition of appropriate reagent grade⁵ chemicals, sea salt, acid, base, distilled or deionized water, and so forth, if desired. When necessary, sea salt may be added to salt water to prevent excessive decreases in salinity (see 8.1.2), if the salt has been shown to cause no adverse effects on the test species at the concentration used.

8.2.3 Chlorinated water should not be used as, or in the preparation of, dilution water because residual chlorine and chlorine-produced oxidants are toxic to many aquatic animals (14). Dechlorinated water should be used only as a last resort because dechlorination is often incomplete. Sodium bisulfite is probably better for dechlorinating water than sodium sulfite and both are more reliable than carbon filters, especially for removing chloramines (23). Some organic chloramines, however, react slowly with sodium bisulfite (24). In addition to residual chlorine, municipal drinking water often contains high concentrations of copper, lead, zinc, and fluoride, and quality is often rather variable. The concentrations of most metals can usually be reduced with a chelating resin (22), but use of a different dilution water might be preferable. If dechlorinated water is used as dilution water or in its preparation, during the test either (1) it must be shown that a sensitive aquatic species (see 8.1.1.1 and 8.1.1.2) will survive, grow, and reproduce acceptably in it, or (2) it must be shown at least three times each week on nonconsecutive days that in fresh samples of dilution water either (a) *Acartia tonsa*, mysids (less than 24-h post-release from the brood sac), bivalve mollusc larvae, or daphnids (less than 24-h old) do not show more signs of stress, such as discoloration, unusual behavior, or death, when held in the water for at least 48 h without food than when similarly held in a water that was not chlorinated and dechlorinated, or (b) the concentration of residual chlorine in fresh water is less than 11 µg/L or the concentration of chlorine-produced oxidants in salt water is less than 7.5 µg/L (14).

8.3 Treatment:

8.3.1 Except as stated in 8.2.1.3, dilution water should be aerated intensively by such means as air stones, surface aerators, or column aerators (25, 26) before adding test material. Adequate aeration will bring the pH and the concentrations of dissolved oxygen and other gases into equilibrium with air and minimize oxygen demand and concentrations of volatiles. The concentration of dissolved oxygen in dilution water should be between 90 and 100 % of saturation (27) to

help ensure that dissolved oxygen concentrations are acceptable in test chambers. Supersaturation by dissolved gases, which might be caused by heating the dilution water, should be avoided to prevent gas bubble disease (25, 26, 28).

8.3.2 For shell deposition tests with bivalve molluscs, unfiltered, unsterilized natural salt water is often used in order to provide as much natural planktonic food as possible (see 10.5.3).

8.3.3 Except for shell deposition tests, filtration through bag, sand, sock, or depth-type cartridge filters may be used to keep the concentration of particulate matter acceptably low (see 8.1.3) and as a pretreatment before ultraviolet sterilization or filtration through a finer filter.

8.3.4 Except for shell deposition tests, dilution water that might be contaminated with facultative pathogens may be passed through a properly maintained ultraviolet sterilizer (29) equipped with an intensity meter and flow controls or passed through a filter with a pore size of 0.45 µm or less. Water that might be contaminated with *Aphanomyces daphniae* should be autoclaved if it is to be used for culturing or testing daphnids (3).

8.3.5 Except for shell deposition tests, salt water from a surface water source should be passed through a filter effective to 15 µm or less to remove parasites and larval stages of predators.

8.4 *Characterization*—The following items should be measured at least twice each year, or more often (1) if such measurements have not been made semiannually for at least two years, or (2) if a surface water is used:

8.4.1 *All Waters*—pH, particulate matter, TOC, organo-phosphorus pesticides, organic chlorine (or organochlorine pesticides plus PCBs), chlorinated phenoxy herbicides, ammonia, cyanide, sulfide, bromide, fluoride, iodide, nitrate, phosphate, sulfate, calcium, magnesium, potassium, aluminum, arsenic, beryllium, boron, cadmium, chromium, cobalt, copper, iron, lead, manganese, mercury, molybdenum, nickel, selenium, silver, and zinc,

8.4.2 *Fresh Water*—Hardness, alkalinity, conductivity, sodium, and chloride, and

8.4.3 *Salt Water*—Salinity or chlorinity.

8.4.4 For each analytical method used (see 12.2) the detection limit should be below either (1) the concentration in the dilution water or (2) the lowest concentration that has been shown to unacceptably affect the test species (30).

9. Test Material

9.1 *General*—The test material should be reagent grade⁵ or better, unless a test on a formulation, commercial product, or technical-grade or use-grade material is specifically needed. Before a test is begun, the following should be known about the test material:

9.1.1 Identities and concentrations of major ingredients and major impurities, for example, impurities constituting more than about 1 % of the material,

9.1.2 Solubility and stability in the dilution water,

9.1.3 Measured or estimated acute toxicity to the test species,

9.1.4 Precision and bias of the analytical method at the planned concentration(s) of the test material, if the test concentrations are to be measured,

9.1.5 Estimate of toxicity to humans, and

9.1.6 Recommended handling procedures (see 7.1).

9.2 Stock Solution:

9.2.1 In some cases the test material can be added directly to the dilution water, but usually it is dissolved in a solvent to form a stock solution that is then added to the dilution water. If a stock solution is used, the concentration and stability of the test material in it should be determined before the beginning of the test. If the test material is subject to photolysis, the stock solution should be shielded from light.

9.2.2 Except possibly for tests on hydrolyzable, oxidizable, and reducible materials, the preferred solvent is dilution water, although filtration or sterilization, or both, of the water might be necessary. If the hardness (or salinity) of the dilution water will not be affected, deionized or distilled water may be used. Several techniques have been specifically developed for preparing aqueous stock solutions of slightly soluble materials (31). The minimum necessary amount of a strong acid or base may be used in the preparation of an aqueous stock solution, but such reagents might affect the pH of test solutions appreciably. Use of a more soluble form of the test material, such as chloride or sulfate salts of organic amines, sodium or potassium salts of phenols and organic acids, and chloride or nitrate salts of metals, might affect the pH more than use of the minimum necessary amount of a strong acid or base.

9.2.3 If a solvent other than dilution water is used, its concentration in test solutions should be kept to a minimum and should be low enough that it does not affect the test species. Triethylene glycol is often a good organic solvent for preparing stock solutions because of its low toxicity to aquatic animals (32), low volatility, and high ability to dissolve many organic chemicals. Other water-miscible organic solvents such as methanol, ethanol, and acetone may also be used, but they might stimulate undesirable growths of microorganisms and acetone is also very volatile (see 7.3). If an organic solvent is used, it should be reagent grade⁵ or better and its concentration in any test solution must not exceed 0.5 mL/L. A surfactant must not be used in the preparation of a stock solution because it might affect the form and toxicity of the test material in the test solutions. (These limitations do not apply to any ingredient in a mixture, formulation, or commercial product unless an extra amount of solvent is used in the preparation of the stock solution or if the test is on a solvent or surfactant.)

9.2.4 If no solvent other than water is used, (1) a dilution-water control must be included in the test, and (2) the percentage of organisms in the control that show signs of disease or stress, such as discoloration, unusual behavior, or death, must be 10 % or less.

9.2.5 If a solvent other than water is used and the concentration of solvent is the same in all test solutions that contain test material, (1) at least one solvent control, containing the same concentration of solvent and using solvent from the same batch used to make the stock solution, must be included in the test, and (2) a dilution-water control should be included in the test. The percentage of organisms that show signs of disease or

stress, such as discoloration, unusual behavior, or death, must be 10 % or less in the solvent control and should be 10 % or less in the dilution-water control, if one is included in the test.

9.2.6 If a solvent other than water is used and the concentration of solvent is not the same in all test solutions that contain test material, both a solvent control, containing the highest concentration of solvent present in any other treatment and using solvent from the same batch used to make the stock solution, and a dilution-water control must be included in the test. The percentage of organisms that show signs of disease or stress, such as discoloration, unusual behavior, or death, must be 10 % or less in the solvent control and in the dilution-water control.

9.2.7 If a solvent other than water is used to prepare a stock solution, it might be desirable to conduct simultaneous tests on the test material using two chemically unrelated solvents or two different concentrations of the same solvent to obtain information concerning the possible effects of the solvent on the results of the test.

9.3 Test Concentration(s):

9.3.1 If the test is intended to allow calculation of an LC50, EC50, or IC50, the test concentrations (see 11.1.1.1) should bracket the predicted concentration. The prediction might be based on the results of a test on the same or a similar test material with the same or a similar species. If a useful prediction is not available, it is usually desirable to conduct a range-finding test in which groups of five or more organisms are exposed for 24 to 96 h to a control and three to five concentrations of the test material that differ by a factor of ten. The greater the similarity between the range-finding test and the definitive test, the more useful the range-finding test will be.

9.3.1.1 If necessary, concentrations above solubility should be used because organisms in the real world are sometimes exposed to concentrations above solubility and because solubility in dilution water is often not well known. The use of concentrations that are more than ten times greater than solubility are probably not worthwhile. With some test materials it might be found that concentrations above solubility do not kill or affect a greater percentage of test organisms than does the concentration that is the solubility limit; such information is certainly worth knowing.

9.3.2 In some (usually regulatory) situations, it is necessary only to determine (1) whether a specific concentration of test material is acutely toxic to the test species, or (2) whether the LC50, EC50, or IC50 is above or below a specific concentration. For example, the specific concentration might be the concentration occurring in a surface water, the concentration resulting from the direct application of the material to a body of water, or the solubility limit of the material in water. When there is interest only in a specific concentration, it is often necessary only to test that concentration (see 11.1.1.2), and it is not necessary to actually determine the LC50, EC50, or IC50.

10. Test Organisms

10.1 *Species*—If an objective of the test is to increase the comparability of results or increase information about a few commonly used species, or both, the test should be conducted

with a species listed in Table 4. These species were selected on the basis of availability; commercial, recreational, and ecological importance; past successful use; and ease of handling in the laboratory. Their use is encouraged to increase the comparability of results and availability of much information about a few species rather than a little information about many species. If a desired species is unavailable, a species from a listed genus should be used. A special strain should be used only when that strain is of specific concern. The species used should be identified using an appropriate taxonomic key.

10.2 Age—All organisms in a test should be uniform in age and size.

10.2.1 Fish—Use of fish weighing between 0.1 and 5.0 g each is usually desirable. Unless data on another life stage are specifically desired, tests should be conducted with juvenile fish, that is, post-larval or older and actively feeding, but not sexually mature, spawning, or spent. Tests may be conducted with newly hatched fish, which are sometimes more sensitive than older stages, and embryos if appropriate precautions are taken. All fish in a test should be from the same year class, and the standard (tip of snout to end of caudal peduncle), fork, or total length of the longest fish should be no more than twice that of the shortest fish.

10.2.2 Invertebrates—Except for shell deposition tests with bivalve molluscs and tests with copepods, immature organisms should be used whenever possible, because they are often more sensitive than older individuals of the same species. Among freshwater invertebrates, daphnids should be less than 24-h old; amphipods, mayflies, and stoneflies in an early instar; and midges in the second or third instar. (The term “daphnid” refers to all species in the family Daphnidae.) Saltwater mysids should be less than 24-h post-release from the brood sac. Since life-cycle tests with mysids must start with organisms less than 24-h old to maximize exposure prior to reproduction (Guide E1191), acute tests that may serve as preliminary tests to a chronic study should also use mysids less than 24-h old. The same is true if comparisons will be made with other studies starting with mysids of similar age or if required by a regulatory guideline. Since mysids less than 24-h old may not be more sensitive to all test materials, juveniles (less than 8-days old) may be used to start acute tests. Oviparous decapod crustaceans and polychaetes with visible developing eggs in the coelom should not be used.

10.2.3 Amphibians—Young larvae should be used whenever possible.

10.3 Source—All organisms in a test should be from the same source, because organisms of the same species from different sources might have different acute sensitivities. Laboratory cultures of test species usually can provide organisms whose history, age, and quality are similar throughout the year. Freshwater amphipods, caddisflies, daphnids, burrowing mayflies, midge larvae, mosquito larvae, and saltwater polychaetes should be cultured in the testing facility (33). Daphnids from cultures in which ephyppia are being produced should not be used. Small fishes such as fathead and sheepshead minnows can also be raised in laboratory cultures. Usual sources of other freshwater fishes are commercial, state, and federal hatcheries. Whenever salmon or trout are to be used, they should be

TABLE 4 Species and Test Temperatures

Species ^A	Test Temperature, °C ^B
Freshwater:	
Invertebrates: ^B	
Daphnids, <i>Daphnia magna</i> , <i>D. pulex</i> , <i>D. pulicaria</i> ,	20 ^C
<i>Ceriodaphnia dubia</i>	25
Amphipods, <i>Gammarus lacustris</i> , <i>G. fasciatus</i> ,	17
<i>G. pseudolimnaeus</i>	17
Crayfish, <i>Orconectes</i> sp., <i>Cambarus</i> sp.,	17, 22
<i>Procambarus</i> sp.,	17, 22
<i>Pacifastacus leniusculus</i>	17
Stoneflies, <i>Pteronarcys</i> sp.	12
Mayflies, <i>Baetis</i> sp., <i>Ephemera</i> sp.	17
<i>Hexagenia limbata</i> , <i>H. bilineata</i>	22
Midges, <i>Chironomus</i> sp.	22
Snails, <i>Physa integra</i> , <i>P. heterostropha</i> , <i>Amnicola</i>	22
<i>limosa</i> , <i>Aplexa hypnorum</i>	
Planaria, <i>Dugesia tigrina</i>	22
Vertebrates:	
Frog, <i>Rana</i> sp.	22
Toad, <i>Bufo</i> sp.	22
Coho salmon, <i>Oncorhynchus kisutch</i>	12
Rainbow trout, <i>Oncorhynchus mykiss</i>	12
Brook trout, <i>Salvelinus fontinalis</i>	12
Goldfish, <i>Carassius auratus</i>	17, 22
Fathead minnow, <i>Pimephales promelas</i>	25 ^C
Channel catfish, <i>Ictalurus punctatus</i>	17, 22
Bluegill, <i>Lepomis macrochirus</i>	17, 22
Green sunfish, <i>Lepomis cyanellus</i>	17, 22
Saltwater:	
Invertebrates: ^B	
Copepods,	
<i>Acartia clausi</i>	12
<i>Acartia tonsa</i>	22
Shrimp, <i>Penaeus setiferus</i> , <i>P. duorarum</i> , <i>P. aztecus</i>	22
Grass shrimp, <i>Palaemonetes pugio</i> , <i>P. intermedius</i> ,	22
<i>P. vulgaris</i>	22
Sand shrimp, <i>Crangon septemspinosa</i>	17
Shrimp, <i>Pandalus jordani</i> , <i>P. danae</i>	12
Bay Shrimp, <i>Crangon nigricauda</i>	17
Mysid, <i>Mysidopsis bahia</i> , <i>M. bigelowi</i> , <i>M. almyra</i>	27 ^C
Blue crab, <i>Callinectes sapidus</i>	22
Shore crab, <i>Hemigrapsus</i> sp., <i>Pachygrapsus</i> sp.	12
Green crab, <i>Carcinus maenas</i>	22
Fiddler crab, <i>Uca</i> sp.	22
Oyster, <i>Crassostrea virginica</i> , <i>C. gigas</i>	22
Polychaete, <i>Capitella capitata</i>	22
Vertebrates:	
Sheepshead minnow, <i>Cyprinodon variegatus</i>	22
Mummichog, <i>Fundulus heteroclitus</i>	22
Longnose killifish, <i>Fundulus similis</i>	22
Silverside, <i>Menidia</i> sp.	22
Threespine stickleback, <i>Gasterosteus aculeatus</i>	17
Pinfish, <i>Lagodon rhomboides</i>	22
Spot, <i>Leiostomus xanthurus</i>	22
Shiner perch, <i>Cymatogaster aggregata</i>	12
Tidepool sculpin, <i>Oligocottus maculosus</i>	12
Sanddab, <i>Citharichthys stigmatæus</i>	12
Flounder, <i>Paralichthys dentatus</i> , <i>P. lethostigma</i>	22
Starry flounder, <i>Platichthys stellatus</i>	12
English sole, <i>Parophrys vetulus</i>	12
Herring, <i>Clupea harengus</i>	12

^A The species should be identified using an appropriate taxonomic key.

^B Freshwater amphipods, daphnids, and midge larvae should be cultured and tested at test temperature. Some life stages of some aquatic invertebrates have rather narrow temperature requirements and so they should be held and tested within 5°C of the temperature of the water from which they were obtained. They should be tested at the listed test temperature if it is within this range; otherwise they should be tested at the temperature from the series 7, 12, 17, 22, 27, and 32°C that is closest to the listed test temperature and is within 5°C of the temperature of the water from which they were obtained.

^C These species survive, grow, and reproduce acceptably at these temperatures and they are conveniently cultured and tested at these temperatures.