

INTERNATIONAL STANDARD



Information technology – Home network resource management –
Part 3: Management application

(standards.iteh.ai)

ISO/IEC 30100-3:2016

<https://standards.iteh.ai/catalog/standards/sist/88376cb5-9509-48c5-96e5-1fa1a0e34f72/iso-iec-30100-3-2016>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2016 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

INTERNATIONAL STANDARD PREVIEW
(standards) (ch) (a)
ISO/IEC 30102-3:2016
<https://standards.iteh.ai/catalog/standards/iso-iec-30102-3-2016>
1fa1a0e34f72/iso-iec-30102-3-2016



ISO/IEC 30100-3

Edition 1.0 2016-04

INTERNATIONAL STANDARD



Information technology – Home network resource management –
Part 3: Management application

STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 30100-3:2016
<https://standards.iteh.ai/catalog/standards/sist/88376cb5-9509-48c5-96e5-1fa1a0e34f72/iso-iec-30100-3-2016>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200

ISBN 978-2-8322-2904-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references.....	6
3 Terms, definitions and abbreviations	6
3.1 Terms and definitions	6
3.2 Abbreviations	8
4 Conformance.....	9
5 Management application	9
5.1 Overview.....	9
5.2 Management application model	9
5.3 Home resource management process	10
5.4 Simple interaction flow using HRMI.....	10
6 Home resource management interface (HRMI)	12
6.1 Overview.....	12
6.2 List of resource management interface services.....	13
6.3 Home resource management interface services	14
6.3.1 Request for user authentication	14
6.3.2 Request for initial setup	14
6.3.3 Request for operation start	15
6.3.4 Request for operation stop	15
6.3.5 Request for operation restart	16
6.3.6 Request for the inquiry of home resource domain.....	16
6.3.7 Request for the inquiry of home resource information.....	17
6.3.8 Request for the inquiry of home resource information by Name	18
6.3.9 Request for the inquiry of home resource information by type.....	19
6.3.10 Request for the inquiry of home resource information by ID.....	19
6.3.11 Request for the inquiry of home relation information.....	20
6.3.12 Request for the inquiry of home relation information by domain	21
6.3.13 Request for the inquiry of home relation information by relation ID	22
6.3.14 Request for the inquiry of home relation information by source ID.....	22
6.3.15 Request for registration of event condition	23
6.3.16 Request for cancellation of event condition	24
6.3.17 Request for inquiry of event.....	24
6.3.18 Request for resource control.....	25
6.3.19 Request for resource probing	26
6.3.20 Request for log data about relation information	26
6.4 Management interface services	28
6.4.1 Data structure of management interface.....	28
6.4.2 Event Name of management interface	29
Annex A (informative) Interface schema for physical space information provider (example)	30
Annex B (informative) Implementation of management application (example)	34
B.1 Overview.....	34
B.2 Fault management application overview.....	34

B.3	Simple fault diagnosis scenario using HRMI.....	35
B.3.1	Initial setup	35
B.3.2	Resource and relation object information acquisition	36
B.3.3	Fault diagnosis.....	37
B.3.4	Event processing.....	37
B.3.5	Fault diagnosis result notify	38
	Bibliography	39
	Figure 1 – Management application model.....	10
	Figure 2 – Example of simple interaction flow	11
	Figure B.1 – Fault management system configuration	34
	Figure B.2 – Fault management application interfaces	35
	Figure B.3 – Sequence flow of initial setup	36
	Figure B.4 – Destroy and logout procedure.....	36
	Figure B.5 – Fault diagnosis result procedure.....	37
	Figure B.6 – Event state change procedure	38

iTeh STANDARD PREVIEW (standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/88376cb5-9509-48c5-96e5-1fa1a0e34f72/iso-iec-30100-3-2016>
[ISO/IEC 30100-3:2016](https://standards.iteh.ai/catalog/standards/sist/88376cb5-9509-48c5-96e5-1fa1a0e34f72/iso-iec-30100-3-2016)

INFORMATION TECHNOLOGY – HOME NETWORK RESOURCE MANAGEMENT –

Part 3: Management application

FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.
- 3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 30100-3 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 30100 series, under the general title *Information technology – Home network resource management*, can be found on the IEC website.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The ISO/IEC 30100 series of standards specifies an abstract model for remote management of home networks conforming to the Home Electronic System (HES) architecture specified in ISO/IEC 14543-2-1. An HES consists of a collection of devices that are able to interwork via a common internal network. In a home environment several HES networks may operate concurrently each with separate control and management methods. This part of ISO/IEC 30100 specifies the architecture and the base methodology to support applications that may span multiple different HES networks. Home resource management allows uniform fault processing, diagnostics and configuration management of HES elements in home environment.

This standard specifies an architecture for the home network resource management, a home resource model for transparent system configuration and a diagnostic processing in the home network.

Currently, ISO/IEC 30100, *Information technology – Interconnection of information technology equipment – Home Network Resource Management*, consists of the following parts:

Part 1: Requirements

Part 2: Architecture

Part 3: Management application

ISO/IEC 30100 is applicable to

- a management server located at a home network service provider,
- an apartment complex server, located in an office at the of apartment complex office,
- a home residential gateway or set top box (STB).

<https://standards.iteh.ai/catalog/standards/sist/88376cb5-9509-48c5-96e5-1fa1a0e34f72/iso-iec-30100-3-2016>

INFORMATION TECHNOLOGY – HOME NETWORK RESOURCE MANAGEMENT –

Part 3: Management application

1 Scope

This part of ISO/IEC 30100 specifies a control and management interface for the integrated home network resources at the top of the interoperability framework specified by ISO/IEC 18012-1. Methods are specified for controlling and managing home network resources through a consistent interface regardless of the underlying home network middleware technologies. Based on the home resource management interface, a management application specifies HES device control services and fault management services. This part of ISO/IEC 30100 specifies the communications data formats and functions for messages sent between the objects of a resource management process and the objects of one or more management applications.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 14543-2-1, *Information technology – Home electronic system (HES) architecture – Part 2-1: Introduction and device modularity*
ISO/IEC 30100-3:2016
https://standards.iteh.ai/catalog/standards/sist/88576cb5-9509-48c5-96c5-1fa1a0e34f72/iso-iec-30100-3-2016

ISO/IEC 18012-1:2004, *Information technology – Home electronic system – Guidelines for product interoperability – Part 1: Introduction*

ISO/IEC 30100-2, *Information technology – Home network resource management – Part 2: Architecture*¹

3 Terms, definitions and abbreviations

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1

apartment complex server

computer remotely managing services for residents in a multiunit dwelling

apartment complex office

management facility that provides services for residents in a multiunit dwelling

3.1.2

application

field of use of home resource management process

¹ To be published.

3.1.3

class

set of instances of home resource

3.1.4

device

distinct physical unit on a network that performs a specific function (a set of functions) in a particular context

Note 1 to entry: A device can either be an end node on the network, or an intermediate node (as in the case of a network gateway device connecting two distinct physical networks).

3.1.5

domain

range of validity of a resource object

3.1.6

HES entity

logical component that has a specified functionality in the HES architecture

Note 1 to entry: The HES architecture is specified in ISO/IEC 14543-2-1.

3.1.7

HES interoperability framework

collection of standards defining device and network interoperability for homes as specified in the ISO/IEC 14543 series

3.1.8

home residential gateway

interface between external networks and home networks

3.1.9

home resource

managed object that can be used for home network services

3.1.10

home resource management interface

logical connection point between management application and home resource management process

3.1.11

home resource management process

element that performs information processing for a particular management application

3.1.12

home resource model

abstract, formal representation of resource objects in a home environment

Note 1 to entry: Resource objects include resource properties, relationships and the operations that can be performed on them.

3.1.13

home resource provider interface

data transfer between resource information provider and home resource management process

3.1.14

instance

example

Note 1 to entry: This term is used in object-oriented programming.

3.1.15

management information

set of components used either in a management application or in a resource management process

3.1.16

network

interconnected devices sharing a common communications protocol

3.1.17

network middleware

software that links an operating system to a communications protocol

3.1.18

object

abstract element representing device functions and data stored within the device

Note 1 to entry: The functions and data contained within an object (referred to as "properties") can be executed, read or modified as appropriate for the property by "messages" sent from other objects. A message causes a "method" within the object to be invoked. This may result in access to an internal data structure or the execution of a subroutine or both. A value may be returned by the recipient object.

3.1.19

physical space

some arbitrary set of reference co-ordinates of a home resource in the real world

3.1.20

resource information provider

functions for home resource management process to control HES entities

Note 1 to entry: Collects data from HES entities and transfers the collected data to a home resource management process.

3.1.21

resource object

managed unit located within the resource management process specified by the home resource model

Note 1 to entry: The resource object includes methods for accessing the properties of the management process and/or interacting with other objects. A resource object can contain one or more HES entities.

3.1.22

resource relation object

managing unit located within the resource management process by the home resource model

3.1.23

service

field of use of an HES

3.1.24

set top box

interface between the external service and home equipment

3.2 Abbreviations

AFM	Automatic Fault Management
BNF	Backus-Naur Form
DM	Device Management
HAN	Home Area Network

HES	Home Electronic System
HNRM	Home Network Resource Management
HRMI	Home Resource Management Interface
HRPI	Home Resource Provider Interface
FMA	Fault Management Application
HMAI	Home Management Application Interface
RM	Remote Management
OSI	Open System Interconnection

4 Conformance

In order to claim conformance to this International Standard, the network application and management software written for managing the home network resources specified in Clause 4 of ISO/IEC 14543-2-1:2006 shall be implemented as follows.

- A home network management application shall be implemented according to the model specified in Clause 5.
- A home network management application shall implement the interface specified in Clause 6.
- A home network management process shall implement the interface specified in Clause 6.

5 Management application

5.1 Overview

The home resource management architecture consists of three parts as described in ISO/IEC 30100-2.


- Resource information provider
- Resource management process
- Management application

A management application is a user process that communicates with a resource management process via an HRMI. The HRMI provides an interface not only for information retrieval for the resources and relationships among resources, but also for the control and management of the resources regardless of the underlying home network middleware technologies.

This standard specifies basic interfaces for the essential home applications such as home resource auto-configuration, fault management and HES device control service.

5.2 Management application model

Figure 1 illustrates a reference model for the HNRM (home network resource management) application model with an HRMI.



IEC

Figure 1 – Management application model


As shown in Figure 1, the HRMI provides a common interface for all home network resource management applications. Therefore, the home network resource management application can be developed to fulfil a requirement to be a stand-alone application or a client-server application. When the home network management application is designed with a client-server model, an interface for the server and client shall be specified. The interface is not specified in this standard. The HRMI interface shall include a resource management process for access control, encryption and signature as a means for security and privacy protection, as specified in 5.5 of ISO/IEC 30100-22.

5.3 Home resource management process

The home resource management process collects all information about a resource entity from at least one resource information provider through pre-defined interfaces. When two or more dissimilar home area networks are installed and interoperate, the network devices providing this information shall comply with Clause 6 of ISO/IEC 18012-1:2004. The interface example for other resources such as network, service and physical space is explained in Annex A. An implementation example is presented in Annex B.

5.4 Simple interaction flow using HRMI

Figure 2 shows the simple interaction flow between a management application and a resource management process using the HRMI function. In Figure 2 messages in brackets “[]” are optional messages. For example, event registration messages are used for registration in order to receive events of interest. However, when there are no events of interest, this message is not used.



IEC

^a Authentication is required.

Figure 2 – Example of simple interaction flow

While Figure 2 is not suitable for describing all use cases, it illustrates an example of a procedure for a home network resource management application to handle home network resources. In Figure 2, the solid line signifies a message for resource management interface service, and the dashed line signifies output parameters of the requested message. Step 1 to Step 4 should be performed sequentially, and the others are not. The procedure using the services listed in 6.2 and specified in 6.3 is as follows.

- First, a user shall be authenticated in order to determine if he/she has a right to access the target resources using "HRM_user_login". This step fulfills the security requirements specified in 5.2 by using methods such as SSL/TLS or SSH.
- After the user authentication process, the setup process with the home network resource management process starts using "HRM_init" and "HRM_start" sequentially. In the initial setup process, functions and modules for the resource management process are initialised.
- When management applications want to receive some specific events, they subscribe to a list of events related to home network resource management applications using