



LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 15.4.0 Release 15)



ReferenceRTS/TSGR-0436101vf40

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and LTE™ are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	30
1 Scope	31
2 References	31
3 Definitions, symbols and abbreviations	31
3.1 Definitions.....	31
3.2 Symbols.....	33
3.3 Abbreviations	36
4 General	37
4.1 Relationship between minimum requirements and test requirements	37
4.2 Applicability of minimum requirements	38
4.3 Void.....	38
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0, UE category M1, UE category M2, UE category 1bis, UE category NB1 and NB2, V2X Communication, MBMS UE)	38
4.4 RF requirements in later releases	40
5 Operating bands and channel arrangement.....	40
5.1 General	40
5.2 Void.....	40
5.3 Void.....	40
5.4 Void.....	40
5.5 Operating bands.....	40
5.5A Operating bands for CA	42
5.5B Operating bands for UL-MIMO	55
5.5C Operating bands for Dual Connectivity.....	55
5.5D Operating bands for ProSe.....	57
5.5E Operating bands for UE category 0, UE category M1 and M2 and UE category 1bis	58
5.5F Operating bands for category NB1 and NB2.....	58
5.5G Operating bands for V2X Communication.....	58
5.6 Channel bandwidth.....	59
5.6.1 Channel bandwidths per operating band.....	60
5.6A Channel bandwidth for CA.....	62
5.6A.1 Channel bandwidths per operating band for CA.....	64
5.6B Channel bandwidth for UL-MIMO	148
5.6B.1 Void	149
5.6C Channel bandwidth for Dual Connectivity.....	149
5.6C.1 Void	149
5.6D Channel bandwidth for ProSe.....	149
5.6D.1 Channel bandwidths per operating band for ProSe.....	149
5.6F Channel bandwidth for category NB1 and NB2.....	150
5.6G Channel bandwidth for V2X Communication.....	151
5.6G.1 Channel bandwidths per operating band for V2X Communication	151
5.7 Channel arrangement.....	153
5.7.1 Channel spacing.....	153
5.7.1A Channel spacing for CA.....	153
5.7.1F Channel spacing for category NB1 and NB2.....	154
5.7.2 Channel raster	154
5.7.2A Channel raster for CA	154
5.7.2F Channel raster for category NB1 and NB2.....	154
5.7.3 Carrier frequency and EARFCN.....	154
5.7.3F Carrier frequency and EARFCN for category NB1 and NB2.....	156

5.7.4	TX–RX frequency separation	156
5.7.4A	TX–RX frequency separation for CA	157
5.7.4E	TX–RX frequency separation for category M1 and M2	157
5.7.4F	TX–RX frequency separation for category NB1 and NB2	157
6	Transmitter characteristics	158
6.1	General	158
6.2	Transmit power	158
6.2.1	Void	158
6.2.2	UE maximum output power	158
6.2.2A	UE maximum output power for CA	160
6.2.2B	UE maximum output power for UL-MIMO	164
6.2.2C	Void	166
6.2.2D	UE maximum output power for ProSe	166
6.2.2E	UE maximum output power for Category M1 and M2 UE	166
6.2.2F	UE maximum output power for category NB1 and NB2	167
6.2.2G	UE maximum output power for V2X Communication	168
6.2.3	UE maximum output power for modulation / channel bandwidth	170
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	171
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	176
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe	176
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1 and M2	177
6.2.3F	UE maximum output power for modulation / channel bandwidth for category NB1 and NB2	179
6.2.3G	UE maximum output power for modulation / channel bandwidth for V2X Communication	179
6.2.3G.1	MPR for Power class 3 V2X UE	179
6.2.3G.2	MPR for Power class 2 V2X UE	180
6.2.4	UE maximum output power with additional requirements	181
6.2.4A	UE maximum output power with additional requirements for CA	199
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	201
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	202
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	203
6.2.4A.4	A-MPR for CA_NS_04	204
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	206
6.2.4A.6	A-MPR for CA_NS_06	207
6.2.4A.7	A-MPR for CA_NS_07	207
6.2.4A.8	A-MPR for CA_NS_08	208
6.2.4A.9	A-MPR for CA_NS_09	209
6.2.4B	UE maximum output power with additional requirements for UL-MIMO	211
6.2.4D	UE maximum output power with additional requirements for ProSe	211
6.2.4E	UE maximum output power with additional requirements for category M1 and M2 UE	211
6.2.4F	UE maximum output power with additional requirements for category NB1 and NB2 UE	216
6.2.4G	UE maximum output power with additional requirements for V2X Communication	216
6.2.5	Configured transmitted power	219
6.2.5A	Configured transmitted power for CA	244
6.2.5B	Configured transmitted power for UL-MIMO	248
6.2.5C	Configured transmitted power for Dual Connectivity	249
6.2.5D	Configured transmitted power for ProSe	250
6.2.5F	Configured transmitted Power for category NB1 and NB2	252
6.2.5G	Configured transmitted power for V2X Communication	253
6.3	Output power dynamics	257
6.3.1	(Void)	257
6.3.2	Minimum output power	257
6.3.2.1	Minimum requirement	257
6.3.2A	UE Minimum output power for CA	257
6.3.2A.1	Minimum requirement for CA	257
6.3.2B	UE Minimum output power for UL-MIMO	257
6.3.2B.1	Minimum requirement	258
6.3.2C	Void	258
6.3.2D	UE Minimum output power for ProSe	258
6.3.2F	UE Minimum output power for category NB1 and NB2	258
6.3.2G	UE Minimum output power for V2X Communication	258
6.3.3	Transmit OFF power	259

6.3.3.1.	Minimum requirement	259
6.3.3A	UE Transmit OFF power for CA	259
6.3.3A.1	Minimum requirement for CA	259
6.3.3B	UE Transmit OFF power for UL-MIMO	260
6.3.3B.1	Minimum requirement	260
6.3.3D	Transmit OFF power for ProSe	260
6.3.3F	Transmit OFF power for category NB1 and NB2	260
6.3.3G	Transmit OFF power for V2X Communication	261
6.3.4	ON/OFF time mask	261
6.3.4.1	General ON/OFF time mask	261
6.3.4.2	PRACH and SRS time mask	262
6.3.4.2.1	PRACH time mask	262
6.3.4.2.2	SRS time mask	263
6.3.4.3	Slot / Sub frame boundary time mask for subframe TTI	264
6.3.4.4	PUCCH / PUSCH / SRS time mask for subframe TTI	266
6.3.4.5	Symbol / Subslot boundary time mask for subslot TTI	268
6.3.4.6	Subslot PUCCH / subslot PUSCH / SRS time mask for subslot TTI	269
6.3.4.7	Symbol / Slot boundary time mask for slot TTI	272
6.3.4.8	Slot PUCCH / slot PUSCH / SRS time mask for slot TTI	273
6.3.4.9	Consecutive subslot and slot TTI or consecutive subslot and subframe TTI time mask	273
6.3.4.10	Consecutive subframe and subslot TTI or consecutive slot and subslot TTI time mask	273
6.3.4.11	Consecutive TTI and slot TTI or consecutive slot TTI and TTI time mask	274
6.3.4A	ON/OFF time mask for CA	275
6.3.4B	ON/OFF time mask for UL-MIMO	275
6.3.4D	ON/OFF time mask for ProSe	275
6.3.4D.1	General time mask for ProSe	275
6.3.4D.2	PSSS/SSSS time mask	276
6.3.4D.3	PSSS / SSSS / PSBCH time mask	277
6.3.4D.4	PSSCH / SRS time mask	277
6.3.4F	ON/OFF time mask for category NB1 and NB2	277
6.3.4F.1	General ON/OFF time mask	277
6.3.4F.2	NPRACH time mask	278
6.3.4G	ON/OFF time mask for V2X Communication	278
6.3.4G.1	PSSS / SSSS / PSBCH time mask	279
6.3.5	Power Control	279
6.3.5.1	Absolute power tolerance	279
6.3.5.1.1	Minimum requirements	279
6.3.5.2	Relative Power tolerance	280
6.3.5.2.1	Minimum requirements	280
6.3.5.3	Aggregate power control tolerance	281
6.3.5.3.1	Minimum requirement	281
6.3.5A	Power control for CA	281
6.3.5A.1	Absolute power tolerance	281
6.3.5A.1.1	Minimum requirements	281
6.3.5A.2	Relative power tolerance	282
6.3.5A.2.1	Minimum requirements	282
6.3.5A.3	Aggregate power control tolerance	282
6.3.5A.3.1	Minimum requirements	282
6.3.5B	Power control for UL-MIMO	283
6.3.5D	Power Control for ProSe	283
6.3.5D.1	Absolute power tolerance	283
6.3.5E	Power control for category M1 and M2	283
6.3.5E.1	Absolute power tolerance	283
6.3.5E.2	Relative Power tolerance	283
6.3.5E.3	Aggregate power control tolerance	284
6.3.5E.3.1	Minimum requirement	284
6.3.5F	Power Control for category NB1 and NB2	284
6.3.5F.1	Absolute power tolerance	285
6.3.5F.2	Relative power tolerance	285
6.3.5F.3	Aggregate power control tolerance for category NB1 and NB2	286
6.3.5F.3.1	Minimum requirement	286
6.3.5G	Power Control for V2X Communication	286

6.3.5G.1	Absolute power tolerance.....	286
6.4	Void.....	287
6.5	Transmit signal quality.....	287
6.5.1	Frequency error.....	287
6.5.1A	Frequency error for CA.....	287
6.5.1B	Frequency error for UL-MIMO.....	287
6.5.1D	Frequency error for ProSe.....	287
6.5.1E	Frequency error for UE category M1 and M2.....	287
6.5.1F	Frequency error for UE category NB1 and NB2.....	287
6.5.1G	Frequency error for V2X Communication.....	288
6.5.2	Transmit modulation quality.....	288
6.5.2.1	Error Vector Magnitude.....	288
6.5.2.1.1	Minimum requirement.....	289
6.5.2.2	Carrier leakage.....	289
6.5.2.2.1	Minimum requirements.....	289
6.5.2.3	In-band emissions.....	290
6.5.2.3.1	Minimum requirements.....	290
6.5.2.4	EVM equalizer spectrum flatness.....	291
6.5.2.4.1	Minimum requirements.....	291
6.5.2A	Transmit modulation quality for CA.....	292
6.5.2A.1	Error Vector Magnitude.....	293
6.5.2A.2	Carrier leakage for CA.....	293
6.5.2A.2.1	Minimum requirements.....	293
6.5.2A.3	In-band emissions.....	293
6.5.2A.3.1	Minimum requirement for CA.....	293
6.5.2B	Transmit modulation quality for UL-MIMO.....	296
6.5.2B.1	Error Vector Magnitude.....	296
6.5.2B.2	Carrier leakage.....	296
6.5.2B.3	In-band emissions.....	296
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO.....	296
6.5.2D	Transmit modulation quality for ProSe.....	296
6.5.2D.1	Error Vector Magnitude.....	296
6.5.2D.2	Carrier leakage.....	297
6.5.2D.3	In-band emissions.....	297
6.5.2D.4	EVM equalizer spectrum flatness for ProSe.....	297
6.5.2E	Transmit modulation quality for category M1 and M2.....	297
6.5.2E.1	Error Vector Magnitude.....	297
The Error Vector Magnitude is defined in section 6.5.2.1.....		297
6.5.2E.2	Carrier leakage.....	297
6.5.2E.2.1	Minimum requirements.....	297
6.5.2E.3	In-band emissions.....	297
6.5.2E.3.1	Minimum requirements.....	297
6.5.2F	Transmit modulation quality for Category NB1 and NB2.....	299
6.5.2F.1	Error Vector Magnitude.....	299
6.5.2F.2	Carrier leakage.....	299
6.5.2F.3	In-band emissions.....	299
6.5.2G	Transmit modulation quality for V2X Communication.....	300
6.5.2G.1	Error Vector Magnitude.....	300
6.5.2G.2	Carrier leakage.....	301
6.5.2G.3	In-band emissions.....	301
6.5.2G.4	EVM equalizer spectrum flatness.....	301
6.6	Output RF spectrum emissions.....	301
6.6.1	Occupied bandwidth.....	301
6.6.1.1	Additional minimum requirement for E-UTRA (network signalled value “NS_29”).....	302
6.6.1A	Occupied bandwidth for CA.....	302
6.6.1B	Occupied bandwidth for UL-MIMO.....	302
6.6.1F	Occupied bandwidth for category NB1 and NB2.....	303
6.6.1G	Occupied bandwidth for V2X Communication.....	303
6.6.2	Out of band emission.....	303
6.6.2.1	Spectrum emission mask.....	303
6.6.2.1.1	Minimum requirement.....	303
6.6.2.1A	Spectrum emission mask for CA.....	304

6.6.2.2	Additional spectrum emission mask	305
6.6.2.2.1	Minimum requirement (network signalled value "NS_03", "NS_11", "NS_20", and "NS_21") ..	306
6.6.2.2.2	Minimum requirement (network signalled value "NS_04")	306
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	307
6.6.2.2.4	Minimum requirement (network signalled value "NS_33" or "NS_34")	307
6.6.2.2.5	Minimum requirement (network signalled value "NS_27" and "NS_43")	308
6.6.2.2.6	Minimum requirement (network signalled value "NS_28")	308
6.6.2.2.7	Minimum requirement (network signalled value "NS_35")	308
6.6.2.2A	Additional Spectrum Emission Mask for CA	309
6.6.2.2A.1	Minimum requirement (network signalled value "CA_NS_04")	309
6.6.2.2A.2	Minimum requirement (network signalled value "CA_NS_09")	310
6.6.2.3	Adjacent Channel Leakage Ratio	310
6.6.2.3.1	Minimum requirement E-UTRA	310
6.6.2.3.1a	Additional minimum requirement for E-UTRA (network signalled value "NS_29")	312
6.6.2.3.1A	Void	312
6.6.2.3.1Aa	Void	312
6.6.2.3.2	Minimum requirements UTRA	312
6.6.2.3.2A	Minimum requirement UTRA for CA	313
6.6.2.3.3A	Minimum requirements for CA E-UTRA	314
6.6.2.4	Void	316
6.6.2.4.1	Void	316
6.6.2A	Void	316
6.6.2B	Out of band emission for UL-MIMO	316
6.6.2C	Void	316
6.6.2D	Out of band emission for ProSe	316
6.6.2F	Out of band emission for category NB1 and NB2	316
6.6.2F.1	Spectrum emission mask	316
6.6.2F.2	Additional Spectrum Emission Mask for Category NB1 and NB2	317
6.6.2F.2.1	Minimum requirement (network signalled value "NS_02")	317
6.6.2F.2.2	Minimum requirement (network signalled value "NS_03")	317
6.6.2F.3	Adjacent Channel Leakage Ratio for category NB1 and NB2	318
6.6.2G	Out of band emission for V2X Communication	318
6.6.3	Spurious emissions	319
6.6.3.1	Minimum requirements	319
6.6.3.1A	Minimum requirements for CA	320
6.6.3.2	Spurious emission band UE co-existence	321
6.6.3.2A	Spurious emission band UE co-existence for CA	328
6.6.3.3	Additional spurious emissions	339
6.6.3.3.1	Minimum requirement (network signalled value "NS_05")	339
6.6.3.3.2	Minimum requirement (network signalled value "NS_07")	339
6.6.3.3.3	Minimum requirement (network signalled value "NS_08")	340
6.6.3.3.4	Minimum requirement (network signalled value "NS_09")	340
6.6.3.3.5	Minimum requirement (network signalled value "NS_12")	340
6.6.3.3.6	Minimum requirement (network signalled value "NS_13")	341
6.6.3.3.7	Minimum requirement (network signalled value "NS_14")	341
6.6.3.3.8	Minimum requirement (network signalled value "NS_15")	341
6.6.3.3.9	Minimum requirement (network signalled value "NS_16")	341
6.6.3.3.10	Minimum requirement (network signalled value "NS_17")	342
6.6.3.3.11	Minimum requirement (network signalled value "NS_18")	342
6.6.3.3.12	Minimum requirement (network signalled value "NS_19")	342
6.6.3.3.13	Minimum requirement (network signalled value "NS_11")	342
6.6.3.3.14	Minimum requirement (network signalled value "NS_20")	343
6.6.3.3.15	Minimum requirement (network signalled value "NS_21")	343
6.6.3.3.16	Minimum requirement (network signalled value "NS_22")	343
6.6.3.3.17	Minimum requirement (network signalled value "NS_23")	344
6.6.3.3.18	Void	344
6.6.3.3.19	Minimum requirement (network signalled value "NS_04")	344
6.6.3.3.20	Minimum requirement (network signalled value "NS_24")	345
6.6.3.3.21	Minimum requirement (network signalled value "NS_25")	345
6.6.3.3.22	Minimum requirement (network signalled value "NS_26")	345
6.6.3.3.23	Minimum requirement (network signalled value "NS_27" and "NS_43")	346
6.6.3.3.24	Minimum requirement (network signalled value "NS_28")	346

6.6.3.3.25	Minimum requirement (network signalled value "NS_29").....	346
6.6.3.3.26	Minimum requirement (network signalled value "NS_30").....	347
6.6.3.3.27	Minimum requirement (network signalled value "NS_31").....	348
6.6.3.3.28	Minimum requirement (network signalled value "NS_36").....	349
6.6.3.3.29	Minimum requirement (network signalled value "NS_38").....	349
6.6.3.3.30	Minimum requirement (network signalled value "NS_39").....	349
6.6.3.3.31	Minimum requirement (network signalled value "NS_40" and "NS_41")	349
6.6.3.3.32	Minimum requirement (network signalled value "NS_42").....	350
6.6.3.3.33	Minimum requirement (network signalled value "NS_44").....	350
6.6.3.3A	Additional spurious emissions for CA	350
6.6.3.3A.1	Minimum requirement for CA_1C (network signalled value "CA_NS_01").....	350
6.6.3.3A.2	Minimum requirement for CA_1C (network signalled value "CA_NS_02").....	351
6.6.3.3A.3	Minimum requirement for CA_1C (network signalled value "CA_NS_03").....	351
6.6.3.3A.4	Minimum requirement for CA_38C (network signalled value "CA_NS_05").....	351
6.6.3.3A.5	Minimum requirement for CA_7C (network signalled value "CA_NS_06").....	352
6.6.3.3A.6	Minimum requirement for CA_39C and CA_39C-41A (network signalled value "CA_NS_07").....	352
6.6.3.3A.7	Minimum requirement for CA_42C (network signalled value "CA_NS_08").....	352
6.6.3.3A.8	Minimum requirement for CA_41C (network signalled value "CA_NS_04").....	353
6.6.3.3A.9	Minimum requirement for CA_41D (network signalled value "CA_NS_04").....	353
6.6.3A	Void	354
6.6.3B	Spurious emission for UL-MIMO	354
6.6.3C	Void	355
6.6.3D	Spurious emission for ProSe.....	355
6.6.3F	Spurious emission for category NB1 and NB2	355
6.6.3G	Spurious emission for V2X Communication	355
6.6A	Void.....	358
6.6B	Void.....	358
6.7	Transmit intermodulation	358
6.7.1	Minimum requirement	358
6.7.1A	Minimum requirement for CA	358
6.7.1B	Minimum requirement for UL-MIMO.....	359
6.7.1F	Minimum requirement for category NB1 and NB2	359
6.7.1G	Minimum requirement for V2X Communication	360
6.8	Void.....	360
6.8A	Void.....	360
6.8B	Time alignment error for UL-MIMO	360
6.8B.1	Minimum Requirements	360
6.8C	Void.....	360
6.8D	Void.....	360
6.8E	Void.....	360
6.8F	Void.....	360
6.8G	Time alignment error.....	360
7	Receiver characteristics	361
7.1	General	361
7.2	Diversity characteristics	361
7.3	Reference sensitivity power level.....	362
7.3.1	Minimum requirements (QPSK).....	362
7.3.1A	Minimum requirements (QPSK) for CA.....	391
7.3.1B	Minimum requirements (QPSK) for UL-MIMO	460
7.3.1D	Minimum requirements (QPSK) for ProSe.....	460
7.3.1E	Minimum requirements (QPSK) for UE category 0, M1, M2 and 1bis	462
7.3.1F	Minimum requirements for UE category NB1 and NB2	470
7.3.1F.1	Reference sensitivity for UE category NB1 and NB2.....	470
7.3.1F.2	Void.....	471
7.3.1G	Minimum requirements (QPSK) for V2X	471
7.3.2	Void	473
7.4	Maximum input level	473
7.4.1	Minimum requirements.....	474
7.4.1A	Minimum requirements for CA	474
7.4.1B	Minimum requirements for UL-MIMO	475

7.4.1D	Minimum requirements for ProSe	475
7.4.1F	Minimum requirements for category NB1 and NB2.....	476
7.4.1G	Minimum requirements for V2X	476
7.4A	Void.....	477
7.4A.1	Void.....	477
7.5	Adjacent Channel Selectivity (ACS).....	477
7.5.1	Minimum requirements.....	477
7.5.1A	Minimum requirements for CA	478
7.5.1B	Minimum requirements for UL-MIMO	482
7.5.1D	Minimum requirements for ProSe	482
7.5.1F	Minimum requirements for category NB1 and NB2.....	483
7.5.1G	Minimum requirements for V2X	484
7.6	Blocking characteristics	486
7.6.1	In-band blocking.....	486
7.6.1.1	Minimum requirements.....	486
7.6.1.1A	Minimum requirements for CA.....	488
7.6.1.1D	Minimum requirements for ProSe.....	491
7.6.1.1F	Minimum requirements for category NB1 and NB2.....	492
7.6.1.1G	Minimum requirements for V2X.....	493
7.6.2	Out-of-band blocking.....	494
7.6.2.1	Minimum requirements.....	494
7.6.2.1A	Minimum requirements for CA.....	496
7.6.2.1D	Minimum requirements for ProSe.....	499
7.6.2.1F	Minimum requirements for category NB1 and NB2.....	500
7.6.2.1G	Minimum requirements for V2X.....	501
7.6.3	Narrow band blocking	502
7.6.3.1	Minimum requirements.....	502
7.6.3.1A	Minimum requirements for CA.....	503
7.6.3.1D	Minimum requirements for ProSe.....	504
7.6A	Void.....	505
7.6B	Blocking characteristics for UL-MIMO	505
7.7	Spurious response.....	505
7.7.1	Minimum requirements.....	505
7.7.1A	Minimum requirements for CA	506
7.7.1B	Minimum requirements for UL-MIMO	507
7.7.1D	Minimum requirements for ProSe	507
7.7.1F	Minimum requirements for UE category NB1 and NB2	508
7.7.1G	Minimum requirements for V2X.....	508
7.8	Intermodulation characteristics	509
7.8.1	Wide band intermodulation.....	509
7.8.1.1	Minimum requirements.....	509
7.8.1A	Minimum requirements for CA	510
7.8.1B	Minimum requirements for UL-MIMO	513
7.8.1D	Minimum requirements for ProSe	513
7.8.1F	Minimum requirements for category NB1 and NB2.....	514
7.8.1G	Minimum requirements.....	514
7.8.2	Void	515
7.9	Spurious emissions	515
7.9.1	Minimum requirements.....	516
7.9.1A	Minimum requirements.....	516
7.10	Receiver image	517
7.10.1	Void.....	517
7.10.1A	Minimum requirements for CA	517
7.10.1G	Minimum requirements for V2X Communication.....	517
8	Performance requirement	518
8.1	General	518
8.1.1	Receiver antenna capability	518
8.1.1.1	Simultaneous unicast and MBMS operations.....	519
8.1.1.2	Dual-antenna receiver capability in idle mode.....	519
8.1.2	Applicability of requirements	519
8.1.2.1	Applicability of requirements for different channel bandwidths.....	519

8.1.2.2	Definition of CA capability	519
8.1.2.2A	Definition of dual connectivity capability	523
8.1.2.3	Applicability and test rules for different CA configurations and bandwidth combination sets	523
8.1.2.3A	Applicability and test rules for different dual connectivity configuration and bandwidth combination set	525
8.1.2.3B	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets	526
8.1.2.3C	Applicability and test rules for SDR tests for 4Rx capable UEs	528
8.1.2.3D	Applicability and test rules for different CA with LAA SCell(s) configurations and bandwidth combination sets	528
8.1.2.4	Test coverage for different number of component carriers	529
8.1.2.5	Applicability of performance requirements for Type B receiver	530
8.1.2.6	Applicability of performance requirements for 4Rx capable UEs	530
8.1.2.6.1	Applicability rule and antenna connection for single carrier tests with 2Rx	531
8.1.2.6.2	Applicability rule and antenna connection for CA and DC tests with 2Rx	532
8.1.2.6.3	Applicability rule and antenna connection for single carrier tests with 4Rx	532
8.1.2.6.4	Applicability rule for 256QAM tests	533
8.1.2.6.5	Applicability rule and antenna connection for CA and DC tests with 4Rx	533
8.1.2.6.6	Applicability rule for Type C with 4Rx	536
8.1.2.7	Applicability of Enhanced Downlink Control Channel Performance Requirements	536
8.1.2.8	Applicability of performance requirements for CDM-multiplexed DM RS with interfering simultaneous transmission (FRC) with multiple CSI-RS configurations	538
8.1.2.8A	Applicability of performance requirements for UE supporting coverage enhancement	538
8.1.2.9	Applicability of SDR requirements for CA and LAA	539
8.1.2.10	Applicability of performance requirements for Multi-user Superposed Transmission	539
8.1.2.11	Applicability CRS interference mitigation receivers performance requirements	540
8.1.3	UE category and UE DL category	540
8.2	Demodulation of PDSCH (Cell-Specific Reference Symbols)	540
8.2.1	FDD (Fixed Reference Channel)	540
8.2.1.1	Single-antenna port performance	541
8.2.1.1.1	Minimum Requirement	541
8.2.1.1.2	Void	546
8.2.1.1.3	Void	546
8.2.1.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN	546
8.2.1.1.4A	Minimum Requirement 1 PRB allocation in presence of FeMBMS Unicast-mixed Cell under CA	547
8.2.1.2	Transmit diversity performance	547
8.2.1.2.1	Minimum Requirement 2 Tx Antenna Port	547
8.2.1.2.2	Minimum Requirement 4 Tx Antenna Port	548
8.2.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	549
8.2.1.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	551
8.2.1.2.4	Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model	553
8.2.1.2.5	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	555
8.2.1.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	556
8.2.1.2.7	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	557
8.2.1.3	Open-loop spatial multiplexing performance	557
8.2.1.3.1	Minimum Requirement 2 Tx Antenna Port	557
8.2.1.3.1A	Soft buffer management test	560
8.2.1.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	562
8.2.1.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	562
8.2.1.3.2	Minimum Requirement 4 Tx Antenna Port	563
8.2.1.3.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	564
8.2.1.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	568
8.2.1.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	570
8.2.1.4	Closed-loop spatial multiplexing performance	571

8.2.1.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	571
8.2.1.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port	571
8.2.1.4.1B	Enhanced Performance Requirement Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	572
8.2.1.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	574
8.2.1.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	576
8.2.1.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	578
8.2.1.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	579
8.2.1.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	580
8.2.1.4.2A	Enhanced Performance Requirement Type C – Multi-layer Spatial Multiplexing 2Tx Antenna Ports	581
8.2.1.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	581
8.2.1.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	585
8.2.1.4.4	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	586
8.2.1.5	MU-MIMO	587
8.2.1.6	[Control channel performance: D-BCH and PCH]	587
8.2.1.7	Carrier aggregation with power imbalance	587
8.2.1.7.1	Minimum Requirement	587
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset	588
8.2.1.8.1	Minimum Requirement	588
8.2.1.9	HST-SFN performance	589
8.2.1.9.1	Minimum Requirement	589
8.2.2	TDD (Fixed Reference Channel)	590
8.2.2.1	Single-antenna port performance	590
8.2.2.1.1	Minimum Requirement	590
8.2.2.1.2	Void	594
8.2.2.1.3	Void	594
8.2.2.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN	594
8.2.2.2	Transmit diversity performance	595
8.2.2.2.1	Minimum Requirement 2 Tx Antenna Port	595
8.2.2.2.2	Minimum Requirement 4 Tx Antenna Port	596
8.2.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	596
8.2.2.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	598
8.2.2.2.4	Enhanced Performance Requirement Type A – 2 Tx Antenna Ports with TM3 interference model	600
8.2.2.2.5	Minimum Requirement 2 Tx Antenna Port (when <i>EIMTA-MainConfigServCell-r12</i> is configured)	602
8.2.2.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	602
8.2.2.2.7	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	604
8.2.2.2.8	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	605
8.2.2.3	Open-loop spatial multiplexing performance	606
8.2.2.3.1	Minimum Requirement 2 Tx Antenna Port	606
8.2.2.3.1A	Soft buffer management test	608
8.2.2.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	609
8.2.2.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	609
8.2.2.3.2	Minimum Requirement 4 Tx Antenna Port	610
8.2.2.3.3	Minimum Requirement 2Tx antenna port (demodulation subframe overlaps with aggressor cell ABS)	611
8.2.2.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	615
8.2.2.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	617
8.2.2.4	Closed-loop spatial multiplexing performance	618

8.2.2.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	618
8.2.2.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port	618
8.2.2.4.1B	Enhanced Performance Requirement Type A – Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	619
8.2.2.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	621
8.2.2.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	623
8.2.2.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	625
8.2.2.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	626
8.2.2.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	628
8.2.2.4.2A	Enhanced Performance Requirement Type C Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	628
8.2.2.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	629
8.2.2.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	632
8.2.2.4.4	Void	634
8.2.2.4.5	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	634
8.2.2.5	MU-MIMO	635
8.2.2.6	[Control channel performance: D-BCH and PCH]	635
8.2.2.7	Carrier aggregation with power imbalance	635
8.2.2.7.1	Minimum Requirement	635
8.2.2.8	Intra-band contiguous carrier aggregation with minimum channel spacing	636
8.2.2.8.1	Minimum Requirement	636
8.2.2.9	HST-SFN performance	637
8.2.2.9.1	Minimum Requirement	637
8.2.3	TDD FDD CA (Fixed Reference Channel)	637
8.2.3.1	Single-antenna port performance	638
8.2.3.1.1	Minimum Requirement for FDD PCell	638
8.2.3.1.2	Minimum Requirement for TDD PCell	642
8.2.3.2	Open-loop spatial multiplexing performance 2Tx Antenna port	644
8.2.3.2.1	Minimum Requirement for FDD PCell	644
8.2.3.2.1A	Soft buffer management test for FDD PCell	647
8.2.3.2.2	Minimum Requirement for TDD PCell	648
8.2.3.2.2A	Soft buffer management test for TDD PCell	651
8.2.3.3	Closed-loop spatial multiplexing performance 4Tx Antenna Port	652
8.2.3.3.1	Minimum Requirement for FDD PCell	652
8.2.3.3.2	Minimum Requirement for TDD PCell	656
8.2.3.4	Minimum Requirement for Closed-loop spatial multiplexing performance 4Tx Antenna Port for dual connectivity	659
8.2.4	LAA	661
8.2.4.1	Closed-loop spatial multiplexing performance 4Tx Antenna Port	661
8.2.4.1.1	FDD PCell (FDD single carrier)	661
8.2.4.1.2	TDD PCell (TDD single carrier)	664
8.3	Demodulation of PDSCH (User-Specific Reference Symbols)	668
8.3.1	FDD	668
8.3.1.1	Single-layer Spatial Multiplexing	668
8.3.1.1A	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model	670
8.3.1.1B	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	672
8.3.1.1C	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference model	674
8.3.1.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model	676
8.3.1.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference model	677
8.3.1.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	678