

ETSI TS 131 111 V11.14.0 (2018-10)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
Universal Subscriber Identity Module (USIM)
Application Toolkit (USAT)
(3GPP TS 31.111 version 11.14.0 Release 11)**



ReferenceRTS/TSGC-063111vbe0

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	11
1 Scope	12
2 References	12
3 Definitions, abbreviations and symbols	14
3.1 Definitions	14
3.2 Abbreviations	15
3.3 Symbols.....	15
4 Overview of USAT	15
4.1 Profile Download	16
4.2 Proactive UICC	16
4.3 Data download to UICC	16
4.4 Menu selection	16
4.5 Call control by USIM	16
4.6 MO Short Message control by USIM.....	16
4.7 Event download.....	16
4.8 Security	17
4.9 Multiple card	17
4.10 Timer Expiration	17
4.11 Bearer Independent Protocol	17
4.12 Description of the access technology indicator mechanism	17
4.13 Description of the network search mode mechanism	17
4.14 Geographical location discovery	17
4.15 Operation in reduced USAT capable terminals	17
4.16 Tag allocation guidelines.....	17
4.17 USAT over the AT interface	17
4.18 USAT facilities provided by eCAT clients.....	17
5 Profile download	18
5.1 Procedure.....	18
5.2 Structure and coding of TERMINAL PROFILE.....	18
5.3 Definition of display parameters in Profile download.....	22
6 Proactive UICC	22
6.1 Introduction	22
6.2 Identification of ME support	22
6.3 General procedure	23
6.4 Proactive UICC commands and procedures	23
6.4.1 DISPLAY TEXT	23
6.4.2 GET INKEY	23
6.4.3 GET INPUT	23
6.4.4 MORE TIME	23
6.4.5 PLAY TONE	23
6.4.6 POLL INTERVAL	23
6.4.7 REFRESH.....	23
6.4.7.1 EF _{IMSI} changing procedure	23
6.4.7.2 Generic Bootstrapping Procedure Request.....	24
6.4.7.3 EF _{UICCIARI} changing procedure	24
6.4.7.4 Steering of roaming and steering of roaming for I-WLAN procedure.....	24
6.4.8 SET UP MENU	24
6.4.9 SELECT ITEM.....	24
6.4.10 SEND SHORT MESSAGE	24
6.4.11 SEND SS	25

6.4.12	SEND USSD.....	26
6.4.12.1	MMI Mode.....	26
6.4.12.2	Application Mode	27
6.4.13	SET UP CALL.....	28
6.4.14	POLLING OFF	28
6.4.15	PROVIDE LOCAL INFORMATION.....	28
6.4.16	SET UP EVENT LIST.....	31
6.4.17	PERFORM CARD APDU	31
6.4.18	POWER OFF CARD	31
6.4.19	POWER ON CARD.....	31
6.4.20	GET READER STATUS.....	31
6.4.21	TIMER MANAGEMENT	31
6.4.22	SET UP IDLE MODE TEXT	31
6.4.23	RUN AT COMMAND	31
6.4.24	SEND DTMF.....	31
6.4.25	LANGUAGE NOTIFICATION	31
6.4.26	LAUNCH BROWSER	31
6.4.27	OPEN CHANNEL	31
6.4.27.1	OPEN CHANNEL related to CS bearer.....	31
6.4.27.2	OPEN CHANNEL related to GPRS/UTRAN packet service/E-UTRAN	32
6.4.27.3	OPEN CHANNEL related to local bearer.....	32
6.4.27.4	OPEN CHANNEL related to Default (network) Bearer	32
6.4.27.5	OPEN CHANNEL related to I-WLAN bearer.....	32
6.4.27.6	OPEN CHANNEL related to Terminal Server Mode	34
6.4.27.7	OPEN CHANNEL related to UICC Server Mode	34
6.4.27.8	OPEN CHANNEL for IMS.....	34
6.4.28	CLOSE CHANNEL.....	34
6.4.29	RECEIVE DATA	34
6.4.30	SEND DATA.....	34
6.4.31	GET CHANNEL STATUS	35
6.4.32	SERVICE SEARCH	35
6.4.33	GET SERVICE INFORMATION.....	35
6.4.34	DECLARE SERVICE	35
6.4.35	RETRIEVE MULTIMEDIA MESSAGE.....	35
6.4.36	SUBMIT MULTIMEDIA MESSAGE.....	35
6.4.37	DISPLAY MULTIMEDIA MESSAGE.....	35
6.4.38	SET FRAMES	35
6.4.39	GET FRAME STATUS.....	35
6.4.40	Geographical Location Request.....	35
6.4.41	ACTIVATE	36
6.4.42	CONTACTLESS STATE CHANGED	36
6.4.43	COMMAND CONTAINER	36
6.4.44	ENCAPSULATED SESSION CONTROL	36
6.5	Common elements in proactive UICC commands	36
6.5.1	Command number	36
6.5.2	Device identities	36
6.5.3	Alpha identifier	36
6.5.4	Icon identifiers	37
6.5.5	Text attribute.....	37
6.5.6	Frame identifier	37
6.6	Structure of proactive UICC commands	37
6.6.1	DISPLAY TEXT	37
6.6.2	GET INKEY	37
6.6.3	GET INPUT.....	37
6.6.4	MORE TIME	37
6.6.5	PLAY TONE	37
6.6.6	POLL INTERVAL	37
6.6.7	SET-UP MENU	37
6.6.8	SELECT ITEM.....	37
6.6.9	SEND SHORT MESSAGE	37
6.6.10	SEND SS	38
6.6.11	SEND USSD.....	38

6.6.12	SET UP CALL.....	38
6.6.13	REFRESH.....	38
6.6.14	POLLING OFF.....	39
6.6.15	PROVIDE LOCAL INFORMATION.....	39
6.6.16	SET UP EVENT LIST.....	39
6.6.17	PERFORM CARD APDU.....	39
6.6.18	POWER OFF CARD.....	39
6.6.19	POWER ON CARD.....	39
6.6.20	GET READER STATUS.....	39
6.6.21	TIMER MANAGEMENT.....	39
6.6.22	SET UP IDLE MODE TEXT.....	39
6.6.23	RUN AT COMMAND.....	39
6.6.24	SEND DTMF COMMAND.....	39
6.6.25	LANGUAGE NOTIFICATION.....	39
6.6.26	LAUNCH BROWSER.....	40
6.6.27	OPEN CHANNEL.....	40
6.6.27.1	OPEN CHANNEL related to I-WLAN Bearer.....	40
6.6.27.2	OPEN CHANNEL for IMS.....	40
6.6.28	CLOSE CHANNEL.....	41
6.6.29	RECEIVE DATA.....	41
6.6.30	SEND DATA.....	41
6.6.31	GET CHANNEL STATUS.....	41
6.6.32	SERVICE SEARCH.....	41
6.6.33	GET SERVICE INFORMATION.....	41
6.6.34	DECLARE SERVICE.....	41
6.6.35	RETRIEVE MULTIMEDIA MESSAGE.....	41
6.6.36	SUBMIT MULTIMEDIA MESSAGE.....	41
6.6.37	DISPLAY MULTIMEDIA MESSAGE.....	41
6.6.38	SET FRAMES.....	41
6.6.39	GET FRAMES STATUS.....	41
6.6.40	Geographical Location Request.....	41
6.6.41	ACTIVATE.....	42
6.6.42	CONTACTLESS STATE CHANGED.....	42
6.6.43	COMMAND CONTAINER.....	42
6.6.44	ENCAPSULATED SESSION CONTROL.....	42
6.7	Command results.....	42
6.8	Structure of TERMINAL RESPONSE.....	43
6.8.1	Command details.....	44
6.8.2	Device identities.....	44
6.8.3	Result.....	44
6.8.4	Duration.....	44
6.8.5	Text string.....	44
6.8.6	Item identifier.....	45
6.8.7	Local information.....	45
6.8.8	Call control requested action.....	45
6.8.9	Result data object 2.....	45
6.8.10	Card reader status.....	45
6.8.11	Card ATR.....	45
6.8.12	R-APDU.....	46
6.8.13	Timer identifier.....	46
6.8.14	Timer value.....	46
6.8.15	AT Response.....	46
6.8.16	Text string 2.....	46
6.8.17	Channel data.....	46
6.8.18	Channel status.....	46
6.8.19	Channel data length.....	46
6.8.20	Bearer description.....	46
6.8.21	Buffer size.....	46
6.8.22	Total Display Duration.....	46
6.8.23	Service Availability.....	46
6.8.24	Service Record.....	46
6.8.25	Other address (local address).....	46

6.8.26	Frames Information.....	46
6.9	Proactive UICC session and ME display interaction.....	47
6.10	Handling of unknown, unforeseen and erroneous messages	47
6.11	Proactive commands versus possible Terminal response	47
7	ENVELOPE Commands	48
7.1	Data download to UICC	48
7.1.1	SMS-PP data download	48
7.1.1.1	Procedure	48
7.1.1.2	Structure of ENVELOPE (SMS-PP DOWNLOAD)	49
7.1.2	Cell Broadcast data download	49
7.1.2.1	Procedure	49
7.1.2.2	Structure of ENVELOPE (CELL BROADCAST DOWNLOAD)	50
7.2	Menu Selection.....	50
7.3	Call Control and MO SMS control by USIM.....	51
7.3.1	Call Control by USIM.....	51
7.3.1.1	Procedure for mobile originated calls	51
7.3.1.2	Procedure for Supplementary Services and USSD	52
7.3.1.3	Indication to be given to the user	53
7.3.1.4	Interaction with Fixed Dialling Number	54
7.3.1.5	Support of Barred Dialling Number (BDN) service.....	54
7.3.1.6	Structure of ENVELOPE (CALL CONTROL)	54
7.3.1.7	Procedure for PDP Context Activation	57
7.3.1.8	Procedure for EPS PDN connection Activation	57
7.3.1.9	Procedure for IMS communications establishment.....	58
7.3.2	MO Short Message Control by USIM	58
7.3.2.1	Description	58
7.3.2.2	Structure of ENVELOPE (MO SHORT MESSAGE CONTROL)	59
7.3.2.3	Indication to be given to the user	60
7.3.2.4	Interaction with Fixed Dialling Number	60
7.4	Timer Expiration	60
7.5	Event download.....	60
7.5.1	I-WLAN Access status event.....	60
7.5.1.1	Procedure	60
7.5.1.2	Structure of ENVELOPE (EVENT DOWNLOAD – I-WLAN Access Status).....	61
7.5.1A	MT Call event	61
7.5.2	Network Rejection event	61
7.5.2.1	Procedure	61
7.5.2.2	Structure of ENVELOPE (EVENT DOWNLOAD – Network Rejection)	61
7.5.2A	Call connected event.....	62
7.5.3	CSG Cell Selection event	62
7.5.3.1	Procedure	62
7.5.3.2	Structure of ENVELOPE (EVENT DOWNLOAD – CSG Cell Selection)	62
7.5.3A	Call disconnected event	63
7.5.4	Location status event	63
7.5.5	User activity event	63
7.5.6	Idle screen available event	63
7.5.7	Card reader status event.....	63
7.5.8	Language selection event.....	64
7.5.9	Browser termination event.....	64
7.5.10	Data available event.....	64
7.5.11	Channel status event	64
7.5.12	Access Technology Change Event.....	64
7.5.13	Display parameters changed event.....	64
7.5.14	Local Connection event	64
7.5.15	Network Search Mode Change Event.....	64
7.5.16	Browsing status event	64
7.5.17	Frames Information changed event.....	64
7.5.18	HCI connectivity event	64
7.5.19	Contactless state request	64
7.5.20	Incoming IMS Data event.....	64
7.5.20.1	Procedure	64

7.5.20.2	Structure of ENVELOPE (EVENT DOWNLOAD – Incoming IMS Data)	65
7.5.21	IMS Registration Event	65
7.5.21.1	Procedure	65
7.5.21.2	Structure of ENVELOPE (EVENT DOWNLOAD – IMS Registration)	65
7.5.22	Profile Container	66
7.5.23	Envelope Container	66
7.6	USSD Data Download	66
7.6.1	Procedure	66
7.6.2	Structure of ENVELOPE (USSD Data Download)	67
7.7	MMS Transfer Status	67
7.8	MMS notification download	67
7.9	Terminal Applications	67
7.10	Geographical Location Reporting	67
7.10.1	Procedure	67
7.10.2	Structure of ENVELOPE (Geographical Location Reporting)	68
8	COMPREHENSION-TLV data objects	68
8.1	Address	68
8.2	Alpha identifier	68
8.3	Subaddress	68
8.4	Capability configuration parameters	69
8.5	Cell Broadcast Page	69
8.6	Command details	69
8.7	Device identities	70
8.8	Duration	70
8.9	Item	70
8.10	Item identifier	70
8.11	Response length	70
8.12	Result	70
8.12.1	Additional information for SEND SS	71
8.12.2	Additional information for ME problem	71
8.12.3	Additional information for network problem	71
8.12.4	Additional information for SS problem	71
8.12.5	Additional information for SMS problem	71
8.12.6	Not used	71
8.12.7	Additional information for USSD problem	71
8.12.8	Additional information for interaction with call control or MO SM control	72
8.12.9	Additional information for MultipleCard commands	72
8.12.10	Additional information for launch browser problem	72
8.12.11	Additional information for Bearer Independent Protocol	72
8.12.12	Additional information for Frames commands	72
8.12.13	Additional information for SUBMIT and RETRIEVE MULTIMEDIA MESSAGE	72
8.13	SMS TPDU	72
8.14	SS string	73
8.15	Text string	73
8.16	Tone	73
8.17	USSD string	73
8.18	File List	73
8.19	Location Information	74
8.20	IMEI	74
8.21	Help Request	74
8.22	Network Measurement Results	74
8.23	Default Text	76
8.24	Items Next Action Indicator	76
8.25	Event list	76
8.26	Cause	76
8.27	Location status	76
8.28	Transaction identifier	76
8.29	BCCH channel list	77
8.30	Call control requested action	77
8.31	Icon Identifier	78
8.32	Item Icon Identifier list	78

8.33	Card reader status	78
8.34	Card ATR	78
8.35	C-APDU	78
8.36	R-APDU	78
8.37	Timer identifier	78
8.38	Timer value	78
8.39	Date-Time and Time zone	78
8.40	AT Command	78
8.41	AT Response	79
8.42	BC Repeat indicator	79
8.43	Immediate response	79
8.44	DTMF string	79
8.45	Language	79
8.46	Timing Advance	79
8.47	Browser Identity	80
8.48	URL	80
8.49	Bearer	80
8.50	Provisioning File Reference	80
8.51	Browser Termination Cause	80
8.52	Bearer description	80
8.52.1	Bearer parameters for CSD	81
8.52.2	Bearer parameters for GPRS/UTRAN Packet Service/E-UTRAN	81
8.52.3	Bearer parameters for UTRAN Packet Service with extended parameters / HSDPA / E-UTRAN	82
8.52.4	Bearer parameters for I-WLAN	83
8.52.5	Bearer parameters for E-UTRAN / mapped UTRAN packet service	83
8.53	Channel data	83
8.54	Channel data length	83
8.55	Buffer size	83
8.56	Channel status	83
8.57	Card reader identifier	84
8.58	Other Address	84
8.59	UICC/ME interface transport level	84
8.60	AID	84
8.61	Network Access Name	84
8.62	Access Technology	84
8.63	Display parameters	84
8.64	Service Record	84
8.65	Device Filter	84
8.66	Service Search	85
8.67	Attribute Information	85
8.68	Service Availability	85
8.69	Remote Entity Address	85
8.70	Text Attribute	85
8.71	Item Text Attribute List	85
8.72	PDP context Activation parameters	85
8.73	UTRAN/E-UTRAN Measurement Qualifier	85
8.74	Multimedia Message Reference	86
8.75	Multimedia Message Identifier	86
8.76	Multimedia Message Transfer status	86
8.77	MM Content Identifier	86
8.78	Multimedia Message Notification	86
8.79	Last Envelope	86
8.80	Frames Layout	86
8.81	Frames Information	86
8.82	Frames identifier	86
8.83	I-WLAN Identifier	86
8.84	I-WLAN Access Status	87
8.85	IMEISV	87
8.86	Network search mode	87
8.87	Battery State	87
8.88	Browsing status	87
8.89	Registry application data	87

8.90	PLMNwAcT List.....	87
8.91	Routing Area Identification.....	88
8.92	Update/Attach Type	88
8.93	Rejection Cause Code	89
8.94	Geographical Location Parameters.....	89
8.95	GAD shapes.....	91
8.96	NMEA sentence	92
8.97	PLMN List.....	92
8.98	EPS PDN connection activation parameters	92
8.99	Tracking Area Identification	93
8.100	CSG ID list identifier	93
8.101	CSG cell selection status	94
8.102	CSG ID	94
8.103	HNB name.....	94
8.104	Activate descriptor	94
8.105	Broadcast Network information	95
8.106	Contactless state request.....	95
8.107	Contactless functionality state	95
8.108	IMS Request-URI.....	95
8.109	Extended registry application data	95
8.110	IARI.....	95
8.111	IMPU List.....	95
8.112	IMS status code	96
8.113	eCAT client profile.....	96
8.114	eCAT client identity	96
8.115	Encapsulated envelope type	96
8.116	Void.....	96
8.117	Void.....	96
8.118	Reserved	96
8.119	Reserved	96
8.120	Call control result	96
8.121	eCAT sequence number	96
8.122	Encrypted TLV list.....	96
8.123	MAC.....	96
8.124	SA template	97
8.125	CAT service list.....	97
9	Tag values	97
9.1	BER-TLV tags in ME to UICC direction.....	97
9.2	BER-TLV tags in UICC TO ME direction.....	97
9.3	COMPREHENSION-TLV tags in both directions.....	98
9.4	Type of Command and Next Action Indicator	98
10	Allowed Type of command and Device identity combinations	99
11	Security requirements.....	99
Annex A (normative):	Support of USAT by Mobile Equipment	100
Annex B (informative):	Example of DISPLAY TEXT Proactive UICC Command	101
Annex C (normative):	Structure of USAT communications	102
Annex D (informative):	ME display in proactive UICC session.....	103
Annex E (informative):	Help information feature processing.....	104
Annex F (informative):	Monitoring of events.....	105
Annex G (normative):	Support of Multiple Card Operation	106
Annex H (informative):	Multiple Card proactive command examples	107
Annex I (informative):	Bearer independent protocol proactive command examples	108

Annex J (informative):	WAP References	109
Annex K (informative):	Use of USAT Bearer independent protocol for local links Bluetooth case	110
Annex L (informative):	Bluetooth Service Discovery protocol	111
Annex M (informative):	Use of USAT Bearer independent protocol for local links, server case ..	112
Annex N (informative):	USSD information flow between the Network, the ME and the UICC...	113
N.1	MMI Mode	113
N.2	Application Mode.....	115
N.3	USSD Data Download.....	117
Annex O (informative):	Geographical location information discovery information flow between the ME and the UICC.....	118
Annex P (normative):	Support of USAT by Terminals with reduced feature capabilities.	119
Annex Q (normative):	Default routing for USAT over AT interface	120
Q.0	3GPP-specific facilities	120
Q.1	Default routing mechanism	120
Q.2	Combination rules for terminal profiles	121
Annex R (informative):	UICC access to IMS, command flow examples.....	122
R.1	Discovery of the UICC's IARI and IMS Registration	122
R.2	Notification of Incoming IMS data	123
R.3	UICC originating a SIP message.....	124
Annex S (informative):	Change History	125
History		129

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- Y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- Z the third digit is incremented when editorial only changes have been incorporated in the document.

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/86ea8ec6-216a-43c5-8028-178d299ae9fd/etsi-ts-131-111-v11.14.0-2018-10>

1 Scope

The present document defines the interface between the UICC and the Mobile Equipment (ME), and mandatory ME procedures, specifically for "USIM Application Toolkit".

The present document refers in its majority to the ETSI TS 102 223 [32], which describes the generic aspects of application toolkits within the UICC.

USAT is a set of commands and procedures for use during the network operation phase of 3G/LTE, in addition to those defined in TS 31.101 [13].

Specifying the interface is to ensure interoperability between a UICC and an ME independently of the respective manufacturers and operators.

The present document defines for 3G/LTE technology:

- the commands;
- the application protocol;
- the mandatory requirements on the UICC and ME for each procedure.

The present document does not specify any aspects related to the administrative management phase. Any internal technical realization of either the UICC or the ME are only specified where these reflect over the interface. The present document does not specify any of the security algorithms which may be used.

For the avoidance of doubt, references to clauses of ETSI TS 102 223 [32] include all the subclauses of that clause, unless specifically mentioned.

The target specification ETSI TS 102 223 [32] contains material that is outside of the scope of 3GPP requirements and the present document indicates which parts are in the scope and which are not.

A 3GPP ME may support functionality that is not required by 3GPP, but the requirements to do so are outside of the scope of 3GPP.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.

- | | |
|-----|--|
| [1] | 3GPP TS 22.002: "Circuit Bearer Services (BS) supported by a Public Land Mobile Network (PLMN)". |
| [2] | 3GPP TS 22.030: "Man-Machine Interface (MMI) of the User Equipment (UE)". |
| [3] | 3GPP TS 22.042: "Network Identity and Time Zone (NITZ); Service description; Stage 1". |
| [4] | 3GPP TS 23.038: "Alphabets and language-specific information". |
| [5] | 3GPP TS 23.040: "Technical realization of the Short Message Service (SMS)". |
| [6] | 3GPP TS 23.041: "Technical realization of Cell Broadcast Service (CBS)". |
| [7] | 3GPP TS 23.122: "Non-Access Stratum functions related to Mobile Station (MS) in idle mode". |