

---

---

**Geotechnical investigation and testing —  
Field testing —**

Part 3:  
**Standard penetration test**

AMENDMENT 1

iTeh STANDARD PREVIEW

(standards.iteh.ai) *Reconnaissance et essais géotechniques — Essais en place —*

*Partie 3: Essai de pénétration au carottier*

ISO 22476-3:2005/Amd 1:2011

AMENDEMENT 1

<https://standards.iteh.ai/catalog/standards/sist/09c38a-94a3-46ec-9359-cc2fb4acfa1a/iso-22476-3-2005-amd-1-2011>



## iTeh STANDARD PREVIEW (standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/09cce38a-94a3-46ec-9359-cc2fb4acfa1a/iso-22476-3-2005-amd-1-2011>



### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO 22476-3:2005 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 341, *Geotechnical Investigation and Testing*, in collaboration with Technical Committee ISO/TC 182, *Geotechnics*, Subcommittee SC 1, *Geotechnical investigation and testing*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

(standards.iteh.ai)

[ISO 22476-3:2005/Amd 1:2011](https://standards.iteh.ai/catalog/standards/sist/09cce38a-94a3-46cc-9359-cc2fb4acfa1a/iso-22476-3-2005-amd-1-2011)

<https://standards.iteh.ai/catalog/standards/sist/09cce38a-94a3-46cc-9359-cc2fb4acfa1a/iso-22476-3-2005-amd-1-2011>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 22476-3:2005/Amd 1:2011](https://standards.iteh.ai/catalog/standards/sist/09cce38a-94a3-46ec-9359-cc2fb4acfa1a/iso-22476-3-2005-amd-1-2011)

<https://standards.iteh.ai/catalog/standards/sist/09cce38a-94a3-46ec-9359-cc2fb4acfa1a/iso-22476-3-2005-amd-1-2011>

# Geotechnical investigation and testing — Field testing —

## Part 3: Standard penetration test

### AMENDMENT 1

#### Page 1, Scope

Replace the first paragraph with the following:

This part of ISO 22476 deals with the equipment requirements for, execution of and reporting on the standard penetration test to complement direct investigations (e.g. ISO 22475-1).

NOTE This part of ISO 22476 fulfils the requirements for standard penetration testing as part of geotechnical investigation and testing in accordance with EN 1997-1 and EN 1997-2.

#### Page 1, Normative references

(standards.iteh.ai)

Replace prEN ISO 22475-1 with the following:

<https://standards.iteh.ai/catalog/standards/sist/09c38a-94a3-46ec-9359-cc207ac1a780/iso-22475-1-2006-amd-1-2011>  
ISO 22475-1:2006, *Geotechnical investigation and testing — Sampling methods and groundwater measurements — Part 1: Technical principles for execution*

#### Page 3, 4.3

After the first sentence of the first paragraph, add the following sentence:

The rod stiffness should be at least that of an AW rod for tests less than 20 m depth, and of a BW rod for greater depth. For definitions of AW and BW rods, see ISO 22475-1:2006, Table C.1.

At the end of the first paragraph, add the following:

The straightness shall be checked by applying one of the following procedures.

- Holding the rod vertically and rotating it. If the rod appears to wobble, the straightness is not acceptable.
- Rolling the rod on a plane surface. If the rod appears to wobble, the straightness is not acceptable.
- Sliding a straight hollow tube which is slightly longer than the rod over the rod. If the rod can pass through the tube without jamming, the straightness is acceptable.

Add the following as the last paragraph:

At greater depth and/or with greater borehole diameters, the vertical alignment of the rod string should be ensured by installing appropriate stabilizers. Also, a stabilizer should be used at the collar at the top of the borehole. Type and number of stabilizers shall be reported.

Page 4, 5.1

After the second sentence of the first paragraph, add the following:

The straightness shall be checked by applying one of the following procedures.

- Holding the rod vertically and rotating it. If the rod appears to wobble, the straightness is not acceptable.
- Rolling the rod on a plane surface. If the rod appears to wobble, the straightness is not acceptable.
- Sliding a straight hollow tube which is slightly longer than the rod over the rod. If the rod can pass through the tube without jamming, the straightness is acceptable.

At the end of the final paragraph, add the following sentence:

The calibration check shall be made annually and after all changes, repairs and modifications to the driving equipment.

Page 4, 5.2

In the second paragraph, replace “bottom discharge, from a safe distance of the test elevation” with “bottom discharge, from a safe distance above the test elevation.”

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

Page 4, 5.3

Replace the fourth sentence in the first paragraph with the following:

Then the sampler shall be driven in the same manner over a test drive of 300 mm. This shall be done in at least two increments (150 mm each). Alternatively, four increments (75 mm each) may be used.

In the last sentence of the first paragraph, replace the text in parentheses with the following:

$(N = N_n + N_{n+1}$  for 150 mm increments;  $N = N_n + N_{n+1} + N_{n+2} + N_{n+3}$  for 75 mm increments).

After the first paragraph, add the following paragraph:

The seating drive shall be 150 mm or 25 blows, whichever is reached first. If the seating drive is terminated at 25 blows, the depth of penetration shall be recorded and the start of the test drive measured from that depth.

In the last paragraph, replace “prEN ISO 22475-1” with “ISO 22475-1”.

Page 5, Clause 6

Replace the first paragraph with the following:

The test results shall be reported and interpreted as the seating drive,  $N_0$ , and the penetration blow resistance,  $\mathbb{X}$ , or the test drive blow number,  $N$ . They shall be reported without any corrections or adjustments. Corrections/adjustments may be considered for further interpretation.

Page 5, 7.1.1 a)

Replace “prEN ISO 22475-1” with “ISO 22475-1”.

Page 6, 7.1.2 c)

Add the following after item 7):

- 8) type and number of stabilizers, as applicable;

Page 6, 7.1.2 d), item 3)

After the first bullet, add the following:

- the number and size of test increments (two, 150 mm or four, 75 mm)

In the existing second bullet, replace “ $N_n, N_{n-1}$ , if required” with “ $N_n, N_{n+1}$  for two increments, or  $N_n, N_{n+1}, N_{n+2}, N_{n+3}$  for four increments of penetration, if required”.

After the existing second bullet, add the following bullet:

- number of blows for the seating drive;

After the existing third bullet, add the following bullet:

- drive penetration if seating drive is terminated at 25 blows;

Page 6, 7.1.2 d), item 13)

Replace “prEN ISO 22475-1” with “ISO 22475-1”.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**  
<https://standards.iteh.ai/catalog/standards/sist/09cce38a-94a3-46cc-9359-cc2fb4acfa1a/iso-22476-3-2005-amd-1-2011>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 22476-3:2005/Amd 1:2011](https://standards.iteh.ai/catalog/standards/sist/09cce38a-94a3-46ec-9359-cc2fb4acfa1a/iso-22476-3-2005-amd-1-2011)  
[https://standards.iteh.ai/catalog/standards/sist/09cce38a-94a3-46ec-9359-  
cc2fb4acfa1a/iso-22476-3-2005-amd-1-2011](https://standards.iteh.ai/catalog/standards/sist/09cce38a-94a3-46ec-9359-cc2fb4acfa1a/iso-22476-3-2005-amd-1-2011)

---

---

**ICS 93.020**

Price based on 3 pages