

Final draft **ETSI EN 303 132** V2.1.0 (2022-08)



**Maritime VHF survivor locating devices employing Digital
Selective Calling (DSC Class M);
Harmonised Standard for access to radio spectrum and
for features for emergency services**

[ETSI EN 303 132 V2.1.0 \(2022-08\)](https://standards.iteh.ai/catalog/standards/sist/2754e59d-c679-4e3c-9e36-6d3dcefa80c9/etsi-en-303-132-v2-1-0-2022-08)

<https://standards.iteh.ai/catalog/standards/sist/2754e59d-c679-4e3c-9e36-6d3dcefa80c9/etsi-en-303-132-v2-1-0-2022-08>

ReferenceREN/ERM-TGMAR-605

Keywordsharmonised standard, maritime, radio, SAR, testing

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.

All rights reserved.

Contents

Intellectual Property Rights	9
Foreword.....	9
Modal verbs terminology.....	10
1 Scope	11
2 References	11
2.1 Normative references	11
2.2 Informative references.....	12
3 Definition of terms, symbols and abbreviations.....	12
3.1 Terms.....	12
3.2 Symbols.....	13
3.3 Abbreviations	14
4 Requirements that can be visually inspected.....	14
4.0 Compliance.....	14
4.1 Construction.....	14
4.1.1 General.....	14
4.1.2 Categories of equipment	15
4.2 Controls	15
4.3 Indicators	15
4.3.1 General.....	15
4.3.2 Visual indicators	15
4.3.2.1 Alarm indicators.....	15
4.3.2.2 Test indicators	16
4.4 Self ID	16
4.5 Labelling.....	16
5 Technical information	16
5.1 Alerting and locating functions	16
5.2 Technical annexes	17
6 General conditions of measurement	17
6.1 Conformity testing.....	17
6.2 Unique identifier (self ID).....	17
6.3 Artificial Antenna	17
6.3.1 For equipment with an integral antenna.....	17
6.3.2 For testing the RF transmitter output	17
6.3.3 For testing the DSC RF receiver input.....	17
6.4 Normal DSC TX Test Modulation	18
6.4.1 Continuous B / Y state	18
6.4.2 Alternating B-Y sequence.....	18
6.4.3 Random B-Y sequence	18
6.4.4 Unmodulated carrier	18
6.5 AIS TX Test Modulation.....	18
6.5.1 Standard test signal number 1	18
6.5.2 Standard test signal number 2	18
6.5.3 Standard test signal number 3	18
6.5.4 Unmodulated carrier	18
6.6 AIS Reference timing signal	18
6.7 Standard test signals for DSC receiver testing	19
6.8 Test conditions power sources and ambient temperatures.....	19
6.8.1 Normal and extreme test conditions.....	19
6.8.2 Test power sources.....	19
6.9 Normal test conditions	19
6.9.1 Normal temperature and humidity	19
6.9.2 Normal test voltage.....	19
6.10 Extreme test conditions	19

6.10.1	Extreme temperatures	19
6.10.2	Extreme test voltages	20
6.10.2.1	Upper extreme test voltage	20
6.10.2.2	Lower extreme test voltage	20
6.11	Reference Bandwidths for emission measurements	20
7	Environmental tests	20
7.1	Introduction	20
7.2	Procedure	20
7.3	Performance check	21
7.4	Drop test	21
7.4.1	Definition	21
7.4.2	Test conditions	21
7.4.3	Method of measurement	21
7.4.4	Required results	21
7.5	Temperature tests	22
7.5.1	Definition	22
7.5.2	Dry heat test	22
7.5.2.1	Method of measurement	22
7.5.2.2	Requirements	22
7.5.3	Damp heat test	22
7.5.3.1	Method of measurement	22
7.5.3.2	Required results	22
7.5.4	Low temperature test	23
7.5.4.1	Method of measurement	23
7.5.4.2	Required results	23
7.5.5	Low temperature battery endurance test	23
7.5.5.1	Method of measurement	23
7.5.5.2	Required results	23
7.6	Vibration test	23
7.6.1	Definition	23
7.6.2	Method of measurement	23
7.6.3	Required results	24
7.7	Saltwater spray test	24
7.7.1	Definition	24
7.7.2	Method of measurement	24
7.7.2.1	The spraying apparatus	24
7.7.2.2	Preparation of EUT	25
7.7.2.3	Test cycles	25
7.7.2.4	Conclusion of testing	25
7.7.3	Required results	25
7.8	Thermal shock test	25
7.8.1	Definition	25
7.8.2	Method of measurement	25
7.8.3	Required results	26
7.9	Buoyancy test	26
7.9.1	Definition	26
7.9.2	Method of measurement	26
7.9.3	Required results and limit	26
7.10	Protection of the transmitter	26
7.10.1	Definition	26
7.10.2	Method of measurement	26
7.10.3	Required results	26
8	Tests on the DSC transmitter	27
8.1	DSC Frequency error	27
8.1.1	Definition	27
8.1.2	Method of measurement	27
8.1.3	Limit	27
8.2	DSC Conducted power variation	27
8.2.1	Purpose	27
8.2.2	Definition	27

8.2.3	Method of measurement	27
8.2.4	Limit	27
8.3	Effective Radiated Power (ERP)	28
8.3.1	Definition	28
8.3.2	Method of measurement	28
8.3.3	Limits	28
8.4	DSC Adjacent channel power	28
8.4.1	Definition	28
8.4.2	Method of measurement	29
8.4.3	Limit	29
8.5	DSC Transmitter transient frequency behaviour	29
8.5.1	Definition	29
8.5.2	Method of measurement	30
8.5.3	Limit	33
8.6	Frequency error (demodulated DSC signal)	33
8.6.1	Definition	33
8.6.2	Method of measurement	33
8.6.3	Limit	33
8.7	Modulation index for DSC	33
8.7.1	Definition	33
8.7.2	Method of measurement	33
8.7.3	Limit	34
8.8	Modulation rate for DSC	34
8.8.1	Definition	34
8.8.2	Method of measurement	34
8.8.3	Limit	34
8.9	Spurious emissions	34
8.9.1	Definition	34
8.9.2	Method of measurement	34
8.9.3	Limit	35
9	Tests on the AIS transmitter	35
9.1	AIS Frequency error	35
9.1.1	Definition	35
9.1.2	Method of measurement	35
9.1.3	Limit	35
9.2	AIS Conducted power variation	35
9.2.1	Purpose	35
9.2.2	Definition	35
9.2.3	Method of measurement	35
9.2.4	Limit	36
9.3	AIS Transmitter spectrum mask	36
9.3.1	Definition	36
9.3.2	Method of measurement	36
9.3.3	Limit	37
9.4	AIS Transmitter transient behaviour (output power)	37
9.4.1	Definition	37
9.4.2	Method of measurement	38
9.4.3	Limit	39
9.5	AIS Transmitter Transient Behaviour (frequency deviation)	39
9.5.1	Definition	39
9.5.2	Method of measurement	39
9.5.3	Limit	39
9.6	AIS Synchronization accuracy	40
9.6.1	Definition	40
9.6.2	Method of measurement	40
9.6.3	Limit	41
10	Tests on the DSC receiver	41
10.1	DSC Maximum usable sensitivity	41
10.1.1	Definition	41
10.1.2	Method of measurement	41

10.1.3	Limit.....	41
10.2	DSC Co-channel rejection.....	41
10.2.1	Definition.....	41
10.2.2	Method of measurement.....	42
10.2.3	Limit.....	42
10.3	DSC Adjacent channel selectivity.....	42
10.3.1	Definition.....	42
10.3.2	Method of measurement.....	42
10.3.3	Limit.....	42
10.4	DSC Spurious response.....	42
10.4.1	Definition.....	42
10.4.2	Spurious response frequency calculations.....	43
10.4.3	Method of measurement.....	43
10.4.4	Limit.....	43
10.5	DSC Intermodulation response.....	43
10.5.1	Definition.....	43
10.5.2	Method of measurement.....	43
10.5.3	Limit.....	44
10.6	Blocking or desensitization.....	44
10.6.1	Definition.....	44
10.6.2	Method of measurement.....	44
10.6.3	Limit.....	44
10.7	DSC Minimum dynamic range.....	44
10.7.1	Definition.....	44
10.7.2	Method of measurement.....	44
10.7.3	Limit.....	45
11	DSC Conformance Testing.....	45
11.1	Active mode tests.....	45
11.1.1	Listen Before Talk (LBT).....	45
11.1.1.1	Method of measurement.....	45
11.1.1.2	Required Results.....	45
11.1.2	First closed loop distress transmissions.....	45
11.1.2.1	Applicability.....	45
11.1.2.2	Method of measurement.....	45
11.1.2.3	Required Results.....	45
11.1.3	First open loop distress transmissions.....	46
11.1.3.1	Applicability.....	46
11.1.3.2	Method of measurement.....	46
11.1.3.3	Required Results.....	47
11.1.4	Open loop distress repeat transmissions.....	47
11.1.4.1	Applicability.....	47
11.1.4.2	Method of measurement.....	48
11.1.4.3	Required Results.....	48
12	AIS VDL Link layer tests.....	48
12.1	Active mode tests.....	48
12.1.1	Method of measurement.....	48
12.1.2	Initialization period - Required results.....	49
12.1.3	Message content of Message 1 - Required results.....	49
12.1.4	Message content of Message 14 - Required results.....	49
12.1.5	Transmission schedule for Message 1 - Required results.....	50
12.1.6	Communication state of Message 1 - Required results.....	50
12.1.7	Transmission schedule of Message 14 - Required results.....	50
12.1.8	Transmission with lost GNSS - Required results.....	50
13	Testing for compliance with technical requirements.....	51
13.1	Environmental conditions for testing.....	51
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU.....	52
Annex B (normative):	Measuring receiver for adjacent channel power measurement.....	54

B.1	Power measuring receiver specification.....	54
B.1.1	General	54
B.1.2	IF filter	54
B.1.3	Attenuation indicator.....	55
B.1.4	r.m.s. value indicator	55
B.1.5	Oscillator and amplifier.....	55
Annex C (normative): Additional Test Supports		56
C.1	Float-free support	56
Annex D (informative): AIS message bursts		57
D.1	Active mode	57
D.2	Test mode	58
D.3	Default message field values.....	59
Annex E (informative): Technical characteristics of class M MLSDs.....		60
E.1	General	60
E.2	DSC transmission characteristics	60
E.3	DSC messages and protocols	61
E.4	AIS transmission characteristics	61
E.4.1	General	61
E.4.2	AIS messages	61
E.4.2.1	General.....	61
E.4.2.2	Active mode.....	61
E.4.2.3	Test mode.....	61
E.4.3	Synchronization.....	62
E.4.3.1	General.....	62
E.4.3.2	Active mode.....	62
E.4.3.3	Test transmission	62
E.4.4	UTC.....	62
E.4.4.1	General.....	62
E.4.4.2	UTC parameters storage	63
E.4.5	Required settings	63
E.4.6	Minimum transmitter performance characteristics	63
E.4.7	VHF Data Link (VDL) Access.....	64
E.4.7.1	General.....	64
E.4.7.2	Active mode.....	64
E.4.7.3	Test mode.....	65
E.5	Position indication.....	65
E.6	Power source	65
E.7	Own vessel MMSI	65
Annex F (informative): Grey-box testing of class M MSLDs.....		66
F.1	Definitions.....	66
F.2	Test interface.....	66
F.3	Test modes.....	66
F.3.1	Supported Modes.....	66
F.3.2	DSC Receiver test mode.....	67
Annex G (informative): Maximum Measurement Uncertainty.....		68
Annex H (informative): Checklist		69
Annex I (informative): Change History		70

History	71
---------------	----

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ETSI EN 303 132 V2.1.0 \(2022-08\)](https://standards.iteh.ai/catalog/standards/sist/2754e59d-c679-4e3c-9e36-6d3dcefa80c9/etsi-en-303-132-v2-1-0-2022-08)

<https://standards.iteh.ai/catalog/standards/sist/2754e59d-c679-4e3c-9e36-6d3dcefa80c9/etsi-en-303-132-v2-1-0-2022-08>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This final draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ETSI EN 303 132 V2.1.0 \(2022-08\)](#)

<https://standards.iteh.ai/catalog/standards/sist/2754e59d-c679-4e3c-9e36-6d3dcefa80c9/etsi-en-303-132-v2-1-0-2022-08>

1 Scope

The present document specifies technical characteristics and methods of measurements for Maritime Survivor Locating Devices (MSLDs) (man overboard devices) employing class M DSC signalling and AIS position locating signalling according to ETSI EN 300 338-6 [1], on the VHF maritime channels 70, AIS 1 and AIS 2.

Class M MSLD (man overboard devices) are included in group A Autonomous Maritime Radio Devices (AMRDs) according to Recommendation ITU-R M.2135.0 [i.6]. The present document incorporates the relevant provisions of the International Telecommunication Union (ITU) radio regulations [i.4] included in Recommendation ITU-R M.493-15 [2] and Recommendation ITU-R M.1371-5 [i.7].

The present document does not provide technical requirements for conformance with the essential requirements of Directive 2014/53/EU [i.1] for any integrated GNSS receiver providing locating function.

NOTE: The relationship between the present document and essential requirements of article 3.2 and 3.3(g) of Directive 2014/53/EU [i.1] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 338-6 (V1.2.1) (06-2020): "Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 6: Class M DSC".
- [2] Recommendation ITU-R M.493-15 (01-2019): "Digital selective-calling system for use in the maritime mobile service".
- [3] ETSI TS 103 052 (V1.1.1) (03-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [4] Recommendation ITU-T O.153 (10-1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [5] IEC 60945 (2002 with COR1:2008): "Maritime Navigation and Radiocommunication Equipment and Systems - General Requirements - Methods of Testing and Required Test Results".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] ETSI EG 203 336 (V1.2.1): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.4] ITU-R Radio Regulations (2020).
- [i.5] ETSI TS 101 570-6 (V1.1.1): "Interoperability Testing for Maritime Digital Selective Calling (DSC) Radios; Part 6: VHF Class M Test Descriptions".
- [i.6] Recommendation ITU-R M.2135.0 (10/2019): "Technical characteristics of autonomous maritime radio devices operating in the frequency band 156-162.05 MHz".
- [i.7] Recommendation ITU-R M.1371-5 (02/2014): "Technical characteristics for an automatic identification system using time-division multiple access in the VHF maritime mobile band".
- [i.8] Recommendation ITU-R M.585-8 (10/2019): "Assignment and use of identities in the maritime mobile service".
- [i.9] IMO Annex 11 - Resolution MSC.149 (77) - (adopted on 3 June 2003): "Adoption of the revised performance standards for survival craft portable two-way VHF radiotelephone apparatus".
- [i.10] EUROCAE ED-14G: "Environmental conditions and test procedures for airborne equipment".
- [i.11] IEC EN 60068-2-64:2008/A1:2019 "Environmental testing - Part 2-64: Tests - Test Fh: Vibration, broadband random and guidance".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

acknowledged: automated procedure it indicates that the objective of the initial DSC message has been achieved

activation: initial triggering of an MSLD i.e. both parts of the two-step procedure are performed

active mode: activated mode, transmitting in an emergency situation

closed loop: individual transmission to own vessel

dedicated antenna: removable antenna supplied and tested with the equipment, designed as an indispensable part of the equipment

default: value selected or an action taken by the equipment software in the absence of any operator input

distress alert: name given to the single distress DSC message with the format symbol 112

distress DSC message: DSC message or acknowledgement containing the distress information

distress information: symbols within a DSC message describing a distress situation consisting of the MMSI of the vessel in distress, the nature of distress, the position of the vessel in distress, the UTC time of that position and the mode of subsequent communication

factory default: default value that is set by the manufacturer such that the field or behaviour is defined prior to any operator intervention

information characters: set of symbols in a DSC message that contains the items of interest for the recipient and is used to compute the ECC symbol that terminates the message

integral antenna: antenna designed to be connected to the equipment without the use of a 50 Ω external connector and considered to be part of the equipment

NOTE: An integral antenna may be fitted internally or externally to the equipment.

non distress DSC message: DSC messages or acknowledgements that do not have the format specifier or category of "distress"

open loop: transmitting to all ships (broadcast)

personal floatation device: buoyancy aid, life jacket or vest worn by person

symbol (as part of the DSC sentence): 7 binary bits of a 10 bit DSC word that have the information content

test mode: self-testing mode, an individual test call to own vessel

UTC lock: GNSS has precisely locked to UTC so that it can determine SOTDMA slot timing correctly

UTC parameters: "Coordinated Universal Time (UTC) offset parameters" GNSS data that contains leap second offset information

word (as part of the DSC sentence): used to describe the 10 binary bits that make up the coded entities of a transmitted DSC message

NOTE: The 10 bits consist of a 7 bit "symbol" that gives the information content and 3 bit error check that gives the number of 0 binary bits in the 7 bit symbol.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

cSt	centi-Stokes
dB	decibel
dBc	Decibels referenced to the carrier power
dBm	Decibels referenced to 1 milliwatt
dB μ V	dB refence to 1 μ V (e.m.f)
GHz	GigaHertz
kHz	kiloHertz
MHz	MegaHertz
ms	milliseconds
mW	milliWatts
nW	NanoWatts
P _{Norm}	conducted power measured under normal conditions
P ₋₂₀	conducted power measured at the lower extreme temperature
P ₊₅₅	conducted power measured at the upper extreme temperature
pps	pulses per second
μ T	microtesla
μ W	MicroWatts

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AIS	Automatic Identification System
AMRD	Autonomous Maritime Radio Device
CIRM	Comité International Radio-Maritime
COG	Course Over Ground
CRC	Cyclic Redundancy Check
CSP	Channel SPacing
DSC	Digital Selective Calling
EIRP	Effective Isotropic Radiated Power
EN	European Norm
ERP	Effective Radiated Power
EUT	Equipment Under Test
FSK	Frequency Shift Keying
FM	Frequency Modulation
GLONASS	GLOBAL NAVIGATION Satellite System
GMDSS	Global Maritime Distress and Safety System
GMSK	Gaussian Minimum Shift Keying
GNSS	Global Navigation Satellite System
GPS	Global Positioning System
ID	Identity
IERS	International Earth Reference and Rotation System Service
IMO	International Maritime Organization
LBT	Listen Before Talk
MMSI	Maritime Mobile Service Identity
MOB	Man Over-Board
MSC	Maritime Safety Committee
MSLD	Maritime Survivor Locating Device
NRZI	Non Return to Zero, Inverted
OOB	Out Of Band
RAIM	Receiver Autonomous Integrity Monitoring
RBW	Reference BandWidth
RF	Radio Frequency
SINAD	(Signal+Noise+Distortion) to (Noise + Distortion)
SOG	Speed Over Ground
SOTDMA	Self-Organized Time Division Multiple Access
TDMA	Time Division Multiple Access
UTC	Coordinated Universal Time
VDL	VHF Data Link
VHF	Very High Frequency
VSWR	Voltage Standing Wave Ratio

4 Requirements that can be visually inspected

4.0 Compliance

Compliance to the requirements of this clause (clause 4) shall be achieved by inspection of the supplied user documentation and by simple inspection of the equipment.

4.1 Construction

4.1.1 General

The exterior of the equipment should have no sharp edges or projections that could easily damage inflatable rafts or injure personnel so as to minimize the risk of internal and external damage during use or stowage.

The equipment shall be portable and be designed as one integral unit. The MSLD shall derive its energy from a battery forming a part of the equipment and incorporate a permanently attached antenna or a detachable antenna that is supplied with the equipment for fitting in a personal floatation device. At least 50 % of the equipment shall be of highly visible yellow or orange colour to assist visual location.

4.1.2 Categories of equipment

Two categories are defined:

- Category 1 MSLDs with sufficient positive buoyancy to float in fresh water (see clause 7.9 for the buoyancy test).
- Category 2 MSLDs intended to be incorporated into or attached to a buoyancy aid (personal floatation device) are not required to float.

Category 1 MSLDs that can float free may have a lanyard to attach them to a person or personal floatation device. Where a lanyard is employed it should meet the requirements of IMO MSC 149(77) [i.9], paragraph 2.3.11. The user manual or instructions shall include necessary information to allow the user to properly attach the lanyard.

The user manual or instructions for Category 2 MSLDs shall include necessary information to allow the user to fit or attach the MSLD to a personal floatation device.

4.2 Controls

The equipment shall be initially activated by the use of two simple, but independent mechanical actions, neither of which on its own shall activate the equipment. If the second mechanical action is replaced by an immersion sensor, then the first mechanical action should be an arming or enabling function thus to ensure the MSLD is armed for automatic activation when submerged.

It should only be possible to activate the equipment after a seal or other mechanical restraint has been removed from the first mechanical action. After activation it shall be simple to de-activate the equipment and the means to deactivate the equipment shall be clearly marked. It should be possible to determine that the equipment has been previously activated, either by the absence of a seal or restraint or by a non-resettable electronic circuit by providing a clear optical indication for the user.

The switch that operates any test facility shall be so designed that it returns automatically to the off-position when released.

4.3 Indicators

4.3.1 General

The equipment shall be provided with visual indications to show the operation of the MSLD as specified in clause 4.3.2.

The equipment may also be provided with audible indications that show the operation of the MSLD.

4.3.2 Visual indicators

4.3.2.1 Alarm indicators

The visual indicator shall clearly distinguish the following states with each indicator being described in the user manual:

- i) The MSLD has been activated and is transmitting in active mode.
- ii) The MSLD has GNSS position lock and is transmitting in active mode.
- iii) The MSLD has received a DSC acknowledgement and the DSC transmitter has been deactivated remotely.
- iv) The MSLD is idle and has been deactivated locally.