

ETSI EN 303 132 V2.1.1 (2022-10)



**Maritime VHF survivor locating devices employing Digital
Selective Calling (DSC Class M);
Harmonised Standard for access to radio spectrum and
for features for emergency services**

[ETSI EN 303 132 V2.1.1 \(2022-10\)](https://standards.iteh.ai/catalog/standards/sist/2754e59d-c679-4e3c-9e36-6d3dcefa80c9/etsi-en-303-132-v2-1-1-2022-10)

<https://standards.iteh.ai/catalog/standards/sist/2754e59d-c679-4e3c-9e36-6d3dcefa80c9/etsi-en-303-132-v2-1-1-2022-10>

ReferenceREN/ERM-TGMAR-605

Keywordsharmonised standard, maritime, radio, SAR, testing

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.
All rights reserved.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definition of terms, symbols and abbreviations.....	11
3.1 Terms.....	11
3.2 Symbols.....	12
3.3 Abbreviations	13
4 Requirements that can be visually inspected.....	13
4.0 Compliance	13
4.1 Construction.....	13
4.1.1 General.....	13
4.1.2 Categories of equipment	14
4.2 Controls	14
4.3 Indicators	14
4.3.1 General.....	14
4.3.2 Visual indicators	14
4.3.2.1 Alarm indicators.....	14
4.3.2.2 Test indicators	15
4.4 Self ID	15
4.5 Labelling.....	15
5 Technical information	15
5.1 Alerting and locating functions	15
5.2 Technical annexes	16
6 General conditions of measurement	16
6.1 Conformity testing.....	16
6.2 Unique identifier (self ID).....	16
6.3 Artificial Antenna	16
6.3.1 For equipment with an integral antenna.....	16
6.3.2 For testing the RF transmitter output.....	16
6.3.3 For testing the DSC RF receiver input.....	16
6.4 Normal DSC TX Test Modulation	17
6.4.1 Continuous B / Y state	17
6.4.2 Alternating B-Y sequence.....	17
6.4.3 Random B-Y sequence	17
6.4.4 Unmodulated carrier	17
6.5 AIS TX Test Modulation.....	17
6.5.1 Standard test signal number 1	17
6.5.2 Standard test signal number 2	17
6.5.3 Standard test signal number 3	17
6.5.4 Unmodulated carrier	17
6.6 AIS Reference timing signal	17
6.7 Standard test signals for DSC receiver testing	18
6.8 Test conditions power sources and ambient temperatures.....	18
6.8.1 Normal and extreme test conditions.....	18
6.8.2 Test power sources.....	18
6.9 Normal test conditions	18
6.9.1 Normal temperature and humidity	18
6.9.2 Normal test voltage.....	18
6.10 Extreme test conditions	18
6.10.1 Extreme temperatures	18

6.10.2	Extreme test voltages.....	19
6.10.2.1	Upper extreme test voltage.....	19
6.10.2.2	Lower extreme test voltage.....	19
6.11	Reference Bandwidths for emission measurements.....	19
7	Environmental tests.....	19
7.1	Introduction.....	19
7.2	Procedure.....	19
7.3	Performance check.....	20
7.4	Drop test.....	20
7.4.1	Definition.....	20
7.4.2	Test conditions.....	20
7.4.3	Method of measurement.....	20
7.4.4	Required results.....	20
7.5	Temperature tests.....	21
7.5.1	Definition.....	21
7.5.2	Dry heat test.....	21
7.5.2.1	Method of measurement.....	21
7.5.2.2	Requirements.....	21
7.5.3	Damp heat test.....	21
7.5.3.1	Method of measurement.....	21
7.5.3.2	Required results.....	21
7.5.4	Low temperature test.....	22
7.5.4.1	Method of measurement.....	22
7.5.4.2	Required results.....	22
7.5.5	Low temperature battery endurance test.....	22
7.5.5.1	Method of measurement.....	22
7.5.5.2	Required results.....	22
7.6	Vibration test.....	22
7.6.1	Definition.....	22
7.6.2	Method of measurement.....	22
7.6.3	Required results.....	23
7.7	Saltwater spray test.....	23
7.7.1	Definition.....	23
7.7.2	Method of measurement.....	23
7.7.2.1	The spraying apparatus.....	23
7.7.2.2	Preparation of EUT.....	24
7.7.2.3	Test cycles.....	24
7.7.2.4	Conclusion of testing.....	24
7.7.3	Required results.....	24
7.8	Thermal shock test.....	24
7.8.1	Definition.....	24
7.8.2	Method of measurement.....	24
7.8.3	Required results.....	25
7.9	Buoyancy test.....	25
7.9.1	Definition.....	25
7.9.2	Method of measurement.....	25
7.9.3	Required results and limit.....	25
7.10	Protection of the transmitter.....	25
7.10.1	Definition.....	25
7.10.2	Method of measurement.....	25
7.10.3	Required results.....	25
8	Tests on the DSC transmitter.....	26
8.1	DSC Frequency error.....	26
8.1.1	Definition.....	26
8.1.2	Method of measurement.....	26
8.1.3	Limit.....	26
8.2	DSC Conducted power variation.....	26
8.2.1	Purpose.....	26
8.2.2	Definition.....	26
8.2.3	Method of measurement.....	26
8.2.4	Limit.....	26

8.3	Effective Radiated Power (ERP).....	27
8.3.1	Definition.....	27
8.3.2	Method of measurement.....	27
8.3.3	Limits.....	27
8.4	DSC Adjacent channel power.....	27
8.4.1	Definition.....	27
8.4.2	Method of measurement.....	28
8.4.3	Limit.....	28
8.5	DSC Transmitter transient frequency behaviour.....	28
8.5.1	Definition.....	28
8.5.2	Method of measurement.....	29
8.5.3	Limit.....	32
8.6	Frequency error (demodulated DSC signal).....	32
8.6.1	Definition.....	32
8.6.2	Method of measurement.....	32
8.6.3	Limit.....	32
8.7	Modulation index for DSC.....	32
8.7.1	Definition.....	32
8.7.2	Method of measurement.....	32
8.7.3	Limit.....	33
8.8	Modulation rate for DSC.....	33
8.8.1	Definition.....	33
8.8.2	Method of measurement.....	33
8.8.3	Limit.....	33
8.9	Spurious emissions.....	33
8.9.1	Definition.....	33
8.9.2	Method of measurement.....	33
8.9.3	Limit.....	34
9	Tests on the AIS transmitter.....	34
9.1	AIS Frequency error.....	34
9.1.1	Definition.....	34
9.1.2	Method of measurement.....	34
9.1.3	Limit.....	34
9.2	AIS Conducted power variation.....	34
9.2.1	Purpose.....	34
9.2.2	Definition.....	34
9.2.3	Method of measurement.....	34
9.2.4	Limit.....	35
9.3	AIS Transmitter spectrum mask.....	35
9.3.1	Definition.....	35
9.3.2	Method of measurement.....	35
9.3.3	Limit.....	36
9.4	AIS Transmitter transient behaviour (output power).....	36
9.4.1	Definition.....	36
9.4.2	Method of measurement.....	37
9.4.3	Limit.....	38
9.5	AIS Transmitter Transient Behaviour (frequency deviation).....	38
9.5.1	Definition.....	38
9.5.2	Method of measurement.....	38
9.5.3	Limit.....	38
9.6	AIS Synchronization accuracy.....	39
9.6.1	Definition.....	39
9.6.2	Method of measurement.....	39
9.6.3	Limit.....	40
10	Tests on the DSC receiver.....	40
10.1	DSC Maximum usable sensitivity.....	40
10.1.1	Definition.....	40
10.1.2	Method of measurement.....	40
10.1.3	Limit.....	40
10.2	DSC Co-channel rejection.....	40
10.2.1	Definition.....	40

10.2.2	Method of measurement	41
10.2.3	Limit.....	41
10.3	DSC Adjacent channel selectivity	41
10.3.1	Definition.....	41
10.3.2	Method of measurement	41
10.3.3	Limit.....	41
10.4	DSC Spurious response	41
10.4.1	Definition.....	41
10.4.2	Spurious response frequency calculations	42
10.4.3	Method of measurement	42
10.4.4	Limit.....	42
10.5	DSC Intermodulation response.....	42
10.5.1	Definition.....	42
10.5.2	Method of measurement	42
10.5.3	Limit.....	43
10.6	Blocking or desensitization	43
10.6.1	Definition.....	43
10.6.2	Method of measurement	43
10.6.3	Limit.....	43
10.7	DSC Minimum dynamic range.....	43
10.7.1	Definition.....	43
10.7.2	Method of measurement	43
10.7.3	Limit.....	44
11	DSC Conformance Testing	44
11.1	Active mode tests	44
11.1.1	Listen Before Talk (LBT).....	44
11.1.1.1	Method of measurement.....	44
11.1.1.2	Required Results	44
11.1.2	First closed loop distress transmissions	44
11.1.2.1	Applicability.....	44
11.1.2.2	Method of measurement.....	44
11.1.2.3	Required Results	44
11.1.3	First open loop distress transmissions.....	45
11.1.3.1	Applicability.....	45
11.1.3.2	Method of measurement.....	45
11.1.3.3	Required Results	46
11.1.4	Open loop distress repeat transmissions	46
11.1.4.1	Applicability.....	46
11.1.4.2	Method of measurement.....	47
11.1.4.3	Required Results	47
12	AIS VDL Link layer tests.....	47
12.1	Active mode tests	47
12.1.1	Method of measurement	47
12.1.2	Initialization period - Required results.....	48
12.1.3	Message content of Message 1 - Required results	48
12.1.4	Message content of Message 14 - Required results	48
12.1.5	Transmission schedule for Message 1 - Required results	49
12.1.6	Communication state of Message 1 - Required results	49
12.1.7	Transmission schedule of Message 14 - Required results.....	49
12.1.8	Transmission with lost GNSS - Required results.....	49
13	Testing for compliance with technical requirements.....	50
13.1	Environmental conditions for testing	50
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	51
Annex B (normative):	Measuring receiver for adjacent channel power measurement.....	53
B.1	Power measuring receiver specification.....	53
B.1.1	General	53
B.1.2	IF filter	53

B.1.3	Attenuation indicator.....	54
B.1.4	r.m.s. value indicator.....	54
B.1.5	Oscillator and amplifier.....	54
Annex C (normative):	Additional Test Supports	55
C.1	Float-free support	55
Annex D (informative):	AIS message bursts	56
D.1	Active mode	56
D.2	Test mode	57
D.3	Default message field values.....	58
Annex E (informative):	Technical characteristics of class M MSLDs.....	59
E.1	General	59
E.2	DSC transmission characteristics	59
E.3	DSC messages and protocols	60
E.4	AIS transmission characteristics	60
E.4.1	General	60
E.4.2	AIS messages	60
E.4.2.1	General.....	60
E.4.2.2	Active mode.....	60
E.4.2.3	Test mode.....	60
E.4.3	Synchronization.....	61
E.4.3.1	General.....	61
E.4.3.2	Active mode.....	61
E.4.3.3	Test transmission	61
E.4.4	UTC.....	61
E.4.4.1	General.....	61
E.4.4.2	UTC parameters storage	62
E.4.5	Required settings	62
E.4.6	Minimum transmitter performance characteristics	62
E.4.7	VHF Data Link (VDL) Access.....	63
E.4.7.1	General.....	63
E.4.7.2	Active mode.....	63
E.4.7.3	Test mode.....	64
E.5	Position indication.....	64
E.6	Power source	64
E.7	Own vessel MMSI	64
Annex F (informative):	Grey-box testing of class M MSLDs.....	65
F.1	Definitions.....	65
F.2	Test interface.....	65
F.3	Test modes.....	65
F.3.1	Supported Modes.....	65
F.3.2	DSC Receiver test mode.....	66
Annex G (informative):	Maximum Measurement Uncertainty.....	67
Annex H (informative):	Checklist	68
Annex I (informative):	Change History	69
History		70

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

National transposition dates

Date of adoption of this EN:	14 October 2022
Date of latest announcement of this EN (doa):	31 January 2023
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2023
Date of withdrawal of any conflicting National Standard (dow):	31 July 2024

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ETSI EN 303 132 V2.1.1 \(2022-10\)](#)

<https://standards.iteh.ai/catalog/standards/sist/2754e59d-c679-4e3c-9e36-6d3dcefa80c9/etsi-en-303-132-v2-1-1-2022-10>

1 Scope

The present document specifies technical characteristics and methods of measurements for Maritime Survivor Locating Devices (MSLDs) (man overboard devices) employing class M DSC signalling and AIS position locating signalling according to ETSI EN 300 338-6 [1], on the VHF maritime channels 70, AIS 1 and AIS 2.

Class M MSLD (man overboard devices) are included in group A Autonomous Maritime Radio Devices (AMRDs) according to Recommendation ITU-R M.2135.0 [i.6]. The present document incorporates the relevant provisions of the International Telecommunication Union (ITU) radio regulations [i.4] included in Recommendation ITU-R M.493-15 [2] and Recommendation ITU-R M.1371-5 [i.7].

The present document does not provide technical requirements for conformance with the essential requirements of Directive 2014/53/EU [i.1] for any integrated GNSS receiver providing locating function.

NOTE: The relationship between the present document and essential requirements of article 3.2 and 3.3(g) of Directive 2014/53/EU [i.1] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 338-6 (V1.2.1) (06-2020): "Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 6: Class M DSC".
- [2] Recommendation ITU-R M.493-15 (01-2019): "Digital selective-calling system for use in the maritime mobile service".
- [3] ETSI TS 103 052 (V1.1.1) (03-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [4] Recommendation ITU-T O.153 (10-1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [5] IEC 60945 (2002 with COR1:2008): "Maritime Navigation and Radiocommunication Equipment and Systems - General Requirements - Methods of Testing and Required Test Results".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] ETSI EG 203 336 (V1.2.1): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.4] ITU-R Radio Regulations (2020).
- [i.5] ETSI TS 101 570-6 (V1.1.1): "Interoperability Testing for Maritime Digital Selective Calling (DSC) Radios; Part 6: VHF Class M Test Descriptions".
- [i.6] Recommendation ITU-R M.2135.0 (10/2019): "Technical characteristics of autonomous maritime radio devices operating in the frequency band 156-162.05 MHz".
- [i.7] Recommendation ITU-R M.1371-5 (02/2014): "Technical characteristics for an automatic identification system using time-division multiple access in the VHF maritime mobile band".
- [i.8] Recommendation ITU-R M.585-8 (10/2019): "Assignment and use of identities in the maritime mobile service".
- [i.9] IMO Annex 11 - Resolution MSC.149 (77) - (adopted on 3 June 2003): "Adoption of the revised performance standards for survival craft portable two-way VHF radiotelephone apparatus".
- [i.10] EUROCAE ED-14G: "Environmental conditions and test procedures for airborne equipment".
- [i.11] IEC EN 60068-2-64:2008/A1:2019: "Environmental testing - Part 2-64: Tests - Test Fh: Vibration, broadband random and guidance".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

acknowledged: automated procedure it indicates that the objective of the initial DSC message has been achieved

activation: initial triggering of an MSLD i.e. both parts of the two-step procedure are performed

active mode: activated mode, transmitting in an emergency situation

closed loop: individual transmission to own vessel

dedicated antenna: removable antenna supplied and tested with the equipment, designed as an indispensable part of the equipment

default: value selected or an action taken by the equipment software in the absence of any operator input

distress alert: name given to the single distress DSC message with the format symbol 112

distress DSC message: DSC message or acknowledgement containing the distress information

distress information: symbols within a DSC message describing a distress situation consisting of the MMSI of the vessel in distress, the nature of distress, the position of the vessel in distress, the UTC time of that position and the mode of subsequent communication

factory default: default value that is set by the manufacturer such that the field or behaviour is defined prior to any operator intervention

information characters: set of symbols in a DSC message that contains the items of interest for the recipient and is used to compute the ECC symbol that terminates the message

integral antenna: antenna designed to be connected to the equipment without the use of a 50 Ω external connector and considered to be part of the equipment

NOTE: An integral antenna may be fitted internally or externally to the equipment.

non distress DSC message: DSC messages or acknowledgements that do not have the format specifier or category of "distress"

open loop: transmitting to all ships (broadcast)

personal floatation device: buoyancy aid, life jacket or vest worn by person

symbol (as part of the DSC sentence): 7 binary bits of a 10 bit DSC word that have the information content

test mode: self-testing mode, an individual test call to own vessel

UTC lock: GNSS has precisely locked to UTC so that it can determine SOTDMA slot timing correctly

UTC parameters: "Coordinated Universal Time (UTC) offset parameters" GNSS data that contains leap second offset information

word (as part of the DSC sentence): used to describe the 10 binary bits that make up the coded entities of a transmitted DSC message

NOTE: The 10 bits consist of a 7 bit "symbol" that gives the information content and 3 bit error check that gives the number of 0 binary bits in the 7 bit symbol.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

cSt	centi-Stokes
dB	decibel
dBc	Decibels referenced to the carrier power
dBm	Decibels referenced to 1 milliwatt
dB μ V	dB refence to 1 μ V (e.m.f)
GHz	GigaHertz
kHz	kiloHertz
MHz	MegaHertz
ms	milliseconds
mW	milliWatts
nW	NanoWatts
P _{Norm}	conducted power measured under normal conditions
P ₋₂₀	conducted power measured at the lower extreme temperature
P ₊₅₅	conducted power measured at the upper extreme temperature
pps	pulses per second
μ T	microtesla
μ W	MicroWatts

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AIS	Automatic Identification System
AMRD	Autonomous Maritime Radio Device
CIRM	Comité International Radio-Maritime
COG	Course Over Ground
CRC	Cyclic Redundancy Check
CSP	Channel SPacing
DSC	Digital Selective Calling
EIRP	Effective Isotropic Radiated Power
EN	European Norm
ERP	Effective Radiated Power
EUT	Equipment Under Test
FM	Frequency Modulation
FSK	Frequency Shift Keying
GLONASS	GLOBAL NAVigation Satellite System
GMDSS	Global Maritime Distress and Safety System
GMSK	Gaussian Minimum Shift Keying
GNSS	Global Navigation Satellite System
GPS	Global Positioning System
ID	Identity
IERS	International Earth Reference and Rotation System Service
IMO	International Maritime Organization
LBT	Listen Before Talk
MMSI	Maritime Mobile Service Identity
MOB	Man Over-Board
MSC	Maritime Safety Committee
MSLD	Maritime Survivor Locating Device
NRZI	Non Return to Zero, Inverted
OOB	Out Of Band
RAIM	Receiver Autonomous Integrity Monitoring
RBW	Reference BandWidth
RF	Radio Frequency
SINAD	(Signal+Noise+Distortion) to (Noise + Distortion)
SOG	Speed Over Ground
SOTDMA	Self-Organized Time Division Multiple Access
TDMA	Time Division Multiple Access
UTC	Coordinated Universal Time
VDL	VHF Data Link
VHF	Very High Frequency
VSWR	Voltage Standing Wave Ratio

4 Requirements that can be visually inspected

4.0 Compliance

Compliance to the requirements of this clause (clause 4) shall be achieved by inspection of the supplied user documentation and by simple inspection of the equipment.

4.1 Construction

4.1.1 General

The exterior of the equipment should have no sharp edges or projections that could easily damage inflatable rafts or injure personnel so as to minimize the risk of internal and external damage during use or stowage.

The equipment shall be portable and be designed as one integral unit. The MSLD shall derive its energy from a battery forming a part of the equipment and incorporate a permanently attached antenna or a detachable antenna that is supplied with the equipment for fitting in a personal floatation device. At least 50 % of the equipment shall be of highly visible yellow or orange colour to assist visual location.

4.1.2 Categories of equipment

Two categories are defined:

- Category 1 MSLDs with sufficient positive buoyancy to float in fresh water (see clause 7.9 for the buoyancy test).
- Category 2 MSLDs intended to be incorporated into or attached to a buoyancy aid (personal floatation device) are not required to float.

Category 1 MSLDs that can float free may have a lanyard to attach them to a person or personal floatation device. Where a lanyard is employed it should meet the requirements of IMO MSC 149(77) [i.9], paragraph 2.3.11. The user manual or instructions shall include necessary information to allow the user to properly attach the lanyard.

The user manual or instructions for Category 2 MSLDs shall include necessary information to allow the user to fit or attach the MSLD to a personal floatation device.

4.2 Controls

The equipment shall be initially activated by the use of two simple, but independent mechanical actions, neither of which on its own shall activate the equipment. If the second mechanical action is replaced by an immersion sensor, then the first mechanical action should be an arming or enabling function thus to ensure the MSLD is armed for automatic activation when submerged.

It should only be possible to activate the equipment after a seal or other mechanical restraint has been removed from the first mechanical action. After activation it shall be simple to de-activate the equipment and the means to deactivate the equipment shall be clearly marked. It should be possible to determine that the equipment has been previously activated, either by the absence of a seal or restraint or by a non-resettable electronic circuit by providing a clear optical indication for the user.

The switch that operates any test facility shall be so designed that it returns automatically to the off-position when released.

4.3 Indicators

4.3.1 General

The equipment shall be provided with visual indications to show the operation of the MSLD as specified in clause 4.3.2.

The equipment may also be provided with audible indications that show the operation of the MSLD.

4.3.2 Visual indicators

4.3.2.1 Alarm indicators

The visual indicator shall clearly distinguish the following states with each indicator being described in the user manual:

- i) The MSLD has been activated and is transmitting in active mode.
- ii) The MSLD has GNSS position lock and is transmitting in active mode.
- iii) The MSLD has received a DSC acknowledgement and the DSC transmitter has been deactivated remotely.
- iv) The MSLD is idle and has been deactivated locally.

4.3.2.2 Test indicators

In addition the visual indicator should also clearly distinguish the following states:

- i) The MSLD is undergoing test and is transmitting in test mode.
- ii) The MSLD cannot complete a test because it has not been properly programmed with own vessel MMSI (for closed loop devices only).
- iii) The MSLD cannot complete a test because it could not obtain a GNSS position.
- iv) The MSLD has received a test acknowledgement as defined in Recommendation ITU-R M.493-15 [2] table A1-4.7 (a momentary indication each time a test acknowledgement is received during testing to clause 10).

4.4 Self ID

MSLDs shall have a freeform number identity (self ID) to distinguish them from other DSC devices.

The self ID for an MSLD is 972xxyyyy, where xx = manufacturer ID 01 to 99; yyyy = the sequence number 0000 to 9999 allocated by the manufacturer as specified in Recommendation ITU-R M.585-8 [i.8], section 2.2 of annex 2. Manufacturers IDs are issued by CIRM (www.cirm.org). Manufacturers shall only use manufacturer IDs that have been issued to them by CIRM, except for training and conformance testing purposes where the ID xx = 00 can be used.

The self ID is tested in clause 12.

After being programmed by the manufacturer, it should not be possible for the user to change the self ID of an MSLD.

4.5 Labelling

The MSLD shall be provided with a label, or labels, permanently affixed to the exterior of the equipment, containing the following information:

- Self ID of the equipment (see clause 4.4).
- Open loop devices shall be marked DSC-MOB-O.
- Closed loop devices shall be marked DSC-MOB-C.
- Adequate instructions to enable the equipment to be activated and deactivated.
- The type of battery as specified by the manufacturer of the MSLD.
- A warning to not block the GNSS antenna.
- The compass safe distance as measured in clause 11.2 of IEC 60945 [5].
- A warning to the effect that the MSLD should not be operated except in an emergency.
- The date on which the battery will need to be replaced (the expiry date of the battery).

5 Technical information

5.1 Alerting and locating functions

Class M MSLDs shall contain:

- i) a DSC transmitter operating on maritime VHF channel 70 (156,525 MHz) for the alerting function;
- ii) a DSC receiver listening to channel 70 to allow the device to be remotely deactivated;