

ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

ISO RECOMMENDATION R 1999

ACOUSTICS

ASSESSMENT OF OCCUPATIONAL NOISE EXPOSURE
FOR HEARING CONSERVATION PURPOSES

1st EDITION

May 1971

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

BRIEF HISTORY

The ISO Recommendation R 1999, *Acoustics – Assessment of occupational noise exposure for hearing conservation purposes*, was drawn up by Technical Committee ISO/TC 43, *Acoustics*, the Secretariat of which is held by the British Standards Institution (BSI).

Work on this question led to the adoption of Draft ISO Recommendation No. 1999, which was circulated to all the ISO Member Bodies for enquiry in May 1970. It was approved, subject to a few modifications of an editorial nature, by the following Member Bodies :

Austria	Greece	Sweden
Belgium	Hungary	Switzerland
Canada	Ireland	U.A.R.
Czechoslovakia	Netherlands	United Kingdom
Denmark	New Zealand	U.S.A.
France	Norway	U.S.S.R.
Germany	South Africa, Rep. of	

The following Member Body opposed the approval of the Draft :

Japan

This Draft ISO Recommendation was then submitted by correspondence to the ISO Council, which decided to accept it as an ISO RECOMMENDATION.

FOREWORD

The human hearing mechanism can be impaired by noise exposure. The degree of impairment depends on the noise level and duration as well as on the sensitivity of the individual.

In many cases permanent impairment of hearing due to noise exposure develops over years resulting in a severe hearing loss greatly affecting the faculty of communication by speech.

This ISO Recommendation results from the need for methods by which the risk for noise-induced impairment of hearing can be estimated. The existence of such methods will make it easier for interested bodies to set up limits for tolerable noise exposure during work and for the institution of hearing conservation programmes.

Emphasis is put on a simple but sufficiently reliable method for sound measurement, a method which can be used also by people without special acoustical knowledge.

The complicated problems connected with the effect of recovery periods within the working day have been considered, but it was felt that further research and consideration were necessary before simple rules applicable to such effects could be established. Similar remarks also apply to some types of impulsive noise.

ISO Recommendation

R 1999

May 1971

ACOUSTICS

ASSESSMENT OF OCCUPATIONAL NOISE EXPOSURE FOR HEARING CONSERVATION PURPOSES

INTRODUCTION

This ISO Recommendation gives a practical relation between noise exposure, expressed in terms of noise level and duration, and the percentage of people that may be expected to show hearing impairment solely as a result of occupational noise exposure.

Hearing impairment can be expressed, for many purposes, in terms of threshold shift at various frequencies. In most cases, however, the previous audiometric history is not available, so that prescriptions in terms of hearing level are necessary. Thus, for the retention of the faculty to understand conversational speech, a limit may be set to the permitted hearing level at frequencies of importance for the intelligibility of speech.

In this ISO Recommendation the recommendations and data are based primarily on the impairment criterion that hearing is considered impaired if the arithmetic average of the permanent threshold shifts for the three frequencies 500, 1000 and 2000 Hz is 25 dB or more.

It is appreciated that for some purposes it may be necessary to widen the frequency range over which the hearing levels are averaged and to vary the criterion for the hearing level.

The manner in which noise exposure is related to hearing impairment, for the purpose of this ISO Recommendation, is through the concept of "risk", defined below, this being an expression of the probability that exposed persons will acquire a specified degree of hearing impairment.

The levels and durations of the noises concerned are measured and an additive index is assigned to each. The sum of these indices is converted to a continuous noise level considered to be equally hazardous to hearing. A table is given to show the percentage of workers for which impairment of hearing according to the above impairment criterion will occur solely as a result of exposure to this noise during normal working time in periods of up to 45 years, the effects of age also being taken into account. Therefore, this ISO Recommendation provides a basis for the fixing of tolerable limits for noise exposure under working conditions by appropriate bodies.

It should be emphasized that if noise control methods are necessary in order to keep the exposure below fixed limits, more complicated measurements than those described in the main body of this ISO Recommendation may be necessary. An example of this is given in the Appendix.

1. SCOPE

This ISO Recommendation gives a practical relation between occupational noise exposure, expressed in terms of A-weighted sound level in dB (commonly called dB (A)) and duration within a normal working week (assumed to be 40 hours), and the percentage of the workers that may be expected to exhibit an increased threshold of hearing amounting to 25 dB or more averaged over the three frequencies 500, 1000 and 2000 Hz solely as a result of the noise exposure.

It is not applicable to impulsive noises consisting of noise of a duration less than 1 second or single high-level transients of a very short duration, for example, from gunfire.

2. DEFINITIONS

- 2.1 *Partial noise exposure index*. An index determined by a sound level and its duration within a working week (40 hours).
- 2.2 *Composite noise exposure index*. The sum of partial noise exposure indices for all relevant sound levels over a working week (40 hours).
- 2.3 *Equivalent continuous sound level*. That sound level in dB (A) which, if present for 40 hours in one week, produces the same composite noise exposure index as the various measured sound levels over 1 week.
- 2.4 *Impairment of hearing for conversational speech*. The hearing of a subject is considered to be impaired if the arithmetic average of the permanent threshold hearing levels of the subject for 500, 1000 and 2000 Hz is shifted by 25 dB or more compared with the corresponding average given in ISO Recommendation R 389, *Standard reference zero for the calibration of pure-tone audiometers*.
- 2.5 *Risk*. The difference between the percentage of people with impaired hearing in a noise-exposed group and the percentage of people with impaired hearing in a non-noise-exposed (but otherwise equivalent) group.
- 2.6 *Risk of hearing impairment for conversational speech*. The particular value of risk when the impairment of hearing in question is as described in clause 2.4.

3. NOISE MEASUREMENTS

The sound level at the approximate position occupied by the listener's ear (but preferably with the listener absent) should be determined over an appropriate time and expressed in dB (A).

If the sound level averaged over a short time (i.e. several seconds or minutes) is almost unchanged within a week or varies in a regular manner among a few clearly distinguishable levels, the measurements may be made with a sound level meter with A-weighting set at "slow" response. The meter should be in accordance with IEC Publication 123, *Recommendations for sound level meters*, or IEC Publication 179, *Precision sound level meters*.

In other cases a statistical analysis of the noise level over a typical period should be made with automatic recording equipment having a performance which equates with the sound level meter used under similar conditions.

In either of these cases, the occurring noise levels should be grouped in classes with a width of 5 dB each. The level and total duration within a week should be recorded for each class.

Noises for which the sound level is less than 80 dB (A) may be disregarded, if there are no corrections to be added in accordance with section 5 of this ISO Recommendation. If corrections are necessary, this rule applies to the corrected value.

4. CALCULATION OF EQUIVALENT CONTINUOUS SOUND LEVEL FOR NON-IMPULSIVE SOUND THAT IS INTERMITTENT OR FLUCTUATING

Step 1. The total duration during 1 week of each sound level is entered at the first column of Table 1 and the partial noise exposure index read at the intersection with the appropriate sound level.

If the total weekly duration is less than 10 minutes, the minimum value of 10 minutes should be used.

Step 2. The arithmetical sum of the partial noise exposure indices so obtained is the composite noise exposure index.

Step 3. Enter this value of composite noise exposure index in Table 2 and read off the equivalent continuous sound level.

TABLE 1 - Partial noise exposure indices for sound levels 80 to 120 dB (A) and duration 10 minutes to 40 hours per week

Duration per week		Partial noise exposure indices								
		Sound level in dB (A) (Class midpoint)								
hours	minutes	80	85	90	95	100	105	110	115	120
	10					5	15	40	130	415
	12					5	15	50	160	500
	14					5	20	60	185	585
	16					5	20	65	210	665
	18					10	25	75	235	750
	20					10	25	85	265	835
	25				5	10	35	105	330	1 040
	30				5	15	40	125	395	1 250
	40				5	15	55	165	525	1 670
	50				5	20	70	210	660	2 080
	60			5	10	25	80	250	790	2 500
	70			5	10	30	90	290	920	2 920
	80			5	10	35	105	330	1 050	3 330
	90			5	10	40	120	375	1 190	3 750
	100			5	15	40	130	415	1 320	4 170
2				5	15	50	160	500	1 580	5 000
2.5				5	20	65	200	625	1 980	6 250
3				10	25	75	235	750	2 370	7 500
3.5			5	10	30	90	275	875	2 770	8 750
4			5	10	30	100	315	1 000	3 160	10 000
5			5	15	40	125	395	1 250	3 950	12 500
6			5	15	45	150	475	1 500	4 740	15 000
7			5	20	55	175	555	1 750	5 530	17 500
8			5	20	65	200	630	2 000	6 320	20 000
9			5	25	70	225	710	2 250	7 110	22 500
10		5	10	25	80	250	790	2 500	7 910	25 000
12		5	10	30	95	300	950	3 000	9 490	30 000
14		5	10	35	110	350	1 110	3 500	11 100	
16		5	15	40	125	400	1 260	4 000	12 600	
18		5	15	45	140	450	1 420	4 500	14 200	
20		5	15	50	160	500	1 580	5 000	15 800	
25		5	20	65	200	625	1 980	6 250	19 800	
30		10	25	75	235	750	2 370	7 500	23 700	
35		10	30	90	275	875	2 770	8 750	27 700	
40		10	30	100	315	1 000	3 160	10 000	31 600	

The values are calculated from the formula :

$$E_i = \frac{\Delta t_i}{40} 10^{0.1 (L_i - 70)}$$

where

E_i is the partial noise exposure index;

L_i is the sound level A in dB corresponding to the midpoint of the class i ;

Δt_i is the total duration in hours per week of sound levels within the class i .

TABLE 2 – Relation between composite noise exposure index and equivalent continuous sound level

Composite noise exposure index	Equivalent continuous sound level, dB (A)
10	80
15	82
20	83
25	84
30	85
40	86
50	87
60	88
80	89
100	90
125	91
160	92
200	93
250	94
315	95
400	96
500	97
630	98
800	99
1 000	100
1 250	101
1 600	102
2 000	103
2 500	104
3 150	105
4 000	106
5 000	107
6 300	108
8 000	109
10 000	110
12 500	111
16 000	112
20 000	113
25 000	114
31 500	115

The values are calculated from the formula

$$L_{eq} = 70 + 10 \log_{10} \Sigma E_i$$

where

L_{eq} is the equivalent continuous sound level in dB (A);

E_i is the partial noise exposure index (from Table 1).

5. CALCULATION OF EQUIVALENT CONTINUOUS SOUND LEVEL OF QUASI-STABLE IMPULSIVE NOISE

The method described in this ISO Recommendation is not applicable to impulsive noises consisting of single bursts of noise of a duration less than 1 second or single high-level transients of a very short duration, for example, from gunfire.

However, for impulsive noise consisting of series of noise bursts of approximately equal amplitudes (for example, noise from rapidly repeated hammering or riveting) an approximation to the partial noise exposure index may be based on a value 10 dB (A) higher than the measured sound level.

A more precise definition of the cases where a correction should be applied is desirable, but this problem can only be solved when the results of further research become available.

6. ESTIMATION OF RISK INVOLVED

Table 3 gives, in the upper row (*a*) of each entry, the risk of hearing impairment for conversational speech (as defined in clause 2.6) as a function of equivalent sound level and years of exposure during working hours, on the assumption of a 40 hour week and 50 weeks per year. In the lower row (*b*) of each entry, it also gives the total percentage of people with impaired hearing in a noise-exposed group. For information, the case of $L_{eq} \leq 80$ dB (A) is included, the lower row (*b*) being the percentage of persons with impaired hearing in a non-noise-exposed group; this value is equal to the difference between corresponding table entries (*b*) and (*a*) for any noise-exposed group. The percentages are rounded off to the nearest integer.

NOTES

1. Limits for tolerable noise exposure during work may be set by competent authorities who generally demand the institution of hearing conservation programmes if the limits are exceeded. In many cases, 85 to 90 dB (A) equivalent continuous sound level has been chosen.
2. Corresponding tables of risk may be constructed by the competent authorities for risks other than that defined in clause 2.6, as data become available.

TABLE 3

- (a) Relation between equivalent continuous sound level during work in 0 to 45 years and risk of hearing impairment for conversational speech.
- (b) Total percentage of people with impaired hearing in a noise-exposed group. (Percentage of people with impaired hearing in a non-noise-exposed group is equal to percentage in a group exposed to continuous sound levels below 80 dB (A).)

(Years of exposure = Age - 18 years)

Equivalent continuous sound level dB (A)	Risk, %, or Total % with impaired hearing		Percentages										
			Years of exposure										
			0	5	10	15	20	25	30	35	40	45	
≤ 80	(a)	Risk, %	0	0	0	0	0	0	0	0	0	0	0
	(b)	Total % with impaired hearing	1	2	3	5	7	10	14	21	33	50	
85	(a)	Risk, %	0	1	3	5	6	7	8	9	10	7	
	(b)	Total % with impaired hearing	1	3	6	10	13	17	22	30	43	57	
90	(a)	Risk, %	0	4	10	14	16	16	18	20	21	15	
	(b)	Total % with impaired hearing	1	6	13	19	23	26	32	41	54	65	
95	(a)	Risk, %	0	7	17	24	28	29	31	32	29	23	
	(b)	Total % with impaired hearing	1	9	20	29	35	39	45	53	62	73	
100	(a)	Risk, %	0	12	29	37	42	43	44	44	41	33	
	(b)	Total % with impaired hearing	1	14	32	42	49	53	58	65	74	83	
105	(a)	Risk, %	0	18	42	53	58	60	62	61	54	41	
	(b)	Total % with impaired hearing	1	20	45	58	65	70	76	82	87	91	
110	(a)	Risk, %	0	26	55	71	78	78	77	72	62	45	
	(b)	Total % with impaired hearing	1	28	58	76	85	88	91	93	95	95	
115	(a)	Risk, %	0	36	71	83	87	84	81	75	64	47	
	(b)	Total % with impaired hearing	1	38	74	88	94	94	95	96	97	97	

NOTE. - These values are based on the limited experimental data available at this time and are liable to revision when the results of further research become available.