

ETSI EN 300 019-2-7 V3.1.1 (2024-09)



**Environmental Engineering (EE);
Environmental conditions and environmental tests
for telecommunications equipment;
Part 2: Specification of environmental tests;
Sub-part 7: Portable and non-stationary use**

[ETSI EN 300 019-2-7 V3.1.1 \(2024-09\)](https://standards.iteh.ai/catalog/standards/etsi/9d5c655b-e4df-4235-be55-feb6d5664e33/etsi-en-300-019-2-7-v3-1-1-2024-09)

<https://standards.iteh.ai/catalog/standards/etsi/9d5c655b-e4df-4235-be55-feb6d5664e33/etsi-en-300-019-2-7-v3-1-1-2024-09>

Reference

REN/EE-017007

Keywords

environment, mobile, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
ETSI [Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword.....	4
Modal verbs terminology.....	4
1 Scope	5
2 References	5
2.1 Normative references	5
2.2 Informative references.....	6
3 Definition of terms, symbols and abbreviations.....	6
3.1 Terms.....	6
3.2 Symbols.....	6
3.3 Abbreviations	6
4 Environmental test specifications.....	6
4.0 General	6
4.1 Equipment setup and configuration.....	7
4.2 Performance criteria	7
4.3 Specification T 7.1: temperature-controlled locations.....	7
4.4 Specification T 7.2: partly temperature-controlled locations	7
4.5 Specification T 7.3: partly weatherprotected and non-weatherprotected locations	8
4.6 Specification T 7.3E: partly weatherprotected and non-weatherprotected locations - extended	8
4.7 Specification T 7.1: temperature-controlled locations - climatic test.....	8
4.8 Specification T 7.2: partly temperature-controlled locations - climatic test.....	11
4.9 Specification T 7.3: partly weatherprotected and non-weatherprotected - climatic test.....	14
4.10 Specification T 7.3E: partly weatherprotected and non-weatherprotected locations - extended - climatic test	17
4.11 Specification T 7.1 to T 7.3E - mechanical tests	20
Annex A (informative): Bibliography.....	22
Annex B (informative): Change history	23
History	24

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Environmental Engineering (EE).

The present document is part 2, sub-part 7 of a multi-part deliverable. Full details of the entire series can be found in part 2, sub-part 0 [i.1].

National transposition dates

Date of adoption of this EN:	12 September 2024
Date of latest announcement of this EN (doa):	31 December 2024
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2025
Date of withdrawal of any conflicting National Standard (dow):	30 June 2025

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document specifies test methods and severities for the verification of the required resistibility of telecommunication equipment according to the relevant environmental class.

The tests defined in the present document apply to portable and non-stationary use of equipment, covering the environments stated in ETSI EN 300 019-1-7 [1].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI EN 300 019-1-7 \(V2.1.4\)](#): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-7: Classification of environmental conditions; Portable and non-stationary use".
- [2] [IEC 60068-2-1 \(03-2007\)](#): "Environmental testing - Part 2-1: Tests - Test A: Cold".
- [3] [IEC 60068-2-2 \(07-2007\)](#): "Environmental testing - Part 2-2: Tests - Test B: Dry heat".
- [4] [IEC 60068-2-14:2023](#): "Environmental testing - Part 2-14: Tests - Test N: Change of temperature".
- [5] [IEC 60068-2-78 \(10-2012\)](#): "Environmental testing - Part 2-78: Tests - Test Cab: Damp heat, steady state".
- [6] [IEC 60068-2-30 \(08-2005\)](#): "Environmental testing - Part 2-30: Tests - Test Db: Damp heat, cyclic (12 h + 12 h cycle)".
- [7] [IEC 60068-2-18 \(03-2017\)](#): "Environmental testing - Part 2-18: Tests - Test R and guidance: Water".
- [8] [IEC 60068-2-64 \(2008+A1:2019\)](#): "Environmental testing - Part 2-64: Tests - Test Fh: Vibration, broadband random and guidance".
- [9] [IEC 60068-2-27 \(02-2008\)](#): "Environmental testing - Part 2-27: Tests - Test Ea and guidance: Shock".
- [10] [IEC 60068-2-31 \(05-2008\)](#): "Environmental testing - Part 2-31: Tests - Test Ec: Rough handling shocks, primarily for equipment-type specimens".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EN 300 019-2-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2: Specification of environmental tests; Sub-part 0: Introduction".
- [i.2] ETSI EN 300 019-1-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [i.3] IEC 60068-2-68 (08-1994): "Environmental testing - Part 2-68: Tests - Test L: Dust and sand".
- [i.4] IEC 60721-3-7 (10-2002): "Classification of environmental conditions - Part 3-7: Classification of groups of environmental parameters and their severities - Portable and non-stationary use".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in ETSI EN 300 019-1-0 [i.2] apply.

3.2 Symbols

For the purposes of the present document, the symbols given in ETSI EN 300 019-1-0 [i.2] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 300 019-1-0 [i.2] apply.

4 Environmental test specifications

4.0 General

The equipment shall be tested in its operational state throughout the test conditions described in the present document. The detailed descriptions of the environmental conditions are given in clauses 4 and 5 of ETSI EN 300 019-1-7 [1].

ETSI EN 300 019-2-0 [i.1] forms a general overview of part 2 of this multi-part deliverable.

4.1 Equipment setup and configuration

The equipment shall be tested in its operational state throughout the test conditions described in the present document unless otherwise stated. Input and load conditions of the equipment shall be chosen to obtain full utilization of the equipment under test. The heat dissipation shall be maximized, except for the steady state, low temperature test, where it shall be minimized.

4.2 Performance criteria

The following performance criteria shall apply in the tests defined by the present document.

Performance criterion A:

The equipment shall function according to the manufacturer specifications before, during and after the tests. No degradation of performance or loss of function is allowed below the performance level specified by the manufacturer when the apparatus is used as intended. If the minimum performance level is not specified by the manufacturer, then this may be deduced from the product description and documentation and what the user may reasonably expect from the apparatus if used as intended.

Performance criterion B:

The equipment shall function according to the manufacturer specifications before and after the tests. During the test it is not required to monitor the equipment functionality. No degradation of performance or loss of function is allowed below the performance level specified by the manufacturer when the apparatus is used as intended. If the minimum performance level is not specified by the manufacturer, then this may be deduced from the product description and documentation and what the user may reasonably expect from the apparatus if used as intended.

Performance criterion C:

The equipment shall function according to the manufacturer specifications before and after the tests. No degradation of performance or loss of function is allowed below the performance level specified by the manufacturer when the apparatus is used as intended. If the minimum performance level is not specified by the manufacturer, then this may be deduced from the product description and documentation and what the user may reasonably expect from the apparatus if used as intended.

During the application of the test, temporary loss of function is allowed but after the test the equipment shall restore to the normal functionality without replacement of components, manual rebooting or human intervention.

The equipment shall sustain the test without permanent structural or mechanical damage.

Performance criterion D:

This performance criterion applies to the enclosure of the equipment. No corrosion traces (e.g. rust) or deterioration of the enclosure shall occur at the end of the test.

4.3 Specification T 7.1: temperature-controlled locations

The tests specifications T 7.1 of the present document shall apply to equipment, depending on the selected IEC mechanical class, used at, and direct transfer between, permanently temperature-controlled and enclosed locations. Humidity is usually not controlled. See tables 1, 5 and 6.

4.4 Specification T 7.2: partly temperature-controlled locations

The tests specifications T 7.2 of the present document shall apply to equipment, depending on the selected IEC mechanical class, used at, and direct transfer between, enclosed locations having neither temperature nor humidity control. See tables 2, 5 and 6.

4.5 Specification T 7.3: partly weatherprotected and non-weatherprotected locations

The tests specifications T 7.3 of the present document shall apply to equipment, depending on the selected IEC mechanical class, used at partly weatherprotected locations in buildings of such a construction that extremely low temperatures are avoided. This class also applies to use at non-weatherprotected locations in a Warm Temperate climate and to transfer between these locations. During cold seasons non-weatherprotected use and transfer is limited. See tables 3, 5 and 6.

4.6 Specification T 7.3E: partly weatherprotected and non-weatherprotected locations - extended

The tests specifications T 7.3E of the present document shall apply to equipment, depending on the selected IEC mechanical class, used at partly weatherprotected locations in buildings of any construction - except in extremely cold and cold climates - where extremely low temperatures shall be avoided. This class also applies at non-weatherprotected locations in moderate open-air climates and to transfer between these conditions (during extremely cold days use and transfer is limited). See tables 4, 5 and 6.

4.7 Specification T 7.1: temperature-controlled locations - climatic test

This specification in table 1 shall apply to use at, and direct transfer between, permanently temperature-controlled enclosed locations where humidity is usually not controlled described in ETSI EN 300 019-1-7 [1]. See tables 1, 5 and 6.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 300 019-2-7 V3.1.1 \(2024-09\)](https://standards.iteh.ai/catalog/standards/etsi/9d5c655b-e4df-4235-be55-feb6d5664e33/etsi-en-300-019-2-7-v3-1-1-2024-09)

<https://standards.iteh.ai/catalog/standards/etsi/9d5c655b-e4df-4235-be55-feb6d5664e33/etsi-en-300-019-2-7-v3-1-1-2024-09>

Table 1: Test specification T 7.1: Temperature-controlled locations - climatic tests

Environmental parameter			Environmental Class 7.1	Environmental test specification T7.1: Portable, Temperature - controlled location						
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Performance criterion	Notes	
Air temperature	Low	(°C)	+5	+5	16 h	IEC 60068-2-1 [2]	Ab/Ad/Ae: Cold	A	1	
	High	(°C)	+40	+40 or +50	16 h	IEC 60068-2-2 [3]	Bb/Bd/Be: Dry heat	A	2	
	Change	(°C)	+5/+25	+5/+25	3 cycles t ₁ = 3 h	IEC 60068-2-14 [4]	Na: Change of temperature	A	3	
Humidity	Relative	low	(%)	5	none				4	
		high	(%)	85	93	96 h	IEC 60068-2-78 [5]	Cab: Damp heat steady state	A	5
		condensation	(°C)	+30	+30					
		(%)	yes	90-100	2 cycles	IEC 60068-2-30 [6]	Db: Damp heat Cyclic, variant 2	A	6	
Absolute	low	(g/m ²)	1	none					4	
	high	(g/m ²)	25						7	
Air	Pressure	low	(kPa)	70	none				8	
		high	(kPa)	106	none				8	
	Speed	(m/s)	5,0	none					4	
Water	Rain	intensity		no						
		low temperature		no						
	Other sources			no						
	Icing & frosting			no						
Radiation	Solar	(W/m ²)	700						9	
	Heat	(W/m ²)	600						10	
Chemically active substances	Sulphur	SO ₂	(mg/m ³)	0,3/1,0	none				11	
		H ₂ S	(mg/m ³)	0,1/0,5	none				11	
	Chlorine	salt mist		sea and road salt	none				11	
		Cl ₂	(mg/m ³)	0,1/0,3	none				11	
		HCl	(mg/m ³)	0,1/0,5	none				11	
	Nitrogen	NO _x	(mg/m ³)	0,5/1,0	none				11	
		NH ₃	(mg/m ³)	1,0/3,0	none				11	
	Hydrogen fluoride HF	(mg/m ³)	0,01/0,03	none					11	
Ozone O ₃	(mg/m ³)	0,05/0,1	none					11		
Dust	sedimentation	(mg/(m ² h))	1,5	none					12	

Environmental parameter			Environmental Class 7.1	Environmental test specification T7.1: Portable, Temperature - controlled location					
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Performance criterion	Notes
Mechanically active substances		suspension (mg/m ³)	0,2	none					12
	Sand	(mg/m ³)	30	none					12
Flora and fauna	Micro organisms		no						
	Rodents, insects		no						
no:	This condition does not occur in this class.								
none:	See corresponding note for detail on why test severity is not required.								
NOTE 1:	(Air temperature, low). The characteristic severity should be used as a cold start up temperature, but it may be modified (within the class characteristic severity range) by the product specification. In this case, the cold start up test shall commence once low temperature stability is achieved.								
NOTE 2:	(Air temperature, high). If two test temperatures are given, the lower test temperature applies if the equipment is protected against solar and heat radiation or the equipment is ventilated (natural or forced). The higher test temperature includes the heating effects of solar and/or heat radiation. If a high temperature start up test is performed, the characteristic severity should be used as a high start up temperature, but it may be modified (within the class characteristic severity range) by the product specification. In this case, the high temperature start up test shall commence once high temperature stability is achieved.								
NOTE 3:	(Air temperature, change). The change of temperature test is normally used to check design tolerancing. IEC test Na is recommended with severities equal to characteristic severities. Whenever possible, the equipment function shall be monitored throughout the test.								
NOTE 4:	(Relative humidity, low). There is no IEC 60068-2 series test method for this parameter.								
NOTE 5:	(Humidity, relative, high). IEC 60068-2-78 [5] Test Cab shall be used with test values not higher than climatogram limits for this class.								
NOTE 6:	(Condensation). IEC 60068-2-30 [6] Test Db shall be used with test values not higher than climatogram limits for this class.								
NOTE 7:	(Humidity, absolute, high). This effect is considered to be partly included in the damp heat test IEC 60068-2-78 [5] Test Cab.								
NOTE 8:	(Air pressure, low and high). No test is recommended for normal applications, because the effect of air pressure is evaluated at the component level.								
NOTE 9:	(Radiation, solar). The higher test temperature as described in note 2 includes the heating effect of solar radiation. Photochemical tests can be made separately for components and materials.								
NOTE 10:	(Radiation, heat). The higher test temperature as described in note 2 includes the heating effect.								
NOTE 11:	(Chemically active substances). The characteristic severities are given as mean/maximum values. These severities should be considered when designing the equipment and when choosing components and materials. No test is recommended in the present document.								
NOTE 12:	(Mechanically active substances). The characteristic severities are much lower than lowest test severity in IEC 60068-2-68 [i.3] Test Lb and therefore no test is recommended. This condition should be considered when designing the equipment and when choosing components and materials.								