

ETSI TS 123 401 V14.10.0 (2018-12)



TECHNICAL SPECIFICATION

LTE;
General Packet Radio Service (GPRS)
enhancements for Evolved Universal Terrestrial
Radio Access Network (E-UTRAN) access
(3GPP TS 23.401 version 14.10.0 Release 14)

PREVIEW
https://standards.iteh.ai/catalog/standards/sis/16c8eb8-4437-42ed-87ba-ac87bd8b45c/etsi-123-401-v14.10.0-2018-12



ReferenceRTS/TSGS-0223401vea0

KeywordsLTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	11
1 Scope	12
2 References	12
3 Definitions and abbreviations.....	15
3.1 Definitions	15
3.2 Abbreviations	17
4 Architecture model and concepts	18
4.1 General concepts	18
4.2 Architecture reference model	18
4.2.1 Non-roaming architecture	18
4.2.2 Roaming architecture.....	19
4.2.3 Reference points	21
4.2.4 Warning System architecture.....	22
4.3 High level functions	22
4.3.1 General.....	22
4.3.2 Network access control functions	22
4.3.2.1 General	22
4.3.2.2 Network/Access network selection.....	23
4.3.2.3 Authentication and authorisation function	23
4.3.2.4 Admission control function.....	23
4.3.2.5 Policy and Charging Enforcement Function	23
4.3.2.6 Lawful Interception.....	23
4.3.2a Support for Dual Connectivity.....	23
4.3.3 Packet routing and transfer functions.....	24
4.3.3.1 General	24
4.3.3.2 IP header compression function.....	24
4.3.3.3 Packet screening function	24
4.3.3.4 IP Multicast Forwarding between a network accessed by LIPA and a UE	24
4.3.4 Security functions	24
4.3.5 Mobility management functions	25
4.3.5.1 General	25
4.3.5.2 Reachability Management for UE in ECM-IDLE state.....	25
4.3.5.3 Tracking Area list management	26
4.3.5.4 Inter-eNodeB mobility anchor function	26
4.3.5.5 Inter-3GPP mobility anchor function.....	26
4.3.5.6 Idle mode signalling reduction function.....	27
4.3.5.7 Mobility Restrictions.....	29
4.3.5.8 IMS voice over PS Session Supported Indication.....	29
4.3.5.8A Homogenous Support of IMS Voice over PS Sessions Indication.....	29
4.3.5.9 Voice domain preference and UE's usage setting.....	30
4.3.5.10 Preferred and Supported Network Behaviour	30
4.3.6 Radio Resource Management functions	31
4.3.7 Network management functions	32
4.3.7.1 General	32
4.3.7.1a GTP-C signalling based Load and Overload Control.....	32
4.3.7.1a.1 GTP-C Load Control	32
4.3.7.1a.2 GTP-C Overload Control.....	32
4.3.7.2 Load balancing between MMEs.....	34
4.3.7.3 Load re-balancing between MMEs	34
4.3.7.4 MME control of overload.....	35
4.3.7.4.1 General	35

4.3.7.4.1a	Throttling of Downlink Data Notification Requests.....	37
4.3.7.4.1b	Throttling of NIDD Submit Requests.....	37
4.3.7.4.2	NAS level congestion control.....	37
4.3.7.5	PDN GW control of overload.....	43
4.3.8	Selection functions.....	43
4.3.8.1	PDN GW selection function (3GPP accesses).....	43
4.3.8.2	Serving GW selection function.....	45
4.3.8.3	MME selection function.....	46
4.3.8.4	SGSN selection function.....	47
4.3.8.5	Selection of PCRF.....	47
4.3.9	IP network related functions.....	47
4.3.9.1	Domain Name Service function.....	47
4.3.9.2	DHCP function.....	47
4.3.9.3	Explicit Congestion Notification.....	47
4.3.10	Functionality for Connection of eNodeBs to Multiple MMEs.....	47
4.3.11	E-UTRAN Sharing Function.....	48
4.3.12	IMS Emergency Session Support.....	48
4.3.12.1	Introduction.....	48
4.3.12.2	Architecture Reference Model for Emergency Services.....	50
4.3.12.3	Mobility and Access Restrictions for Emergency Services.....	50
4.3.12.3a	Reachability Management for UE in ECM-IDLE state.....	50
4.3.12.4	PDN GW selection function (3GPP accesses) for Emergency Services.....	50
4.3.12.5	QoS for Emergency Services.....	51
4.3.12.6	PCC for Emergency Services.....	51
4.3.12.7	Load re-balancing between MMEs for Emergency Services.....	51
4.3.12.8	IP Address Allocation.....	51
4.3.12.9	Handling of PDN Connections for Emergency Bearer Services.....	51
4.3.12.10	ISR function for Emergency Bearer Services.....	52
4.3.12.11	Support of eCall Only Mode.....	52
4.3.13	Closed Subscriber Group functions.....	52
4.3.14	Location Service functions.....	53
4.3.15	Selected IP Traffic Offload (SIPTO) function.....	53
4.3.15a	Selected IP Traffic Offload (SIPTO) at the Local Network.....	54
4.3.15a.1	General.....	54
4.3.15a.2	SIPTO at the Local Network with stand-alone GW (with S-GW and L-GW collocated) function.....	54
4.3.15a.3	SIPTO at the Local Network with L-GW function collocated with the (H)eNB.....	55
4.3.16	Local IP Access (LIPA) function.....	55
4.3.17	Support for Machine Type Communications (MTC).....	56
4.3.17.1	General.....	56
4.3.17.2	Overview of protection from Potential MTC Related Overload.....	57
4.3.17.3	Optimizing periodic TAU Signalling.....	58
4.3.17.4	UE configuration and usage of indicators.....	58
4.3.17.5	Void.....	60
4.3.17.6	Support of UEs configured for low access priority, Extended Access Barring and permission for override.....	60
4.3.17.7	High latency communication.....	60
4.3.17.8	Support for Non-IP Data Delivery (NIDD).....	61
4.3.17.8.1	General.....	61
4.3.17.8.2	ESM Procedures.....	61
4.3.17.8.3	Delivery mechanism.....	61
4.3.18	Multimedia Priority Service.....	63
4.3.18.1	General.....	63
4.3.18.2	IMS-based Multimedia Priority Services.....	64
4.3.18.2.1	Originating IMS-based MPS Session.....	64
4.3.18.2.2	Terminating IMS-based MPS Session.....	64
4.3.18.3	Priority EPS Bearer Services.....	64
4.3.18.4	CS fallback.....	65
4.3.18.5	Network Congestion Controls for MPS.....	65
4.3.18.6	Load Re-balancing between MMEs for MPS.....	65
4.3.19	Core Network node resolution.....	65
4.3.19.1	General.....	65
4.3.19.2	MSB in LAC and MME Group ID.....	65

4.3.19.3	Explicit Indication.....	65
4.3.20	Relaying function.....	66
4.3.20.1	General.....	66
4.3.20.2	RN startup and attach procedure.....	66
4.3.20.2.1	General.....	66
4.3.20.2.2	Attach for RN preconfiguration.....	67
4.3.20.2.3	Attach for RN operation.....	67
4.3.20.3	DeNB E-RAB activation/modification.....	68
4.3.21	Core Network assisted eNodeB parameters tuning.....	69
4.3.21.1	CN Assistance Information.....	69
4.3.21.2	Void.....	69
4.3.21.3	Core Network Assistance Procedures.....	69
4.3.22	UE Power Saving Mode.....	70
4.3.23	Access network selection and traffic steering based on RAN-assisted WLAN interworking.....	71
4.3.23a	Access network selection and traffic steering based on RAN-Controlled WLAN interworking.....	72
4.3.24	RAN user plane congestion management function.....	72
4.3.24.1	General.....	72
4.3.24.2	RAN user plane congestion mitigation in the RAN.....	72
4.3.24.3	RAN user plane congestion mitigation in the CN.....	72
4.3.25	Dedicated Core Networks (DCNs).....	73
4.3.25.1	General.....	73
4.3.25.1a	UE assisted Dedicated Core Network selection.....	74
4.3.25.2	Considerations for Roaming.....	74
4.3.25.3	Considerations for Network Sharing.....	75
4.3.26	Support for Monitoring Events.....	75
4.3.27	Paging Enhancements.....	75
4.3.27.1	Paging for Enhanced Coverage.....	75
4.3.27a	Restriction of use of Enhanced Coverage for voice centric UE.....	75
4.3.27b	Enhanced Coverage for data centric UEs.....	76
4.3.28	Restriction of use of Enhanced Coverage.....	76
4.3.29	3GPP PS Data Off.....	76
4.3.29.1	General.....	76
4.4	Network elements.....	77
4.4.1	E-UTRAN.....	77
4.4.2	MME.....	77
4.4.3	Gateway.....	78
4.4.3.1	General.....	78
4.4.3.2	Serving GW.....	78
4.4.3.3	PDN GW.....	79
4.4.4	SGSN.....	80
4.4.5	GERAN.....	80
4.4.6	UTRAN.....	80
4.4.7	PCRF.....	80
4.4.7.1	General.....	80
4.4.7.2	Home PCRF (H-PCRF).....	81
4.4.7.3	Visited PCRF (V-PCRF).....	81
4.4.8	PDN GW's associated AAA Server.....	81
4.4.9	HeNB subsystem.....	81
4.4.10	DeNB.....	82
4.4.11	CSG Subscriber Server.....	83
4.4.12	RAN Congestion Awareness Function.....	83
4.5	Void.....	83
4.6	EPS Mobility Management and Connection Management states.....	83
4.6.1	General.....	83
4.6.2	Definition of main EPS Mobility Management states.....	84
4.6.2.1	EMM-DEREGISTERED.....	84
4.6.2.2	EMM-REGISTERED.....	84
4.6.3	Definition of EPS Connection Management states.....	85
4.6.3.1	ECM-IDLE.....	85
4.6.3.2	ECM-CONNECTED.....	85
4.6.4	State transition and functions.....	86
4.7	Overall QoS concept.....	87

4.7.1	PDN connectivity service	87
4.7.2	The EPS bearer	87
4.7.2.1	The EPS bearer in general	87
4.7.2.2	The EPS bearer with GTP-based S5/S8	90
4.7.2.3	The EPS bearer with PMIP-based S5/S8	90
4.7.3	Bearer level QoS parameters	91
4.7.4	Support for Application / Service Layer Rate Adaptation	92
4.7.5	Application of PCC in the Evolved Packet System	93
4.7.6	Bearer Control Mode in EPC	93
4.7.7	Support of rate control of user data using CIoT EPS optimisation	94
4.7.7.1	General	94
4.7.7.2	Serving PLMN Rate Control	94
4.7.7.3	APN Rate Control	95
4.7.8	Inter-UE QoS for NB-IoT UEs using Control Plane CIoT EPS Optimisation	95
4.8	Compatibility Issues	96
4.8.1	Network Configuration for Interaction with UTRAN/GERAN	96
4.9	Paging Policy Differentiation	96
4.10	Introduction of CIoT EPS Optimisations	96
4.11	User Plane CIoT EPS Optimisation	97
5	Functional description and information flows	98
5.1	Control and user planes	98
5.1.0	General	98
5.1.1	Control Plane	98
5.1.1.1	General	98
5.1.1.2	eNodeB - MME	98
5.1.1.3	UE - MME	99
5.1.1.4	SGSN - MME	99
5.1.1.5	SGSN - S-GW	100
5.1.1.6	S-GW - P-GW	100
5.1.1.7	MME - MME	101
5.1.1.8	MME - S-GW	101
5.1.1.9	MME - HSS	102
5.1.1.10	MME - EIR	102
5.1.1.11	Void	102
5.1.1.12	MME - CSS	103
5.1.1.13	MME - RCAF	103
5.1.2	User Plane	104
5.1.2.1	UE - P-GW user plane with E-UTRAN	104
5.1.2.2	eNodeB - S-GW	104
5.1.2.3	UE - PDN GW user plane with 2G access via the S4 interface	105
5.1.2.4	UE - PDN GW user plane with 3G access via the S12 interface	106
5.1.2.5	UE - PDN GW user plane with 3G access via the S4 interface	107
5.1.2.6	UE - P-GW user plane with Control Plane CIoT Optimisations	108
5.2	Identities	108
5.2.1	EPS bearer identity	108
5.2.2	Globally Unique Temporary UE Identity	108
5.2.3	Tracking Area Identity (TAI)	108
5.2.4	eNodeB S1-AP UE Identity (eNodeB S1-AP UE ID)	109
5.2.5	MME S1-AP UE Identity (MME S1-AP UE ID)	109
5.2.6	Closed Subscriber Group ID	109
5.3	Authentication, security and location management	109
5.3.1	IP address allocation	109
5.3.1.1	General	109
5.3.1.2	IP address allocation, renewal and release mechanisms for GTP based S5/S8	112
5.3.1.2.1	IPv4 address allocation via default bearer activation and release via PDN connection release	112
5.3.1.2.2	Allocation, renewal and release of the IPv6 default prefix via IPv6 stateless address autoconfiguration	112
5.3.1.2.3	IPv6 parameter configuration via stateless DHCPv6	113
5.3.1.2.4	IPv4 address allocation, renewal and release and IPv4 parameter configuration via DHCPv4	113
5.3.1.2.5	Void	113
5.3.1.2.6	IPv6 Prefix Delegation via DHCPv6	113

5.3.2	Attach procedure.....	114
5.3.2.1	E-UTRAN Initial Attach	114
5.3.2.2	UTRAN/GERAN Initial Attach	129
5.3.3	Tracking Area Update procedures	129
5.3.3.0	Triggers for tracking area update	129
5.3.3.0A	Provision of UE's TAI to MME in ECM-CONNECTED state	130
5.3.3.1	Tracking Area Update procedure with Serving GW change	131
5.3.3.1A	Tracking Area Update procedure with Serving GW change and data forwarding	140
5.3.3.2	E-UTRAN Tracking Area Update without S-GW Change	142
5.3.3.3	Routing Area Update with MME interaction and without S-GW change.....	151
5.3.3.4	Void.....	158
5.3.3.5	Void.....	158
5.3.3.6	Routing Area Update with MME interaction and with S-GW change	158
5.3.4	Service Request procedures	165
5.3.4.1	UE triggered Service Request	165
5.3.4.2	Handling of abnormal conditions in UE triggered Service Request.....	168
5.3.4.3	Network Triggered Service Request	169
5.3.4A	Connection Suspend procedure.....	174
5.3.4B	Data Transport in Control Plane CIoT EPS optimisation	175
5.3.4B.1	General.....	175
5.3.4B.2	Mobile Originated Data Transport in Control Plane CIoT EPS optimisation with P-GW connectivity	176
5.3.4B.3	Mobile Terminated Data Transport in Control Plane CIoT EPS optimisation with P-GW connectivity	179
5.3.4B.4	Establishment of S1-U bearer during Data Transport in Control Plane CIoT EPS optimisation	185
5.3.4B.5	eNB Control Plane Relocation Indication procedure	186
5.3.5	S1 release procedure	187
5.3.5A	Connection Resume procedure	188
5.3.6	Void	190
5.3.6A	PDN GW Pause of Charging procedure	190
5.3.7	GUTI Reallocation procedure	192
5.3.8	Detach procedure	192
5.3.8.1	General	192
5.3.8.2	UE-initiated Detach procedure.....	193
5.3.8.2.1	UE-initiated Detach procedure for E-UTRAN	193
5.3.8.2.2	UE-initiated Detach procedure for GERAN/UTRAN with ISR activated.....	194
5.3.8.3	MME-initiated Detach procedure.....	196
5.3.8.3A	SGSN-initiated Detach procedure with ISR activated	198
5.3.8.4	HSS-initiated Detach procedure.....	199
5.3.9	HSS User Profile management function procedure	201
5.3.9.1	General	201
5.3.9.2	Insert Subscriber Data procedure	201
5.3.9.3	Purge function	202
5.3.10	Security Function.....	202
5.3.10.1	General	202
5.3.10.2	Authentication and Key Agreement	203
5.3.10.3	User Identity Confidentiality.....	203
5.3.10.4	User Data and Signalling Confidentiality	203
5.3.10.4.1	AS security mode command procedure	203
5.3.10.4.2	NAS Security Mode Command procedure	203
5.3.10.5	ME identity check procedure	203
5.3.11	UE Reachability procedures	204
5.3.11.1	General	204
5.3.11.2	UE Reachability Notification Request procedure	204
5.3.11.3	UE Activity Notification procedure	204
5.3.12	Update CSG Location Procedure.....	205
5.3.13	CSS subscription data management function procedure.....	205
5.3.13.1	General	205
5.3.13.2	Insert CSG Subscriber Data procedure	206
5.3.14	UE Radio Capability Match Request.....	206
5.4	Session Management, QoS and interaction with PCC functionality	207
5.4.1	Dedicated bearer activation.....	207

5.4.2	Bearer modification with bearer QoS update.....	210
5.4.2.1	PDN GW initiated bearer modification with bearer QoS update.....	210
5.4.2.2	HSS Initiated Subscribed QoS Modification.....	212
5.4.3	PDN GW initiated bearer modification without bearer QoS update.....	213
5.4.4	Bearer deactivation.....	215
5.4.4.1	PDN GW initiated bearer deactivation.....	215
5.4.4.2	MME Initiated Dedicated Bearer Deactivation.....	219
5.4.5	UE requested bearer resource modification.....	220
5.4.6	Void.....	223
5.4.7	E-UTRAN initiated E-RAB modification procedure.....	223
5.4.8	E-UTRAN initiated UE Context Modification procedure.....	225
5.5	Handover.....	225
5.5.1	Intra-E-UTRAN handover.....	226
5.5.1.1	X2-based handover.....	226
5.5.1.1.1	General.....	226
5.5.1.1.2	X2-based handover without Serving GW relocation.....	226
5.5.1.1.3	X2-based handover with Serving GW relocation.....	229
5.5.1.2	S1-based handover.....	231
5.5.1.2.1	General.....	231
5.5.1.2.2	S1-based handover, normal.....	232
5.5.1.2.3	S1-based handover, Reject.....	238
5.5.1.2.4	S1-based handover, Cancel.....	239
5.5.2	Inter RAT handover.....	239
5.5.2.0	General.....	239
5.5.2.1	E-UTRAN to UTRAN Iu mode Inter RAT handover.....	240
5.5.2.1.1	General.....	240
5.5.2.1.2	Preparation phase.....	240
5.5.2.1.3	Execution phase.....	244
5.5.2.1.4	E-UTRAN to UTRAN Iu mode Inter RAT handover Reject.....	247
5.5.2.2	UTRAN Iu mode to E-UTRAN Inter RAT handover.....	247
5.5.2.2.1	General.....	247
5.5.2.2.2	Preparation phase.....	248
5.5.2.2.3	Execution phase.....	251
5.5.2.2.4	UTRAN Iu mode to E-UTRAN Inter RAT handover reject.....	254
5.5.2.3	E-UTRAN to GERAN A/Gb mode Inter RAT handover.....	254
5.5.2.3.1	General.....	254
5.5.2.3.2	Preparation phase.....	255
5.5.2.3.3	Execution phase.....	258
5.5.2.3.4	E-UTRAN to GERAN A/Gb mode Inter RAT handover reject.....	261
5.5.2.4	GERAN A/Gb mode to E-UTRAN Inter RAT handover.....	262
5.5.2.4.1	General.....	262
5.5.2.4.2	Preparation phase.....	263
5.5.2.4.3	Execution phase.....	266
5.5.2.4.4	GERAN A/Gb mode to E-UTRAN Inter RAT handover reject.....	268
5.5.2.5	Inter RAT handover Cancel.....	269
5.5.2.5.1	General.....	269
5.5.2.5.2	Source RAN to Target RAN Inter RAT handover Cancel.....	270
5.6	Network Assisted Cell Change.....	271
5.6.1	Architecture Principles for E-UTRAN to GERAN NACC.....	271
5.6.2	Void.....	272
5.7	Information storage.....	272
5.7.1	HSS.....	273
5.7.2	MME.....	277
5.7.3	Serving GW.....	282
5.7.4	PDN GW.....	285
5.7.5	UE.....	288
5.7.6	Handling of Wild Card APN.....	289
5.7.7	CSS.....	290
5.7A	Charging.....	290
5.8	MBMS.....	291
5.9	Interactions with other services.....	291
5.9.1	Location Reporting Procedure.....	291

5.9.2	Location Change Reporting Procedure	291
5.9.2.1	General	291
5.9.2.2	Reporting at Presence Reporting Area entering and leaving	294
5.9.3	IMSI and APN information retrieval procedure	295
5.10	Multiple-PDN support and PDN activation for UEs supporting "Attach without PDN connectivity"	295
5.10.1	General	295
5.10.2	UE requested PDN connectivity	296
5.10.3	UE or MME requested PDN disconnection	304
5.10.4	MME triggered Serving GW relocation	306
5.11	UE Capability Handling	308
5.11.1	General	308
5.11.2	UE Radio Capability Handling	308
5.11.3	UE Core Network Capability	309
5.11.4	UE Radio Capability for Paging Information	310
5.12	Warning message delivery	310
5.12.1	General	310
5.12.2	Void	310
5.12.3	Void	311
5.13	Discontinuous Reception and UE Specific DRX Parameter handling	311
5.13a	Extended Idle mode Discontinuous Reception (DRX)	311
5.14	Configuration Transfer procedure	312
5.14.1	Architecture Principles for Configuration Transfer	312
5.14.2	Addressing, routing and relaying	313
5.14.2.1	Addressing	313
5.14.2.2	Routing	313
5.14.2.3	Relaying	313
5.14.2.4	Applications using the Configuration Transfer procedures	314
5.15	RAN Information Management (RIM) procedures	314
5.15.1	General	314
5.15.2	Addressing, routing and relaying	314
5.15.2.1	Addressing	314
5.15.2.2	Routing	314
5.15.2.3	Relaying	314
5.15.3	Applications using the RIM Procedures	314
5.16	MME-initiated procedure on UE's CSG membership change	315
5.17	Home eNodeB Multicast Packet Forwarding Function	315
5.18	HPLMN Notification with specific indication due to MME initiated Bearer removal	315
5.19	Procedures to support Dedicated Core Networks	315
5.19.1	NAS Message Redirection Procedure	315
5.19.2	Attach, TAU and RAU procedure for Dedicated Core Network	316
5.19.2a	Impacts to Handover Procedures	319
5.19.3	MME/SGSN or HSS initiated Dedicated Core Network Reselection	320
Annex A (informative):	Void	322
Annex B (informative):	Void	323
Annex C (informative):	Void	324
Annex D (normative):	Interoperation with Gn/Gp SGSNs	325
D.1	General Considerations	325
D.2	Interoperation Scenario	325
D.2.1	Roaming interoperation scenario	325
D.2.2	Non-roaming interoperation scenario	326
D.3	Interoperation procedures	326
D.3.1	General	326
D.3.2	Void	326
D.3.3	MME to 3G SGSN combined hard handover and SRNS relocation procedure	327
D.3.4	3G SGSN to MME combined hard handover and SRNS relocation procedure	332
D.3.5	Routing Area Update	338

D.3.6	Gn/Gp SGSN to MME Tracking Area Update.....	343
D.3.7	E-UTRAN to GERAN A/Gb mode Inter RAT handover.....	350
D.3.7.1	General.....	350
D.3.7.2	Preparation phase.....	351
D.3.7.3	Execution phase.....	354
D.3.8	GERAN A/Gb mode to E-UTRAN Inter RAT handover.....	356
D.3.8.1	General.....	356
D.3.8.2	Preparation phase.....	357
D.3.8.3	Execution phase.....	359
Annex E (normative):	Mapping between EPS and Release 99 QoS parameters.....	362
Annex F (normative):	Dedicated bearer activation in combination with the default bearer activation at Attach and UE requested PDN connectivity procedures ...	365
Annex G (informative):	Void	368
Annex H (normative):	Mapping between temporary and area identities	369
Annex I (informative):	Guidance for contributors to this specification.....	370
Annex J (informative):	High Level ISR description.....	371
J.1	General description of the ISR concept.....	371
J.2	Usage of the TIN	372
J.3	ISR activation.....	372
J.4	Downlink data transfer	373
J.5	ISR deactivation	374
J.6	Handling of special situations	374
Annex K (informative):	Isolated E-UTRAN Operation for Public Safety.....	376
K.1	General description of the IOPS concept.....	376
K.2	Operation of isolated public safety networks using a Local EPC	376
K.2.1	General Description.....	376
K.2.2	UE configuration	376
K.2.3	IOPS network configuration.....	376
K.2.4	IOPS network establishment/termination.....	377
K.2.5	UE mobility	379
Annex L (Informative):	Optimized EPS Architecture option for CIoT	381
L.1	Introduction	381
L.2	Non-Roaming Architecture	381
L.3	Roaming architecture	382
L.4	C-SGN.....	382
Annex M (informative):	Functions and procedures over NB-IoT RAT	383
Annex N (informative):	Change history	387
History		394

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

x the first digit:

- 1 presented to TSG for information;
- 2 presented to TSG for approval;
- 3 or greater indicates TSG approved document under change control.

y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.

z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/a16c8eb8-4437-42ed-87ba-ac87bd8b45c7/etsi-ts-123-401-v14.10.0-2018-12>

1 Scope

The present document defines the Stage 2 service description for the Evolved 3GPP Packet Switched Domain - also known as the Evolved Packet System (EPS) in this document. The Evolved 3GPP Packet Switched Domain provides IP connectivity using the Evolved Universal Terrestrial Radio Access Network (E-UTRAN).

The specification covers both roaming and non-roaming scenarios and covers all aspects, including mobility between E-UTRAN and pre-E-UTRAN 3GPP radio access technologies, policy control and charging, and authentication.

The Radio Access Network functionality is documented only to the extent necessary to describe the overall system. TS 36.300 [5] contains the overall description of the Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN).

ITU-T Recommendation I.130 [3] describes a three-stage method for characterisation of telecommunication services, and ITU-T Recommendation Q.65 [4] defines Stage 2 of the method.

TS 23.402 [2] is a companion specification to this specification.

An Evolved Packet System architecture optimised for the support of Cellular IoT (Internet of Things) applications is also defined in this document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.402: "Architecture enhancements for non-3GPP accesses".
- [3] ITU-T Recommendation I.130: "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [4] ITU-T Recommendation Q.65: "The unified functional methodology for the characterization of services and network capabilities".
- [5] 3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2".
- [6] 3GPP TS 23.203: "Policy and charging control architecture".
- [7] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2".
- [8] 3GPP TS 43.129: "Packet-switched handover for GERAN A/Gb mode; Stage 2".
- [9] 3GPP TS 23.003: "Numbering, addressing and identification".
- [10] 3GPP TS 23.122: "Non-Access-Stratum (NAS) functions related to Mobile Station in idle mode".
- [11] 3GPP TS 43.022: "Functions related to MS in idle mode and group receive mode".
- [12] 3GPP TS 25.304: "UE procedures in idle mode and procedures for cell re-selection in connected mode".