

ETSI TS 123 401 V15.6.0 (2019-03)



LTE;
**General Packet Radio Service (GPRS) enhancements for
Evolved Universal Terrestrial
Radio Access Network (E-UTRAN) access
(3GPP TS 23.401 version 15.6.0 Release 15)**

PRELIMINARY REVIEW
https://standards.iteh.ai/catalog/standards/sist/19fe59cf-7b97-4a9c-b98f-36b8cc2618d0/etsi-ts-123-401-v15-6-0-2019-03



Reference

RTS/TSGS-0223401vf60

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope	13
2 References	13
3 Definitions and abbreviations.....	16
3.1 Definitions	16
3.2 Abbreviations	18
4 Architecture model and concepts	19
4.1 General concepts	19
4.2 Architecture reference model	20
4.2.1 Non-roaming architecture	20
4.2.2 Roaming architecture.....	21
4.2.3 Reference points	23
4.2.4 Warning System architecture.....	24
4.3 High level functions	24
4.3.1 General.....	24
4.3.2 Network access control functions	25
4.3.2.1 General	25
4.3.2.2 Network/Access network selection.....	25
4.3.2.3 Authentication and authorisation function	25
4.3.2.4 Admission control function.....	25
4.3.2.5 Policy and Charging Enforcement Function	25
4.3.2.6 Lawful Interception.....	25
4.3.2a Support for Dual Connectivity.....	25
4.3.3 Packet routing and transfer functions.....	27
4.3.3.1 General	27
4.3.3.2 IP header compression function.....	27
4.3.3.3 Packet screening function	27
4.3.3.4 IP Multicast Forwarding between a network accessed by LIPA and a UE	27
4.3.4 Security functions	27
4.3.5 Mobility management functions	27
4.3.5.1 General	27
4.3.5.2 Reachability Management for UE in ECM-IDLE state.....	27
4.3.5.3 Tracking Area list management	29
4.3.5.4 Inter-eNodeB mobility anchor function	29
4.3.5.5 Inter-3GPP mobility anchor function.....	29
4.3.5.6 Idle mode signalling reduction function.....	29
4.3.5.7 Mobility Restrictions.....	31
4.3.5.8 IMS voice over PS Session Supported Indication.....	32
4.3.5.8A Homogenous Support of IMS Voice over PS Sessions Indication.....	32
4.3.5.9 Voice domain preference and UE's usage setting.....	32
4.3.5.10 Preferred and Supported Network Behaviour	33
4.3.6 Radio Resource Management functions	34
4.3.7 Network management functions	34
4.3.7.1 General	34
4.3.7.1a GTP-C signalling based Load and Overload Control.....	35
4.3.7.1a.1 GTP-C Load Control	35
4.3.7.1a.2 GTP-C Overload Control.....	35
4.3.7.2 Load balancing between MMEs.....	37
4.3.7.3 Load re-balancing between MMEs	37
4.3.7.4 MME control of overload.....	38
4.3.7.4.1 General	38

4.3.7.4.1a	Throttling of Downlink Data Notification Requests.....	40
4.3.7.4.1b	Throttling of NIDD Submit Requests.....	40
4.3.7.4.2	NAS level congestion control.....	40
4.3.7.5	PDN GW control of overload.....	46
4.3.8	Selection functions.....	46
4.3.8.1	PDN GW selection function (3GPP accesses)	46
4.3.8.2	Serving GW selection function	48
4.3.8.3	MME selection function.....	49
4.3.8.4	SGSN selection function	50
4.3.8.5	Selection of PCRF.....	50
4.3.9	IP network related functions	50
4.3.9.1	Domain Name Service function	50
4.3.9.2	DHCP function.....	50
4.3.9.3	Explicit Congestion Notification.....	50
4.3.10	Functionality for Connection of eNodeBs to Multiple MMEs.....	50
4.3.11	E-UTRAN Sharing Function	51
4.3.12	IMS Emergency Session Support	51
4.3.12.1	Introduction.....	51
4.3.12.2	Architecture Reference Model for Emergency Services	53
4.3.12.3	Mobility and Access Restrictions for Emergency Services.....	53
4.3.12.3a	Reachability Management for UE in ECM-IDLE state.....	53
4.3.12.4	PDN GW selection function (3GPP accesses) for Emergency Services	53
4.3.12.5	QoS for Emergency Services	54
4.3.12.6	PCC for Emergency Services.....	54
4.3.12.7	Load re-balancing between MMEs for Emergency Services	54
4.3.12.8	IP Address Allocation	54
4.3.12.9	Handling of PDN Connections for Emergency Bearer Services.....	54
4.3.12.10	ISR function for Emergency Bearer Services.....	55
4.3.12.11	Support of eCall Only Mode	55
4.3.13	Closed Subscriber Group functions	55
4.3.14	Location Service functions	56
4.3.15	Selected IP Traffic Offload (SIPTO) function.....	56
4.3.15a	Selected IP Traffic Offload (SIPTO) at the Local Network.....	57
4.3.15a.1	General	57
4.3.15a.2	SIPTO at the Local Network with stand-alone GW (with S-GW and L-GW collocated) function	57
4.3.15a.3	SIPTO at the Local Network with L-GW function collocated with the (H)eNB	58
4.3.16	Local IP Access (LIPA) function.....	58
4.3.17	Support for Machine Type Communications (MTC).....	59
4.3.17.1	General	59
4.3.17.2	Overview of protection from Potential MTC Related Overload	60
4.3.17.3	Optimising periodic TAU Signalling	61
4.3.17.4	UE configuration and usage of indicators	62
4.3.17.5	Void.....	63
4.3.17.6	Support of UEs configured for low access priority, Extended Access Barring and permission for override	63
4.3.17.7	High latency communication	64
4.3.17.8	Support for Non-IP Data Delivery (NIDD).....	64
4.3.17.8.1	General	64
4.3.17.8.2	ESM Procedures	65
4.3.17.8.3	Delivery mechanism.....	65
4.3.17.9	Service Gap Control.....	66
4.3.18	Multimedia Priority Service.....	68
4.3.18.1	General	68
4.3.18.2	IMS-based Multimedia Priority Services	69
4.3.18.2.1	Originating IMS-based MPS Session	69
4.3.18.2.2	Terminating IMS-based MPS Session.....	69
4.3.18.3	Priority EPS Bearer Services.....	69
4.3.18.4	CS fallback.....	70
4.3.18.5	Network Congestion Controls for MPS	70
4.3.18.6	Load Re-balancing between MMEs for MPS	70
4.3.19	Core Network node resolution	70
4.3.19.1	General	70

4.3.19.2	MSB in LAC and MME Group ID.....	70
4.3.19.3	Explicit Indication.....	70
4.3.20	Relaying function.....	71
4.3.20.1	General.....	71
4.3.20.2	RN startup and attach procedure.....	71
4.3.20.2.1	General.....	71
4.3.20.2.2	Attach for RN preconfiguration.....	72
4.3.20.2.3	Attach for RN operation.....	72
4.3.20.3	DeNB E-RAB activation/modification.....	73
4.3.21	Core Network assisted eNodeB parameters tuning.....	74
4.3.21.1	CN Assistance Information.....	74
4.3.21.2	Void.....	74
4.3.21.3	Core Network Assistance Procedures.....	74
4.3.22	UE Power Saving Mode.....	75
4.3.23	Access network selection and traffic steering based on RAN-assisted WLAN interworking.....	76
4.3.23a	Access network selection and traffic steering based on RAN-Controlled WLAN interworking.....	77
4.3.24	RAN user plane congestion management function.....	77
4.3.24.1	General.....	77
4.3.24.2	RAN user plane congestion mitigation in the RAN.....	77
4.3.24.3	RAN user plane congestion mitigation in the CN.....	77
4.3.25	Dedicated Core Networks (DCNs).....	78
4.3.25.1	General.....	78
4.3.25.1a	UE assisted Dedicated Core Network selection.....	79
4.3.25.2	Considerations for Roaming.....	79
4.3.25.3	Considerations for Network Sharing.....	80
4.3.26	Support for Monitoring Events.....	80
4.3.27	Paging Enhancements.....	80
4.3.27.1	Paging for Enhanced Coverage.....	80
4.3.27a	Restriction of use of Enhanced Coverage for voice centric UE.....	80
4.3.27b	Enhanced Coverage for data centric UEs.....	81
4.3.28	Restriction of use of Enhanced Coverage.....	81
4.3.29	3GPP PS Data Off.....	81
4.3.29.1	General.....	81
4.3.30	Unlicensed spectrum aggregation (LAA/LWA/LWIP).....	82
4.3.31	Subscription handling for Aerial UEs.....	82
4.4	Network elements.....	83
4.4.1	E-UTRAN.....	83
4.4.2	MME.....	83
4.4.3	Gateway.....	84
4.4.3.1	General.....	84
4.4.3.2	Serving GW.....	84
4.4.3.3	PDN GW.....	85
4.4.4	SGSN.....	86
4.4.5	GERAN.....	86
4.4.6	UTRAN.....	86
4.4.7	PCRF.....	86
4.4.7.1	General.....	86
4.4.7.2	Home PCRF (H-PCRF).....	87
4.4.7.3	Visited PCRF (V-PCRF).....	87
4.4.8	PDN GW's associated AAA Server.....	87
4.4.9	HeNB subsystem.....	87
4.4.10	DeNB.....	88
4.4.11	CSG Subscriber Server.....	89
4.4.12	RAN Congestion Awareness Function.....	89
4.5	Void.....	89
4.6	EPS Mobility Management and Connection Management states.....	89
4.6.1	General.....	89
4.6.2	Definition of main EPS Mobility Management states.....	90
4.6.2.1	EMM-DEREGISTERED.....	90
4.6.2.2	EMM-REGISTERED.....	90
4.6.3	Definition of EPS Connection Management states.....	91
4.6.3.1	ECM-IDLE.....	91

4.6.3.2	ECM-CONNECTED.....	91
4.6.4	State transition and functions.....	92
4.7	Overall QoS concept	93
4.7.1	PDN connectivity service	93
4.7.2	The EPS bearer	93
4.7.2.1	The EPS bearer in general.....	93
4.7.2.2	The EPS bearer with GTP-based S5/S8.....	96
4.7.2.3	The EPS bearer with PMIP-based S5/S8	96
4.7.3	Bearer level QoS parameters	97
4.7.4	Support for Application / Service Layer Rate Adaptation	98
4.7.5	Application of PCC in the Evolved Packet System	99
4.7.6	Bearer Control Mode in EPC.....	99
4.7.7	Support of rate control of user data using CIoT EPS Optimisation	100
4.7.7.1	General.....	100
4.7.7.2	Serving PLMN Rate Control.....	100
4.7.7.3	APN Rate Control	101
4.7.8	Inter-UE QoS for NB-IoT UEs using Control Plane CIoT EPS Optimisation.....	102
4.8	Compatibility Issues	102
4.8.1	Network Configuration for Interaction with UTRAN/GERAN.....	102
4.9	Paging Policy Differentiation.....	102
4.10	Introduction of CIoT EPS Optimisations	103
4.11	User Plane CIoT EPS Optimisation	103
4.12	Supporting up to 15 EPS bearers per UE	104
5	Functional description and information flows.....	105
5.1	Control and user planes	105
5.1.0	General.....	105
5.1.1	Control Plane	105
5.1.1.1	General.....	105
5.1.1.2	eNodeB - MME.....	106
5.1.1.3	UE - MME	106
5.1.1.4	SGSN - MME.....	107
5.1.1.5	SGSN - S-GW.....	107
5.1.1.6	S-GW - P-GW	108
5.1.1.7	MME - MME	108
5.1.1.8	MME - S-GW.....	109
5.1.1.9	MME - HSS	109
5.1.1.10	MME - EIR	110
5.1.1.11	Void.....	110
5.1.1.12	MME - CSS.....	110
5.1.1.13	MME - RCAF	111
5.1.2	User Plane.....	111
5.1.2.1	UE - P-GW user plane with E-UTRAN.....	111
5.1.2.2	eNodeB - S-GW	112
5.1.2.3	UE - PDN GW user plane with 2G access via the S4 interface	112
5.1.2.4	UE - PDN GW user plane with 3G access via the S12 interface	113
5.1.2.5	UE - PDN GW user plane with 3G access via the S4 interface	114
5.1.2.6	UE - P-GW user plane with Control Plane CIoT EPS Optimisations	115
5.2	Identities.....	115
5.2.1	EPS bearer identity	115
5.2.2	Globally Unique Temporary UE Identity	115
5.2.3	Tracking Area Identity (TAI).....	115
5.2.4	eNodeB S1-AP UE Identity (eNodeB S1-AP UE ID)	116
5.2.5	MME S1-AP UE Identity (MME S1-AP UE ID)	116
5.2.6	Closed Subscriber Group ID.....	116
5.3	Authentication, security and location management.....	116
5.3.1	IP address allocation	116
5.3.1.1	General	116
5.3.1.2	IP address allocation, renewal and release mechanisms for GTP based S5/S8.....	119
5.3.1.2.1	IPv4 address allocation via default bearer activation and release via PDN connection release.....	119
5.3.1.2.2	Allocation, renewal and release of the IPv6 default prefix via IPv6 stateless address autoconfiguration.....	119

5.3.1.2.3	IPv6 parameter configuration via stateless DHCPv6.....	120
5.3.1.2.4	IPv4 address allocation, renewal and release and IPv4 parameter configuration via DHCPv4.....	120
5.3.1.2.5	Void.....	120
5.3.1.2.6	IPv6 Prefix Delegation via DHCPv6.....	120
5.3.2	Attach procedure.....	121
5.3.2.1	E-UTRAN Initial Attach.....	121
5.3.2.2	UTRAN/GERAN Initial Attach.....	136
5.3.3	Tracking Area Update procedures.....	137
5.3.3.0	Triggers for tracking area update.....	137
5.3.3.0A	Provision of UE's TAI to MME in ECM-CONNECTED state.....	138
5.3.3.1	Tracking Area Update procedure with Serving GW change.....	139
5.3.3.1A	Tracking Area Update procedure with Serving GW change and data forwarding.....	148
5.3.3.2	E-UTRAN Tracking Area Update without S-GW Change.....	150
5.3.3.3	Routing Area Update with MME interaction and without S-GW change.....	159
5.3.3.4	Void.....	166
5.3.3.5	Void.....	166
5.3.3.6	Routing Area Update with MME interaction and with S-GW change.....	166
5.3.4	Service Request procedures.....	173
5.3.4.1	UE triggered Service Request.....	173
5.3.4.2	Handling of abnormal conditions in UE triggered Service Request.....	176
5.3.4.3	Network Triggered Service Request.....	177
5.3.4A	Connection Suspend procedure.....	182
5.3.4B	Data Transport in Control Plane CIoT EPS Optimisation.....	183
5.3.4B.1	General.....	183
5.3.4B.2	Mobile Originated Data Transport in Control Plane CIoT EPS Optimisation with P-GW connectivity.....	184
5.3.4B.3	Mobile Terminated Data Transport in Control Plane CIoT EPS Optimisation with P-GW connectivity.....	188
5.3.4B.4	Establishment of S1-U bearer during Data Transport in Control Plane CIoT EPS Optimisation.....	194
5.3.4B.5	eNB Control Plane Relocation Indication procedure.....	195
5.3.5	S1 release procedure.....	196
5.3.5A	Connection Resume procedure.....	198
5.3.6	Void.....	200
5.3.6A	PDN GW Pause of Charging procedure.....	200
5.3.7	GUTI Reallocation procedure.....	202
5.3.8	Detach procedure.....	202
5.3.8.1	General.....	202
5.3.8.2	UE-initiated Detach procedure.....	202
5.3.8.2.1	UE-initiated Detach procedure for E-UTRAN.....	203
5.3.8.2.2	UE-initiated Detach procedure for GERAN/UTRAN with ISR activated.....	204
5.3.8.3	MME-initiated Detach procedure.....	206
5.3.8.3A	SGSN-initiated Detach procedure with ISR activated.....	208
5.3.8.4	HSS-initiated Detach procedure.....	209
5.3.9	HSS User Profile management function procedure.....	211
5.3.9.1	General.....	211
5.3.9.2	Insert Subscriber Data procedure.....	211
5.3.9.3	Purge function.....	212
5.3.10	Security Function.....	213
5.3.10.1	General.....	213
5.3.10.2	Authentication and Key Agreement.....	213
5.3.10.3	User Identity Confidentiality.....	213
5.3.10.4	User Data and Signalling Confidentiality.....	213
5.3.10.4.1	AS security mode command procedure.....	213
5.3.10.4.2	NAS Security Mode Command procedure.....	213
5.3.10.5	ME identity check procedure.....	214
5.3.11	UE Reachability procedures.....	214
5.3.11.1	General.....	214
5.3.11.2	UE Reachability Notification Request procedure.....	215
5.3.11.3	UE Activity Notification procedure.....	215
5.3.12	Update CSG Location Procedure.....	215
5.3.13	CSS subscription data management function procedure.....	216
5.3.13.1	General.....	216

5.3.13.2	Insert CSG Subscriber Data procedure	216
5.3.14	UE Radio Capability Match Request	217
5.4	Session Management, QoS and interaction with PCC functionality	218
5.4.1	Dedicated bearer activation.....	218
5.4.2	Bearer modification with bearer QoS update.....	220
5.4.2.1	PDN GW initiated bearer modification with bearer QoS update.....	220
5.4.2.2	HSS Initiated Subscribed QoS Modification.....	223
5.4.3	PDN GW initiated bearer modification without bearer QoS update.....	224
5.4.4	Bearer deactivation	226
5.4.4.1	PDN GW initiated bearer deactivation.....	226
5.4.4.2	MME Initiated Dedicated Bearer Deactivation.....	230
5.4.5	UE requested bearer resource modification	231
5.4.6	Void	234
5.4.7	E-UTRAN initiated E-RAB modification procedure.....	234
5.4.8	E-UTRAN initiated UE Context Modification procedure	236
5.5	Handover	237
5.5.1	Intra-E-UTRAN handover	237
5.5.1.1	X2-based handover.....	237
5.5.1.1.1	General	237
5.5.1.1.2	X2-based handover without Serving GW relocation.....	238
5.5.1.1.3	X2-based handover with Serving GW relocation	240
5.5.1.2	S1-based handover	242
5.5.1.2.1	General	242
5.5.1.2.2	S1-based handover, normal	244
5.5.1.2.3	S1-based handover, Reject	250
5.5.1.2.4	S1-based handover, Cancel.....	251
5.5.2	Inter RAT handover	251
5.5.2.0	General	251
5.5.2.1	E-UTRAN to UTRAN Iu mode Inter RAT handover	252
5.5.2.1.1	General	252
5.5.2.1.2	Preparation phase.....	253
5.5.2.1.3	Execution phase	256
5.5.2.1.4	E-UTRAN to UTRAN Iu mode Inter RAT handover Reject	259
5.5.2.2	UTRAN Iu mode to E-UTRAN Inter RAT handover	260
5.5.2.2.1	General	260
5.5.2.2.2	Preparation phase.....	260
5.5.2.2.3	Execution phase.....	264
5.5.2.2.4	UTRAN Iu mode to E-UTRAN Inter RAT handover reject.....	267
5.5.2.3	E-UTRAN to GERAN A/Gb mode Inter RAT handover.....	267
5.5.2.3.1	General	267
5.5.2.3.2	Preparation phase.....	268
5.5.2.3.3	Execution phase.....	271
5.5.2.3.4	E-UTRAN to GERAN A/Gb mode Inter RAT handover reject	275
5.5.2.4	GERAN A/Gb mode to E-UTRAN Inter RAT handover.....	275
5.5.2.4.1	General	275
5.5.2.4.2	Preparation phase.....	276
5.5.2.4.3	Execution phase.....	279
5.5.2.4.4	GERAN A/Gb mode to E-UTRAN Inter RAT handover reject	282
5.5.2.5	Inter RAT handover Cancel	282
5.5.2.5.1	General	282
5.5.2.5.2	Source RAN to Target RAN Inter RAT handover Cancel	283
5.6	Network Assisted Cell Change.....	284
5.6.1	Architecture Principles for E-UTRAN to GERAN NACC.....	284
5.6.2	Void	285
5.7	Information storage	285
5.7.1	HSS.....	286
5.7.2	MME.....	290
5.7.3	Serving GW	295
5.7.4	PDN GW.....	298
5.7.5	UE.....	301
5.7.6	Handling of Wild Card APN.....	302
5.7.7	CSS	303

5.7A	Charging	303
5.7A.1	General	303
5.7A.2	Usage Data Reporting for Secondary RAT	304
5.7A.3	Secondary RAT Usage Data Reporting Procedure	304
5.7A.4	Secondary RAT Periodic Usage Data Reporting Procedure	306
5.8	MBMS	306
5.9	Interactions with other services	306
5.9.1	Location Reporting Procedure	306
5.9.2	Location Change Reporting Procedure	307
5.9.2.1	General	307
5.9.2.2	Reporting at Presence Reporting Area entering and leaving	309
5.9.3	IMSI and APN information retrieval procedure	310
5.10	Multiple-PDN support and PDN activation for UEs supporting "Attach without PDN connectivity"	311
5.10.1	General	311
5.10.2	UE requested PDN connectivity	311
5.10.3	UE or MME requested PDN disconnection	319
5.10.4	MME triggered Serving GW relocation	321
5.11	UE Capability Handling	323
5.11.1	General	323
5.11.2	UE Radio Capability Handling	323
5.11.3	UE Core Network Capability	325
5.11.4	UE Radio Capability for Paging Information	326
5.11.5	UE Radio Capability for Category M Differentiation	326
5.12	Warning message delivery	326
5.12.1	General	326
5.12.2	Void	327
5.12.3	Void	327
5.13	Discontinuous Reception and UE Specific DRX Parameter handling	327
5.13a	Extended Idle mode Discontinuous Reception (DRX)	327
5.14	Configuration Transfer procedure	328
5.14.1	Architecture Principles for Configuration Transfer	328
5.14.2	Addressing, routing and relaying	329
5.14.2.1	Addressing	329
5.14.2.2	Routing	329
5.14.2.3	Relaying	330
5.14.2.4	Applications using the Configuration Transfer procedures	330
5.15	RAN Information Management (RIM) procedures	330
5.15.1	General	330
5.15.2	Addressing, routing and relaying	330
5.15.2.1	Addressing	330
5.15.2.2	Routing	330
5.15.2.3	Relaying	330
5.15.3	Applications using the RIM Procedures	330
5.16	MME-initiated procedure on UE's CSG membership change	331
5.17	Home eNodeB Multicast Packet Forwarding Function	331
5.18	HPLMN Notification with specific indication due to MME initiated Bearer removal	331
5.19	Procedures to support Dedicated Core Networks	331
5.19.1	NAS Message Redirection Procedure	331
5.19.2	Attach, TAU and RAU procedure for Dedicated Core Network	332
5.19.2a	Impacts to Handover Procedures	335
5.19.3	MME/SGSN or HSS initiated Dedicated Core Network Reselection	336
Annex A (informative):	Void	338
Annex B (informative):	Void	339
Annex C (informative):	Void	340
Annex D (normative):	Interoperation with Gn/Gp SGSNs	341
D.1	General Considerations	341
D.2	Interoperation Scenario	341

D.2.1	Roaming interoperation scenario.....	341
D.2.2	Non-roaming interoperation scenario.....	342
D.3	Interoperation procedures.....	342
D.3.1	General.....	342
D.3.2	Void.....	342
D.3.3	MME to 3G SGSN combined hard handover and SRNS relocation procedure.....	343
D.3.4	3G SGSN to MME combined hard handover and SRNS relocation procedure.....	348
D.3.5	Routing Area Update.....	354
D.3.6	Gn/Gp SGSN to MME Tracking Area Update.....	360
D.3.7	E-UTRAN to GERAN A/Gb mode Inter RAT handover.....	367
D.3.7.1	General.....	367
D.3.7.2	Preparation phase.....	368
D.3.7.3	Execution phase.....	371
D.3.8	GERAN A/Gb mode to E-UTRAN Inter RAT handover.....	373
D.3.8.1	General.....	373
D.3.8.2	Preparation phase.....	374
D.3.8.3	Execution phase.....	376
Annex E (normative):	Mapping between EPS and Release 99 QoS parameters.....	379
Annex F (normative):	Dedicated bearer activation in combination with the default bearer activation at Attach and UE requested PDN connectivity procedures ...	382
Annex G (informative):	Void.....	385
Annex H (normative):	Mapping between temporary and area identities.....	386
Annex I (informative):	Guidance for contributors to this specification.....	387
Annex J (informative):	High Level ISR description.....	388
J.1	General description of the ISR concept.....	388
J.2	Usage of the TIN.....	389
J.3	ISR activation.....	389
J.4	Downlink data transfer.....	390
J.5	ISR deactivation.....	391
J.6	Handling of special situations.....	391
Annex K (informative):	Isolated E-UTRAN Operation for Public Safety.....	393
K.1	General description of the IOPS concept.....	393
K.2	Operation of isolated public safety networks using a Local EPC.....	393
K.2.1	General Description.....	393
K.2.2	UE configuration.....	393
K.2.3	IOPS network configuration.....	393
K.2.4	IOPS network establishment/termination.....	394
K.2.5	UE mobility.....	396
Annex L (informative):	Optimised EPS Architecture option for CIoT.....	398
L.1	Introduction.....	398
L.2	Non-Roaming Architecture.....	398
L.3	Roaming architecture.....	399
L.4	C-SGN.....	399
Annex M (informative):	Functions and procedures over NB-IoT RAT.....	400
Annex N (informative):	Change history.....	404

History412

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/9fea59cf-7897-4a9c-b98f-36b8cc2618db/etsi-ts-123-401-v15.6.0-2019-03>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

x the first digit:

- 1 presented to TSG for information;
- 2 presented to TSG for approval;
- 3 or greater indicates TSG approved document under change control.

y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.

z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/9fea59cf-7f97-4a9c-b98f-36b8cc2618db/etsi-ts-123-401-v15.6.0-2019-03>