

ETSI TS 123 501 V15.4.0 (2019-03)



5G; System Architecture for the 5G System (3GPP TS 23.501 version 15.4.0 Release 15)

*iTeh STANDARD PREVIEW
(standards.it-ebooks.net)
Full standard: <https://standards.iteh.ai/catalog/standards/sist/2df5b0be-cfef-439b-b675-6b69fd70de42/etsi-ts-123-501-2019-03>*



Reference

RTS/TSGS-0223501vf40

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	11
1 Scope	12
2 References	12
3 Definitions and abbreviations.....	15
3.1 Definitions	15
3.2 Abbreviations	17
4 Architecture model and concepts	19
4.1 General concepts	19
4.2 Architecture reference model	19
4.2.1 General.....	19
4.2.2 Network Functions and entities	20
4.2.3 Non-roaming reference architecture	20
4.2.4 Roaming reference architectures.....	23
4.2.5 Data Storage architectures	25
4.2.6 Service-based interfaces	27
4.2.7 Reference points	27
4.2.8 Support of non-3GPP access.....	29
4.2.8.1 General Concepts to Support Non-3GPP Access.....	29
4.2.8.2 Architecture Reference Model for Non-3GPP Accesses.....	30
4.2.8.2.1 Non-roaming Architecture for Non-3GPP Accesses.....	30
4.2.8.2.2 LBO Roaming Architecture for Non-3GPP Accesses, N3IWF in same PLMN as 3GPP access.....	30
4.2.8.2.3 Home-routed Roaming Architecture for Non-3GPP Accesses, N3IWF in same PLMN as 3GPP access	31
4.2.8.2.4 LBO Roaming Architecture for Non-3GPP Accesses, N3IWF in different PLMN from 3GPP access.....	32
4.2.8.2.5 Home-routed Roaming Architecture for Non-3GPP Accesses, N3IWF in different PLMN from 3GPP access.....	33
4.2.8.3 Non-3GPP Access Reference Points.....	34
4.2.9 Network Analytics architecture	34
4.3 Interworking with EPC.....	34
4.3.1 Non-roaming architecture	34
4.3.2 Roaming architecture.....	35
4.3.3 Interworking between 5GC via non-3GPP access and E-UTRAN connected to EPC.....	37
4.3.3.1 Non-roaming architecture	37
4.3.3.2 Roaming architecture	38
4.3.4 Interworking between ePDG connected to EPC and 5GS	40
4.3.4.1 Non-roaming architecture	40
4.3.4.2 Roaming architectures.....	41
4.4 Specific services	43
4.4.1 Public Warning System	43
4.4.2 SMS over NAS	43
4.4.2.1 Architecture to support SMS over NAS.....	43
4.4.2.2 Reference point to support SMS over NAS	45
4.4.2.3 Service based interface to support SMS over NAS	45
4.4.3 IMS support	45
4.4.4 Location services	46
4.4.4.1 Architecture to support Location Services	46
4.4.4.2 Reference point to support Location Services.....	46
4.4.4.3 Service Based Interfaces to support Location Services.....	47
4.4.5 Application Triggering Services	47
5 High level features.....	47

5.1	General	47
5.2	Network Access Control	47
5.2.1	General.....	47
5.2.2	Network selection	47
5.2.3	Identification and authentication.....	47
5.2.4	Authorisation	48
5.2.5	Access control and barring	48
5.2.6	Policy control.....	48
5.2.7	Lawful Interception.....	48
5.3	Registration and Connection Management.....	49
5.3.1	General.....	49
5.3.2	Registration Management	49
5.3.2.1	General	49
5.3.2.2	5GS Registration Management states.....	49
5.3.2.2.1	General	49
5.3.2.2.2	RM-DEREGISTERED state.....	49
5.3.2.2.3	RM-REGISTERED state.....	50
5.3.2.2.4	5GS Registration Management State models	50
5.3.2.3	Registration Area management	51
5.3.2.4	Support of a UE registered over both 3GPP and Non-3GPP access	51
5.3.3	Connection Management	53
5.3.3.1	General	53
5.3.3.2	5GS Connection Management states.....	53
5.3.3.2.1	General	53
5.3.3.2.2	CM-IDLE state	53
5.3.3.2.3	CM-CONNECTED state	54
5.3.3.2.4	5GS Connection Management State models	54
5.3.3.2.5	CM-CONNECTED with RRC Inactive state	54
5.3.3.3	NAS signalling connection management	56
5.3.3.3.1	General	56
5.3.3.3.2	NAS signalling connection establishment	57
5.3.3.3.3	NAS signalling connection Release.....	57
5.3.3.4	Support of a UE connected over both 3GPP and Non-3GPP access	57
5.3.4	UE Mobility	57
5.3.4.1	Mobility Restrictions.....	57
5.3.4.1.1	General	57
5.3.4.1.2	Management of Service Area Restrictions	59
5.3.4.2	Mobility Pattern	59
5.3.4.3	Radio Resource Management functions.....	60
5.3.4.4	UE mobility event notification.....	60
5.4	3GPP access specific aspects.....	61
5.4.1	UE reachability in CM-IDLE.....	61
5.4.1.1	General	61
5.4.1.2	UE reachability allowing mobile terminated data while the UE is CM-IDLE	62
5.4.1.3	Mobile Initiated Connection Only (MICO) mode	62
5.4.2	UE reachability in CM-CONNECTED.....	63
5.4.3	Paging strategy handling	63
5.4.3.1	General	63
5.4.3.2	Paging Policy Differentiation.....	64
5.4.3.3	Paging Priority	64
5.4.4	UE Radio Capability handling	65
5.4.4.1	UE radio capability information storage in the AMF.....	65
5.4.4.2	Void.....	65
5.4.4.2a	UE Radio Capability Match Request	65
5.4.4.3	Paging assistance information.....	65
5.4.4a	UE MM Core Network Capability handling.....	66
5.4.4b	UE 5GSM Core Network Capability handling	66
5.4.5	DRX (Discontinuous Reception) framework.....	66
5.4.6	Core Network assistance information for RAN optimization	67
5.4.6.1	General	67
5.4.6.2	Core Network assisted RAN parameters tuning.....	67
5.4.6.3	Core Network assisted RAN paging information.....	68

5.4.7	NG-RAN location reporting	68
5.5	Non-3GPP access specific aspects	68
5.5.1	Registration Management	68
5.5.2	Connection Management	69
5.5.3	UE Reachability	69
5.5.3.1	UE reachability in CM-IDLE	69
5.5.3.2	UE reachability in CM-CONNECTED	70
5.6	Session Management	70
5.6.1	Overview	70
5.6.2	Interaction between AMF and SMF	72
5.6.3	Roaming	73
5.6.4	Single PDU Session with multiple PDU Session Anchors	74
5.6.4.1	General	74
5.6.4.2	Usage of an UL Classifier for a PDU Session	74
5.6.4.3	Usage of IPv6 multi-homing for a PDU Session	75
5.6.5	Support for Local Area Data Network	77
5.6.6	Secondary authentication/authorization by a DN-AAA server during the establishment of a PDU Session	79
5.6.7	Application Function influence on traffic routing	80
5.6.8	Selective activation and deactivation of UP connection of existing PDU Session	85
5.6.9	Session and Service Continuity	86
5.6.9.1	General	86
5.6.9.2	SSC mode	86
5.6.9.2.1	SSC Mode 1	86
5.6.9.2.2	SSC Mode 2	86
5.6.9.2.3	SSC Mode 3	86
5.6.9.3	SSC mode selection	87
5.6.10	Specific aspects of different PDU Session types	87
5.6.10.1	Support of IP PDU Session type	87
5.6.10.2	Support of Ethernet PDU Session type	88
5.6.10.3	Support of Unstructured PDU Session type	89
5.6.11	UE presence in Area of Interest reporting usage by SMF	90
5.6.12	Use of Network Instance	91
5.6.13	Always-on PDU session	91
5.7	QoS model	92
5.7.1	General Overview	92
5.7.1.1	QoS Flow	92
5.7.1.2	QoS Profile	92
5.7.1.3	Control of QoS Flows	93
5.7.1.4	QoS Rules	93
5.7.1.5	QoS Flow mapping	94
5.7.1.6	DL traffic	95
5.7.1.7	UL Traffic	96
5.7.1.8	AMBR/MFBR enforcement and rate limitation	96
5.7.1.9	Precedence Value	96
5.7.2	5G QoS Parameters	97
5.7.2.1	5QI	97
5.7.2.2	ARP	97
5.7.2.3	RQA	97
5.7.2.4	Notification control	97
5.7.2.5	Flow Bit Rates	98
5.7.2.6	Aggregate Bit Rates	98
5.7.2.7	Default values	99
5.7.2.8	Maximum Packet Loss Rate	99
5.7.3	5G QoS characteristics	99
5.7.3.1	General	99
5.7.3.2	Resource Type	100
5.7.3.3	Priority Level	100
5.7.3.4	Packet Delay Budget	100
5.7.3.5	Packet Error Rate	101
5.7.3.6	Averaging Window	101
5.7.3.7	Maximum Data Burst Volume	101

5.7.4	Standardized 5QI to QoS characteristics mapping.....	101
5.7.5	Reflective QoS.....	104
5.7.5.1	General.....	104
5.7.5.2	UE Derived QoS Rule.....	105
5.7.5.3	Reflective QoS Control.....	105
5.7.6	Packet Filter Set.....	107
5.7.6.1	General.....	107
5.7.6.2	IP Packet Filter Set.....	107
5.7.6.3	Ethernet Packet Filter Set.....	107
5.8	User Plane Management.....	108
5.8.1	General.....	108
5.8.2	Functional Description.....	108
5.8.2.1	General.....	108
5.8.2.2	UE IP Address Management.....	108
5.8.2.2.1	General.....	108
5.8.2.2.2	Routing rules configuration.....	110
5.8.2.2.3	The procedure of Stateless IPv6 Address Autoconfiguration.....	110
5.8.2.3	Management of CN Tunnel Info.....	110
5.8.2.3.1	General.....	110
5.8.2.3.2	Management of CN Tunnel Info in the SMF.....	111
5.8.2.3.3	Management of CN Tunnel Info in the UPF.....	111
5.8.2.4	Traffic Detection.....	111
5.8.2.4.1	General.....	111
5.8.2.4.2	Traffic Detection Information.....	111
5.8.2.5	Control of User Plane Forwarding.....	112
5.8.2.6	Charging and Usage Monitoring Handling.....	113
5.8.2.6.1	General.....	113
5.8.2.6.2	Activation of Usage Reporting in UPF.....	113
5.8.2.6.3	Reporting of Usage Information towards SMF.....	113
5.8.2.7	PDU Session and QoS Flow Policing.....	114
5.8.2.8	PCC Related Functions.....	114
5.8.2.8.1	Activation/Deactivation of predefined PCC rules.....	114
5.8.2.8.2	Enforcement of Dynamic PCC Rules.....	115
5.8.2.8.3	Redirection.....	115
5.8.2.8.4	Support of PFD Management.....	115
5.8.2.9	Functionality of Sending of "End marker".....	116
5.8.2.9.0	Introduction.....	116
5.8.2.9.1	UPF Constructing the "End marker" Packets.....	116
5.8.2.9.2	SMF Constructing the "End marker" Packets.....	116
5.8.2.10	UP Tunnel Management.....	117
5.8.2.11	Parameters for N4 session management.....	117
5.8.2.11.1	General.....	117
5.8.2.11.2	N4 Session Context.....	118
5.8.2.11.3	Packet Detection Rule.....	118
5.8.2.11.4	QoS Enforcement Rule.....	118
5.8.2.11.5	Usage Reporting Rule.....	120
5.8.2.11.6	Forwarding Action Rule.....	122
5.8.2.11.7	Usage Report generated by UPF.....	125
5.8.2.12	Reporting of the UE MAC addresses used in a PDU Session.....	125
5.8.3	Explicit Buffer Management.....	126
5.8.3.1	General.....	126
5.8.3.2	Buffering at UPF.....	126
5.8.3.3	Buffering at SMF.....	126
5.8.4	SMF Pause of Charging.....	126
5.9	Identifiers.....	127
5.9.1	General.....	127
5.9.2	Subscription Permanent Identifier.....	127
5.9.2a	Subscription Concealed Identifier.....	127
5.9.3	Permanent Equipment Identifier.....	127
5.9.4	5G Globally Unique Temporary Identifier.....	127
5.9.5	AMF Name.....	128
5.9.6	Data Network Name (DNN).....	128

5.9.7	Internal-Group Identifier.....	128
5.9.8	Generic Public Subscription Identifier.....	129
5.9.9	AMF UE NGAP ID	129
5.10	Security aspects	129
5.10.1	General.....	129
5.10.2	Security Model for non-3GPP access	129
5.10.2.1	Signalling Security	129
5.10.3	PDU Session User Plane Security.....	129
5.11	Support for Dual Connectivity, Multi-Connectivity.....	131
5.11.1	Support for Dual Connectivity.....	131
5.12	Charging.....	132
5.12.1	General.....	132
5.12.2	Usage Data Reporting for Secondary RAT.....	132
5.12.3	Secondary RAT Periodic Usage Data Reporting Procedure.....	132
5.13	Support for Edge Computing.....	132
5.14	Policy Control	133
5.15	Network slicing	133
5.15.1	General.....	133
5.15.2	Identification and selection of a Network Slice: the S-NSSAI and the NSSAI.....	134
5.15.2.1	General	134
5.15.2.2	Standardised SST values	135
5.15.3	Subscription aspects.....	135
5.15.4	UE NSSAI configuration and NSSAI storage aspects	136
5.15.4.1	General	136
5.15.4.1.1	UE Network Slice configuration	136
5.15.4.1.2	Mapping of S-NSSAI values in the Allowed NSSAI and in the Requested NSSAI to the S-NSSAI values used in the HPLMN.....	137
5.15.4.2	Update of UE Network Slice configuration.....	138
5.15.5	Detailed Operation Overview	138
5.15.5.1	General	138
5.15.5.2	Selection of a Serving AMF supporting the Network Slices.....	138
5.15.5.2.1	Registration to a set of Network Slices.....	138
5.15.5.2.2	Modification of the Set of Network Slice(s) for a UE.....	141
5.15.5.2.3	AMF Re-allocation due to Network Slice(s) Support.....	142
5.15.5.3	Establishing a PDU Session in a Network Slice	143
5.15.6	Network Slicing Support for Roaming	144
5.15.7	Network slicing and Interworking with EPS	144
5.15.7.1	General	144
5.15.7.2	Idle mode aspects.....	145
5.15.7.3	Connected mode aspects	145
5.15.8	Configuration of Network Slice availability in a PLMN.....	145
5.16	Support for specific services	147
5.16.1	Public Warning System	147
5.16.2	SMS over NAS	147
5.16.2.1	General	147
5.16.2.2	SMS over NAS transport	147
5.16.3	IMS support	147
5.16.3.1	General	147
5.16.3.2	IMS voice over PS Session Supported Indication over 3GPP access	147
5.16.3.2a	IMS voice over PS Session Supported Indication over non-3GPP access	148
5.16.3.3	Homogeneous support for IMS voice over PS Session supported indication	148
5.16.3.4	P-CSCF address delivery	149
5.16.3.5	Domain selection for UE originating sessions / calls.....	149
5.16.3.6	Terminating domain selection for IMS voice.....	149
5.16.3.7	UE's usage setting	150
5.16.3.8	Domain and Access Selection for UE originating SMS.....	150
5.16.3.8.1	UE originating SMS for IMS Capable UEs supporting SMS over IP	150
5.16.3.8.2	Access Selection for SMS over NAS	150
5.16.3.9	SMF support for P-CSCF restoration procedure.....	150
5.16.3.10	IMS Voice Service via EPS Fallback or RAT fallback in 5GS.....	150
5.16.4	Emergency Services.....	151
5.16.4.1	Introduction.....	151

5.16.4.2	Architecture Reference Model for Emergency Services	153
5.16.4.3	Mobility Restrictions and Access Restrictions for Emergency Services.....	153
5.16.4.4	Reachability Management.....	153
5.16.4.5	SMF and UPF selection function for Emergency Services	154
5.16.4.6	QoS for Emergency Services	154
5.16.4.7	PCC for Emergency Services.....	154
5.16.4.8	IP Address Allocation	154
5.16.4.9	Handling of PDU Sessions for Emergency Services.....	154
5.16.4.9a	Handling of PDU Sessions for normal services for Emergency Registered UEs.....	154
5.16.4.10	Support of eCall Only Mode	155
5.16.4.11	Emergency Services Fallback	155
5.16.5	Multimedia Priority Services	155
5.16.6	Mission Critical Services	157
5.17	Interworking and Migration	158
5.17.1	Support for Migration from EPC to 5GC.....	158
5.17.1.1	General	158
5.17.1.2	User Plane management to support interworking with EPS.....	159
5.17.2	Interworking with EPC	159
5.17.2.1	General	159
5.17.2.2	Interworking Procedures with N26 interface	161
5.17.2.2.1	General	161
5.17.2.2.2	Mobility for UEs in single-registration mode.....	162
5.17.2.3	Interworking Procedures without N26 interface	163
5.17.2.3.1	General	163
5.17.2.3.2	Mobility for UEs in single-registration mode.....	164
5.17.2.3.3	Mobility for UEs in dual-registration mode.....	165
5.17.2.3.4	Redirection for UEs in connected state	166
5.17.2.4	Mobility between 5GS and GERAN/UTRAN	166
5.17.3	Interworking with EPC in presence of Non-3GPP PDU Sessions.....	166
5.17.4	Network sharing support and interworking between EPS and 5GS.....	166
5.18	Network Sharing	167
5.18.1	General concepts.....	167
5.18.2	Broadcast system information for network sharing	167
5.18.2a	PLMN list handling for network sharing	167
5.18.3	Network selection by the UE	168
5.18.4	Network selection by the network	168
5.18.5	Network Sharing and Network Slicing.....	168
5.19	Control Plane Load Control, Congestion and Overload Control.....	169
5.19.1	General.....	169
5.19.2	TNLA Load Balancing and TNLA Load Re-Balancing	169
5.19.3	AMF Load Balancing	169
5.19.4	AMF Load Re-Balancing.....	169
5.19.5	AMF Control Of Overload	170
5.19.5.1	General	170
5.19.5.2	AMF Overload Control	170
5.19.6	SMF Overload Control	171
5.19.7	NAS level congestion control	171
5.19.7.1	General	171
5.19.7.2	General NAS level congestion control.....	171
5.19.7.3	DNN based congestion control	172
5.19.7.4	S-NSSAI based congestion control	173
5.19.7.5	Group specific NAS level congestion control	174
5.20	External Exposure of Network Capability.....	174
5.21	Architectural support for virtualized deployments	175
5.21.0	General.....	175
5.21.1	Architectural support for N2.....	175
5.21.1.1	TNL associations.....	175
5.21.1.2	NGAP UE-TNLA-binding	175
5.21.1.3	N2 TNL association selection	175
5.21.2	AMF Management.....	176
5.21.2.1	AMF Addition/Update	176
5.21.2.2	AMF planned removal procedure	176

5.21.2.2.1	AMF planned removal procedure with UDSF deployed	176
5.21.2.2.2	AMF planned removal procedure without UDSF.....	178
5.21.2.3	Procedure for AMF Auto-recovery	179
5.22	System Enablers for priority mechanism.....	181
5.22.1	General.....	181
5.22.2	Subscription-related Priority Mechanisms	181
5.22.3	Invocation-related Priority Mechanisms	182
5.22.4	QoS Mechanisms applied to established QoS Flows.....	183
5.23	Supporting for Asynchronous Type Communication.....	183
5.24	3GPP PS Data Off	183
5.25	Support of OAM Features	184
5.25.1	Support of Tracing: Signalling Based Activation/Deactivation of Tracing	184
5.26	Configuration Transfer Procedure.....	185
5.26.1	Architecture Principles for Configuration Transfer	185
5.26.2	Addressing, routing and relaying.....	186
5.26.2.1	Addressing	186
5.26.2.2	Routing.....	186
5.26.2.3	Relaying	186
6	Network Functions	186
6.1	General	186
6.2	Network Function Functional description	186
6.2.1	AMF.....	186
6.2.2	SMF	187
6.2.3	UPF.....	188
6.2.4	PCF	188
6.2.5	NEF.....	189
6.2.5.1	Support for CAPIF	189
6.2.6	NRF	189
6.2.7	UDM.....	191
6.2.8	AUSF	191
6.2.9	N3IWF	191
6.2.10	AF	192
6.2.11	UDR.....	192
6.2.12	UDSF	192
6.2.13	SMSF	193
6.2.14	NSSF.....	193
6.2.15	5G-EIR.....	193
6.2.16	LMF	193
6.2.17	SEPP	193
6.2.18	Network Data Analytics Function (NWDAF)	194
6.3	Principles for Network Function and Network Function Service discovery and selection	194
6.3.1	General.....	194
6.3.2	SMF discovery and selection.....	195
6.3.3	User Plane Function Selection.....	196
6.3.3.1	Overview.....	196
6.3.3.2	SMF Provisioning of available UPF(s).....	196
6.3.3.3	Selection of an UPF for a particular PDU Session.....	196
6.3.4	AUSF discovery and selection.....	197
6.3.5	AMF discovery and selection	198
6.3.6	N3IWF selection.....	199
6.3.6.1	General	199
6.3.6.2	Stand-alone N3IWF selection	200
6.3.6.3	Combined N3IWF/ePDG Selection	200
6.3.7	PCF discovery and selection	201
6.3.7.0	General principles	201
6.3.7.1	PCF discovery and selection for a UE or a PDU Session	201
6.3.7.2	Providing policy requirements that apply to multiple UE and hence to multiple PCF.....	202
6.3.7.3	Binding an AF request targeting an IP address to the relevant PCF	202
6.3.8	UDM discovery and selection.....	202
6.3.9	UDR discovery and selection.....	203
6.3.10	SMSF discovery and selection.....	203

6.3.11	CHF discovery and selection	204
7	Network Function Services and descriptions	204
7.1	Network Function Service Framework.....	204
7.1.1	General.....	204
7.1.2	NF Service Consumer - NF Service Producer interactions.....	204
7.1.3	Network Function Service discovery.....	205
7.1.4	Network Function Service Authorization	205
7.1.5	Network Function and Network Function Service registration and de-registration.....	206
7.2	Network Function Services	206
7.2.1	General.....	206
7.2.2	AMF Services	207
7.2.3	SMF Services.....	208
7.2.4	PCF Services.....	208
7.2.5	UDM Services	209
7.2.6	NRF Services	209
7.2.7	AUSF Services.....	209
7.2.8	NEF Services	210
7.2.9	SMSF Services.....	210
7.2.10	UDR Services	210
7.2.11	5G-EIR Services	211
7.2.12	NWDAF Services	211
7.2.13	UDSF Services.....	211
7.2.14	NSSF Services	211
7.2.15	BSF Services.....	212
7.2.16	LMF Services.....	212
7.2.17	CHF Services	212
7.3	Exposure.....	212
8	Control and User Plane Protocol Stacks.....	213
8.1	General	213
8.2	Control Plane Protocol Stacks	213
8.2.1	Control Plane Protocol Stacks between the 5G-AN and the 5G Core: N2	213
8.2.1.1	General	213
8.2.1.2	AN - AMF.....	214
8.2.1.3	AN - SMF	214
8.2.2	Control Plane Protocol Stacks between the UE and the 5GC.....	214
8.2.2.1	General	214
8.2.2.2	UE - AMF	216
8.2.2.3	UE - SMF	216
8.2.3	Control Plane Protocol Stacks between the network functions in 5GC	217
8.2.3.1	The Control Plane Protocol Stack for the service based interface.....	217
8.2.3.2	The Control Plane protocol stack for the N4 interface between SMF and UPF.....	217
8.2.4	Control Plane for untrusted non 3GPP Access	217
8.3	User Plane Protocol Stacks.....	218
8.3.1	User Plane Protocol Stack for a PDU Session	218
8.3.2	User Plane for untrusted non 3GPP Access	220
Annex A (informative):	Relationship between Service-Based Interfaces and Reference Points...	221
Annex B (normative):	Mapping between temporary identities	223
Annex C (informative):	Guidelines and Principles for Compute-Storage Separation.....	224
Annex D (informative):	Change history	225
History		234

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

ITEH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/2df5b0be-cfe1-439b-b675-6b69fd70de42/etsi-ts-123-501-v15.4.0-2019-03>

1 Scope

The present document defines the Stage 2 system architecture for the 5G System. The 5G System provides data connectivity and services.

This specification covers both roaming and non-roaming scenarios in all aspects, including interworking between 5GS and EPS, mobility within 5GS, QoS, policy control and charging, authentication and in general 5G System wide features e.g. SMS, Location Services, Emergency Services.

ITU-T Recommendation I.130 [11] describes a three-stage method for characterisation of telecommunication services, and ITU-T Recommendation Q.65 [12] defines Stage 2 of the method.

TS 23.502 [3] contains the stage 2 procedures and flows for 5G System and it is a companion specification to this specification.

TS 23.503 [45] contains the stage 2 Policy Control and Charging architecture for 5G System and it is a companion specification to this specification.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 22.261: "Service requirements for next generation new services and markets; Stage 1".
- [3] 3GPP TS 23.502: "Procedures for the 5G System; Stage 2".
- [4] 3GPP TS 23.203: "Policies and Charging control architecture; Stage 2".
- [5] 3GPP TS 23.040: "Technical realization of the Short Message Service (SMS); Stage 2".
- [6] 3GPP TS 24.011: "Point-to-Point (PP) Short Message Service (SMS) support on mobile radio interface: Stage 3".
- [7] IETF RFC 7157: "IPv6 Multihoming without Network Address Translation".
- [8] IETF RFC 4191: "Default Router Preferences and More-Specific Routes".
- [9] IETF RFC 2131: "Dynamic Host Configuration Protocol".
- [10] IETF RFC 4862: "IPv6 Stateless Address Autoconfiguration".
- [11] ITU-T Recommendation I.130: "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [12] ITU-T Recommendation Q.65: "The unified functional methodology for the characterization of services and network capabilities".
- [13] 3GPP TS 24.301: "Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS): Stage 3".
- [14] IETF RFC 3736: "Stateless DHCP Service for IPv6".