



**5G;
NR;**

**Base Station (BS) conformance testing
Part 1: Conducted conformance testing
(3GPP TS 38.141-1 version 15.0.0 Release 15)**



ReferenceDTS/TSGR-0438141-1vf00

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope	13
2 References	13
3 Definitions, symbols and abbreviations	15
3.1 Definitions	15
3.2 Symbols.....	17
3.3 Abbreviations	18
4 General conducted test conditions and declarations.....	20
4.1 Measurement uncertainties and test requirements	20
4.1.1 General.....	20
4.1.2 Acceptable uncertainty of Test System.....	20
4.1.2.1 General	20
4.1.2.2 Measurement of transmitter	21
4.1.2.3 Measurement of receiver.....	22
4.1.2.4 Measurement of performance requirements.....	25
4.1.3 Interpretation of measurement results.....	25
4.2 Conducted requirement reference points	25
4.2.1 BS type 1-C	25
4.2.2 BS type 1-H.....	26
4.3 Base station classes	27
4.4 Regional requirements.....	27
4.5 BS configurations	28
4.5.1 BS type 1-C	28
4.5.1.1 Transmit configurations	28
4.5.1.1.1 General	28
4.5.1.1.2 Transmission with multiple transmitter antenna connectors.....	28
4.5.1.2 Receive configurations.....	29
4.5.1.2.1 General	29
4.5.1.2.2 Reception with multiple receiver antenna connectors, receiver diversity.....	29
4.5.1.3 Duplexers	29
4.5.1.4 Power supply options	30
4.5.1.5 Ancillary RF amplifiers.....	30
4.5.2 BS type 1-H.....	31
4.5.2.1 Transmit configurations	31
4.5.2.2 Receive configurations.....	31
4.5.2.3 Power supply options	32
4.6 Manufacturer declarations	32
4.7 Test configurations	37
4.7.1 General.....	37
4.7.2 Test signal used to build Test Configurations.....	37
4.7.3 NRTC1: Contiguous spectrum operation.....	37
4.7.3.1 NRTC1 generation	37
4.7.3.2 NRTC1 power allocation	37
4.7.4 NRTC2: Contiguous CA occupied bandwidth.....	37
4.7.4.1 NRTC2 generation	38
4.7.4.2 NRTC2 power allocation	38
4.7.5 NRTC3: Non-contiguous spectrum operation	38
4.7.5.1 NRTC3 generation	38
4.7.5.2 NRTC3 power allocation	39
4.7.6 NRTC4: Multi-band test configuration for full carrier allocation.....	39
4.7.6.1 NRTC4 generation	39

4.7.6.2	NRTC4 power allocation	39
4.7.7	NRTC5: Multi-band test configuration with high PSD per carrier	39
4.7.7.1	NRTC5 generation	39
4.7.7.2	NRTC5 power allocation	40
4.8	Applicability of requirements	40
4.8.1	General	40
4.8.2	Requirement set applicability	40
4.8.3	Applicability of test configurations for single-band operation	41
4.8.4	Applicability of test configurations for multi-band operation	42
4.9	RF channels and test models	43
4.9.1	RF channels	43
4.9.2	Test models	44
4.9.2.1	General	44
4.9.2.2	NR FR1 test models	44
4.9.2.2.1	NR FR1 test model 1.1 (NR-FR1-TM1.1)	45
4.9.2.2.2	NR FR1 test model 1.2 (NR-FR1-TM1.2)	46
4.9.2.2.3	NR FR1 test model 2 (NR-FR1-TM2)	46
4.9.2.2.4	NR FR1 test model 2a (NR-FR1-TM2a)	47
4.9.2.2.5	NR FR1 test model 3.1 (NR-FR1-TM3.1)	47
4.9.2.2.6	NR FR1 test model 3.1a (NR-FR1-TM3.1a)	47
4.9.2.2.7	NR FR1 test model 3.2 (NR-FR1-TM3.2)	48
4.9.2.2.8	NR FR1 test model 3.3 (NR-FR1-TM3.3)	48
4.9.2.3	Data content of Physical channels and Signals for NR-FR1-TM	49
4.9.2.3.1	PDCCH	49
4.9.2.3.2	PDSCH	49
4.10	Requirements for contiguous and non-contiguous spectrum	50
4.11	Requirements for BS capable of multi-band operation	50
4.12	Format and interpretation of tests	51
5	Operating bands and channel arrangement	53
6	Conducted transmitter characteristics	54
6.1	General	54
6.1.1	BS type 1-C	54
6.1.2	BS type 1-H	54
6.2	Base station output power	54
6.2.1	Definition and applicability	54
6.2.2	Minimum requirement	55
6.2.3	Test purpose	55
6.2.4	Method of test	55
6.2.4.1	Initial conditions	55
6.2.4.2	Procedure	55
6.2.5	Test requirement	56
6.3	Output power dynamics	56
6.3.1	General	56
6.3.2	RE power control dynamic range	56
6.3.2.1	Definition and applicability	56
6.3.2.2	Minimum requirement	56
6.3.2.3	Test purpose	56
6.3.3	Total power dynamic range	56
6.3.3.1	Definition and applicability	56
6.3.3.2	Minimum requirement	56
6.3.3.3	Test purpose	57
6.3.3.4	Method of test	57
6.3.3.4.1	Initial conditions	57
6.3.3.4.2	Procedure	57
6.3.3.5	Test requirements	57
6.4	Transmit ON/OFF power	58
6.4.1	Transmitter OFF power	58
6.4.1.1	Definition and applicability	58
6.4.1.2	Minimum requirement	58
6.4.1.3	Test purpose	58

6.4.1.4	Method of test	58
6.4.1.5	Test requirements	58
6.4.2	Transmitter transient period	59
6.4.2.1	Definition and applicability	59
6.4.2.2	Minimum requirement	59
6.4.2.3	Test purpose	59
6.4.2.4	Method of test	59
6.4.2.4.1	Initial conditions	59
6.4.2.4.2	Procedure	60
6.4.2.5	Test requirements	60
6.5	Transmitted signal quality	60
6.5.1	General	60
6.5.2	Frequency error	60
6.5.2.1	Definition and applicability	60
6.5.2.2	Minimum Requirement	61
6.5.2.3	Test purpose	61
6.5.2.4	Method of test	61
6.5.2.5	Test Requirements	61
6.5.3	Modulation quality	61
6.5.3.1	Definition and applicability	61
6.5.3.2	Minimum Requirement	61
6.5.3.3	Test purpose	61
6.5.3.4	Method of test	61
6.5.3.4.1	Initial conditions	61
6.5.3.4.2	Procedure	62
6.5.3.5	Test requirements	62
6.5.4	Time alignment error	64
6.5.4.1	Definition and applicability	64
6.5.4.2	Minimum requirement	64
6.5.4.3	Test purpose	64
6.5.4.4	Method of test	64
6.5.4.4.1	Initial conditions	64
6.5.4.4.2	Procedure	64
6.5.4.5	Test requirement	65
6.6	Unwanted emissions	65
6.6.1	General	65
6.6.2	Occupied bandwidth	66
6.6.2.1	Definition and applicability	66
6.6.2.2	Minimum Requirements	66
6.6.2.3	Test purpose	66
6.6.2.4	Method of test	66
6.6.2.4.1	Initial conditions	66
6.6.2.4.2	Procedure	67
6.6.2.5	Test requirements	67
6.6.3	Adjacent Channel Leakage Power Ratio (ACLR)	67
6.6.3.1	Definition and applicability	67
6.6.3.2	Minimum requirement	68
6.6.3.3	Test purpose	68
6.6.3.4	Method of test	68
6.6.3.4.1	Initial conditions	68
6.6.3.4.2	Procedure	68
6.6.3.5	Test requirements	69
6.6.3.5.1	General requirements	69
6.6.3.5.2	Limits and <i>basic limits</i>	69
6.6.3.5.3	<i>BS type 1-C</i>	71
6.6.3.5.4	<i>BS type 1-H</i>	72
6.6.4	Operating band unwanted emissions	72
6.6.4.1	Definition and applicability	72
6.6.4.2	Minimum requirement	73
6.6.4.3	Test purpose	74
6.6.4.4	Method of test	74
6.6.4.4.1	Initial conditions	74

6.6.4.4.2	Procedure.....	74
6.6.4.5	Test requirements.....	75
6.6.4.5.1	General requirements.....	75
6.6.4.5.2	Basic limits for Wide Area BS (Category A).....	75
6.6.4.5.3	Basic limits for Wide Area BS (Category B).....	76
6.6.4.5.3.1	Category B requirements (Option 1).....	76
6.6.4.5.3.2	Category B requirements (Option 2).....	77
6.6.4.5.4	Basic limits for Medium Range BS (Category A and B).....	78
6.6.4.5.5	Basic limits for Local Area BS (Category A and B).....	80
6.6.4.5.6	Basic limits for additional requirements.....	81
6.6.4.5.6.1	Limits in FCC Title 47.....	81
6.6.4.5.6.2	Protection of DTT.....	81
6.6.4.5.7	BS type 1-C.....	81
6.6.4.5.8	BS type 1-H.....	81
6.6.5	Transmitter spurious emissions.....	82
6.6.5.1	Definition and applicability.....	82
6.6.5.2	Minimum requirement.....	82
6.6.5.3	Test purpose.....	82
6.6.5.4	Method of test.....	82
6.6.5.4.1	Initial conditions.....	82
6.6.5.4.2	Procedure.....	83
6.6.5.5	Test requirements.....	83
6.6.5.5.1	Basic limits.....	83
6.6.5.5.1.1	Tx spurious emissions.....	83
6.6.5.5.1.2	Protection of the BS receiver of own or different BS.....	84
6.6.5.5.1.3	Additional spurious emissions requirements.....	84
6.6.5.5.1.4	Co-location with other base stations.....	91
6.6.5.5.3	BS type 1-C.....	95
6.6.5.5.4	BS type 1-H.....	96
6.7	Transmitter intermodulation.....	96
6.7.1	Definition and applicability.....	96
6.7.2	Minimum requirement.....	96
6.7.3	Test purpose.....	96
6.7.4	Method of test.....	97
6.7.4.1	Initial conditions.....	97
6.7.4.2	Procedure.....	97
6.7.5	Test requirements.....	98
6.7.5.1	BS type 1-C.....	98
6.7.5.1.1	Co-location minimum requirements.....	98
6.7.5.1.2	Additional requirements.....	99
6.7.5.2	BS type 1-H.....	99
6.7.5.2.1	Co-location minimum requirements.....	99
6.7.5.2.2	Intra-system minimum requirements.....	99
6.7.5.2.3	Additional requirements.....	99
7	Conducted receiver characteristics.....	100
7.1	General.....	100
7.2	Reference sensitivity level.....	100
7.2.1	Definition and applicability.....	100
7.2.2	Minimum requirement.....	100
7.2.3	Test purpose.....	100
7.2.4	Method of test.....	100
7.2.4.1	Initial conditions.....	100
7.2.4.2	Procedure.....	101
7.2.5	Test requirements.....	101
7.3	Dynamic range.....	102
7.3.1	Definition and applicability.....	102
7.3.2	Minimum requirement.....	102
7.3.3	Test purpose.....	103
7.3.4	Method of test.....	103
7.3.4.1	Initial conditions.....	103
7.3.4.2	Procedure.....	103

7.3.5	Test requirements.....	103
7.4	In-band selectivity and blocking	106
7.4.1	Adjacent Channel Selectivity (ACS)	106
7.4.1.1	Definition and applicability.....	106
7.4.1.2	Minimum requirement	106
7.4.1.3	Test purpose	107
7.4.1.4	Method of test	107
7.4.1.4.1	Initial conditions.....	107
7.4.1.4.2	Procedure.....	107
7.4.1.5	Test requirements.....	107
7.4.2	In-band blocking.....	108
7.4.2.1	Definition and applicability.....	108
7.4.2.2	Minimum requirement	108
7.4.2.3	Test purpose	109
7.4.2.4	Method of test	109
7.4.2.4.1	Initial conditions.....	109
7.4.2.4.2	Procedure for general blocking.....	109
7.4.2.4.3	Procedure for narrowband blocking	109
7.4.2.5	Test requirements.....	110
7.5	Out-of-band blocking	112
7.5.1	Definition and applicability	112
7.5.2	Minimum requirement	112
7.5.3	Test purpose.....	112
7.5.4	Method of test	113
7.5.4.1	Initial conditions	113
7.5.4.2	Procedure	113
7.5.5	Test requirements.....	113
7.5.5.1	General requirements	113
7.5.5.2	Co-location requirements	114
7.6	Receiver spurious emissions.....	114
7.6.1	Definition and applicability	114
7.6.2	Minimum requirement	115
7.6.3	Test purpose.....	115
7.6.4	Method of test	115
7.6.4.1	Initial conditions	115
7.6.4.2	Procedure	115
7.6.5	Test requirements.....	116
7.6.5.1	Basic limits.....	116
7.6.5.2	BS type 1-C.....	116
7.6.5.3	BS type 1-H.....	116
7.7	Receiver intermodulation	117
7.7.1	Definition and applicability	117
7.7.2	Minimum requirement	117
7.7.3	Test purpose.....	117
7.7.4	Method of test	117
7.7.4.1	Initial conditions	117
7.7.4.2	Procedure	117
7.7.5	Test requirements.....	118
7.8	In-channel selectivity	121
7.8.1	Definition and applicability	121
7.8.2	Minimum requirement	121
7.8.3	Test purpose.....	121
7.8.4	Method of test	121
7.8.4.1	Initial conditions	121
7.8.4.2	Procedure	121
7.8.5	Test requirements.....	121
8	Conducted performance characteristics.....	125
8.1	General	125
8.2	Performance requirements for PUSCH	125
8.2.1	Performance requirements for PUSCH with transmission precoding disabled.....	125
8.2.1.1	Definition and applicability.....	125

8.2.1.2	Minimum Requirement	125
8.2.1.3	Test Purpose	125
8.2.1.4	Method of test	126
8.2.1.4.1	Initial Conditions	126
8.2.1.4.2	Procedure	126
8.2.1.5	Test Requirement	127
8.2.2	Performance requirements for PUSCH with transmission precoding enabled	133
8.2.2.1	Definition and applicability	133
8.2.2.2	Minimum Requirement	133
8.2.2.3	Test Purpose	133
8.2.2.4	Method of test	134
8.2.2.4.1	Initial Conditions	134
8.2.2.4.2	Procedure	134
8.2.2.5	Test Requirement	135
8.3	Performance requirements for PUCCH	135
8.3.1	Performance requirements for PUCCH format 0	135
8.3.1.1	Definition and applicability	135
8.3.1.2	Minimum Requirement	135
8.3.1.3	Test purpose	135
8.3.1.4	Method of test	136
8.3.1.4.1	Initial conditions	136
8.3.1.4.2	Procedure	136
8.3.1.5	Test Requirement	136
8.3.2	Performance requirements for PUCCH format 1	137
8.3.2.1	NACK to ACK detection	137
8.3.2.1.1	Definition and applicability	137
8.3.2.1.2	Minimum Requirement	137
8.3.2.1.3	Test purpose	137
8.3.2.1.4	Method of test	137
8.3.2.1.4.1	Initial Conditions	137
8.3.2.1.4.2	Procedure	138
8.3.2.1.5	Test Requirement	138
8.3.2.2	ACK missed detection	139
8.3.2.2.1	Definition and applicability	139
8.3.2.2.2	Minimum Requirement	139
8.3.2.2.3	Test purpose	139
8.3.2.2.4	Method of test	139
8.3.2.2.4.1	Initial Conditions	139
8.3.2.2.4.2	Procedure	140
8.3.2.2.5	Test Requirement	140
8.3.3	Performance requirements for PUCCH format 2	141
8.3.3.1	ACK missed detection	141
8.3.3.1.1	Definition and applicability	141
8.3.3.1.2	Minimum requirements	141
8.3.3.1.3	Test purpose	141
8.3.3.1.4	Method of test	142
8.3.3.1.4.1	Initial Condition	142
8.3.3.1.4.2	Procedure	142
8.3.3.1.5	Test requirements	142
8.3.3.2	UCI BLER performance requirements	143
8.3.3.2.1	Definition and applicability	143
8.3.3.2.2	Minimum Requirement	143
8.3.3.2.3	Test purpose	143
8.3.3.2.4	Method of test	143
8.3.3.2.4.1	Initial Condition	143
8.3.3.2.4.2	Procedure	143
8.3.3.2.5	Test requirements	144
8.3.4	Performance requirements for PUCCH format 3	145
8.3.4.1	Definition and applicability	145
8.3.4.2	Minimum requirement	145
8.3.4.3	Test purpose	145
8.3.4.4	Method of test	145

8.3.4.4.1	Initial conditions	145
8.3.4.4.2	Procedure	145
8.3.4.5	Test requirement	146
8.3.5	Performance requirements for PUCCH format 4	147
8.3.5.1	Definition and applicability	147
8.3.5.2	Minimum requirement	147
8.3.5.3	Test purpose	147
8.3.5.4	Method of test	147
8.3.5.4.1	Initial conditions	147
8.3.5.4.2	Procedure	148
8.3.5.5	Test requirement	148
8.4	Performance requirements for PRACH	149
8.4.1	PRACH false alarm probability and missed detection	149
8.4.1.1	Definition and applicability	149
8.4.1.2	Minimum requirement	150
8.4.1.3	Test purpose	150
8.4.1.4	Method of test	150
8.4.1.4.1	Initial conditions	150
8.4.1.4.2	Procedure	150
8.4.1.5	Test requirement	151
Annex A (normative):	Reference measurement channels	153
A.1	Fixed Reference Channels for receiver sensitivity and in-channel selectivity (QPSK, R=1/3)	153
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3)	153
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024)	154
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024)	157
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024)	159
A.6	PRACH test preambles	160
Annex B (normative):	Environmental requirements for the BS equipment	162
B.1	General	162
B.2	Normal test environment	162
B.3	Extreme test environment	162
B.3.1	Extreme temperature	162
B.4	Vibration	163
B.5	Power supply	163
B.6	Measurement of test environments	163
Annex C (informative):	Test tolerances and derivation of test requirements	164
C.1	Measurement of transmitter	164
C.2	Measurement of receiver	166
C.3	Measurement of performance requirements	166
Annex D (informative):	Measurement system set-up	167
D.1	BS type 1-C transmitter	167
D.1.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for BS type 1-C	167
D.1.2	Transmitter intermodulation for BS type 1-C	167
D.1.3	Time alignment error for BS type 1-C	168
D.2	BS type 1-C receiver	168
D.2.1	Reference sensitivity level for BS type 1-C	168
D.2.2	Dynamic range for BS type 1-C	169

D.2.3	In-channel selectivity for BS type 1-C	169
D.2.4	Adjacent Channel Selectivity (ACS) and narrowband blocking for BS type 1-C	170
D.2.5	Blocking characteristics for BS type 1-C	170
D.2.6	Receiver spurious emission for BS type 1-C	170
D.2.7	Intermodulation characteristics for BS type 1-C	171
D.3	BS type 1-H transmitter	171
D.3.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for BS type 1-H	171
D.3.2	Transmitter intermodulation for BS type 1-H	172
D.3.3	Transmitter spurious emissions for BS type 1-H	172
D.4	BS type 1-H receiver	174
D.4.1	Reference sensitivity level for BS type 1-H	174
D.4.2	Receiver dynamic range for BS type 1-H	174
D.4.3	Receiver adjacent channel selectivity and narrowband blocking for BS type 1-H	175
D.4.4	Receiver spurious emissions	175
D.4.5	Receiver In-channel selectivity for BS type 1-H	176
D.4.6	Receiver intermodulation for BS type 1-H	177
D.5	BS type 1-C performance requirements	177
D.5.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions	177
D.5.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	178
D.5.3	Performance requirements for PRACH in static conditions	178
D.6	BS type 1-H performance requirements	179
D.6.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions	179
D.6.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	179
D.6.3	Performance requirements for PRACH in static conditions	180
Annex E (normative):	Characteristics of interfering signals	181
Annex F (normative):	In-channel Tx tests	182
F.1	General	182
F.2	Reference point for measurement	182
F.3	Basic unit of measurement	182
F.4	Modified signal under test	183
F.5	Estimation of frequency offset	183
F.6	Estimation of time offset	183
F.7	Estimation of TX chain amplitude and frequency response parameters	184
F.8	Averaged EVM	185
Annex G (normative):	Propagation conditions	187
G.1	Static propagation condition	187
G.2	Multi-path fading propagation conditions	187
G.2.1	Delay profiles	187
G.2.1.1	Delay profiles for FR1	188
G.2.2	Combinations of channel model parameters	189
G.2.3	MIMO channel correlation matrices	189
G.2.3.1	MIMO correlation matrices using Uniform Linear Array	189
G.2.3.1.1	Definition of MIMO correlation matrices	189
G.2.3.1.2	MIMO correlation matrices at high, medium and low level	190
G.2.3.2	Multi-antenna channel models using cross polarized antennas	192
G.2.3.2.1	Definition of MIMO correlation matrices using cross polarized antennas	192
G.2.3.2.2	Spatial correlation matrices at UE and gNB sides	193

G.2.3.2.2.1	Spatial correlation matrices at UE side.....	193
G.2.3.2.2.2	Spatial correlation matrices at gNB side	193
G.2.3.2.3	MIMO correlation matrices using cross polarized antennas	193
Annex H (informative): Change history		194
History		199

iTech STANDARD PREVIEW
(standards.itech.ai)
Full standard:
<https://standards.itech.ai/catalog/standards/sist/863b296b-7800-4bae-82da-790dfb487206/etsi-ts-138-141-1-v15.0.0-2019-04>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/863b296b-7800-4bae-82da-790dfb487206/etsi-ts-138-141-1-v15.0.0-2019-04>