



**SLOVENSKI STANDARD**  
**oSIST prEN 300 718-1 V2.2.0:2021**  
**01-maj-2021**

---

**Lavinske žolne, ki delujejo v območju 457 kHz - Oddajno-sprejemni sistemi - 1. del:  
Harmonizirani standard za dostop do radijskega spektra**

Avalanche Beacons operating at 457 kHz - Transmitter-receiver systems - Part 1:  
Harmonised Standard for access to radio spectrum

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

**Ta slovenski standard je istoveten z: ETSI EN 300 718-1 V2.2.0 (2021-02)**

oSIST prEN 300 718-1 V2.2.0:2021  
<https://standards.iteh.ai/catalog/standards/sist/243f0417-e81c-423b-a336-733b5bbf009f/osist-pren-300-718-1-v2-2-0-2021>

**ICS:**

13.200	Preprečevanje nesreč in katastrof	Accident and disaster control
33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment

**oSIST prEN 300 718-1 V2.2.0:2021**      **en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[oSIST prEN 300 718-1 V2.2.0:2021](https://standards.iteh.ai/catalog/standards/sist/243f0417-e81c-423b-a336-733b5bbf009f/osist-pren-300-718-1-v2-2-0-2021)

<https://standards.iteh.ai/catalog/standards/sist/243f0417-e81c-423b-a336-733b5bbf009f/osist-pren-300-718-1-v2-2-0-2021>

Draft **ETSI EN 300 718-1** V2.2.0 (2021-02)



**Avalanche Beacons operating at 457 kHz;  
Transmitter-receiver systems;  
Part 1: Harmonised (Standard for access) to radio spectrum**

[oSIST prEN 300 718-1 V2.2.0:2021  
https://standards.iteh.ai/catalog/standards/sist/243f0417-e81c-423b-a336-733b5bbf009f/osist-pren-300-718-1-v2-2-0-2021](https://standards.iteh.ai/catalog/standards/sist/243f0417-e81c-423b-a336-733b5bbf009f/osist-pren-300-718-1-v2-2-0-2021)

---

**Reference**REN/ERM-TG28-559

---

---

**Keywords**harmonised standard, radio, testing

---

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

---

**Important notice**

---

<https://standards.iteh.ai/catalog/standards/sist/243f0417-e81c-423b-a336-735629b109/osist-pre-300-718-1-v2-2-0-2021>  
The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Modal verbs terminology.....	7
1 Scope .....	8
2 References .....	8
2.1 Normative references .....	8
2.2 Informative references.....	8
3 Definition of terms, symbols and abbreviations.....	9
3.1 Terms.....	9
3.2 Symbols.....	10
3.3 Abbreviations .....	10
4 Technical requirements specifications .....	11
4.1 Environmental profile.....	11
4.2 Conformance requirements for transmitters .....	11
4.2.1 Modulation and carrier keying.....	11
4.2.1.1 Applicability.....	11
4.2.1.2 Description.....	11
4.2.1.3 Limits .....	11
4.2.1.4 Conformance.....	12
4.2.2 Frequency error.....	12
4.2.2.1 Applicability.....	12
4.2.2.2 Description .....	12
4.2.2.3 Limits .....	12
4.2.2.4 Conformance.....	12
4.2.3 Output field strength (H-field).....	12
4.2.3.1 Applicability.....	12
4.2.3.2 Description .....	12
4.2.3.3 Limits .....	12
4.2.3.4 Conformance.....	12
4.2.4 Transmitter spurious emissions.....	13
4.2.4.1 Applicability.....	13
4.2.4.2 Description .....	13
4.2.4.3 Limits .....	13
4.2.4.4 Conformance.....	13
4.3 Conformance requirements for receiver parameters.....	13
4.3.1 Receiver sensitivity.....	13
4.3.1.1 Applicability.....	13
4.3.1.2 Description .....	13
4.3.1.3 Limits .....	14
4.3.1.4 Conformance.....	14
4.3.2 Receiver blocking .....	14
4.3.2.1 Applicability.....	14
4.3.2.2 Description .....	14
4.3.2.3 Limits .....	14
4.3.2.4 Conformance.....	14
4.3.3 Receiver spurious emissions .....	14
4.3.3.1 Applicability.....	14
4.3.3.2 Description .....	14
4.3.3.3 Limits .....	14
4.3.3.4 Conformance.....	15
5 Testing for compliance with technical requirements.....	15
5.1 Environmental conditions for testing .....	15
5.1.1 General.....	15
5.1.2 External test power source.....	15

5.1.3	Normal test conditions .....	16
5.1.3.1	Normal temperature and humidity .....	16
5.1.3.2	Normal test voltage .....	16
5.1.3.3	Normal test modulation .....	16
5.1.4	Extreme test conditions .....	16
5.1.4.1	Extreme temperatures .....	16
5.1.4.2	Extreme test voltages .....	16
5.2	Interpretation of test results .....	16
5.3	Compliance test procedures .....	17
5.3.1	Modulation and carrier keying .....	17
5.3.2	Frequency error .....	17
5.3.3	Output field strength (H-field) .....	17
5.3.4	Transmitter spurious emissions .....	17
5.3.4.1	Method of measurement Radiated H-field (< 30 MHz) .....	17
5.3.4.2	Method of measurement Effective radiated power (≥ 30 MHz) .....	18
5.3.5	Receiver sensitivity .....	18
5.3.6	Receiver blocking .....	19
5.3.7	Receiver spurious emissions .....	19
5.3.7.1	Method of measurement Radiated H-Field (< 30 MHz) .....	19
5.3.7.2	Method of measurement Effective radiated power (≥ 30 MHz) .....	19
5.4	Measuring receiver .....	20
<b>Annex A (informative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>21</b>
<b>Annex B (normative):</b>	<b>Radiated measurement .....</b>	<b>22</b>
B.0	General .....	22
B.1	Test sites and general arrangements for measurements involving the use of radiated fields .....	22
B.1.0	Test sites .....	22
B.1.1	Anechoic chamber .....	22
B.1.2	Anechoic chamber with a conductive ground plane .....	23
B.1.3	Open Area Test Site (OATS) .....	25
B.1.3.0	General for OATS .....	25
B.1.3.1	Measurements below 30 MHz .....	25
B.1.3.2	Measurements above 30 MHz .....	25
B.1.4	Test antenna .....	26
B.1.5	Substitution antenna .....	27
B.1.6	Measuring antenna .....	27
B.2	Guidance on the use of radiation test sites .....	27
B.2.0	General .....	27
B.2.1	Verification of the test site .....	27
B.2.2	Preparation of the EUT .....	27
B.2.3	Power supplies to the EUT .....	28
B.2.4	Range length .....	28
B.2.4.1	Far-field length above 30 MHz .....	28
B.2.4.2	Near-field and Far-field length below 30 MHz .....	29
B.2.5	Site preparation .....	29
B.3	Coupling of signals .....	29
B.3.1	General .....	29
B.3.2	Data signals .....	29
B.4	Standard test position .....	29
<b>Annex C (normative):</b>	<b>Spurious limits, radiated H-field at 10 m distances .....</b>	<b>30</b>
<b>Annex D (informative):</b>	<b>E-fields in the near field at low frequencies .....</b>	<b>31</b>
<b>Annex E (informative):</b>	<b>Justification of receiver requirements .....</b>	<b>34</b>
E.1	Introduction .....	34

E.2	Justification of receiver requirements chosen in the present document .....	34
<b>Annex F (informative):</b>	<b>Maximum Measurement uncertainty .....</b>	<b>37</b>
<b>Annex G (informative):</b>	<b>Determination and use of the measurement bandwidth.....</b>	<b>38</b>
<b>Annex H (informative):</b>	<b>Change history .....</b>	<b>39</b>
History .....		40

## **iTeh STANDARD PREVIEW** **(standards.iteh.ai)**

[oSIST prEN 300 718-1 V2.2.0:2021](https://standards.iteh.ai/catalog/standards/sist/243f0417-e81c-423b-a336-733b5bbf009f/osist-pren-300-718-1-v2-2-0-2021)

<https://standards.iteh.ai/catalog/standards/sist/243f0417-e81c-423b-a336-733b5bbf009f/osist-pren-300-718-1-v2-2-0-2021>

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

# Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 1 of a multi-part deliverable covering avalanche beacons operating at 457 kHz transmitter-receiver systems, as identified below:

- Part 1:** "Harmonised Standard for access to radio spectrum";
  - Part 2: "Harmonised Standard for features for emergency services";
  - Part 3: "Harmonized EN covering essential requirements of article 3.3e of the R&TTE Directive".
- NOTE: This part 3 is obsolete and has been replaced with ETSI EN 300 718-2 [2].

<b>Proposed national transposition dates</b>	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa



---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[oSIST prEN 300 718-1 V2.2.0:2021](#)

<https://standards.iteh.ai/catalog/standards/sist/243f0417-e81c-423b-a336-733b5bbf009f/osist-pren-300-718-1-v2-2-0-2021>

---

# 1 Scope

The present document specifies technical characteristics and methods of measurements for avalanche beacon transmitter-receiver systems operating from 456,9 kHz to 457,1 kHz. The frequency range 456,9 kHz to 457,1 kHz is EU wide harmonised for emergency detections of buried victims and valuable items devices according to [i.9].

An avalanche beacon comprises in one unit at least a transmitter/receiver including antenna and battery.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given in annex A.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CISPR 16-1-4 (2019): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements".  
<https://standards.itsi.it/catalog/standards/sist/243f0417-e81c-423b-a336-733b5bb009f0/sist-pren-300-718-1-v2-2-0-2021>
- [2] ETSI EN 300 718-2 (V2.1.1) (01-2018): "Avalanche Beacons operating at 457 kHz; Transmitter-receiver systems; Part 2: Harmonised Standard for features for emergency services".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] ANSI C63.5: "American National Standard for Electromagnetic Compatibility-Radiated Emission Measurements in Electromagnetic Interference (EMI) Control-Calibration of Antennas (9 kHz to 40 GHz)".

- [i.4] ETSI TR 100 028 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.5] ETSI TR 102 273-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
- [i.6] ETSI TR 102 273-3: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 3: Anechoic chamber with a ground plane".
- [i.7] ETSI TR 102 273-4: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 4: Open area test site".
- [i.8] ECC Report 284 (September 2018): "Feasibility studies of Person detection and collision avoidance applications in the 442.2-457.1 kHz range".
- [i.9] Commission Implementing decision (EU) 2019/1345 of 2 August 2019 amending Decision 2006/771/EC updating harmonised technical conditions in the area of radio spectrum use for short-range devices.
- [i.10] ERC Recommendation 70-03 (June 2019): "Relating to the use of Short Range Devices (SRD)".
- [i.11] ETSI EG 203 336 (V1.2.1): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.12] ETSI TS 103 361 (V1.1.1): "Short Range Devices (SRD) using Ultra Wide Band technology (UWB); Receiver technical requirements, parameters and measurement procedures to fulfil the requirements of the Directive 2014/53/EU".
- [i.13] ETSI TS 103 567 (V1.1.1): "Requirements on signal interferer handling".
- [i.14] Directive 2002/21/EC of the European Parliament and of the Council of 7 March 2002 on a common regulatory framework for electronic communications networks and services.
- [i.15] Directive 2009/140/EC of the European Parliament and of the Council of 25 November 2009 amending Directives 2002/21/EC on a common regulatory framework for electronic communications networks and services, 2002/19/EC on access to, and interconnection of, electronic communications networks and associated facilities, and 2002/20/EC on the authorisation of electronic communications networks and services.

---

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the following terms apply:

**avalanche beacons:** portable radio systems used for locating avalanche victims, for the purpose of direct rescue (i.e. for rescue by comrades not buried by the avalanche)

NOTE: An avalanche beacon has two operating modes: transmit and receive.

**E-field:** electric component of the field measured as voltage per unit length

**environmental profile:** range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

**H-field:** magnetic component of the field measured as current per unit length

**H-field test antenna:** electrically screened loop or equivalent antenna, with which the magnetic component of the field can be measured

**integral antenna:** antenna designed as an indispensable part of the equipment, with or without the use of an antenna connector

**measuring receiver:** selective voltmeter or a spectrum analyser

NOTE: See clause 5.4.

**radiated measurements:** measurements which involve the absolute measurement of a radiated field

**receive mode:** operating mode of the avalanche beacon where it receives, or is ready to receive, the signal(s) of other avalanche beacon(s) (also called: SEARCH mode)

**transmit mode:** operating mode of the avalanche beacon where it radiates a magnetic field with carrier frequency and on/off keying as defined in the present document (also called: SEND mode)

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

E	Electrical field strength
E <sub>o</sub>	Reference electrical field strength
f	Frequency
H	Magnetic field strength
H <sub>o</sub>	Reference magnetic field strength
N	Newton
P	Power
R	Distance
R <sub>o</sub>	Reference distance
t	Time
Z	Wave impedance
l	Wavelength

STANDARD PREVIEW  
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/243f0417-e81c-423b-a336-733b5bbf009f/osist-pren-300-718-1-v2-2-0-2021>

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CEPT	Conférence des administrations Européennes des Postes et Telecommunications
CISPR	Comité International Spécial des Perturbations Radioélectriques
DSP	Digital Signal Processor
EC	European Commission
ECC	Electronic Communications Committee
EFTA	European Free Trade Association
ERC	European Radio communications Committee
EU	European Union
EUT	Equipment Under Test
OATS	Open Area Test Site
RF	Radio Frequency
UWB	Ultra Wideband
VSWR	Voltage Standing Wave Ratio

## 4 Technical requirements specifications

### 4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be in accordance with its intended use, but as a minimum, shall be that specified in the test conditions contained in the present document (see clause 5.1). The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the operational environmental profile defined by its intended use.

### 4.2 Conformance requirements for transmitters

#### 4.2.1 Modulation and carrier keying

##### 4.2.1.1 Applicability

This requirement applies to all avalanche beacons.

##### 4.2.1.2 Description

The modulation used for avalanche beacons is carrier keying. The carrier keying defines the on and off times for a non-continuous carrier.

##### 4.2.1.3 Limits

The carrier keying shall be as shown in figure 1:

- on time: 70 ms minimum;
- off time: 400 ms minimum;
- period: 1 000 ms  $\pm$  300 ms (on time plus off time).




Figure 1