



SLOVENSKI STANDARD
SIST EN 301 908-14 V15.1.1:2021

01-november-2021

Celična omrežja IMT - Harmonizirani standard za dostop do radijskega spektra - 14. del: Bazne postaje za razviti prizemni radijski dostop za UMTS (E-UTRA), izdaja 15

IMT cellular networks - Harmonised Standard for access to radio spectrum - Part 14: Evolved Universal Terrestrial Radio Access (E-UTRA) Base Stations (BS) Release 15

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 908-14 V15.1.1:2021](https://standards.iteh.ai/catalog/standards/sist/07b4099e-dca1-4665-98-9867bcc38714/sist-en-301-908-14-v15-1-1-2021)

Ta slovenski standard je istoveten z: ETSI EN 301 908-14 V15.1.1 (2021-09)

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.070.99	Druge mobilne storitve	Other mobile services

SIST EN 301 908-14 V15.1.1:2021 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 908-14 V15.1.1:2021](https://standards.iteh.ai/catalog/standards/sist/07b4099e-daa1-4665-98c9-867bcc38714f/sist-en-301-908-14-v15-1-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/07b4099e-daa1-4665-98c9-867bcc38714f/sist-en-301-908-14-v15-1-1-2021>

ETSI EN 301 908-14 V15.1.1 (2021-09)



**IMT cellular networks;
Harmonised Standard for access to radio spectrum;
Part 14: Evolved Universal Terrestrial Radio Access (E-UTRA)
Base Stations (BS)
Release 15**

<https://standards.iteh.ai/catalog/standards/sist/en-301-908-14-v15-1-1-2021>
<https://standards.iteh.ai/catalog/standards/sist/en-301-908-14-v15-1-1-2021>

ReferenceREN/MSG-TFES-15-14

Keywords3G, 3GPP, cellular, digital, E-UTRA, IMT,
IMT-2000, LTE, mobile, radio, regulation, UMTS

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	8
Introduction	8
1 Scope	9
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definition of terms, symbols and abbreviations.....	13
3.1 Terms.....	13
3.2 Symbols.....	20
3.3 Abbreviations	21
4 Technical requirements specifications	22
4.1 Environmental profile.....	22
4.2 Conformance requirements	23
4.2.1 Introduction.....	23
4.2.2 Operating band unwanted emissions	25
4.2.2.1 Definition	25
4.2.2.2 Limits	25
4.2.2.2.0 General	25
4.2.2.2.1 Limits for Wide Area BS (bands 1, 3, 7, 8, 32, 33, 34, 38, 65, 69)	27
4.2.2.2.2 Limits for Wide Area BS (bands 7, 22, 38, 40, 41, 42, 43, 50, 69, 75)	28
4.2.2.2.3 Limits for Wide Area BS (bands 20, 28, 31, 67, 68, 72, 87, 88)	31
4.2.2.2.4 Limits for Local Area BS	32
4.2.2.2.5 Limits for Home BS	33
4.2.2.2.6 Void	35
4.2.2.2.7 Void	35
4.2.2.2.8 Limits for Medium Range BS	35
4.2.2.2.9 Additional limits for operation in bands 32, 75, 76	40
4.2.2.2.10 Minimum requirements for Local Area and Medium Range BS in band 46	40
4.2.2.2.11 Minimum requirements for stand-alone NB-IoT Wide Area BS	42
4.2.2.2.12 Minimum requirements for stand-alone NB-IoT Local Area BS	43
4.2.2.2.13 Minimum requirements for stand-alone NB-IoT Home BS	44
4.2.2.2.14 Minimum requirements for stand-alone NB-IoT Medium Range BS	45
4.2.2.2.15 Additional limits for operation in bands 50 and 75 within 1 432 - 1 452 MHz, and in bands 51 and 76	46
4.2.2.2.16 Additional limits for operation in band 43 for co-existence with FSS/FS	46
4.2.2.3 Conformance.....	47
4.2.3 Adjacent Channel Leakage power Ratio (ACLR)	47
4.2.3.1 Definition	47
4.2.3.2 Void.....	47
4.2.3.3 Void.....	47
4.2.3.4 Limits	47
4.2.3.4.1 ACLR Limits	47
4.2.3.4.2 Cumulative ACLR test requirement in non-contiguous spectrum limits.....	50
4.2.3.5 Conformance.....	51
4.2.4 Transmitter spurious emissions.....	52
4.2.4.1 Definition	52
4.2.4.2 Limits	52
4.2.4.2.1 Spurious emissions	52
4.2.4.2.2 Co-existence with other systems	53
4.2.4.2.3 Protection of the BS receiver of own or different BS	56
4.2.4.2.4 Co-existence with Home BS operating in other bands	56
4.2.4.3 Conformance.....	57

4.2.5	Base Station maximum output power	57
4.2.5.1	Definition	57
4.2.5.2	Limit	58
4.2.5.3	Conformance	58
4.2.6	Transmitter intermodulation	58
4.2.6.1	Definition	58
4.2.6.2	Limit	59
4.2.6.3	Conformance	59
4.2.7	Receiver spurious emissions	59
4.2.7.1	Definition	59
4.2.7.2	Limit	60
4.2.7.3	Conformance	60
4.2.8	Blocking characteristics	60
4.2.8.1	Definition	60
4.2.8.2	Limit	61
4.2.8.3	Conformance	73
4.2.9	Receiver intermodulation characteristics	73
4.2.9.1	Definition	73
4.2.9.2	Limit	73
4.2.9.3	Conformance	86
4.2.10	Adjacent Channel Selectivity (ACS) and narrow-band blocking	87
4.2.10.1	Definition	87
4.2.10.2	Limit	87
4.2.10.3	Conformance	96
4.2.11	Home BS output power for adjacent UTRA channel protection	96
4.2.11.1	Definition	96
4.2.11.2	Limit	96
4.2.11.3	Conformance	97
4.2.12	Home BS output power for adjacent E-UTRA channel protection	97
4.2.12.1	Definition and applicability	97
4.2.12.2	Limit	97
4.2.12.3	Conformance	98
4.2.13	Home BS output power for co-channel E-UTRA protection	98
4.2.13.1	Definition and applicability	98
4.2.13.2	Limit	98
4.2.13.3	Conformance	99
4.2.14	Reference sensitivity level	99
4.2.14.1	Definition	99
4.2.14.2	Limits	100
4.2.14.3	Conformance	104
4.2.15	Downlink channel access procedure (Listen Before Talk (LBT))	105
4.2.15.1	General	105
4.2.15.2	Limits	105
4.2.15.3	Conformance	105
4.2.16	Dynamic Frequency Selection (DFS)	105
4.2.16.1	General	105
4.2.16.2	Limits	105
4.2.16.3	Conformance	105
4.2.17	Base Station output power (band 46)	105
4.2.17.1	General	105
4.2.17.2	Limits	106
4.2.17.3	Conformance	106
5	Testing for compliance with technical requirements	106
5.1	Environmental conditions for testing	106
5.2	Void	106
5.3	Essential radio test suites	106
5.3.0	Introduction	106
5.3.1	Operating band unwanted emissions	107
5.3.1.0	General	107
5.3.1.1	Initial conditions	107
5.3.1.2	Procedure	107

5.3.1.3	Test requirement	108
5.3.2	Adjacent Channel Leakage power Ratio (ACLR)	108
5.3.2.1	Initial conditions	108
5.3.2.2	Procedure	109
5.3.2.3	Test requirement	109
5.3.3	Transmitter spurious emissions	109
5.3.3.0	General	109
5.3.3.1	Initial conditions	109
5.3.3.2	Procedure	110
5.3.3.3	Test requirements	110
5.3.4	Base Station maximum output power	111
5.3.4.0	General	111
5.3.4.1	Initial conditions	111
5.3.4.2	Procedure	111
5.3.4.3	Test requirement	112
5.3.5	Transmitter intermodulation	112
5.3.5.0	General	112
5.3.5.1	Initial conditions	112
5.3.5.2	Procedures	112
5.3.5.3	Test requirement	113
5.3.6	Receiver spurious emissions	113
5.3.6.0	General	113
5.3.6.1	Initial conditions	113
5.3.6.2	Procedure	114
5.3.6.3	Test requirement	114
5.3.7	Blocking characteristics	115
5.3.7.0	General	115
5.3.7.1	Initial conditions	115
5.3.7.2	Procedure	115
5.3.7.3	Test requirement	117
5.3.8	Receiver intermodulation characteristics	117
5.3.8.0	General	117
5.3.8.1	Initial conditions	117
5.3.8.2	Procedures	118
5.3.8.3	Test requirement	119
5.3.9	Adjacent Channel Selectivity (ACS) and narrow-band blocking	119
5.3.9.0	General	119
5.3.9.1	Initial conditions	119
5.3.9.2	Procedure for Adjacent Channel Selectivity	119
5.3.9.3	Procedure for narrow-band blocking	120
5.3.9.4	Test requirement	122
5.3.10	Home BS output power for adjacent UTRA channel protection	122
5.3.10.1	Initial conditions	122
5.3.10.2	Procedure	122
5.3.10.3	Test requirement	123
5.3.11	Home BS output power for adjacent E-UTRA channel protection	123
5.3.11.1	Initial conditions	123
5.3.11.2	Procedure	123
5.3.11.3	Test requirement	124
5.3.12	Home BS output power for co-channel E-UTRA protection	124
5.3.12.1	Initial conditions	124
5.3.12.2	Procedure	125
5.3.12.3	Test requirement	125
5.3.13	Reference sensitivity level	126
5.3.13.0	General	126
5.3.13.1	Initial conditions	126
5.3.13.2	Procedure	126
5.3.13.3	Test requirement	126
5.3.14	Downlink channel access procedure	126
5.3.14.1	General	126
5.3.14.2	Initial conditions	127
5.3.14.3	Procedure	127

5.3.14.4	Test requirements	127
5.3.15	Dynamic Frequency Selection (DFS)	127
5.3.16	Base Station output power (band 46)	128
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	129
Annex B (normative):	Base Station configurations	131
B.1	Reception with multiple receiver antenna connectors, receiver diversity	131
B.2	Duplexers	131
B.3	Power supply options	131
B.4	Ancillary RF amplifiers	132
B.5	BS using antenna arrays	132
B.5.0	General	132
B.5.1	Receiver tests	133
B.5.2	Transmitter tests	133
B.6	Transmission with multiple transmitter antenna connectors	134
B.7	BS with integrated Iuant BS modem	134
Annex C (informative):	Maximum measurement uncertainty	135
Annex D (informative):	Bibliography	137
Annex E (informative):	Change history	138
History		139

SIST EN 301 908-14 V15.1.1:2021
<https://standards.iteh.ai/catalog/standards/sist/07b4099e-daa1-4665-98c9-867bcc38714f/sist-en-301-908-14-v15-1-1-2021>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITEH STANDARD PREVIEW
(standards.iteh.ai)

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).
SIST EN 301 908-14 V15.1.1:2021
https://standards.iteh.ai/catalog/standards/sist/301-908-14-v15-1-1-2021
867bcc38714f/sist-en-301-908-14-v15-1-1-2021

For non-EU countries, the present document may be used for regulatory (Type Approval) purposes.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.1] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A-1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 14 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.7].

National transposition dates	
Date of adoption of this EN:	21 September 2021
Date of latest announcement of this EN (doa):	31 December 2021
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2022
Date of withdrawal of any conflicting National Standard (dow):	30 June 2023

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI that are designed to fit in a modular structure to cover radio equipment within the scope of the Radio Equipment Directive [i.2]. The present document is produced following the guidance in ETSI EG 203 336 [i.3] as applicable.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 908-14 V15.1.1:2021](#)

<https://standards.iteh.ai/catalog/standards/sist/07b4099e-daa1-4665-98c9-867bcc38714f/sist-en-301-908-14-v15-1-1-2021>

1 Scope

The present document specifies technical characteristics and methods of measurements for the types of equipment:

- 1) Base Station for Evolved Universal Terrestrial Radio Access (E-UTRA).
- 2) Base Station for Evolved Universal Terrestrial Radio Access (E-UTRA) with NB-IoT.
- 3) Base Station for NB-IoT standalone.

This radio equipment type is capable of operating in all or any part of the operating bands given in table 1-1. Unless stated otherwise, requirements specified for the TDD duplex mode apply for downlink and uplink operations in Frame Structure Type 2. NB-IoT is designed to operate in the E-UTRA operating bands 1, 3, 8, 20, 28, 31, 41, 42, 43, 65, 72, 87, 88 which are defined in table 1-1.

Table 1-1: E-UTRA Base Station operating bands

E-UTRA band	Direction of transmission	E-UTRA Base Station operating bands	Relevant EC/ECC decision
1	Transmit	2 110 MHz to 2 170 MHz	[i.24] and [i.25]
	Receive	1 920 MHz to 1 980 MHz	
3	Transmit	1 805 MHz to 1 880 MHz	[i.22] and [i.23]
	Receive	1 710 MHz to 1 785 MHz	
7	Transmit	2 620 MHz to 2 690 MHz	[i.26] and [i.27]
	Receive	2 500 MHz to 2 570 MHz	
8	Transmit	925 MHz to 960 MHz	[i.22] and [i.23]
	Receive	880 MHz to 915 MHz	
20	Transmit	791 MHz to 821 MHz	[i.17] and [i.18]
	Receive	832 MHz to 862 MHz	
22	Transmit	3 510 MHz to 3 590 MHz	[i.12] and [i.29]
	Receive	3 410 MHz to 3 490 MHz	
28 (note 5)	Transmit	758 MHz to 803 MHz	[i.14] and [i.15]
	Receive	703 MHz to 748 MHz	
31	Transmit	462,5 MHz to 467,5 MHz	[i.16]
	Receive	452,5 MHz to 457,5 MHz	
32 (note 1)	Transmit	1 452 MHz to 1 496 MHz	[i.19], [i.20] and [i.21]
	Receive	N/A	
33	Transmit and Receive	1 900 MHz to 1 920 MHz	[i.24]
34	Transmit and Receive	2 010 MHz to 2 025 MHz	[i.24]
38	Transmit and Receive	2 570 MHz to 2 620 MHz	[i.27] and [i.28]
40	Transmit and Receive	2 300 MHz to 2 400 MHz	[i.26]
41 (note 6)	Transmit and Receive	2 496 MHz to 2 690 MHz	[i.27] and [i.28]
42	Transmit and Receive	3 400 MHz to 3 600 MHz	[i.12] and [i.29]
43	Transmit and Receive	3 600 MHz to 3 800 MHz	[i.12] and [i.29]
46 (notes 3 and 4)	Transmit and Receive	5 150 MHz to 5 925 MHz	[i.10] and [i.11]
50 (note 1)	Transmit	1 432 MHz to 1 517 MHz	[i.20]
	Receive	1 432 MHz to 1 517 MHz	
51 (note 1)	Transmit	1 427 MHz to 1 432 MHz	[i.20]
	Receive	1 427 MHz to 1 432 MHz	
65 (note 7)	Transmit	2 110 MHz to 2 200 MHz	[i.24], [i.25] and [i.30]
	Receive	1 920 MHz to 2 010 MHz	
67	Transmit	738 MHz to 758 MHz	[i.14] and [i.15]
	Receive	N/A	
68	Transmit	753 MHz to 783 MHz	[i.14] and [i.15]
	Receive	698 MHz to 728 MHz	
69 (note 1)	Transmit	2 570 MHz to 2 620 MHz	[i.27] and [i.28]
	Receive	N/A	
72	Transmit	461 MHz to 466 MHz	[i.16]
	Receive	451 MHz to 456 MHz	
75 (note 1)	Transmit	1 432 MHz to 1 517 MHz	[i.19], [i.20] and [i.21]
76 (note 1)	Transmit	1 427 MHz to 1 432 MHz	[i.20] and [i.21]

E-UTRA band	Direction of transmission	E-UTRA Base Station operating bands	Relevant EC/ECC decision
87	Transmit	420 MHz to 425 MHz	[i.16]
	Receive	410 MHz to 415 MHz	
88	Transmit	422 MHz to 427 MHz	[i.16]
	Receive	412 MHz to 417 MHz	

NOTE 1: Restricted to E-UTRA DL operation when carrier aggregation is configured. The downlink operating band is paired with the uplink operating band (external) of the carrier aggregation configuration that is supporting the configured Pcell.

NOTE 2: Void.

NOTE 3: This band is an unlicensed band restricted to licensed-assisted operation using Frame Structure Type 3. In Europe according to [i.10] and [i.11], radio equipment in band 46 operates between 5 150 MHz and 5 725 MHz as in table 1-2.

NOTE 4: In this version of the present document, restricted to E-UTRA DL operation when carrier aggregation is configured. Band 46 is divided into three sub-bands as in table 1-2.

NOTE 5: In Europe according to [i.14] and [i.15], radio equipment in band 28 operates between 758 MHz to 791 MHz for the transmitter ($F_{DL_low} = 758$ MHz and $F_{DL_high} = 791$ MHz) and between 703 MHz to 736 MHz for the receiver ($F_{UL_low} = 703$ MHz and $F_{UL_high} = 736$ MHz).

NOTE 6: In Europe according to [i.27] and [i.28], radio equipment in band 41 operates between 2 570 MHz and 2 620 MHz ($F_{DL_low} = 2 570$ MHz and $F_{DL_high} = 2 620$ MHz).

NOTE 7: This band includes two frequency ranges that are harmonised in Europe:

(a) Based on [i.30], radio equipment in band 65 operates between 2 170 MHz to 2 200 MHz for the transmitter ($F_{DL_low} = 2 170$ MHz and $F_{DL_high} = 2 200$ MHz) and between 1 980 MHz to 2 010 MHz for the receiver ($F_{UL_low} = 1 980$ MHz and $F_{UL_high} = 2 010$ MHz) as the Complementary Ground Component (CGC) of a Mobile-satellite service by reference to the present Harmonised Standard.

(b) According to [i.24] and [i.25], radio equipment in band 65 operates between 2 110 MHz to 2 170 MHz for the transmitter ($F_{DL_low} = 2 110$ MHz and $F_{DL_high} = 2 170$ MHz), and between 1 920 MHz to 1 980 MHz for the receiver ($F_{UL_low} = 1 920$ MHz and $F_{UL_high} = 1 980$ MHz).

Table 1-2: Sub-bands for band 46

E-UTRA Operating band	Uplink (UL) operating band BS receive UE transmit	Downlink (DL) operating band BS transmit UE receive	Relevant EC/ECC decision
	$F_{UL_low} - F_{UL_high}$	$F_{DL_low} - F_{DL_high}$	
46a	5 150 MHz to 5 250 MHz	5 150 MHz to 5 250 MHz	[i.10] and [i.11]
46b	5 250 MHz to 5 350 MHz	5 250 MHz to 5 350 MHz	[i.10] and [i.11]
46c	5 470 MHz to 5 725 MHz	5 470 MHz to 5 725 MHz	[i.10] and [i.11]

The present document covers conducted requirements for E-UTRA Base Stations for 3GPP Release 8, 9, 10, 11, 12, 13, 14 and 15. Additionally, it includes the requirements for E-UTRA Base Station operating bands and E-UTRA CA operating bands from 3GPP Release 16.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 136 141 (V15.9.0) (07-2020): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) conformance testing (3GPP TS 36.141 version 15.9.0 Release 15)".
- [2] ETSI TS 125 104 (V15.5.0) (04-2019): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (FDD) (3GPP TS 25.104 version 15.5.0 Release 15)".
- [3] ETSI TS 125 105 (V15.0.0) (07-2018): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (TDD) (3GPP TS 25.105 version 15.0.0 Release 15)".
- [4] ETSI TS 136 104 (V15.9.0) (07-2020): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception (3GPP TS 36.104 version 15.9.0 Release 15)".
- [5] ETSI TS 125 141 (V15.4.0) (04-2019): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) conformance testing (FDD) (3GPP TS 25.141 version 15.4.0 Release 15)".
- [6] ETSI TS 136 211 (V15.9.0) (04-2020): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical channels and modulation (3GPP TS 36.211 version 15.9.0 Release 15)".
- [7] ETSI EN 301 908-18 (V15.1.1) (09-2021): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 18: E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS) Release 15".
- [8] ETSI EN 301 893 (V2.1.1) (05-2017): "5 GHz RLAN; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU".
- [9] ETSI TS 136 213 (V15.9.0) (04-2020): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures (3GPP TS 36.213 version 15.9.0 Release 15)".
- [10] ETSI TS 136 101 (V15.11.0) (08-2020): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception (3GPP TS 36.101 version 15.11.0 Release 15)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Commission implementing decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.2] Directive 2014/53/EU of the European Parliament and of the council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI EG 203 336 (V1.2.1) (05-2020): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.4] Recommendation ITU-R SM.329-12 (09-2012): "Unwanted emissions in the spurious domain".

- [i.5] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.6] Void.
- [i.7] ETSI EN 301 908-1: "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 1: Introduction and common requirements Release 15".
- [i.8] Void.
- [i.9] ETSI TS 136 214 (V15.5.0) (01-2020): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer; Measurements (3GPP TS 36.214 version 15.5.0 Release 15)".
- [i.10] Commission Decision 2005/513/EC of 11 July 2005 on the harmonised use of radio spectrum in the 5 GHz frequency band for the implementation of Wireless Access Systems including Radio Local Area Networks (WAS/RLANs).
- [i.11] Commission Decision 2007/90/EC of 12 February 2007 amending Decision 2005/513/EC on the harmonised use of radio spectrum in the 5 GHz frequency band for the implementation of Wireless Access Systems including Radio Local Area Networks (WAS/RLANs).
- [i.12] Commission Decision 2019/235/EC of 24 January 2019 on amending Decision 2008/411/EC as regards an update of relevant technical conditions applicable to the 3 400-3 800 MHz frequency band.
- [i.13] ETSI TS 103 807: "Mobile Standards Group (MSG); IMT Cellular Networks Base Stations (BS)".
- [i.14] ECC Decision (15)01: "Harmonised technical conditions for mobile/fixed communications networks (MFCN) in the band 694-790 MHz including a paired frequency arrangement (Frequency Division Duplex 2x30 MHz) and an optional unpaired frequency arrangement (Supplemental Downlink)", approved 06 March 2015.
- [i.15] Commission Implementing Decision (EU) 2016/687 of 28 April 2016 on the harmonisation of the 694-790 MHz frequency band for terrestrial systems capable of providing wireless broadband electronic communications services and for flexible national use in the Union.
- [i.16] ECC Decision (16)02: "Harmonised technical conditions and frequency bands for the implementation of Broadband Public Protection and Disaster Relief (BB-PPDR) systems", approved 17 June 2016.
- [i.17] ECC Decision (09)03: "Harmonised conditions for mobile/fixed communications networks (MFCN) operating in the band 790 - 862 MHz", 30 October 2009.
- [i.18] Commission Decision 2010/267/EU of 6 May 2010 on harmonised technical conditions of use in the 790-862 MHz frequency band for terrestrial systems capable of providing electronic communications services in the European Union.
- [i.19] ECC Decision (13)03: "The harmonised use of the frequency band 1 452-1 492 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)".
- [i.20] ECC Decision 17(06): "The harmonised use of the frequency bands 1 427-1 452 MHz and 1492-1518 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)", approved 17 November 2017, corrected 2 March 2018.
- [i.21] Commission Implementing Decision (EU) 2018/661 of 26 April 2018 amending Implementing Decision (EU) 2015/750 on the harmonisation of the 1452-1492 MHz frequency band for terrestrial systems capable of providing electronic communications services in the Union as regards its extension in the harmonised 1427-1452 MHz and 1492-1517 MHz frequency bands.
- [i.22] Commission Implementing Decision 2011/251/EU of 18 April 2011 amending Decision 2009/766/EC on the harmonisation of the 900 MHz and 1800 MHz frequency bands for terrestrial systems capable of providing pan-European electronic communications services in the Community.

- [i.23] ECC Decision (06)13: "Designation of the bands 880-915 MHz, 925-960 MHz, 1710-1785 MHz and 1805-1880 MHz for terrestrial UMTS, LTE, WiMAX and IoT cellular systems", approved 01 December 2006, amended 8 March 2019.
- [i.24] ECC Decision (06)01: "The harmonised utilisation of the bands 1920-1980 MHz and 2110-2170 MHz for mobile/fixed communications networks (MFCN) including terrestrial IMT systems", approved 24 March 2006, amended 8 March 2019.
- [i.25] Commission Implementing Decision (EU) 2020/667 of 6 May 2020 amending Decision 2012/688/EU as regards an update of relevant technical conditions applicable to the frequency bands 1 920-1 980 MHz and 2 110-2 170 MHz.
- [i.26] ECC Decision 14(02): "Harmonised technical and regulatory conditions for the use of the band 2 300-2 400 MHz for Mobile/Fixed Communications Networks (MFCN)", approved 27 June 2014.
- [i.27] ECC Decision 05(05): "Harmonised utilization of spectrum for Mobile/Fixed Communications Networks (MFCN) operating within the band 2 500-2 690 MHz", approved 18 March 2005, amended 05 July 2019.
- [i.28] Commission Implementing Decision (EU) 2020/636 of 8 May 2020 amending Decision 2008/477/EC as regards an update of relevant technical conditions applicable to the 2 500-2 690 MHz frequency band.
- [i.29] ECC Decision 11(06): "Harmonised frequency arrangements and least restrictive technical conditions (LRTC) for mobile/fixed communications networks (MFCN) operating in the band 3400-3800 MHz", approved 09 December 2011, amended 26 October 2018.
- [i.30] ECC Decision 06(09): "Designation of the bands 1980-2010 MHz and 2170-2200 MHz for use by systems in the Mobile-Satellite Service including those supplemented by a Complementary Ground Component (CGC)", approved 01 December 2006, amended 05 September 2007.

Tech STANDARD PREVIEW
(standards.iteh.ai)

3 Definition of terms, symbols and abbreviations

SIST EN 301 908-14 V15.1.1:2021
<https://standards.iteh.ai/catalog/standards/sist/07b4099e-daa1-4665-98c9-867bcc38714f/sist-en-301-908-14-v15-1-1-2021>

3.1 Terms

For the purposes of the present document, the following terms apply:

aggregated channel bandwidth: RF bandwidth in which a Base Station transmits and/or receives multiple contiguously aggregated carriers

NOTE: The Aggregated Channel Bandwidth is measured in MHz.

Base Station class: Wide Area Base Station, Medium Range Base Station, Local Area Base Station or Home Base Station, as declared by the manufacturer

Base Station RF bandwidth: RF bandwidth in which a Base Station transmits and/or receives single or multiple carrier(s) within a supported operating band

NOTE: In single E-UTRA carrier operation, the Base Station RF Bandwidth is equal to the channel bandwidth.

Base Station RF bandwidth edge: frequency of one of the edges of the Base Station RF Bandwidth

NOTE: Base Station RF Bandwidth edges are separated by the Base Station RF Bandwidth.

carrier: modulated waveform conveying the E-UTRA or UTRA (WCDMA) physical channels

carrier aggregation: aggregation of two or more component carriers in order to support wider transmission bandwidths

carrier aggregation band: set of one or more operating bands across which multiple carriers are aggregated with a specific set of technical requirements

NOTE: Carrier aggregation band(s) for an E-UTRA BS is declared by the manufacturer according to the designations in ETSI TS 136 101 [10].