

---

**Celična omrežja IMT - Harmonizirani standard za dostop do radijskega spektra - 14. del: Bazne postaje za razviti prizemni radijski dostop za UMTS (E-UTRA), izdaja 15**

IMT cellular networks - Harmonised Standard for access to radio spectrum - Part 14: Evolved Universal Terrestrial Radio Access (E-UTRA) Base Stations (BS) Release 15

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[oSIST prEN 301 908-14 V15.1.0:2021](https://standards.iteh.ai/catalog/standards/sist/07b4009e-daa1-4665-98e9-867bcc38714f/osist-pr-en-301-908-14-v15-1-0-2021)

**Ta slovenski standard je istoveten z: ETSI EN 301 908-14 V15.1.0 (2021-06)**

---

**ICS:**

|           |                                       |                                         |
|-----------|---------------------------------------|-----------------------------------------|
| 33.060.99 | Druga oprema za radijske komunikacije | Other equipment for radiocommunications |
| 33.070.99 | Druge mobilne storitve                | Other mobile services                   |

**oSIST prEN 301 908-14 V15.1.0:2021**      **en**

## **iTeh STANDARD PREVIEW (standards.iteh.ai)**

[oSIST prEN 301 908-14 V15.1.0:2021](https://standards.iteh.ai/catalog/standards/sist/07b4099e-daa1-4665-98c9-867bcc38714f/osist-pren-301-908-14-v15-1-0-2021)

<https://standards.iteh.ai/catalog/standards/sist/07b4099e-daa1-4665-98c9-867bcc38714f/osist-pren-301-908-14-v15-1-0-2021>

Draft **ETSI EN 301 908-14** V15.1.0 (2021-06)



**IMT cellular networks;  
Harmonised Standard for access to radio spectrum;  
Part 14: Evolved Universal Terrestrial Radio Access (E-UTRA)  
Base Stations (BS)  
Release 15**

<https://standards.iteh.ai/catalog/standards/sist/301-908-14-v15-1-0-2021>  
867bcc38714f/osist-pren-301-908-14-v15-1-0-2021

## Reference

REN/MSG-TFES-15-14

## Keywords

3G, 3GPP, cellular, digital, E-UTRA, IMT,  
IMT-2000, LTE, mobile, radio, regulation, UMTS**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871**Important notice**The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.  
All rights reserved.

# Contents

|                                                                                                                    |    |
|--------------------------------------------------------------------------------------------------------------------|----|
| Intellectual Property Rights .....                                                                                 | 7  |
| Foreword.....                                                                                                      | 7  |
| Modal verbs terminology.....                                                                                       | 8  |
| Introduction .....                                                                                                 | 8  |
| 1 Scope .....                                                                                                      | 9  |
| 2 References .....                                                                                                 | 11 |
| 2.1 Normative references .....                                                                                     | 11 |
| 2.2 Informative references.....                                                                                    | 12 |
| 3 Definition of terms, symbols and abbreviations.....                                                              | 14 |
| 3.1 Terms.....                                                                                                     | 14 |
| 3.2 Symbols.....                                                                                                   | 20 |
| 3.3 Abbreviations .....                                                                                            | 22 |
| 4 Technical requirements specifications .....                                                                      | 23 |
| 4.1 Environmental profile.....                                                                                     | 23 |
| 4.2 Conformance requirements .....                                                                                 | 23 |
| 4.2.1 Introduction.....                                                                                            | 23 |
| 4.2.2 Operating band unwanted emissions .....                                                                      | 26 |
| 4.2.2.1 Definition .....                                                                                           | 26 |
| 4.2.2.2 Limits .....                                                                                               | 26 |
| 4.2.2.2.0 General .....                                                                                            | 26 |
| 4.2.2.2.1 Limits for Wide Area BS (bands 1, 3, 7, 8, 32, 33, 34, 38, 65, 69) .....                                 | 27 |
| 4.2.2.2.2 Limits for Wide Area BS (bands 7, 22, 38, 40, 41, 42, 43, 50, 69, 75) .....                              | 29 |
| 4.2.2.2.3 Limits for Wide Area BS (bands 20, 28, 31, 67, 68, 72, 87, 88) .....                                     | 32 |
| 4.2.2.2.4 Limits for Local Area BS .....                                                                           | 33 |
| 4.2.2.2.5 Limits for Home BS .....                                                                                 | 34 |
| 4.2.2.2.6 Void .....                                                                                               | 36 |
| 4.2.2.2.7 Void .....                                                                                               | 36 |
| 4.2.2.2.8 Limits for Medium Range BS .....                                                                         | 36 |
| 4.2.2.2.9 Additional limits for operation in bands 32, 75, 76 .....                                                | 41 |
| 4.2.2.2.10 Minimum requirements for Local Area and Medium Range BS in band 46 .....                                | 41 |
| 4.2.2.2.11 Minimum requirements for stand-alone NB-IoT Wide Area BS.....                                           | 43 |
| 4.2.2.2.12 Minimum requirements for stand-alone NB-IoT Local Area BS .....                                         | 44 |
| 4.2.2.2.13 Minimum requirements for stand-alone NB-IoT Home BS .....                                               | 45 |
| 4.2.2.2.14 Minimum requirements for stand-alone NB-IoT Medium Range BS .....                                       | 46 |
| 4.2.2.2.15 Additional limits for operation in bands 50 and 75 within 1 432-1 452 MHz, and in bands 51 and 76 ..... | 47 |
| 4.2.2.2.16 Additional limits for operation in band 43 for co-existence with FSS/FS .....                           | 47 |
| 4.2.2.3 Conformance.....                                                                                           | 48 |
| 4.2.3 Adjacent Channel Leakage power Ratio (ACLR) .....                                                            | 48 |
| 4.2.3.1 Definition .....                                                                                           | 48 |
| 4.2.3.2 Void.....                                                                                                  | 48 |
| 4.2.3.3 Void.....                                                                                                  | 48 |
| 4.2.3.4 Limits .....                                                                                               | 48 |
| 4.2.3.4.1 ACLR Limits .....                                                                                        | 48 |
| 4.2.3.4.2 Cumulative ACLR test requirement in non-contiguous spectrum limits.....                                  | 51 |
| 4.2.3.5 Conformance .....                                                                                          | 52 |
| 4.2.4 Transmitter spurious emissions.....                                                                          | 53 |
| 4.2.4.1 Definition .....                                                                                           | 53 |
| 4.2.4.2 Limits .....                                                                                               | 53 |
| 4.2.4.2.1 Spurious emissions .....                                                                                 | 53 |
| 4.2.4.2.2 Co-existence with other systems .....                                                                    | 54 |
| 4.2.4.2.3 Protection of the BS receiver of own or different BS .....                                               | 57 |
| 4.2.4.2.4 Co-existence with Home BS operating in other bands .....                                                 | 57 |
| 4.2.4.3 Conformance.....                                                                                           | 58 |

|          |                                                                    |     |
|----------|--------------------------------------------------------------------|-----|
| 4.2.5    | Base Station maximum output power .....                            | 58  |
| 4.2.5.1  | Definition .....                                                   | 58  |
| 4.2.5.2  | Limit .....                                                        | 59  |
| 4.2.5.3  | Conformance .....                                                  | 59  |
| 4.2.6    | Transmitter intermodulation .....                                  | 59  |
| 4.2.6.1  | Definition .....                                                   | 59  |
| 4.2.6.2  | Limit .....                                                        | 60  |
| 4.2.6.3  | Conformance .....                                                  | 60  |
| 4.2.7    | Receiver spurious emissions .....                                  | 60  |
| 4.2.7.1  | Definition .....                                                   | 60  |
| 4.2.7.2  | Limit .....                                                        | 61  |
| 4.2.7.3  | Conformance .....                                                  | 61  |
| 4.2.8    | Blocking characteristics .....                                     | 61  |
| 4.2.8.1  | Definition .....                                                   | 61  |
| 4.2.8.2  | Limit .....                                                        | 62  |
| 4.2.8.3  | Conformance .....                                                  | 74  |
| 4.2.9    | Receiver intermodulation characteristics .....                     | 74  |
| 4.2.9.1  | Definition .....                                                   | 74  |
| 4.2.9.2  | Limit .....                                                        | 74  |
| 4.2.9.3  | Conformance .....                                                  | 87  |
| 4.2.10   | Adjacent Channel Selectivity (ACS) and narrow-band blocking .....  | 88  |
| 4.2.10.1 | Definition .....                                                   | 88  |
| 4.2.10.2 | Limit .....                                                        | 88  |
| 4.2.10.3 | Conformance .....                                                  | 98  |
| 4.2.11   | Home BS output power for adjacent UTRA channel protection .....    | 98  |
| 4.2.11.1 | Definition .....                                                   | 98  |
| 4.2.11.2 | Limit .....                                                        | 98  |
| 4.2.11.3 | Conformance .....                                                  | 99  |
| 4.2.12   | Home BS output power for adjacent E-UTRA channel protection .....  | 99  |
| 4.2.12.1 | Definition and applicability .....                                 | 99  |
| 4.2.12.2 | Limit .....                                                        | 99  |
| 4.2.12.3 | Conformance .....                                                  | 100 |
| 4.2.13   | Home BS output power for co-channel E-UTRA protection .....        | 100 |
| 4.2.13.1 | Definition and applicability .....                                 | 100 |
| 4.2.13.2 | Limit .....                                                        | 100 |
| 4.2.13.3 | Conformance .....                                                  | 101 |
| 4.2.14   | Reference sensitivity level .....                                  | 101 |
| 4.2.14.1 | Definition .....                                                   | 101 |
| 4.2.14.2 | Limits .....                                                       | 102 |
| 4.2.14.3 | Conformance .....                                                  | 106 |
| 4.2.15   | Downlink channel access procedure (Listen Before Talk (LBT)) ..... | 107 |
| 4.2.15.1 | General .....                                                      | 107 |
| 4.2.15.2 | Limits .....                                                       | 107 |
| 4.2.15.3 | Conformance .....                                                  | 107 |
| 4.2.16   | Dynamic Frequency Selection (DFS) .....                            | 107 |
| 4.2.16.1 | General .....                                                      | 107 |
| 4.2.16.2 | Limits .....                                                       | 107 |
| 4.2.16.3 | Conformance .....                                                  | 107 |
| 4.2.17   | Base Station output power (band 46) .....                          | 107 |
| 4.2.17.1 | General .....                                                      | 107 |
| 4.2.17.2 | Limits .....                                                       | 108 |
| 4.2.17.3 | Conformance .....                                                  | 108 |
| 5        | Testing for compliance with technical requirements .....           | 108 |
| 5.1      | Environmental conditions for testing .....                         | 108 |
| 5.2      | Void .....                                                         | 108 |
| 5.3      | Essential radio test suites .....                                  | 108 |
| 5.3.0    | Introduction .....                                                 | 108 |
| 5.3.1    | Operating band unwanted emissions .....                            | 109 |
| 5.3.1.0  | General .....                                                      | 109 |
| 5.3.1.1  | Initial conditions .....                                           | 109 |
| 5.3.1.2  | Procedure .....                                                    | 109 |

|          |                                                                   |     |
|----------|-------------------------------------------------------------------|-----|
| 5.3.1.3  | Test requirement .....                                            | 110 |
| 5.3.2    | Adjacent Channel Leakage power Ratio (ACLR) .....                 | 110 |
| 5.3.2.1  | Initial conditions .....                                          | 110 |
| 5.3.2.2  | Procedure .....                                                   | 111 |
| 5.3.2.3  | Test requirement .....                                            | 111 |
| 5.3.3    | Transmitter spurious emissions.....                               | 111 |
| 5.3.3.0  | General .....                                                     | 111 |
| 5.3.3.1  | Initial conditions .....                                          | 111 |
| 5.3.3.2  | Procedure .....                                                   | 112 |
| 5.3.3.3  | Test requirements .....                                           | 112 |
| 5.3.4    | Base Station maximum output power .....                           | 113 |
| 5.3.4.0  | General .....                                                     | 113 |
| 5.3.4.1  | Initial conditions .....                                          | 113 |
| 5.3.4.2  | Procedure .....                                                   | 113 |
| 5.3.4.3  | Test requirement .....                                            | 114 |
| 5.3.5    | Transmitter intermodulation .....                                 | 114 |
| 5.3.5.0  | General .....                                                     | 114 |
| 5.3.5.1  | Initial conditions .....                                          | 114 |
| 5.3.5.2  | Procedures .....                                                  | 114 |
| 5.3.5.3  | Test requirement .....                                            | 115 |
| 5.3.6    | Receiver spurious emissions .....                                 | 115 |
| 5.3.6.0  | General .....                                                     | 115 |
| 5.3.6.1  | Initial conditions .....                                          | 115 |
| 5.3.6.2  | Procedure .....                                                   | 116 |
| 5.3.6.3  | Test requirement .....                                            | 116 |
| 5.3.7    | Blocking characteristics .....                                    | 117 |
| 5.3.7.0  | General .....                                                     | 117 |
| 5.3.7.1  | Initial conditions .....                                          | 117 |
| 5.3.7.2  | Procedure .....                                                   | 117 |
| 5.3.7.3  | Test requirement .....                                            | 119 |
| 5.3.8    | Receiver intermodulation characteristics .....                    | 119 |
| 5.3.8.0  | General .....                                                     | 119 |
| 5.3.8.1  | Initial conditions .....                                          | 119 |
| 5.3.8.2  | Procedures .....                                                  | 120 |
| 5.3.8.3  | Test requirement .....                                            | 121 |
| 5.3.9    | Adjacent Channel Selectivity (ACS) and narrow-band blocking ..... | 121 |
| 5.3.9.0  | General .....                                                     | 121 |
| 5.3.9.1  | Initial conditions .....                                          | 121 |
| 5.3.9.2  | Procedure for Adjacent Channel Selectivity .....                  | 121 |
| 5.3.9.3  | Procedure for narrow-band blocking .....                          | 122 |
| 5.3.9.4  | Test requirement .....                                            | 124 |
| 5.3.10   | Home BS output power for adjacent UTRA channel protection.....    | 124 |
| 5.3.10.1 | Initial conditions .....                                          | 124 |
| 5.3.10.2 | Procedure .....                                                   | 124 |
| 5.3.10.3 | Test requirement .....                                            | 125 |
| 5.3.11   | Home BS output power for adjacent E-UTRA channel protection.....  | 125 |
| 5.3.11.1 | Initial conditions .....                                          | 125 |
| 5.3.11.2 | Procedure .....                                                   | 125 |
| 5.3.11.3 | Test requirement .....                                            | 126 |
| 5.3.12   | Home BS output power for co-channel E-UTRA protection .....       | 126 |
| 5.3.12.1 | Initial conditions .....                                          | 126 |
| 5.3.12.2 | Procedure .....                                                   | 127 |
| 5.3.12.3 | Test requirement .....                                            | 127 |
| 5.3.13   | Reference sensitivity level .....                                 | 128 |
| 5.3.13.0 | General .....                                                     | 128 |
| 5.3.13.1 | Initial conditions .....                                          | 128 |
| 5.3.13.2 | Procedure .....                                                   | 128 |
| 5.3.13.3 | Test requirement .....                                            | 128 |
| 5.3.14   | Downlink channel access procedure .....                           | 128 |
| 5.3.14.1 | General .....                                                     | 128 |
| 5.3.14.2 | Initial conditions .....                                          | 128 |
| 5.3.14.3 | Procedure .....                                                   | 129 |

|                               |                                                                                                               |            |
|-------------------------------|---------------------------------------------------------------------------------------------------------------|------------|
| 5.3.14.4                      | Test requirements .....                                                                                       | 129        |
| 5.3.15                        | Dynamic Frequency Selection (DFS) .....                                                                       | 129        |
| 5.3.16                        | Base Station output power (band 46) .....                                                                     | 130        |
| <b>Annex A (informative):</b> | <b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b> | <b>131</b> |
| <b>Annex B (normative):</b>   | <b>Base Station configurations .....</b>                                                                      | <b>133</b> |
| B.1                           | Reception with multiple receiver antenna connectors, receiver diversity .....                                 | 133        |
| B.2                           | Duplexers .....                                                                                               | 133        |
| B.3                           | Power supply options .....                                                                                    | 133        |
| B.4                           | Ancillary RF amplifiers .....                                                                                 | 134        |
| B.5                           | BS using antenna arrays .....                                                                                 | 134        |
| B.5.0                         | General .....                                                                                                 | 134        |
| B.5.1                         | Receiver tests .....                                                                                          | 135        |
| B.5.2                         | Transmitter tests .....                                                                                       | 135        |
| B.6                           | Transmission with multiple transmitter antenna connectors .....                                               | 136        |
| B.7                           | BS with integrated Iuant BS modem .....                                                                       | 136        |
| <b>Annex C (informative):</b> | <b>Maximum measurement uncertainty .....</b>                                                                  | <b>137</b> |
| <b>Annex D (informative):</b> | <b>Bibliography .....</b>                                                                                     | <b>139</b> |
| <b>Annex E (informative):</b> | <b>Change history .....</b>                                                                                   | <b>140</b> |
| History .....                 |                                                                                                               | 141        |

<https://standards.iteh.ai/catalog/standards/sist/07b4099e-daa1-4665-98c9-867bcc38714f/osist-pren-301-908-14-v15-1-0-2021>  
 oSIST prEN 301 908-14 V15.1.0:2021



# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITCH STANDARD PREVIEW  
(standards.itech.ai)

## Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

For non-EU countries, the present document may be used for regulatory (Type Approval) purposes.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.1] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A-1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 14 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.7].

| Proposed national transposition dates                                                  |                                 |
|----------------------------------------------------------------------------------------|---------------------------------|
| Date of latest announcement of this EN (doa):                                          | 3 months after ETSI publication |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 6 months after doa              |
| Date of withdrawal of any conflicting National Standard (dow):                         | 18 months after doa             |

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The present document is part of a set of standards developed by ETSI that are designed to fit in a modular structure to cover radio equipment within the scope of the Radio Equipment Directive [i.2]. The present document is produced following the guidance in ETSI EG 203 336 [i.3] as applicable.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[oSIST prEN 301 908-14 V15.1.0:2021](https://standards.iteh.ai/catalog/standards/sist/07b4099e-daa1-4665-98c9-867bcc38714f/osist-pren-301-908-14-v15-1-0-2021)  
<https://standards.iteh.ai/catalog/standards/sist/07b4099e-daa1-4665-98c9-867bcc38714f/osist-pren-301-908-14-v15-1-0-2021>

# 1 Scope

The present document specifies technical characteristics and methods of measurements for the types of equipment:

- 1) Base Station for Evolved Universal Terrestrial Radio Access (E-UTRA).
- 2) Base Station for Evolved Universal Terrestrial Radio Access (E-UTRA) with NB-IoT.
- 3) Base Station for NB-IoT standalone.

This radio equipment type is capable of operating in all or any part of the operating bands given in table 1-1. Unless stated otherwise, requirements specified for the TDD duplex mode apply for downlink and uplink operations in Frame Structure Type 2. NB-IoT is designed to operate in the E-UTRA operating bands 1, 3, 8, 20, 28, 31, 41, 42, 43, 65, 72, 87, 88 which are defined in table 1-1.

**Table 1-1: E-UTRA Base Station operating bands**

| E-UTRA band           | Direction of transmission | E-UTRA Base Station operating bands | Relevant EC/ECC decision  |
|-----------------------|---------------------------|-------------------------------------|---------------------------|
| 1                     | Transmit                  | 2 110 MHz to 2 170 MHz              | [i.24] and [i.25]         |
|                       | Receive                   | 1 920 MHz to 1 980 MHz              |                           |
| 3                     | Transmit                  | 1 805 MHz to 1 880 MHz              | [i.22] and [i.23]         |
|                       | Receive                   | 1 710 MHz to 1 785 MHz              |                           |
| 7                     | Transmit                  | 2 620 MHz to 2 690 MHz              | [i.26] and [i.27]         |
|                       | Receive                   | 2 500 MHz to 2 570 MHz              |                           |
| 8                     | Transmit                  | 925 MHz to 960 MHz                  | [i.22] and [i.23]         |
|                       | Receive                   | 880 MHz to 915 MHz                  |                           |
| 20                    | Transmit                  | 791 MHz to 821 MHz                  | [i.17] and [i.18]         |
|                       | Receive                   | 832 MHz to 862 MHz                  |                           |
| 22                    | Transmit                  | 3 510 MHz to 3 590 MHz              | [i.12] and [i.29]         |
|                       | Receive                   | 3 410 MHz to 3 490 MHz              |                           |
| 28<br>(note 5)        | Transmit                  | 758 MHz to 803 MHz                  | [i.14] and [i.15]         |
|                       | Receive                   | 703 MHz to 748 MHz                  |                           |
| 31                    | Transmit                  | 462,5 MHz to 467,5 MHz              | [i.16]                    |
|                       | Receive                   | 452,5 MHz to 457,5 MHz              |                           |
| 32<br>(note 1)        | Transmit                  | 1 452 MHz to 1 496 MHz              | [i.19], [i.20] and [i.21] |
|                       | Receive                   | N/A                                 |                           |
| 33                    | Transmit and Receive      | 1 900 MHz to 1 920 MHz              | [i.24]                    |
| 34                    | Transmit and Receive      | 2 010 MHz to 2 025 MHz              | [i.24]                    |
| 38                    | Transmit and Receive      | 2 570 MHz to 2 620 MHz              | [i.27] and [i.28]         |
| 40                    | Transmit and Receive      | 2 300 MHz to 2 400 MHz              | [i.26]                    |
| 41 (note 6)           | Transmit and Receive      | 2 496 MHz to 2 690 MHz              | [i.27] and [i.28]         |
| 42                    | Transmit and Receive      | 3 400 MHz to 3 600 MHz              | [i.12] and [i.29]         |
| 43                    | Transmit and Receive      | 3 600 MHz to 3 800 MHz              | [i.12] and [i.29]         |
| 46<br>(notes 3 and 4) | Transmit and Receive      | 5 150 MHz to 5 925 MHz              | [i.10] and [i.11]         |
| 50 (note 1)           | Transmit                  | 1 432 MHz to 1 517 MHz              | [i.20]                    |
|                       | Receive                   | 1 432 MHz to 1 517 MHz              |                           |
| 51 (note 1)           | Transmit                  | 1 427 MHz to 1 432 MHz              | [i.20]                    |
|                       | Receive                   | 1 427 MHz to 1 432 MHz              |                           |
| 65 (note 7)           | Transmit                  | 2 110 MHz to 2 200 MHz              | [i.24], [i.25] and [i.30] |
|                       | Receive                   | 1 920 MHz to 2 010 MHz              |                           |
| 67                    | Transmit                  | 738 MHz to 758 MHz                  | [i.14] and [i.15]         |
|                       | Receive                   | N/A                                 |                           |
| 68                    | Transmit                  | 753 MHz to 783 MHz                  | [i.14] and [i.15]         |
|                       | Receive                   | 698 MHz to 728 MHz                  |                           |
| 69<br>(note 1)        | Transmit                  | 2 570 MHz to 2 620 MHz              | [i.27] and [i.28]         |
|                       | Receive                   | N/A                                 |                           |
| 72                    | Transmit                  | 461 MHz to 466 MHz                  | [i.16]                    |
|                       | Receive                   | 451 MHz to 456 MHz                  |                           |
| 75 (note 1)           | Transmit                  | 1 432 MHz to 1 517 MHz              | [i.19], [i.20] and [i.21] |
| 76 (note 1)           | Transmit                  | 1 427 MHz to 1 432 MHz              | [i.20] and [i.21]         |

| E-UTRA band                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Direction of transmission | E-UTRA Base Station operating bands | Relevant EC/ECC decision |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-------------------------------------|--------------------------|
| 87                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Transmit                  | 420 MHz to 425 MHz                  | [i.16]                   |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Receive                   | 410 MHz to 415 MHz                  |                          |
| 88                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Transmit                  | 422 MHz to 427 MHz                  | [i.16]                   |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Receive                   | 412 MHz to 417 MHz                  |                          |
| <p>NOTE 1: Restricted to E-UTRA DL operation when carrier aggregation is configured. The downlink operating band is paired with the uplink operating band (external) of the carrier aggregation configuration that is supporting the configured Pcell.</p> <p>NOTE 2: Void.</p> <p>NOTE 3: This band is an unlicensed band restricted to licensed-assisted operation using Frame Structure Type 3. In Europe according to [i.10] and [i.11], radio equipment in band 46 operates between 5 150 MHz and 5 725 MHz as in table 1-2.</p> <p>NOTE 4: In this version of the present document, restricted to E-UTRA DL operation when carrier aggregation is configured. Band 46 is divided into three sub-bands as in table 1-2.</p> <p>NOTE 5: In Europe according to [i.14] and [i.15], radio equipment in band 28 operates between 758 MHz to 791 MHz for the transmitter (<math>F_{DL\_low} = 758</math> MHz and <math>F_{DL\_high} = 791</math> MHz) and between 703 MHz to 736 MHz for the receiver (<math>F_{UL\_low} = 703</math> MHz and <math>F_{UL\_high} = 736</math> MHz).</p> <p>NOTE 6: In Europe according to [i.27] and [i.28], radio equipment in band 41 operates between 2 570 MHz and 2 620 MHz (<math>F_{DL\_low} = 2 570</math> MHz and <math>F_{DL\_high} = 2 620</math> MHz).</p> <p>NOTE 7: This band includes two frequency ranges that are harmonised in Europe:</p> <p>(a) Based on [i.30], radio equipment in band 65 operates between 2 170 MHz to 2 200 MHz for the transmitter (<math>F_{DL\_low} = 2 170</math> MHz and <math>F_{DL\_high} = 2 200</math> MHz) and between 1 980 MHz to 2 010 MHz for the receiver (<math>F_{UL\_low} = 1 980</math> MHz and <math>F_{UL\_high} = 2 010</math> MHz) as the Complementary Ground Component (CGC) of a Mobile-satellite service by reference to the present Harmonised Standard.</p> <p>(b) According to [i.24] and [i.25], radio equipment in band 65 operates between 2 110 MHz to 2 170 MHz for the transmitter (<math>F_{DL\_low} = 2 110</math> MHz and <math>F_{DL\_high} = 2 170</math> MHz), and between 1 920 MHz to 1 980 MHz for the receiver (<math>F_{UL\_low} = 1 920</math> MHz and <math>F_{UL\_high} = 1 980</math> MHz).</p> |                           |                                     |                          |

## iTEh STANDARD PREVIEW

### (standards.iteh.ai)

Table 1-2: Sub-bands for band 46

| E-UTRA Operating band | Uplink (UL) operating band<br>BS receive<br>UE transmit | Downlink (DL) operating band<br>BS transmit<br>UE receive | Relevant EC/ECC decision |
|-----------------------|---------------------------------------------------------|-----------------------------------------------------------|--------------------------|
|                       | $F_{UL\_low} - F_{UL\_high}$                            | $F_{DL\_low} - F_{DL\_high}$                              |                          |
| 46a                   | 5 150 MHz to 5 250 MHz                                  | 5 150 MHz to 5 250 MHz                                    | [i.10] and [i.11]        |
| 46b                   | 5 250 MHz to 5 350 MHz                                  | 5 250 MHz to 5 350 MHz                                    | [i.10] and [i.11]        |
| 46c                   | 5 470 MHz to 5 725 MHz                                  | 5 470 MHz to 5 725 MHz                                    | [i.10] and [i.11]        |

The present document covers conducted requirements for E-UTRA Base Stations for 3GPP Release 8, 9, 10, 11, 12, 13, 14 and 15. Additionally, it includes the requirements for E-UTRA Base Station operating bands and E-UTRA CA operating bands from 3GPP Release 16.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given in annex A.

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 136 141 (V15.9.0) (07-2020): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) conformance testing (3GPP TS 36.141 version 15.9.0 Release 15)".
- [2] ETSI TS 125 104 (V15.5.0) (04-2019): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (FDD) (3GPP TS 25.104 version 15.5.0 Release 15)".
- [3] ETSI TS 125 105 (V15.0.0) (07-2018): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (TDD) (3GPP TS 25.105 version 15.0.0 Release 15)".
- [4] ETSI TS 136 104 (V15.9.0) (07-2020): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception (3GPP TS 36.104 version 15.9.0 Release 15)".
- [5] ETSI TS 125 141 (V15.4.0) (04-2019): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) conformance testing (FDD) (3GPP TS 25.141 version 15.4.0 Release 15)".
- [6] ETSI TS 136 211 (V15.9.0) (04-2020): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical channels and modulation (3GPP TS 36.211 version 15.9.0 Release 15)".
- [7] ETSI EN 301 908-18 (V15.0.1) (06-2021): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 18: E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS) Release 15".
- [8] ETSI EN 301 893 (V2.1.1) (05-2017): "5 GHz RLAN; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU".
- [9] ETSI TS 136 213 (V15.9.0) (04-2020): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures (3GPP TS 36.213 version 15.9.0 Release 15)".
- [10] ETSI TS 136 101 (V15.11.0) (08-2020): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception (3GPP TS 36.101 version 15.11.0 Release 15)".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Commission implementing decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.2] Directive 2014/53/EU of the European Parliament and of the council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI EG 203 336 (V1.2.1) (05-2020): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.4] Recommendation ITU-R SM.329-12 (09-2012): "Unwanted emissions in the spurious domain".
- [i.5] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.6] Void.
- [i.7] ETSI EN 301 908-1: "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 1: Introduction and common requirements Release 15"  
<https://standards.iteh.ai/catalog/standards/sist/07b-4099c-daa1-4665-98c9-867bcc38714f/osist-pr-en-301-908-14-v15-1-0-2021>
- [i.8] Void.
- [i.9] ETSI TS 136 214 (V15.5.0) (01-2020): "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer; Measurements (3GPP TS 36.214 version 15.5.0 Release 15)".
- [i.10] Commission Decision 2005/513/EC of 11 July 2005 on the harmonised use of radio spectrum in the 5 GHz frequency band for the implementation of Wireless Access Systems including Radio Local Area Networks (WAS/RLANs).
- [i.11] Commission Decision 2007/90/EC of 12 February 2007 amending Decision 2005/513/EC on the harmonised use of radio spectrum in the 5 GHz frequency band for the implementation of Wireless Access Systems including Radio Local Area Networks (WAS/RLANs).
- [i.12] Commission Decision 2019/235/EC of 24 January 2019 on amending Decision 2008/411/EC as regards an update of relevant technical conditions applicable to the 3 400-3 800 MHz frequency band.
- [i.13] ETSI TS 103 807: "Mobile Standards Group (MSG); IMT Cellular Networks Base Stations (BS)".
- [i.14] ECC Decision (15)01: "Harmonised technical conditions for mobile/fixed communications networks (MFCN) in the band 694-790 MHz including a paired frequency arrangement (Frequency Division Duplex 2x30 MHz) and an optional unpaired frequency arrangement (Supplemental Downlink)", approved 06 March 2015.
- [i.15] Commission Implementing Decision (EU) 2016/687 of 28 April 2016 on the harmonisation of the 694-790 MHz frequency band for terrestrial systems capable of providing wireless broadband electronic communications services and for flexible national use in the Union.

- [i.16] ECC Decision (16)02: "Harmonised technical conditions and frequency bands for the implementation of Broadband Public Protection and Disaster Relief (BB-PPDR) systems", approved 17 June 2016.
- [i.17] ECC Decision (09)03: "Harmonised conditions for mobile/fixed communications networks (MFCN) operating in the band 790 - 862 MHz", 30 October 2009.
- [i.18] Commission Decision 2010/267/EU of 6 May 2010 on harmonised technical conditions of use in the 790-862 MHz frequency band for terrestrial systems capable of providing electronic communications services in the European Union.
- [i.19] ECC Decision (13)03: "The harmonised use of the frequency band 1 452-1 492 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)".
- [i.20] ECC Decision 17(06): "The harmonised use of the frequency bands 1 427-1 452 MHz and 1492-1518 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)", approved 17 November 2017, corrected 2 March 2018.
- [i.21] Commission Implementing Decision (EU) 2018/661 of 26 April 2018 amending Implementing Decision (EU) 2015/750 on the harmonisation of the 1452-1492 MHz frequency band for terrestrial systems capable of providing electronic communications services in the Union as regards its extension in the harmonised 1427-1452 MHz and 1492-1517 MHz frequency bands.
- [i.22] Commission Implementing Decision 2011/251/EU of 18 April 2011 amending Decision 2009/766/EC on the harmonisation of the 900 MHz and 1800 MHz frequency bands for terrestrial systems capable of providing pan-European electronic communications services in the Community.
- [i.23] ECC Decision (06)13: "Designation of the bands 880-915 MHz, 925-960 MHz, 1710-1785 MHz and 1805-1880 MHz for terrestrial UMTS, LTE, WiMAX and IoT cellular systems", approved 01 December 2006, amended 8 March 2019.
- [i.24] ECC Decision (06)01: "The harmonised utilisation of the bands 1920-1980 MHz and 2110-2170 MHz for mobile/fixed communications networks (MFCN) including terrestrial IMT systems", approved 24 March 2006, amended 8 March 2019.
- [i.25] Commission Implementing Decision (EU) 2020/667 of 6 May 2020 amending Decision 2012/688/EU as regards an update of relevant technical conditions applicable to the frequency bands 1 920-1 980 MHz and 2 110-2 170 MHz.
- [i.26] ECC Decision 14(02): "Harmonised technical and regulatory conditions for the use of the band 2 300-2 400 MHz for Mobile/Fixed Communications Networks (MFCN)", approved 27 June 2014.
- [i.27] ECC Decision 05(05): "Harmonised utilization of spectrum for Mobile/Fixed Communications Networks (MFCN) operating within the band 2 500-2 690 MHz", approved 18 March 2005, amended 05 July 2019.
- [i.28] Commission Implementing Decision (EU) 2020/636 of 8 May 2020 amending Decision 2008/477/EC as regards an update of relevant technical conditions applicable to the 2 500-2 690 MHz frequency band.
- [i.29] ECC Decision 11(06): "Harmonised frequency arrangements and least restrictive technical conditions (LRTC) for mobile/fixed communications networks (MFCN) operating in the band 3400-3800 MHz", approved 09 December 2011, amended 26 October 2018.
- [i.30] ECC Decision 06(09): "Designation of the bands 1980-2010 MHz and 2170-2200 MHz for use by systems in the Mobile-Satellite Service including those supplemented by a Complementary Ground Component (CGC)", approved 01 December 2006, amended 05 September 2007.