

Draft **ETSI EN 301 908-3** V15.0.0 (2024-02)



**IMT cellular networks;
Harmonised Standard for access to radio spectrum;
Part 3: CDMA Direct Spread (UTRA FDD)
Base Stations (BS)
Release 15**

[ETSI EN 301 908-3 V15.0.0 \(2024-02\)](https://standards.iteh.ai/catalog/standards/etsi/cf0c9676-a2ea-465a-9c55-8d35968fc7e6/etsi-en-301-908-3-v15-0-0-2024-02)

<https://standards.iteh.ai/catalog/standards/etsi/cf0c9676-a2ea-465a-9c55-8d35968fc7e6/etsi-en-301-908-3-v15-0-0-2024-02>

ReferenceREN/MSG-TFES-15-3

Keywords3G, 3GPP, cellular, digital, E-UTRA, IMT,
IMT-2000, IMT-Advanced, mobile, radio,
regulation, UMTS, UTRA, WCDMA**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:
<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	7
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definition of terms, symbols and abbreviations.....	10
3.1 Terms.....	10
3.2 Symbols.....	12
3.3 Abbreviations	14
4 Technical requirements specifications	15
4.1 Environmental profile.....	15
4.2 Conformance requirements	15
4.2.1 Introduction.....	15
4.2.2 Spectrum emissions mask.....	19
4.2.2.1 Definition	19
4.2.2.2 Limit.....	19
4.2.2.3 Conformance.....	25
4.2.3 Adjacent Channel Leakage power Ratio (ACLR)	25
4.2.3.1 Definition	25
4.2.3.2 Limits	25
4.2.3.2.1 General	25
4.2.3.2.2 Absolute limits	25
4.2.3.2.3 Relative limits.....	26
4.2.3.3 Conformance	27
4.2.4 Transmitter spurious emissions.....	27
4.2.4.1 Definition	27
4.2.4.2 Limits	28
4.2.4.2.1 General spurious emissions limits	28
4.2.4.2.2 Co-existence with other systems	28
4.2.4.2.3 Void.....	31
4.2.4.2.4 Protection of the BS receiver of own or different BS.....	31
4.2.4.2.5 Co-existence with Home BS operating in other bands	32
4.2.4.3 Conformance.....	32
4.2.5 Base Station maximum output power	32
4.2.5.1 Definition	32
4.2.5.2 Limit.....	32
4.2.5.3 Conformance.....	32
4.2.6 Transmitter intermodulation	33
4.2.6.1 Definition	33
4.2.6.2 Limit.....	33
4.2.6.3 Conformance.....	34
4.2.7 Receiver spurious emissions	34
4.2.7.1 Definition	34
4.2.7.2 Limit.....	34
4.2.7.3 Conformance.....	34
4.2.8 Blocking characteristics	35
4.2.8.1 Definition	35
4.2.8.2 Limit.....	35
4.2.8.3 Conformance.....	39
4.2.9 Receiver intermodulation characteristics	39
4.2.9.1 Definition	39

4.2.9.2	Limit.....	39
4.2.9.3	Conformance.....	41
4.2.10	Receiver adjacent channel selectivity.....	41
4.2.10.1	Definition.....	41
4.2.10.2	Limit.....	41
4.2.10.3	Conformance.....	42
4.2.11	Home BS output power for adjacent channel protection.....	42
4.2.11.1	Definition.....	42
4.2.11.2	Limit.....	42
4.2.11.3	Conformance.....	42
4.2.12	Reference sensitivity level.....	43
4.2.12.1	Definition.....	43
4.2.12.2	Limit.....	43
4.2.12.3	Conformance.....	43
5	Testing for compliance with technical requirements.....	43
5.1	Environmental conditions for testing.....	43
5.2	Interpretation of measurement results.....	43
5.3	Essential radio test suites.....	43
5.3.0	Introduction.....	43
5.3.1	Spectrum emission mask (SEM).....	44
5.3.1.0	General.....	44
5.3.1.1	Initial conditions.....	44
5.3.1.2	Procedures.....	44
5.3.1.3	Test requirement.....	45
5.3.2	Adjacent Channel Leakage power Ratio (ACLR).....	45
5.3.2.1	Initial conditions.....	45
5.3.2.2	Procedure.....	45
5.3.2.3	Test requirement.....	46
5.3.3	Transmitter spurious emissions.....	46
5.3.3.0	General.....	46
5.3.3.1	Initial conditions.....	46
5.3.3.2	Procedure.....	46
5.3.3.3	Test requirement.....	47
5.3.4	Base Station maximum output power.....	47
5.3.4.0	General.....	47
5.3.4.1	Initial conditions.....	47
5.3.4.2	Procedure.....	47
5.3.4.3	Test requirement.....	48
5.3.5	Transmit intermodulation.....	48
5.3.5.0	General.....	48
5.3.5.1	Initial conditions.....	48
5.3.5.2	Procedures.....	48
5.3.5.3	Test requirement.....	49
5.3.6	Receiver spurious emissions.....	49
5.3.6.0	General.....	49
5.3.6.1	Initial conditions.....	49
5.3.6.2	Procedure.....	50
5.3.6.3	Test requirement.....	50
5.3.7	Blocking characteristics.....	50
5.3.7.0	General.....	50
5.3.7.1	Initial conditions.....	50
5.3.7.2	Procedure.....	51
5.3.7.3	Test requirement.....	52
5.3.8	Receiver intermodulation characteristics.....	52
5.3.8.0	General.....	52
5.3.8.1	Initial conditions.....	52
5.3.8.2	Procedures.....	52
5.3.8.3	Test requirement.....	53
5.3.9	Receiver adjacent channel selectivity (ACS).....	53
5.3.9.0	General.....	53
5.3.9.1	Initial conditions.....	53

5.3.9.2	Procedure	53
5.3.9.3	Test requirement	54
5.3.10	Home BS output power for adjacent channel protection	54
5.3.10.1	Initial conditions	54
5.3.10.2	Procedure	54
5.3.10.3	Test requirement	54
5.3.11	Reference sensitivity level	55
5.3.11.0	General	55
5.3.11.1	Initial Conditions.....	55
5.3.11.2	Procedure	55
5.3.11.3	Test requirement	55
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	56
Annex B (normative):	Base Station configurations.....	58
B.1	Receive configurations	58
B.1.1	General	58
B.1.2	Receiver diversity.....	58
B.2	Duplexers	58
B.3	Power supply options	58
B.4	Ancillary RF amplifiers.....	59
B.5	BS using antenna arrays	59
B.5.0	Introduction	59
B.5.1	Receiver tests.....	60
B.5.2	Transmitter tests	60
B.6	Transmit configurations	60
B.6.1	General	60
B.6.2	Diversity and MIMO transmission.....	61
B.7	BS with integrated Iuant BS modem.....	61
Annex C (informative):	Maximum Measurement Uncertainty.....	62
Annex D (informative):	Checklist	64
Annex E (informative):	Bibliography.....	65
Annex F (informative):	Change history	66
History		67

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI Standardisation Request deliverable Approval Procedure.

For non EU countries, the present document may be used for regulatory (Type Approval) purposes.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.1] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A-1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 3 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.5].

Proposed national transposition dates

Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI that are designed to fit in a modular structure to cover radio equipment within the scope of the Radio Equipment Directive [i.2]. The present document is produced following the guidance in ETSI EG 203 336 [i.3] as applicable.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ETSI EN 301 908-3 V15.0.0 (2024-02)

<http://standards.iteh.ai/catalog/standards/etsi/en/301-908-3-v15.0.0-2024-02>

1 Scope

The present document specifies technical characteristics and methods of measurements for types of radio equipment:

- Base Stations for IMT 2000 CDMA Direct Spread (UTRA FDD).

These radio equipment types are capable of operating in whole or any part of the operating band(s) given in table 1-1.

Table 1-1: UTRA FDD Base Station operating bands

UTRA FDD band	Direction of transmission	UTRA FDD Base Station operating bands	Related EC/ECC decision
I	Transmit	2 110 MHz to 2 170 MHz	[i.8] and [i.9]
	Receive	1 920 MHz to 1 980 MHz	
III	Transmit	1 805 MHz to 1 880 MHz	[i.10] and [i.11]
	Receive	1 710 MHz to 1 785 MHz	
VII	Transmit	2 620 MHz to 2 690 MHz	[i.12] and [i.13]
	Receive	2 500 MHz to 2 570 MHz	
VIII	Transmit	925 MHz to 960 MHz	[i.10] and [i.11]
	Receive	880 MHz to 915 MHz	
XX	Transmit	791 MHz to 821 MHz	[i.14] and [i.15]
	Receive	832 MHz to 862 MHz	
XXII	Transmit	3 510 MHz to 3 590 MHz	[i.16] and [i.17]
	Receive	3 410 MHz to 3 490 MHz	
XXXII (see note)	Transmit	1 452 MHz to 1 496 MHz	[i.18] and [i.19]
	Receive	-	

NOTE: Radio equipment in band XXXII only operates in transmit mode (downlink only). Only transmitter requirements are applicable.

The present document covers conducted requirements for UTRA Base Stations for 3GPP Release 15. Additionally, it includes requirements for selected operating bands from 3GPP Releases 16 and 17.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI TS 125 141 \(V15.4.0\) \(04-2019\)](#): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) conformance testing (FDD) (3GPP TS 25.141 version 15.4.0 Release 15)".
- [2] [ETSI TS 145 004 \(V15.0.0\) \(07-2018\)](#): "Digital cellular telecommunications system (Phase 2+) (GSM); GSM/ EDGE Modulation (3GPP TS 45.004 version 15.0.0 Release 15)".
- [3] [ETSI TS 125 104 \(V15.5.0\) \(04-2019\)](#): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (FDD) (3GPP TS 25.104 version 15.5.0 Release 15)".

- [4] [ETSI EN 301 908-18 \(V15.1.1\) \(09-2021\)](#): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 18: E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS) Release 15".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] [Commission implementing decision C\(2015\) 5376](#) final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.2] [Directive 2014/53/EU](#) of the European parliament and of the council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI EG 203 336 (V1.1.1) (08-2015): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.4] Void. (<https://standards.iteh.ai>)
- [i.5] ETSI EN 301 908-1 (V15.1.1) (09-2021): "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 1: Introduction and common requirements Release 15".
- [i.6] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.7] Recommendation ITU-R SM.329-12 (09-2012): "Unwanted emissions in the spurious domain".
- [i.8] [Commission Implementing Decision \(EU\) 2020/667](#) of 6 May 2020 amending Decision 2012/688/EU as regards an update of relevant technical conditions applicable to the frequency bands 1 920-1 980 MHz and 2 110-2 170 MHz.
- [i.9] [ECC Decision \(06\)01](#): "The harmonised utilisation of the bands 1920-1980 MHz and 2110-2170 MHz for mobile/fixed communications networks (MFCN), including terrestrial IMT systems", Approved 24 March 2006, Amended 8 March 2019.
- [i.10] [Commission Implementing Decision \(EU\) 2022/173](#) of 7 February 2022 on the harmonisation of the 900 MHz and 1800 MHz frequency bands for terrestrial systems capable of providing electronic communications services in the Union and repealing Decision 2009/766/EC.
- [i.11] [ECC Decision \(06\)13](#): "Designation of the bands 880-915 MHz, 925-960 MHz, 1710-1785 MHz and 1805-1880 MHz for terrestrial UMTS, LTE, WiMAX and IoT cellular systems", Approved 01 December 2006, Amended 8 March 2019.
- [i.12] [Commission Implementing Decision \(EU\) 2020/636](#) of 8 May 2020 amending Decision 2008/477/EC as regards an update of relevant technical conditions applicable to the 2 500-2 690 MHz frequency band.
- [i.13] [ECC Decision 05\(05\)](#): "Harmonised utilization of spectrum for Mobile/Fixed Communications Networks (MFCN) operating within the band 2 500-2 690 MHz", Approved 18 March 2005, Amended 05 July 2019.

- [i.14] [Commission Decision 2010/267/EU](#) of 6 May 2010 on harmonised technical conditions of use in the 790-862 MHz frequency band for terrestrial systems capable of providing electronic communications services in the European Union.
- [i.15] [ECC Decision \(09\)03](#): "Harmonised conditions for mobile/fixed communications networks (MFCN) operating in the band 790 - 862 MHz", 30 October 2009.
- [i.16] [Commission implementing Decision \(EU\) 2019/235](#) of 24 January 2019 on amending Decision 2008/411/EC as regards an update of relevant technical conditions applicable to the 3 400-3 800 MHz frequency band.
- [i.17] [ECC Decision 11\(06\)](#): "Harmonised frequency arrangements and least restrictive technical conditions (LRTC) for mobile/fixed communications networks (MFCN) operating in the band 3400-3800 MHz", Approved 09 December 2011, Amended 26 October 2018.
- [i.18] [Commission Implementing Decision \(EU\) 2018/661](#) of 26 April 2018 amending Implementing Decision (EU) 2015/750 on the harmonisation of the 1452-1492 MHz frequency band for terrestrial systems capable of providing electronic communications services in the Union as regards its extension in the harmonised 1427-1452 MHz and 1492-1517 MHz frequency bands.
- [i.19] [ECC Decision \(13\)03](#): "The harmonised use of the frequency band 1 452-1 492 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)".
- [i.20] ETSI TR 103 877 (V1.1.1): "Task Force for European Standards for IMT-2000 (MSG); Technical Parameter selection in ETSI EN 301 908 Base Station (BS) Harmonised Standards".
- [i.21] ETSI TS 103 807 (V1.1.1) (06-2021): "Mobile Standards Group (MSG); IMT Cellular Networks Base Stations (BS) Additional Regulatory Requirements".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

ancillary equipment: equipment (apparatus) used in connection with a Base Station

NOTE: This is considered as an ancillary equipment (apparatus) if:

- the equipment is intended for use in conjunction with a Base Station to provide additional operational and/or control features to the radio equipment (e.g. to extend control to another position or location);
- the equipment cannot be used on a standalone basis to provide user functions independently of a BS; and
- the BS to which it is connected, is capable of providing some intended operation, such as transmitting and/or receiving without the ancillary equipment (i.e. it is not a sub-unit of the main equipment essential to the main equipment basic functions).

Base Station (BS) class: classification of BS according to its intended use

NOTE: There are three BS classes in the present document: wide area Base Station, medium range Base Station and local Area Base Station.

BS receiver: composite receiver function of a BS receiving in an operating band

BS RF Bandwidth: RF bandwidth in which a base station transmits and/or receives single or multiple carrier(s) within a supported operating band

NOTE: In single carrier operation, the Base Station RF Bandwidth is equal to the channel bandwidth.

BS RF bandwidth edge: frequency of one of the edges of the BS RF Bandwidth

NOTE: Base Station RF Bandwidth edges are separated by the Base Station RF Bandwidth.

channel bandwidth: RF bandwidth supporting a single UTRA RF carrier

NOTE: The channel bandwidth is measured in MHz and is used as a reference for transmitter and receiver RF requirements.

chip rate: rate of "chips" (modulated symbols after spreading) per second

NOTE: The UTRA FDD chip rate is 3,84 Mchip/s.

contiguous carriers: set of two or more carriers configured in a spectrum block where there are no RF requirements based on co-existence for un-coordinated operation within the spectrum block

contiguous spectrum: spectrum consisting of a contiguous block of spectrum with no sub-block gap(s)

downlink operating band: part of the operating band designated for downlink (BS transmit)

environmental profile: range of environmental conditions under which equipment, within the scope of the present document, is required to comply with the provisions of the present document

home Base Station: Base Station characterized by requirements derived from femtocell scenarios

inter-band gap: frequency gap between two supported consecutive operating bands

inter RF bandwidth gap: frequency gap between two consecutive BS RF Bandwidths that are placed within two supported operating bands

Local Area Base Station: Base Station characterized by requirements derived from picocell scenarios with a BS to UE minimum coupling loss equal to 45 dB

lower sub-block edge: frequency at the lower edge of one sub-block

NOTE: It is used as a frequency reference point for both transmitter and receiver requirements.

maximum BS RF bandwidth: maximum RF bandwidth supported by a BS within each supported operating band

maximum output power per carrier: mean power level per carrier of the Base Station measured at the antenna connector in a specified reference condition

maximum radio bandwidth: maximum frequency difference between the upper edge of the highest used carrier and the lower edge of the lowest used carrier

mean power: power (transmitted or received) in a bandwidth of at least $(1 + \alpha)$ times the chip rate of the radio access mod, when applied to a WCDMA-modulated signal

NOTE 1: The period of measurement is at least one timeslot unless otherwise stated.

NOTE 2: $\alpha = 0,22$ is the roll-off factor of the WCDMA signal.

medium range Base Station: Base Station characterized by requirements derived from microcell scenarios with a BS to UE minimum coupling loss equal to 53 dB

MIMO mode: downlink MIMO configuration with two transmit antennas

MIMO mode with four transmit antennas: downlink MIMO configuration with four transmit antennas

minimum coupling loss: minimum distance loss including antenna gain, measured between antenna connectors

multi-band Base Station: Base Station characterized by the ability of its transmitter and/or receiver to process two or more carriers in common active RF components simultaneously, where at least one carrier is configured at a different operating band (which is not a sub-band or superseding-band of another supported operating band) than the other carrier(s)

multi-band receiver: receiver characterized by the ability to process two or more carriers in common active RF components simultaneously, where at least one carrier is configured at a different operating band (which is not a sub-band or superseding-band of another supported operating band) than the other carrier(s)

multi-band transmitter: transmitter characterized by the ability to process two or more carriers in common active RF components simultaneously, where at least one carrier is configured at a different operating band (which is not a sub-band or superseding-band of another supported operating band) than the other carrier(s)

multi-carrier transmission configuration: set of one or more contiguous or non-contiguous carriers that a BS is able to transmit simultaneously according to the manufacturer's specification

non-contiguous spectrum: spectrum consisting of two or more sub-blocks separated by sub-block gap(s)

operating band: frequency range that is defined with a specific set of technical requirements, in which UTRA FDD operates

NOTE: The operating band(s) is declared by the manufacturer according to the designations in table 1-1.

output power: mean power of one carrier of the Base Station, delivered to a load with resistance equal to the nominal load impedance of the transmitter

rated output power: mean power level per carrier that the manufacturer has declared to be available at the antenna connector

rated total output power: mean power level that the manufacturer has declared to be available at the antenna connector

RRC filtered mean power: mean power as measured through a root raised cosine filter with roll-off factor α and a bandwidth equal to the chip rate of the radio access mode

NOTE: The RRC filtered mean power of a perfectly modulated WCDMA signal is 0,246 dB less than the mean power of the same signal.

sub-band: part of the uplink and downlink frequency range of the operating band

sub-block: one contiguous allocated block of spectrum for use by the same Base Station

NOTE: There may be multiple instances of sub-blocks within a BS RF Bandwidth.

sub-block bandwidth: RF bandwidth of one sub-block

sub-block gap: frequency gap between two consecutive sub-blocks within a BS RF Bandwidth, where the RF requirements in the gap are based on co-existence for un-coordinated operation

superseding-band: band that includes the whole of the uplink and downlink frequency range of the operating band

Total RF bandwidth: maximum sum of BS RF Bandwidths in all supported operating bands

uplink operating band: part of the operating band designated for uplink (BS receive)

upper sub-block edge: frequency at the higher edge of one sub-block

NOTE: It is used as a frequency reference point for both transmitter and receiver requirements.

wide area Base Station: Base Station characterized by requirements derived from Macro Cell scenarios with a BS to UE minimum coupling loss equal to 70 dB

NOTE: This Base Station class has the same requirements as the general purpose Base Station in Releases 99, 4 and 5.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

α Roll-off factor

Δf Frequency offset of the measurement filter -3 dB point

NOTE: As defined in clause 4.2.2.2.

Δf_{\max}	The largest value of Δf used for defining the requirement
B	Appropriate frequency in the Bottom of the operating band of the BS
B_{RFBW}	Maximum BS RF Bandwidth located at the bottom of the supported frequency range in each operating band
BW_{\max}	Maximum Radio Bandwidth
BW_{tot}	Total RF Bandwidth
CPICH \hat{E}_c	Common Pilot Channel code power (on the adjacent channel)
E_b	Average energy per information bit
E_c	Total energy per PN chip
F_{filter}	Filter centre frequency
F_{high}	The highest BS transmit frequency of the downlink operating band
F_{low}	The lowest BS transmit frequency of the downlink operating band
F_{uw}	Frequency offset of unwanted signal
I_{oh}	Total received power density excluding own Home BS signal
luant	BS internal logical interface between the implementation specific O&M function and the RET antennas and TMAs control unit function of the BS
f	Frequency
$F_{\text{DL_low}}$	The lowest frequency of the downlink operating band
$F_{\text{DL_high}}$	The highest frequency of the downlink operating band
$F_{\text{DL_Offset}}$	The offset parameter used to calculate the UARFCN
$F_{\text{UL_low}}$	The lowest frequency of the uplink operating band
$F_{\text{UL_high}}$	The highest frequency of the uplink operating band
$F_{\text{UL_Offset}}$	The offset parameter used to calculate the UARFCN
M	Appropriate frequency in the Middle of the operating band of the BS
M_{RFBW}	Maximum BS RF Bandwidth located in the middle of the supported frequency range in each operating band
$P_{\max,c}$	Maximum output power (per carrier)
P_{out}	Output power
$P_{\text{rated,c}}$	Rated output power (per carrier)
$P_{\text{rated,t}}$	Rated total output power
P_{REFSENS}	Reference sensitivity power level
T	Appropriate frequency in the Top of the operating band of the BS
T_{RFBW}	Maximum BS RF Bandwidth located at the top of the supported frequency range in each operating band
W_{gap}	Sub-block gap or Inter RF Bandwidth gap size




Figure 3.2-1: Illustration of Maximum Radio Bandwidth BW_{\max} and Total RF Bandwidth for Multi-band Base Station BW_{tot}

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACLR	Adjacent Channel Leakage power Ratio
ACS	Adjacent Channel Selectivity
AWGN	Additive White Gaussian Noise
BER	Bit Error Ratio
BS	Base Station
BTS	Base Transceiver Station
CACLR	Cumulative ACLR
CDMA	Code Division Multiple Access
CEPT	Conférence Européenne des administrations des Postes et des Télécommunications
CPICH	Common Pilot CHannel
CW	Continuous Wave
DB-DC	Dual Band and Dual Carrier
DC	Direct Current
DL	Down Link (forward link)
DPCH	Dedicated Physical CHannel
DTT	Digital Terrestrial Television
DUT	Device Under Test
EC	European Commission
ECC	Electronic Communications Committee
EFTA	European Free Trade Association
EUT	Equipment Under Test
E-UTRA	Evolved UTRA
FDD	Frequency Division Duplexing
GMSK	Gaussian Minimum Shift Keying
GSM	Global System for Mobile communications
HARQ	Hybrid Automatic Repeat reQuest
HSDPA	High-Speed Downlink Packet Access
IMT	International Mobile Telecommunications
LNA	Low Noise Amplifier
MIMO	Multiple Input Multiple Output
MS	Mobile Station
MSR	Multi-Standard Radio
NC	Non-Contiguous