



## Network Functions Virtualisation (NFV) Release 2; Management and Orchestration; Network Service Templates Specification

!Teh STAN!AP! REVIEW  
(standards.iteh.ai)  
Full standard/catalog/standards/si/976048e-6acb-  
424-bb49-b3f053a89b84/etsi-gs-nfv-ifa-014-v2-7-1-2019-09

### Disclaimer

The present document has been produced and approved by the Network Functions Virtualisation (NFV) ETSI Industry Specification Group (ISG) and represents the views of those members who participated in this ISG. It does not necessarily represent the views of the entire ETSI membership.

---

**Reference**

RGS/NFV-IFA014ed271

---

**Keywords**

MANO, network, NFV, service, virtualisation

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Modal verbs terminology.....	6
1 Scope .....	7
2 References .....	7
2.1 Normative references .....	7
2.2 Informative references.....	7
3 Definition of terms, symbols and abbreviations.....	8
3.1 Terms.....	8
3.2 Symbols.....	8
3.3 Abbreviations .....	8
4 Overview .....	9
4.1 Network Service Descriptions.....	9
4.2 Relation to other ETSI NFV Group Specifications .....	10
4.3 Conventions.....	10
4.4 Various levels of NFV entities .....	11
5 Functional requirements .....	11
5.1 Void.....	11
5.2 Functional requirements for Network Service Descriptor .....	12
5.3 Functional requirements for Network Service Deployment Flavour.....	12
5.4 Functional requirements for VNF Forwarding Graph Descriptor .....	13
5.5 Functional requirements for Virtual Link Descriptor.....	13
5.6 Functional requirements for Physical Network Function Descriptor .....	13
5.7 Functional requirements for PNFD archive.....	14
6 Descriptors formats and contents .....	14
6.1 Void.....	14
6.2 Information elements related to the Network Service Descriptor .....	14
6.2.1 Introduction.....	14
6.2.2 Network Service Descriptor information element .....	15
6.2.2.1 Description .....	15
6.2.2.2 Attributes.....	15
6.2.3 Sapid information element.....	16
6.2.3.1 Description .....	16
6.2.3.2 Attributes.....	16
6.2.4 Void .....	16
6.2.5 SecurityParameters information element .....	16
6.2.5.1 Description .....	16
6.2.5.2 Attributes.....	17
6.2.6 MonitoredData Information element .....	17
6.2.6.1 Description .....	17
6.2.6.2 Attributes.....	17
6.2.7 VnfIndicatorData Information element.....	17
6.2.7.1 Description .....	17
6.2.7.2 Attributes.....	17
6.2.8 MonitoringParameter Information element .....	18
6.2.8.1 Description .....	18
6.2.8.2 Attributes.....	18
6.2.9 LifeCycleManagementScript Information element.....	18
6.2.9.1 Description .....	18
6.2.9.2 Attributes.....	18
6.2.10 Information elements related to NS lifecycle management operations.....	18
6.2.10.1 Introduction.....	18
6.2.10.2 NsLcmAdditionalParams information element.....	19

6.2.10.2.1	Description .....	19
6.2.10.2.2	Attributes .....	19
6.2.10.3	InstantiateNsAdditionalParams information element.....	19
6.2.10.3.1	Description .....	19
6.2.10.3.2	Attributes .....	19
6.2.10.4	ScaleNsAdditionalParams information element.....	19
6.2.10.4.1	Description .....	19
6.2.10.4.2	Attributes .....	19
6.2.10.5	HealNsAdditionalParams information element.....	20
6.2.10.5.1	Description .....	20
6.2.10.5.2	Attributes .....	20
6.3	Information elements related to the Network Service Deployment Flavour .....	20
6.3.1	Introduction.....	20
6.3.2	NsDf information element .....	20
6.3.2.1	Description .....	20
6.3.2.2	Attributes.....	21
6.3.3	VnfProfile information element.....	21
6.3.3.1	Description .....	21
6.3.3.2	Attributes.....	21
6.3.4	VirtualLinkProfile information element .....	22
6.3.4.1	Description .....	22
6.3.4.2	Attributes.....	22
6.3.5	AffinityOrAntiAffinityGroup information element.....	23
6.3.5.1	Description .....	23
6.3.5.2	Attributes.....	23
6.3.6	PnfProfile information element.....	24
6.3.6.1	Description .....	24
6.3.6.2	Attributes.....	24
6.3.7	NsVirtualLinkConnectivity information element .....	24
6.3.7.1	Description .....	24
6.3.7.2	Attributes.....	24
6.3.8	LocalAffinityOrAntiAffinityRule information element.....	24
6.3.8.1	Description .....	24
6.3.8.2	Attributes.....	25
6.3.9	NsLevel information element .....	25
6.3.9.1	Description .....	25
6.3.9.2	Attributes.....	25
6.3.10	NsScaleInfo information element.....	26
6.3.10.1	Description .....	26
6.3.10.2	Attributes.....	26
6.3.11	NsProfile information element.....	26
6.3.11.1	Description .....	26
6.3.11.2	Attributes.....	26
6.3.12	Dependencies information element.....	27
6.3.12.1	Description .....	27
6.3.12.2	Attributes.....	27
6.4	Information elements related to the VNF Forwarding Graph Descriptor.....	27
6.4.1	Introduction.....	27
6.4.2	Vnffgd information element .....	27
6.4.2.1	Description .....	27
6.4.2.2	Attributes.....	27
6.4.3	Nfpd information element.....	28
6.4.3.1	Description .....	28
6.4.3.2	Attributes.....	28
6.4.4	Void.....	29
6.4.5	NfpPositionDesc information element.....	29
6.4.5.1	Description .....	29
6.4.5.2	Attributes.....	29
6.4.6	NfpPositionElement information element .....	29
6.4.6.1	Description .....	29
6.4.6.2	Attributes.....	30
6.4.7	ConstituentProfileElements information element - DEPRECATED.....	30

6.4.7.1	Description .....	30
6.4.7.2	Attributes .....	30
6.4.8	CpdInConstituentElement information element .....	30
6.4.8.1	Description .....	30
6.4.8.2	Attributes .....	30
6.5	Information elements related to the Network Service Virtual Link Descriptor .....	31
6.5.1	Introduction .....	31
6.5.2	NsVirtualLinkDesc information element .....	31
6.5.2.1	Description .....	31
6.5.2.2	Attributes .....	31
6.5.3	ConnectivityType information element .....	31
6.5.3.1	Description .....	31
6.5.3.2	Attributes .....	31
6.5.4	VirtualLinkDf information element .....	32
6.5.4.1	Description .....	32
6.5.4.2	Attributes .....	32
6.5.5	LinkBitrateRequirements information element .....	32
6.5.5.1	Description .....	32
6.5.5.2	Attributes .....	32
6.5.6	NsQoS information element .....	33
6.5.6.1	Description .....	33
6.5.6.2	Attributes .....	33
6.6	Information elements related to the PNFD .....	33
6.6.1	Introduction .....	33
6.6.2	Pnfd information element .....	33
6.6.2.1	Description .....	33
6.6.2.2	Attributes .....	33
6.6.3	Cpd information element .....	34
6.6.3.1	Description .....	34
6.6.3.2	Attributes .....	34
6.6.4	PnfExtCpd information element .....	34
6.6.4.1	Description .....	34
6.6.4.2	Attributes .....	34
6.7	Information elements related to scaling .....	34
6.7.1	Introduction .....	34
6.7.2	NsScalingAspect information element .....	34
6.7.2.1	Description .....	34
6.7.2.2	Attributes .....	34
6.7.3	Void .....	35
6.7.4	VnfToLevelMapping information element .....	35
6.7.4.1	Description .....	35
6.7.4.2	Attributes .....	35
6.7.5	VirtualLinkToLevelMapping information element .....	35
6.7.5.1	Description .....	35
6.7.5.2	Attributes .....	35
6.7.6	NsToLevelMapping information element .....	36
6.7.6.1	Description .....	36
6.7.6.2	Attributes .....	36
<b>Annex A (informative):</b>	<b>Support of service function chaining .....</b>	<b>37</b>
A.1	Introduction .....	37
A.2	IETF SFC concepts .....	37
A.3	Use of the NFP Management interface .....	39
A.4	Mapping .....	39
<b>Annex B (informative):</b>	<b>Authors &amp; contributors .....</b>	<b>41</b>
<b>Annex C (informative):</b>	<b>Change History .....</b>	<b>43</b>
History .....		44

---

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

## Foreword

This Group Specification (GS) has been produced by ETSI Industry Specification Group (ISG) Network Functions Virtualisation (NFV).

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document specifies requirements and templates for describing Network Functions Virtualisation (NFV) Network Services (NSs) in the form of meta-data.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI GS NFV 003: "Network Functions Virtualisation (NFV); Terminology for Main Concepts in NFV".
- [2] ETSI GS NFV-IFA 011: "Network Functions Virtualisation (NFV); Management and Orchestration; VNF Descriptor and Packaging Specification".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI GS NFV 002: "Network Functions Virtualisation (NFV); Architectural Framework".
- [i.2] ETSI GS NFV-IFA 013: "Network Functions Virtualisation (NFV); Management and Orchestration; Os-Ma-Nfvo reference point - Interface and Information Model Specification".
- [i.3] ETSI GS NFV-SWA 001: "Network Functions Virtualisation (NFV); Virtual Network Functions Architecture".
- [i.4] ISO/IEC 9646-7: "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 7: Implementation Conformance Statements".
- [i.5] ETSI GS NFV-REL 001: "Network Functions Virtualisation (NFV); Resiliency Requirements".
- [i.6] IETF RFC 7665: "Service Function Chaining (SFC) Architecture".
- [i.7] ETSI GS NFV-IFA 005: "Network Functions Virtualisation (NFV); Management and Orchestration; Or-Vi reference point - Interface and Information Model Specification".

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in ETSI GS NFV 003 [1] and the following apply:

**Service Access Point (SAP):** connection point where a NS can be accessed

NOTE: A SAP can either provide access to an NS, e.g. to an end-user, or interconnect different NS.

### 3.2 Symbols

Void.

### 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI GS NFV 003 [1] and the following apply:

CDN	Content Delivery Network
CM	Conditional Mandatory
CO	Conditional Optional
CP	Connection Point
CPD	Connection Point Descriptor
DF	Deployment Flavour
DSL	Domain Specific Language
E-LAN	Ethernet Local Area Network
GS	Group Specification
IPV4	Internet Protocol Version 4
IPV6	Internet Protocol Version 6
LAN	Local Area Network
MANO	Management and Orchestration
MPLS	MultiProtocol Label Switching
NCT	Network Connectivity Topology
NFP	Network Forwarding Path
NFPD	Network Forwarding Path Descriptor
NS	Network Service
NSD	Network Service Descriptor
ODU2	Optical channel Data Unit - type 2
PM	Performance Management
PNFD	Physical Network Function Descriptor
SAP	Service Access Point
SAPD	Service Access Point Descriptor
SFC	Service Function Chaining
UML	Unified Modelling Language
VL	Virtual Link
VLD	Virtual Link Descriptor
VNFFG	VNF Forwarding Graph
VNFFGD	VNF Forwarding Graph Descriptor
XOR	eXclusive OR



## 4 Overview

### 4.1 Network Service Descriptions

The Network Service Descriptor (NSD) is a deployment template which consists of information used by the NFV Orchestrator (NFVO) for life cycle management of an NS.

An NS is a composition of Network Functions (NF) arranged as a set of functions with unspecified connectivity between them or according to one or more forwarding graphs. As illustrated in figure 4.1-1, the description of a NS as used by the NFV Management and Orchestration (MANO) functions to deploy an NS instance includes or references the descriptors of its constituent objects:

- zero, one or more Virtualised Network Function Descriptors (VNFD);
- zero, one or more Physical Network Function Descriptors (PNFD) used by the NFVO to determine how to connect PNFs to VLs;
- zero, one or more nested NSD;

NOTE 1: The information contained within the PNFD is limited to the description of the connectivity requirements to integrate PNFs in an NS.

NOTE 2: An NSD references at least either one VNFD or one nested NSD.

- zero, one or more Virtual Link Descriptors (VLD) used by the NFVO to deploy Virtual Links (VL); and
- zero, one or more VNF Forwarding Graph Descriptors (VNFFGD).

A VNF Forwarding Graph Descriptor (VNFFGD) describes a topology of the NS or a portion of the NS, by referencing a pool of connection points and service access points, the descriptors of its constituent VNFs, PNFs and of the VLs that connect them. It may also contain one or more Network Forwarding Path (NFP) descriptors.

NOTE 3: Different VNFFGDs can be contained in a given NSD. Each VNFFGD uses subsets of the lists of VLDs, VNFDs and PNFDs included in the NSD.

NOTE 4: For a given NS different VNFFGDs can result in packets/frames traversing identical sequences of (V)NFs, depending on the NFP descriptors included in the VNFFGDs.

NOTE 5: In a given VNFFGD the connectivity topology represents how the (V)NFs among which packets/frames can be exchanged are connected to each other. A Network Connectivity Topology (NCT), as defined in ETSI GS NFV-SWA 001 [i.3] represents a higher logical level connectivity, possibly a global view of combined connectivity from different VNFFGDs of a given NS.




Figure 4.1-1: NSD overview

## 4.2 Relation to other ETSI NFV Group Specifications

The concepts of network services and forwarding graphs are described in ETSI GS NFV 002 [i.1].

Instances of objects created according to the templates specified in the present document are exchanged at the Os-Ma-Nfvo reference point as specified in ETSI GS NFV-IFA 013 [i.2].

The format of the VNF descriptors referenced in a network service template shall comply with the specifications in ETSI GS NFV-IFA 011 [2].

## 4.3 Conventions

The attributes of the NSD and associated information elements are described in the tables provided in clause 6. Each table has 5 columns, with the following significance:

- The "Attribute" column provides the attribute name.
- The "Qualifier" column indicates whether the support of the attribute is mandatory, optional or conditional.
- The "Cardinality" column contains the minimum and maximum cardinality of this information element (e.g. 1, 2, 0..N, 1..N). A cardinality range starting with 0 indicates that the attribute needs not always to be included.
- The "Content" column provides information on the type of the attribute values. It can be the name of an Information Element, a primitive type (Identifier, DateTime, etc.) or a generic UML type (String, Integer, etc.). If a cell in the "Content" column is marked as "Not specified", this means that the specification of the type is left to the data model design stage.
- The "Description column" provides a brief explanatory description and additional constraints.

The following notations, defined in ISO/IEC 9646-7 [i.4], are used for the qualifier column of information elements:

- M mandatory - the attribute shall be supported.
- O optional - the attribute may, but need not, be supported.
- CM conditional mandatory - the attribute shall be supported under certain conditions. If the specified conditions are met then the attribute shall be supported. These conditions are specified in the Description column.

- CO conditional optional - the attribute may, but need not, be supported under certain conditions. If the specified conditions are met then the attribute may, but need not, be supported. These conditions are specified in the Description column.

The following notation is used for parameters that represent identifiers, and for attributes that represent identifiers in information elements and notifications:

- If parameters are referring to an identifier of an actual object, their type is "Identifier".
- If an object (information element or notification) contains an attribute that identifies the object, the type of that attribute is "Identifier" and the description states that the attribute is the identifier of that particular notification or information element.

EXAMPLE 1: Identifier "resourceId" of the "NetworkSubnet information element" has type "Identifier" and description "Identifier of this NetworkSubnet information element".

- If an object (information element or notification) contains an attribute that references another object or objects defined in an ETSI NFV Group Specification (GS), the type of the attribute is "Identifier", followed by the list of objects it references.

EXAMPLE 2: "Identifier (Reference to Vnfc)" or "Identifier (Reference to Vnfc, VirtualLink or VirtualStorage)".

## 4.4 Various levels of NFV entities

For NFV management and orchestration, there are four basic levels of entities:

- Descriptors - general type definitions for things such as NSs, VNFs and VLs.
- Descriptor objects - an instance of a descriptor, e.g. an instance of an NSD (not an instance of a NS instantiated according to this NSD):
  - A descriptor object may provide (among other things) value ranges and default values for the attributes in the associated NFV entity class.
  - In the present document, the creation of subclasses of generic descriptors (e.g. NSD\_x as a subclass of NSD) has been avoided, since this approach would create a proliferation of descriptor classes.
- NFV entity classes - these are classes that represent various NFV entities such as NS, VNF and VL. There is one-to-one mapping between the set of descriptor objects and the set of NFV entity classes. An example of NFV entity class is CDN NS.
- NFV entity instances - these are instances of a given NFV entity class. An NFV entity instance is used to represent the current state and attribute values for a given NFV entity. Each NFV entity instance is bound by the associated descriptor object, e.g. value ranges and default values for attributes. More than one NFV entity instance can be created from the same associated descriptor object. An example of NFV entity instance is CDN NS instance.

Each level puts constraints on the subsequent levels.

Information in a lower level does not appear in a higher level, e.g. NFV entity instance information does not appear in the associated NFV entity class, descriptor object or descriptor.

---

## 5 Functional requirements

### 5.1 Void

## 5.2 Functional requirements for Network Service Descriptor

Table 5.2-1 specifies functional requirements applicable to the templates for NSD instances.

**Table 5.2-1: Functional requirements for NSD**

Numbering	Requirement description
NST_NSDD001	The NSD shall reference the VNFDs applicable to its constituent VNFs.
NST_NSDD002	The NSD shall include the VLDs applicable to the VLs used by the NS to interconnect its constituent NFs.
NST_NSDD003	The NSD shall reference the PNFDs applicable to its constituent PNFs.
NST_NSDD004	The NSD shall specify the Service Access Points (SAPs) of the NS.
NST_NSDD005	The NSD shall include the descriptors of the VNFFGs applicable to the NS. See note 1.
NST_NSDD006	The NSD shall support the capability to include or reference NS life cycle management scripts describing how to react upon specific life cycle events, fault detection, performance threshold crossing detection and other events that can occur at the NFVO reference points.
NST_NSDD007	The NSD shall support the capability to provide monitoring parameters to be tracked during the lifetime of a NS instance. See note 2.
NST_NSDD008	The NSD shall support the capability to describe one or more NS DF(s).
NST_NSDD009	The NSD shall support the capability to describe auto scale rules, associating criteria to scaling actions (e.g. removing existing VNF instances from an NS instance).
NST_NSDD010	The NSD shall include security information enabling validating its authenticity and integrity.
NST_NSDD011	The NSD shall support the capability to reference NSDs used to instantiate nested or appended NSs. See note 3.
NST_NSDD012	The NSD shall include a globally unique identifier for identifying each descriptor instance.
NOTE 1: A NS might have multiple graphs, for example, for: <ol style="list-style-type: none"> <li>1) Control plane traffic.</li> <li>2) Management plane traffic.</li> <li>3) User plane traffic.</li> </ol>	
NOTE 2: These can be used for specifying different Deployment Flavours (DF) for the NS in the NSD or in determining the need to scale-out.	
NOTE 3: NSs are composable, i.e. they can include other NSs (a.k.a. nested NS) or other NSs can be appended to them.	

## 5.3 Functional requirements for Network Service Deployment Flavour

Table 5.3-1 specifies functional requirements applicable to the templates for describing NS DF.

**Table 5.3-1: Functional requirements for NS DF description**

Numbering	Requirement description
NST_NSDF001	An NS DF description shall describe how many instances of each constituent VNF are required.
NST_NSDF002	An NS DF description shall reference a VNF flavour to be used for each constituent VNF.
NST_NSDF003	An NS DF description shall enable describing affinity and anti-affinity rules between the different instances of a constituent VNF.
NST_NSDF004	An NS DF description shall enable describing affinity and anti-affinity rules between the constituent VNFs.
NST_NSDF005	An NS DF description shall enable referencing a VL flavour to be used for each VL connected to its constituent VNFs.
NST_NSDF006	An NS DF description shall enable describing affinity and anti-affinity rules between the different instances of a constituent VL.
NST_NSDF007	An NS DF description shall enable describing affinity and anti-affinity rules between the constituent VLs.
NST_NSDF008	An NS DF description shall support the capability to describe dependencies between VNF and/or nested NS instances in terms of primary and secondary entities. See note.
NOTE: This information is used, for example, to define the sequence in which various numbered VNF and/or nested NS should be instantiated by the NFVO.	