

ETSI EN 303 676 V1.1.1 (2021-07)



**Navigation radar used on inland waterways;
Operational, functional and technical requirements
(standards.iteh.ai)**

<https://standards.iteh.ai/catalog/standards/sist/795b37b8-4ba7-42c1-a331-0525fce1be60/etsi-en-303-676-v1-1-1-2021-07>

ReferenceDEN/ERM-TGMAR-609

Keywordsmaritime, navigation, radar, radio

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Contents

Intellectual Property Rights	9
Foreword.....	9
Modal verbs terminology.....	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	10
3 Definition of terms, symbols and abbreviations.....	11
3.1 Terms.....	11
3.2 Symbols.....	11
3.3 Abbreviations	12
4 General requirements	12
4.1 Purpose of the radar equipment.....	12
4.2 Construction and design	13
4.3 Operational controls	13
4.4 Interfaces.....	13
4.4.1 Fail safe design	13
4.4.2 Display of data received via interfaces	13
4.4.3 Operation of equipment connected via interfaces.....	14
4.4.4 Interpretation and presentation of data delivered via interfaces.....	14
4.5 Software	14
4.5.1 Software performance.....	14
4.5.2 Software protection.....	14
4.6 Equipment labelling	14
4.7 Operating and service manuals.....	14
5 Testing requirements specifications.....	15
5.1 Environmental profile.....	15
5.2 Conformance Requirements	15
5.2.1 Tests under extreme conditions	15
5.2.1.1 Performance check procedure.....	15
5.2.1.1.1 Definition.....	15
5.2.1.1.2 Required test results	15
5.2.1.1.3 Conformance	15
5.2.1.2 Temperature test of the indoor unit.....	15
5.2.1.2.1 Definition.....	15
5.2.1.2.2 Required test results	15
5.2.1.2.3 Conformance	15
5.2.1.3 Temperature test of the outdoor unit.....	16
5.2.1.3.1 Definition.....	16
5.2.1.3.2 Required test results	16
5.2.1.3.3 Conformance	16
5.2.1.4 Damp heat test of outdoor unit.....	16
5.2.1.4.1 Definition.....	16
5.2.1.4.2 Required test results	16
5.2.1.4.3 Conformance	16
5.2.1.5 Extreme power voltage and frequency test	16
5.2.1.5.1 Definition.....	16
5.2.1.5.2 Required test results	16
5.2.1.5.3 Conformance	16
5.2.1.6 Extreme vibration test	16
5.2.1.6.1 Definition.....	16
5.2.1.6.2 Required test results	16
5.2.1.6.3 Conformance	17
5.2.2 Operational and functional requirements.....	17

5.2.2.1	Start-up time.....	17
5.2.2.1.1	Definition.....	17
5.2.2.1.2	Required test results	17
5.2.2.1.3	Conformance	17
5.2.2.2	System sensitivity	17
5.2.2.2.1	Definition.....	17
5.2.2.2.2	Required test results	17
5.2.2.2.3	Conformance	17
5.2.2.3	Gain dynamic range	17
5.2.2.3.1	Definition.....	17
5.2.2.3.2	Required test results	17
5.2.2.3.3	Conformance	18
5.2.2.4	Minimum range.....	18
5.2.2.4.1	Definition.....	18
5.2.2.4.2	Required test results	18
5.2.2.4.3	Conformance	18
5.2.2.5	Radial resolution capability.....	18
5.2.2.5.1	Definition.....	18
5.2.2.5.2	Required test results	18
5.2.2.5.3	Conformance	18
5.2.2.6	Azimuthal resolution capability	18
5.2.2.6.1	Definition.....	18
5.2.2.6.2	Required test results	18
5.2.2.6.3	Conformance	18
5.2.2.7	Range scales and fixed range rings	19
5.2.2.7.1	Definition.....	19
5.2.2.7.2	Required test results	19
5.2.2.7.3	Conformance	19
5.2.2.8	Variable Range Marker (VRM)	19
5.2.2.8.1	Definition.....	19
5.2.2.8.2	Required test results	19
5.2.2.8.3	Conformance	20
5.2.2.9	Heading line and radar picture azimuth angular error	20
5.2.2.9.1	Definition.....	20
5.2.2.9.2	Required test results	20
5.2.2.9.3	Conformance	20
5.2.2.10	Bearing facilities and bearing scale.....	20
5.2.2.10.1	Definition.....	20
5.2.2.10.2	Required test results	20
5.2.2.10.3	Conformance	21
5.2.2.11	Nautical information and navigation lines	21
5.2.2.11.1	Definition.....	21
5.2.2.11.2	Required test results	21
5.2.2.11.3	Conformance	21
5.2.2.12	Facilities for suppressing sea and rain clutter.....	21
5.2.2.12.1	Definition.....	21
5.2.2.12.2	Required test results	22
5.2.2.12.3	Conformance	22
5.2.2.13	Suppression of interference from other radars	22
5.2.2.13.1	Definition.....	22
5.2.2.13.2	Required test results	22
5.2.2.13.3	Conformance	22
5.2.2.14	Compatibility with radar beacons and search and rescue radar transponders	22
5.2.2.14.1	Definition.....	22
5.2.2.14.2	Required test results	23
5.2.2.14.3	Conformance	23
5.2.2.15	Special modes of operation	23
5.2.2.15.1	Definition.....	23
5.2.2.15.2	Required test results	23
5.2.2.15.3	Conformance	23
5.2.3	Operation controls and indicators	23
5.2.3.1	Directly accessible operation controls.....	23

5.2.3.1.1	Definition.....	23
5.2.3.1.2	Required test results	23
5.2.3.1.3	Conformance	24
5.2.3.2	Brilliance controls	24
5.2.3.2.1	Definition.....	24
5.2.3.2.2	Required test results	24
5.2.3.2.3	Conformance	25
5.2.3.3	Heading line on/off control (SHM).....	25
5.2.3.3.1	Definition.....	25
5.2.3.3.2	Required test results	25
5.2.3.3.3	Conformance	25
5.2.3.4	Frequency tuning control and indicator.....	25
5.2.3.4.1	Definition.....	25
5.2.3.4.2	Required test results	25
5.2.3.4.3	Conformance	25
5.2.4	Display unit characteristics	25
5.2.4.1	Display screen dimensions.....	25
5.2.4.1.1	Definition.....	25
5.2.4.1.2	Required test results	26
5.2.4.1.3	Conformance	26
5.2.4.2	Display screen brilliance	26
5.2.4.2.1	Definition.....	26
5.2.4.2.2	Required test results	26
5.2.4.2.3	Conformance	26
5.2.4.3	Display resolution	26
5.2.4.3.1	Definition.....	26
5.2.4.3.2	Required test results	26
5.2.4.3.3	Conformance	26
5.2.4.4	Picture generation characteristics.....	27
5.2.4.4.1	Definition.....	27
5.2.4.4.2	Required test results	27
5.2.4.4.3	Conformance	27
5.2.4.5	Supplementary displays	27
5.2.4.5.1	Definition.....	27
5.2.4.5.2	Required test results	27
5.2.4.5.3	Conformance	27
5.2.4.6	Screen reflection characteristics.....	28
5.2.4.6.1	Definition.....	28
5.2.4.6.2	Required test results	28
5.2.4.6.3	Conformance	28
5.2.5	Radar picture characteristics	28
5.2.5.1	Radar picture	28
5.2.5.1.1	Definition.....	28
5.2.5.1.2	Required test results	28
5.2.5.1.3	Conformance	28
5.2.5.2	Effective diameter of the radar picture.....	28
5.2.5.2.1	Definition.....	28
5.2.5.2.2	Required test results	28
5.2.5.2.3	Conformance	28
5.2.5.3	Colours of picture presentation	29
5.2.5.3.1	Definition.....	29
5.2.5.3.2	Required test results	29
5.2.5.3.3	Conformance	29
5.2.5.4	Radar picture refresh rate and storage.....	29
5.2.5.4.1	Definition.....	29
5.2.5.4.2	Required test results	29
5.2.5.4.3	Conformance	29
5.2.5.5	Target trails	29
5.2.5.5.1	Definition.....	29
5.2.5.5.2	Required test results	30
5.2.5.5.3	Conformance	30
5.2.5.6	Off-centring.....	30

5.2.5.6.1	Definition.....	30
5.2.5.6.2	Required test results	30
5.2.5.6.3	Conformance	30
5.2.6	Antenna and antenna drive characteristics	30
5.2.6.1	Radiation pattern in the horizontal plane	30
5.2.6.1.1	Definition.....	30
5.2.6.1.2	Required test results	30
5.2.6.1.3	Conformance	31
5.2.6.2	Radiation pattern in the vertical plane.....	31
5.2.6.2.1	Definition.....	31
5.2.6.2.2	Required test results	31
5.2.6.2.3	Conformance	31
5.2.6.3	Antenna drive characteristics	31
5.2.6.3.1	Definition.....	31
5.2.6.3.2	Required test results	31
5.2.6.3.3	Conformance	31
5.2.7	Interfaces.....	32
5.2.7.1	Analogue input and display for ROT indicators.....	32
5.2.7.1.1	Definition.....	32
5.2.7.1.2	Required test results	32
5.2.7.1.3	Conformance	32
5.2.7.2	Analogue output interface for raw radar	32
5.2.7.2.1	Definition.....	32
5.2.7.2.2	Required test results	32
5.2.7.2.3	Conformance	32
5.2.7.3	Interfaces for nautical sensors	32
5.2.7.3.1	Definition.....	32
5.2.7.3.2	Required test results	33
5.2.7.3.3	Conformance	33
5.2.8	Safety distance requirements	33
5.2.8.1	Compass safety distance requirements.....	33
5.2.8.1.1	Definition.....	33
5.2.8.1.2	Required test results	33
5.2.8.1.3	Conformance	33
5.2.9	Display of other navigation information.....	33
5.2.9.1	Display of tracking and tracing information	33
5.2.9.1.1	Definition.....	33
5.2.9.1.2	Required test results	34
5.2.9.1.3	Conformance	35
5.2.9.2	Display of navigation guiding lines.....	35
5.2.9.2.1	Definition.....	35
5.2.9.2.2	Required test results	35
5.2.9.2.3	Conformance	35
6	Testing for compliance with technical requirements.....	35
6.1	General requirements	35
6.2	Standard operating mode of the radar equipment.....	36
6.3	Environmental conditions for testing	36
6.3.1	Test conditions.....	36
6.3.2	Normal test conditions.....	36
6.3.2.1	Introduction.....	36
6.3.2.2	Normal temperature and humidity	37
6.3.2.3	Normal test power supply	37
6.3.2.3.1	AC test power supply	37
6.3.2.3.2	DC test power supply	37
6.3.3	Extreme test conditions.....	37
6.3.3.1	Indoor unit.....	37
6.3.3.2	Outdoor unit.....	37
6.3.3.3	Extreme power supply voltage test conditions.....	37
6.3.3.4	Extreme vibration test conditions.....	38
6.4	Interpretation of the measurements results.....	38
6.5	Performance tests	38

6.5.1	Tests under extreme conditions	38
6.5.1.1	Performance check procedure	38
6.5.1.2	Temperature test of the indoor unit	38
6.5.1.3	Temperature test of the outdoor unit	38
6.5.1.4	Damp heat test of the outdoor unit	39
6.5.1.5	Extreme power voltage and frequency test	39
6.5.1.6	Extreme vibration test	40
6.5.2	Operational and functional requirements	40
6.5.2.1	Start-up time	40
6.5.2.2	System sensitivity	40
6.5.2.3	Gain dynamic range	40
6.5.2.4	Minimum range	41
6.5.2.5	Radial resolution capability	41
6.5.2.6	Azimuthal resolution capability	41
6.5.2.7	Range scales and fixed range rings	41
6.5.2.8	Variable Range Marker (VRM)	42
6.5.2.9	Heading line and radar picture azimuth angular error	42
6.5.2.10	Bearing facilities and bearing scale	42
6.5.2.11	Nautical information and navigation lines	42
6.5.2.12	Facilities for suppressing sea and rain clutter	42
6.5.2.13	Suppression of interference from other radars	42
6.5.2.14	Compatibility with radar beacons and search and rescue radar transponders	43
6.5.2.15	Special modes of operation	43
6.5.3	Operation controls and indicators	43
6.5.3.1	Directly accessible operation controls	43
6.5.3.2	Brilliance controls	43
6.5.3.3	Heading line on/off control (SHM)	43
6.5.3.4	Frequency tuning control and indicator	44
6.5.4	Display unit characteristics	44
6.5.4.1	Display screen dimensions	44
6.5.4.2	Display screen brilliance	44
6.5.4.3	Display resolution	44
6.5.4.4	Picture generation characteristics	44
6.5.4.5	Supplementary displays	45
6.5.4.6	Screen reflection characteristics	45
6.5.5	Radar picture characteristics	45
6.5.5.1	Radar picture	45
6.5.5.2	Effective diameter of the radar picture	45
6.5.5.3	Colours of picture presentation	45
6.5.5.4	Radar picture refresh rate and storage	45
6.5.5.5	Target trails	46
6.5.5.6	Off-centring	46
6.5.6	Antenna and antenna drive characteristics	46
6.5.6.1	Radiation pattern in the horizontal plane	46
6.5.6.2	Radiation pattern in the vertical plane	46
6.5.6.3	Antenna drive characteristics	46
6.5.7	Interfaces	46
6.5.7.1	Analogue input and display for ROT indicators	46
6.5.7.2	Analogue output interface for raw radar	47
6.5.7.3	Interfaces for nautical sensors	47
6.5.8	Safety distance requirements	47
6.5.8.1	Compass safety distance requirements	47
6.5.9	Display of other navigation information	47
6.5.9.1	Display of tracking and tracing information	47
6.5.9.2	Display of navigation guiding lines	47
Annex A (normative):	Set-up of the radar reflectors at the test field and preparation of the radar equipment under test	48
A.1	Test site	48
A.2	Standard reflectors	48

A.3	Set-up of the radar reflectors at the test field	48
A.4	Preparation of radar equipment to test	50
Annex B (informative): Minimum range, radial resolution and azimuthal resolutions		51
B.1	Minimum range	51
B.2	Radial resolution	51
B.3	Azimuthal resolution in all range scales up to and including 1 200 m.....	52
Annex C (informative): Calculation of the equivalent Radar Cross Section (RCS).....		53
C.1	Definition	53
Annex D (normative): Measuring the reflection coefficient		54
D.1	Principle of test.....	54
D.2	Preconditions.....	54
D.3	Measurement setup.....	55
D.4	Measuring the reflection of the radar screen	55
D.4.1	Measuring the luminance of the illuminator.....	55
D.4.2	Measuring the luminance of radar screen.....	55
D.5	Calculating of reflection coefficient.....	56
History	58

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[ETSI EN 303 676 V1.1.1 \(2021-07\)](https://standards.iteh.ai/catalog/standards/sist/795b37b8-4ba7-42c1-a331-0525fce1be60/etsi-en-303-676-v1-1-1-2021-07)

<https://standards.iteh.ai/catalog/standards/sist/795b37b8-4ba7-42c1-a331-0525fce1be60/etsi-en-303-676-v1-1-1-2021-07>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITEH STANDARD PREVIEW
(standards.iteh.ai)

Foreword

ETSI EN 303 676 V1.1.1 (2021-07)

This European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

<https://standards.iteh.ai/catalog/standards/sist/9589766-40a7-42e1-a581-0525fce1be60/etsi-en-303-676-v1-1-1-2021-07>

National transposition dates

Date of adoption of this EN:	30 June 2021
Date of latest announcement of this EN (doa):	30 September 2021
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2022
Date of withdrawal of any conflicting National Standard (dow):	31 March 2022

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document defines the functional and operational requirements for navigational radar installations used in inland waterways as required by CESNI ES-TRIN standard [i.1].

The present document is applicable to radar equipment and its associated primary navigational display intended for the navigation of vessels on inland waterways with the following characteristics:

- Transmitter Peak Envelope Power up to 10 kW.
- The antenna is rotating and passive.
- Unmodulated single carrier frequency only may be utilized.

The applicable frequencies of operation of this type of radio equipment are given in table 1. These frequencies are allocated to the radio navigation service, as defined in article 5 of the ITU Radio Regulations [i.4].

Table 1: Radio navigation service frequencies

	Radio navigation service frequencies
Transmit	9 300 MHz to 9 500 MHz
Receive	9 300 MHz to 9 500 MHz

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] IMCO Resolution A.278 (VIII) (1973): "Symbols for controls on marine navigational radar equipment".
- [2] ISO 25862:2019: "Ships and marine technology -- Marine magnetic compasses, binnacles and azimuth reading devices".
- [3] IEC EN 60945 (2002): "Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CESNI: "European Standard laying down Technical Requirements for Inland Navigation vessels, ES-TRIN".
- [i.2] Recommendation ITU-R M.824-4 (02/2013): "Technical parameters of radar beacons".
- [i.3] Recommendation ITU-R M.628-5 (03/2012): "Technical characteristics for search and rescue radar transponders".
- [i.4] ITU Radio Regulations (2020).
- [i.5] IEC 62388 (2013): "Maritime navigation and radiocommunication equipment and systems - Shipborne radar - Performance requirements, methods of testing and required test results".
- [i.6] IEC 62288 (2014): "Maritime navigation and radiocommunication equipment and systems - Presentation of navigation-related information on shipborne navigational displays - General requirements, methods of testing and required test results".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

conventional radar: radar where the output signal is generated by a magnetron, using pulsed emissions but not using frequency, phase or power modulation

FTC: function to suppress rain clutter

IR: function to suppress interference from other radars

Peak Envelope Power (PEP): average power supplied to the antenna transmission line by a transmitter during one radio frequency cycle at the crest of the modulation envelope taken under normal operating conditions

NOTE: This definition is taken from ITU Radio Regulations [i.4].

Radar Cross-Section (RCS): cross-section determining the power density returned to the radar for a particular power density incident on a target

radar echo: signal reflected by a target to a radar antenna that appears in the radar video signal and radar image

radar equipment: equipment and its associated primary navigational display intended for the navigation of vessels on inland waterways

RAIN: function to suppress rain clutter, other term for FTC

SEA: sea clutter suppression, other term for STC

standard reflector: radar reflector with an equivalent Radar Cross Section (RCS) at a frequency of 9 400 MHz equal to 10 m²

STC: function to suppress sea clutter

3.2 Symbols

For the purposes of the present document, the following symbols apply:

dB	decibel
t	time
λ	wavelength

π	mathematical constant: 3,14159265...
ρ	reflection coefficient
σ	radar cross section

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Alternating Current
ACP	Azimuth Clock Pulse
AIS	Automatic Identification System
AR	Azimuthal Resolution
ARP	Azimuth Reference Pulse
AtoN	Aids to Navigation
CESNI	European Committee for drawing up standards in the field of inland navigation
COG	Course Over Ground
DC	Direct Current
EBL	Electronic Bearing Line
ECDIS	Electronic Chart Display and Information System
EN	European Norm
ES-TRIN	European Standard laying down Technical Requirements for Inland Navigation vessels
EUT	Equipment Under Test
FTC	Fast Time Constant
GNSS	Global Navigation Satellite System
IEC	International Electrotechnical Committee
IHO	International Hydrographic Organization
IMCO	Inter-Governmental Maritime Consultative Organization
IR	Interference Rejection
ISO	International Organization for Standardization
ITU-R	International Telecommunications Union - Radiocommunications
LED	Light Emitting Diode
MR	Minimum Range
P-Line	Parallel-Line
PRF	Pulse Repetition Frequency
RCS	Radar Cross-Section
ROT	Rate-Of-Turn indicator
RR	Radial Resolution
SART	Search and Rescue Radar Transponder
SHM	Ships Heading Marker
SOG	Speed Over Ground
SOLAS	Safety Of Life At Sea
STC	Sensitivity Time Control
Tr	Trigger
V	Video
VRM	Variable Range Marker

4 General requirements

4.1 Purpose of the radar equipment

The radar equipment shall facilitate the navigation of vessels on inland waterways by providing an intelligible radar picture of their position in relation to buoys, shorelines and other navigational marks as well as enabling the reliable and timely recognition of other ships and obstructions protruding above the water surface.

4.2 Construction and design

Mechanical and electrical construction and design of the radar equipment shall be suitable for operation on board vessels navigating on inland waterways.

4.3 Operational controls

The equipment shall be designed in such a way that incorrect operation will not cause the equipment to fail.

One person shall be able to operate the radar equipment and watch the display simultaneously.

Control panel shall be provided as a separate unit. It shall contain all controls used directly for radar navigation. The use of cordless remote controls is not permitted.

The equipment shall not have more controls than are necessary for its correct operation. The design, markings and controls of the equipment shall enable simple, unambiguous and fast operation. The arrangement shall be such that the possibility of operating mistakes is minimized.

All controls shall be arranged in such a way that when a control is operated the associated indication remains visible and that the radar navigation can continue without restriction.

The effect of operation of controls shall be such that movements to the right or upwards shall have a positive effect on the manipulated variable, while movements to the left or downwards have a negative effect.

If pushbuttons are used, they shall be designed in such a way that they can also be found by touch. Moreover they shall have a noticeable pressure point (tactile feedback).

Controls to switch off the equipment shall be protected against unintentional operation.

All controls and indicators shall be equipped with a dazzle-free source of lighting suitable for use under all conditions of light which can be adjusted to zero by means of an independent control.

All controls and indicators shall be provided with symbols and/or a description in English and, if possible, switchable to the users language. Symbols shall meet the requirements of IMCO Resolution No. A.278 (VIII) [1].

The height of all indicative markings shall be at least 4 mm unless this is not technically feasible and therefore a reduction to 3 mm will be allowed.

Any functions additional to the minimum functions specified in the present document, as well as any connections for external apparatus, shall not impair the capability to meet the minimum requirements contained in the present document.

The antenna unit shall have a safety switch by means of which the transmitter and the rotator drive can be switched off. After switching the equipment to the STBY or to the ON state, a message shall occur on the display, if the safety switch is activated.

4.4 Interfaces

4.4.1 Fail safe design

All interfaces shall be designed fail safe, so that connecting, disconnecting or a failure of the connected equipment or a short circuit shall not cause any deterioration of the radar equipment performance.

4.4.2 Display of data received via interfaces

Unless otherwise specified, all information received via an interface shall be displayed outside of the radar picture. Existing requirements concerning the presentation of such received data shall be fulfilled.

4.4.3 Operation of equipment connected via interfaces

Unless otherwise specified all operation menus for equipment connected via interfaces shall be placed outside of the radar picture. Existing requirements concerning the presentation and the functionality of such menus shall be fulfilled.

4.4.4 Interpretation and presentation of data delivered via interfaces

If the radar acts as a display for an external device it shall receive and display all information including alarms or status messages concerning the quality of the input data.

4.5 Software

4.5.1 Software performance

Software used in equipment of the present document is assumed to be a safety critical part of a navigation system. Manufacturers of navigation systems shall make sure that all software components allow secure navigation in every situation. Software components have to be clearly designed by means of established software design methods and ergonomic criteria.

4.5.2 Software protection

Manufacturer shall implement provisions to protect all operational software incorporated in the equipment. Any software required in equipment to ensure operation in accordance with its equipment standard, including that for its initial activation or reactivation, shall be permanently installed within the equipment, in such a way that it is not possible for the operator to have access to this software. It shall not be possible for the operator to augment, amend or erase any software in the equipment required for operation in accordance with its equipment standard.

4.6 Equipment labelling

Each unit of the equipment including any external power supply, shall be clearly and indelibly marked on the exterior with the identification of the manufacturer, the type designation of the equipment and the serial number of the unit. All operating controls, indicators and terminals shall be clearly marked in accordance with IEC EN 60945 [3]. The compass safety distance shall be stated on the outdoor unit and on the display unit.

4.7 Operating and service manuals

A detailed operating manual and a summarized operating manual on a durable medium shall be supplied with each equipment in the language(s) of the country(ies) in which it is intended to be placed on the market.

The detailed version of the operating manual shall contain at least the following information:

- activation and operation;
- maintenance and servicing;
- instructions as to the correct technical installation;
- general safety instructions with special reminders of safety risks due to the rotating antenna, and of the power flux density of the microwave radiation compared with the actual limits;
- link to CE declaration by manufacturer; can alternatively be supplied by separate paper document.

Each detailed operating manual shall contain a manufacturer's statement to the effect that the equipment meets the requirements of the present document.

A detailed installation manual shall be provided.

Service manuals may be written in the English language only.

5 Testing requirements specifications

5.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be in accordance with its intended use, but as a minimum, shall be that specified in the test conditions contained in the present document. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the operational environmental profile defined by its intended use.

5.2 Conformance Requirements

5.2.1 Tests under extreme conditions

5.2.1.1 Performance check procedure

5.2.1.1.1 Definition

Where stated in the present document a performance check as described in this clause shall be carried out to ensure proper functionality.

5.2.1.1.2 Required test results

The following results are required:

- the warm up time shall not exceed 4 minutes;
- after switching to ON the antenna shall rotate and the transmitter functions;
- the display shall indicate the regular status of the equipment;
- the display shall be readable without any degradation;
- the operation of GAIN, TUNE, STC, FTC, EBL and VRM controls shall function correctly.

5.2.1.1.3 Conformance

The conformance tests are specified in clause 6.5.1.1.

5.2.1.2 Temperature test of the indoor unit

5.2.1.2.1 Definition

This test determines the ability of the indoor unit to work under extreme temperatures without resulting in mechanical weakness or degradation in performance.

5.2.1.2.2 Required test results

The indoor equipment shall satisfy all requirements of the performance checks as described in clause 5.2.1.1 for ambient temperatures of the indoor unit of 0 °C and +40 °C.

5.2.1.2.3 Conformance

The conformance tests are specified in clause 6.5.1.2.