

INTERNATIONAL STANDARD

IEC
60825-4

Edition 1.2

2003-10

Edition 1:1997 consolidated with amendments 1:2002 and 2:2003

Safety of laser products –

Part 4: Laser guards

Sécurité des appareils à laser –

*Partie 4:
Barrières laser*

IEC 60825-4:1997

<https://standards.iteh.ai/catalog/standards-iec/7/1920785-3393-44d3-bdd9-e1e3ce5e7103/iec-60825-4-1997>



Reference number
IEC 60825-4:1997+A1:2002+A2:2003

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

<https://standards.iteh.ai/catalog/standards/sic/7-920785-3393-44d3-bdd9-e1c3ce5e7103/iec-60825-4-1997>

INTERNATIONAL STANDARD

IEC 60825-4

Edition 1.2

2003-10

Edition 1:1997 consolidated with amendments 1:2002 and 2:2003

Safety of laser products –

Part 4: Laser guards

Sécurité des appareils à laser –

*Partie 4:
Barrières laser*

© IEC 2003 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

CONTENTS

| | |
|---|----|
| FOREWORD | 3 |
| INTRODUCTION | 5 |
| 1 General..... | 6 |
| 1.1 Scope | 6 |
| 1.2 Normative references..... | 6 |
| 1.3 Definitions | 6 |
| 2 Laser processing machines | 8 |
| 2.1 Design requirements | 8 |
| 2.2 Performance requirements | 9 |
| 2.3 Validation..... | 9 |
| 2.4 User information | 10 |
| 3 Proprietary laser guards | 10 |
| 3.1 Design requirements | 10 |
| 3.2 Performance requirements | 10 |
| 3.3 Specification requirements | 10 |
| 3.4 Test requirements | 11 |
| 3.5 Labelling requirements | 11 |
| 3.6 User information | 12 |
| Annex A (informative) General guidance on the design and selection of laser guards | 13 |
| Annex B (informative) Assessment of foreseeable exposure limit | 15 |
| Annex C (informative) Elaboration of defined terms..... | 22 |
| Annex D (normative) Proprietary laser guard testing | 24 |
| Annex E (informative) Guidelines on the arrangement and installation of laser guards | 26 |
| Bibliography | 36 |
| Figure B.1 – Calculation of diffuse reflections | 16 |
| Figure B.2 – Calculation of specular reflections..... | 16 |
| Figure B.3 – Some examples of a foreseeable fault condition..... | 17 |
| Figure B.4 – Four examples of errant laser beams that might have to be contained by a temporary guard under service conditions | 18 |
| Figure B.5 – Illustration of laser guard exposure during repetitive machine operation | 19 |
| Figure B.6 – Two examples of assessed duration of exposure..... | 20 |
| Figure B.7 – Assessed duration of exposure for a machine with no safety monitoring | 21 |
| Figure C.1 – Illustration of guarding around a laser processing machine..... | 22 |
| Figure C.2 – Illustration of active laser guard parameters..... | 23 |
| Figure D.1 – Simplified diagram of the test arrangement | 24 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SAFETY OF LASER PRODUCTS –

Part 4: Laser guards

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60825-4 has been prepared by IEC technical committee 76: Optical radiation safety and laser equipment.

This consolidated version of IEC 60825-4 is based on the first edition (1997) [documents 76/159/FDIS and 76/168/RVD], its amendment 1 (2002) [documents 76/242/FDIS and 76/252/RVD] and its amendment 2 (2003) [documents 76/263/FDIS and 76/273/RVD].

It bears the edition number 1.2.

A vertical line in the margin shows where the base publication has been modified by amendments 1 and 2.

Annex D forms an integral part of this standard.

Annexes A, B, C and E are for information only.

The French version of this standard will be issued separately.

The committee has decided that the contents of this publication will remain unchanged until 2005. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

Withdrawn

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[IEC 60825-4:1997](https://standards.itih.ai/standards/iec/71920785-3393-44d3-bdd9-e1e3ce5e7103/iec-60825-4-1997)

<https://standards.itih.ai/standards/iec/71920785-3393-44d3-bdd9-e1e3ce5e7103/iec-60825-4-1997>

INTRODUCTION

At low levels of irradiance or radiant exposure, the selection of material and thickness for shielding against laser radiation is determined primarily by a need to provide sufficient optical attenuation. However, at higher levels, an additional consideration is the ability of the laser radiation to remove guard material – typically by melting, oxidation or ablation; processes that could lead to laser radiation penetrating a normally opaque material.

IEC 60825-1 deals with basic issues concerning laser guards, including human access, interlocking and labelling, and gives general guidance on the design of protective housings and enclosures for high-power lasers.

This part of IEC 60825 deals with protection against laser radiation only. Hazards from secondary radiation that may arise during material processing are not addressed.

Laser guards may also comply with standards for laser protective eyewear, but such compliance is not necessarily sufficient to satisfy the requirements of this standard.

Where the term “irradiance” is used, the expression “irradiance or radiant exposure, as appropriate” is implied.

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

<https://standards.itih.ai/standards/iec/71920785-3393-44d3-bdd9-e1e3ce5e7103/iec-60825-4-1997>

<https://standards.itih.ai/standards/iec/71920785-3393-44d3-bdd9-e1e3ce5e7103/iec-60825-4-1997>

WITHDRAWN

SAFETY OF LASER PRODUCTS –

Part 4: Laser guards

1 General

1.1 Scope

This part of IEC 60825 specifies the requirements for laser guards, permanent and temporary (for example for service), that enclose the process zone of a laser processing machine, and specifications for proprietary laser guards.

This standard applies to all component parts of a guard including clear (visibly transmitting) screens and viewing windows, panels, laser curtains and walls. Requirements for beam path components, beam stops and those other parts of a protective housing of a laser product which do not enclose the process zone are contained in IEC 60825-1.

In addition this part of IEC 60825 indicates:

- a) how to assess and specify the protective properties of a laser guard; and
- b) how to select a laser guard.

1.2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60825-1: 1993, *Safety of laser products – Part 1: Equipment classification, requirements and user's guide*

ISO/TR12100-1: 1992, *Safety of machinery – Basic concepts, general principles for design – Part 1: Basic terminology, methodology*

ISO/TR12100-2: 1992, *Safety of machinery – Basic concepts, general principles for design – Part 2: Technical principles and specifications*

ISO 11553: 1996, *Safety of machinery – Laser processing machines – Safety requirements*

1.3 Definitions

For the purpose of this part of IEC 60825, the following definitions apply in addition to the definitions given in IEC 60825-1.

1.3.1

active guard protection time

for a given laser exposure of the front surface of an active laser guard, the minimum time, measured from the issue of an active guard termination signal, for which the active laser guard can safely prevent laser radiation accessible at its rear surface from exceeding the class 1 AEL.

1.3.2

active guard termination signal

the signal issued by an active guard in response to an excess exposure of its front surface to laser radiation and which is intended to lead to automatic termination of the laser radiation

NOTE The action of a safety interlock becoming open circuit is considered a "signal" in this context.

1.3.3

active laser guard

a laser guard which is part of a safety-related control system. The control system generates an active guard termination signal in response to the effect of laser radiation on the front surface of the laser guard

1.3.4

foreseeable exposure limit (FEL)

the maximum laser exposure on the front surface of the laser guard, within the maintenance inspection interval, assessed under normal and reasonably foreseeable fault conditions

1.3.5

front surface

the face of the laser guard intended for exposure to laser radiation

1.3.6

laser guard

a physical barrier which limits the extent of a danger zone by preventing laser radiation accessible at its rear surface from exceeding the class 1 AEL

1.3.7

laser processing machine

a machine which uses a laser to process materials and is within the scope of ISO 11553

1.3.8

laser termination time

the maximum time taken, from generation of an active guard termination signal, for the laser radiation to be terminated

NOTE Laser termination time does not refer to the response of an active laser guard but to the response of the laser processing machine, in particular the laser safety shutter.

1.3.9

maintenance inspection interval

the time between successive safety maintenance inspections of a laser guard

1.3.10

passive laser guard

a laser guard which relies for its operation on its physical properties only

1.3.11

process zone

the zone where the laser beam interacts with the material to be processed

1.3.12

proprietary laser guard

a passive or active laser guard, offered by its manufacturer as a guard with a specified protective exposure limit

1.3.13

protective exposure limit (PEL)

the maximum laser exposure of the front surface of a laser guard which is specified to prevent laser radiation accessible at its rear surface from exceeding the class 1 AEL

NOTE 1 In practice, there may be more than one maximum exposure.

NOTE 2 Different PELs may be assigned to different regions of a laser guard if these regions are clearly identifiable (for example a viewing window forming an integral part of a laser guard).

1.3.14

rear surface

any surface of a laser guard that is remote from the associated laser radiation and usually accessible to the user

1.3.15

reasonably foreseeable

an event (or condition) when it is credible and its likelihood of occurrence (or existence) cannot be disregarded

1.3.16

safety maintenance inspection

documented inspection performed in accordance with manufacturer's instructions

1.3.17

temporary laser guard

a substitute or supplementary active or passive laser guard intended to limit the extent of the danger zone during some service operations of the laser processing machine

2 Laser processing machines

This clause specifies the requirements for laser guards that enclose the process zone and are supplied by the laser processing machine manufacturer.

2.1 Design requirements

A laser guard shall satisfy ISO/TR12100-2 with respect to the general requirements for guards and also the more specific requirements with regard to its location and method of fixture. In addition, the following specific laser requirements shall be met.

2.1.1 General requirements

A laser guard, in its intended location, shall not give rise to any associated hazard at or beyond its rear surface when exposed to laser radiation up to the foreseeable exposure limit.

NOTE 1 Examples of associated hazards include: high temperature, the release of toxic materials, fire, explosion, electricity.

NOTE 2 See annex B for assessment of foreseeable exposure limit.

2.1.2 Consumable parts of laser guards

Provision shall be made for the replacement of parts of a laser guard prone to damage by laser radiation.

NOTE An example of such a part would be a sacrificial or interchangeable screen.

2.2 Performance requirements

2.2.1 General

When the front surface of a laser guard is subjected to exposure to laser radiation at the foreseeable exposure limit, the laser guard shall prevent laser radiation accessible at its rear surface from exceeding the class 1 AEL at any time over the period of the maintenance inspection interval. For automated laser processing machines, the minimum value of the maintenance inspection interval shall be 8 h.

This requirement shall be satisfied over the intended lifetime of the laser guard under expected conditions of operation.

NOTE 1 This requirement implies both low transmission of laser radiation and resistance to laser-induced damage.

NOTE 2 Some materials may lose their protective properties due to ageing, exposure to ultraviolet radiation, certain gases, temperature, humidity and other environmental conditions. Additionally, some materials will transmit laser radiation under high-intensity laser exposure, even though there may be no visible damage (i.e. reversible bleaching).

2.2.2 Active laser guards

- a) The active guard protection time shall exceed the laser termination time up to the foreseeable exposure limits.
- b) The generation of an active guard termination signal shall give rise to a visible or audible warning. A manual reset is required before laser emission can recommence.

NOTE See annex C.2 for an elaboration of terms.

2.3 Validation

If the laser processing machine manufacturer chooses to make a laser guard, the manufacturer shall confirm that the guard complies with the design requirements of 2.1 and can satisfy the performance requirements set out in 2.2.

NOTE See annex A for guidance on the design and selection of laser guards.

2.3.1 Validation of performance

2.3.1.1 The complete laser guard, or an appropriate sample of the material of construction of the laser guard, shall be tested at each FEL identified.

NOTE 1 A table of predetermined PELs for common combinations of lasers and guarding materials, together with suitable testing procedures shall be issued as an informative annex in a future amendment to this standard. This could provide a simple alternative to direct testing for the majority of cases.

NOTE 2 See annex B for the assessment of FEL.

2.3.1.2 For testing purposes, the FEL exposure shall be achieved either:

- a) by calculating or measuring the exposure and reproducing the conditions; or
- b) without quantifying the FEL, by creating the machine conditions under which the FEL is produced.

The condition of the laser guard or sample shall be such as to replicate those physical conditions of the front surface permitted within the scope of the routine inspection instructions and within the service life of the guard, which minimize the laser radiation protective properties of the laser guard (for example wear and tear and surface contamination) (see 2.4.2).

2.4 User information

2.4.1 The manufacturer shall document and provide to the user the maintenance inspection interval for the laser guard, and details of inspection and test procedures, cleaning, replacement or repair of damaged parts, together with any restrictions of use.

2.4.2 The manufacturer shall document and provide to the user instructions that after any actuation of the safety control system of an active guard, the cause shall be investigated, checks shall be made for damage, and the necessary remedial action to be taken before resetting the control system.

3 Proprietary laser guards

This clause specifies the requirements to be satisfied by suppliers of proprietary laser guards.

3.1 Design requirements

A proprietary laser guard shall not create any associated hazard at or beyond its rear surface when exposed to laser radiation up to the specified PEL when used as specified in the user information (see 3.6).

3.2 Performance requirements

The accessible laser radiation at the rear surface of the laser guard shall not exceed the class 1 AEL when its front surface is subjected to laser radiation at the specified PEL. For an active laser guard, this requirement shall apply to laser radiation accessible over the period of the active guard protection time, measured from the moment an active guard termination signal is issued.

This requirement shall be satisfied over the intended lifetime of the guard under expected service conditions.

3.3 Specification requirements

The full specification of a PEL shall include the following information:

- a) the magnitude and variation with time of irradiance or radiant exposure at the front surface of the laser guard (in units of Wm^{-2} or Jm^{-2} respectively), specifying any upper limit to the area of exposure;
- b) the overall duration of exposure under these conditions;
- c) the wavelength for which this PEL applies;
- d) the angle of incidence and (if relevant) the polarization of the incident laser radiation;
- e) any minimum dimensions to the irradiated area (for example as might apply to an active laser guard with discrete sensor elements so that a small diameter laser beam could pass through the guard undetected);
- f) for an active laser guard, the active guard protection time.

NOTE 1 See clause B.1 for an elaboration of terms.

NOTE 2 In all cases, a range or set of values can be stated rather than a single value.

NOTE 3 A graphical form of presentation (for example irradiance vs. duration with all other parameters constant).