

ETSI TS 123 228 V15.4.0 (2019-04)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
IP Multimedia Subsystem (IMS);
Stage 2
(3GPP TS 23.228 version 15.4.0 Release 15)**



Reference

RTS/TSGS-0223228vf40

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	15
1 Scope	16
2 References	16
3 Definitions, symbols and abbreviations	20
3.1 Definitions.....	20
3.2 Symbols.....	22
3.3 Abbreviations	23
4 IP multimedia subsystem concepts.....	24
4.0 General	24
4.1 Relationship to CS domain and the IP-Connectivity Access Network.....	25
4.2 IMS services concepts	26
4.2.1 Home-network based services	26
4.2.1.1 Support of CAMEL or IN	26
4.2.1.2 Support of OSA.....	26
4.2.1.3 Dynamic services interactions handling.....	26
4.2.1.3.1 Service information exchanged between Application Servers	26
4.2.1.3.2 Handling by the Application Server	26
4.2.1.3.3 Deletion of services interaction information.....	26
4.2.2 Support of numbers in non-international format in the IMS.....	26
4.2.3 Support of roaming users	27
4.2.4 IP multimedia Subsystem Service Control Interface (ISC)	29
4.2.4a HSS to service platform Interface	31
4.2.4b S-CSCF Service Control Model.....	33
4.2.4c I-CSCF to AS reference point (Ma).....	34
4.2.5 The QoS requirements for an IM CN subsystem session.....	35
4.2.6 QoS Requirements for IM CN subsystem signalling.....	36
4.2.7 Support of SIP forking.....	37
4.2.7.1 SIP Forking	37
4.2.7.2 Forking within and outside the IM CN Subsystem	37
4.2.7.3 Support for forked requests.....	38
4.3 Naming and addressing concepts	38
4.3.1 Address management.....	38
4.3.2 Void	38
4.3.3 Identification of users	38
4.3.3.0 General	38
4.3.3.1 Private User Identities	38
4.3.3.2 Public User Identities	39
4.3.3.2a Globally Routable User Agent URI (GRUU)	40
4.3.3.2a.1 Architecture Requirements	40
4.3.3.2b Wildcarded Public User Identity	41
4.3.3.3 Routing of SIP signalling within the IP multimedia subsystem.....	41
4.3.3.3a Handling of dialled number formats	42
4.3.3.3b Termination of session with the TEL URI format Public User Identity.....	42
4.3.3.4 Relationship of Private and Public User Identities	42
4.3.3.5 Relationship of Public User Identities, GRUUs, and UEs	43
4.3.4 Identification of network nodes	44
4.3.5 E.164 address to SIP URI resolution in an IM CN subsystem.....	44
4.3.5.1 ENUM/DNS translation mechanism.....	44
4.3.5.2 Handling of Tel URIs.....	44
4.3.5.3 Handling of SIP URIs representing a telephone number	44
4.3.6 Public Service Identities	45
4.4 Signalling concepts.....	45

4.5	Mobility related concepts	46
4.6	Roles of Session Control Functions	46
4.6.0	General.....	46
4.6.1	Proxy-CSCF.....	46
4.6.2	Interrogating-CSCF	47
4.6.2.0	General	47
4.6.2.1	Void.....	48
4.6.3	Serving-CSCF.....	48
4.6.4	Breakout Gateway Control Function	50
4.6.5	Void	51
4.7	Multimedia Resource Function	51
4.7a	Media Resource Broker.....	52
4.8	Security Concepts.....	52
4.9	Charging Concepts	52
4.10	IMS group management concepts	52
4.10.0	General.....	52
4.10.1	IMS group administration.....	52
4.10.2	Group identifiers	53
4.11	Relationship to 3GPP Generic User Profile (GUP).....	53
4.12	Network Address Translation traversal in access network	53
4.13	Identification of IMS communication Services	53
4.13.1	General.....	53
4.13.2	Identification of IMS communication Services	53
4.13.3	Identification of IMS applications	55
4.14	Border Control concepts.....	56
4.15	IMS in transit network scenarios	57
4.15.1	General concepts.....	57
4.15.2	IMS transit network configurations	57
4.15.3	Providing IMS application services in transit network scenarios	57
4.15a	Roaming Architecture for Voice over IMS with Local Breakout.....	58
4.15b	Roaming Architecture for Voice over IMS with home routed traffic	59
4.16	Support of multimedia telephony	59
4.16.1	Telephony Application Server	59
4.16.2	Identification of multimedia telephony	59
4.16.3	Session setup principles.....	60
4.17	Support of short message service	60
4.17.1	IP Short Message Gateway (IP-SM-GW)	60
4.18	Support of Number portability	60
4.18.1	Number portability.....	60
4.19	Support of Preferred Circuit Carrier Access and Per Call Circuit Carrier Selection	61
4.19.1	Preferred Circuit Carrier Access and Per Call Circuit Carrier Selection	61
4.20	Support of IMS Service Centralization and Continuity	61
4.21	Support of Overlap Signalling.....	61
4.22	Support of Explicit Congestion Notification (ECN)	62
4.22.1	General.....	62
4.22.2	CS GERAN/UTRAN Interworking at MGCF/IM-MGW	62
4.22.3	Interworking with non-ECN IP network and/or terminal at IBCF/TrGW	63
4.22.4	Interworking with non-3GPP ECN IP terminal at IBCF/TrGW	63
4.22.5	ECN support at IMS-ALG/IMS-AGW	63
4.22.6	ECN support at MRFC/MRFP.....	64
4.22.7	CS GERAN/UTRAN Interworking at the MSC Server enhanced for ICS/MSC Server enhanced for SRVCC with SIP/CS-MGW	64
4.23	Support of Load Balancing.....	64
4.23.1	General.....	64
4.23.2	Registration-based load balancing of S-CSCFs	64
4.23.3	Registration independent load balancing of Transit Functions	65
4.24	Support of Restoration Procedures	65
4.25	Support of Overload Control	65
4.25.1	General.....	65
4.25.2	Next-hop monitoring of overload	65
4.25.3	Filter based Overload Control.....	66
4.26	Support for Business Trunking.....	66

5	IP multimedia subsystem procedures	66
5.0	General	66
5.0a	Session-unrelated procedures	67
5.1	CSCF related procedures.....	67
5.1.0	Establishing IP-Connectivity Access Network bearer for IM CN Subsystem Related Signalling.....	67
5.1.1	Procedures related to Proxy-CSCF discovery.....	67
5.1.1.0	General	67
5.1.1.1	DHCP/DNS procedure for P-CSCF discovery.....	67
5.1.1.2	Void.....	68
5.1.2	Procedures related to Serving-CSCF assignment	68
5.1.2.1	Assigning a Serving-CSCF for a user	68
5.1.2.2	Cancelling the Serving-CSCF assignment	69
5.1.2.3	Void.....	69
5.1.3	Procedures related to Interrogating-CSCF.....	69
5.1.4	Procedures related to Proxy-CSCF	70
5.1.5	Subscription Updating Procedures.....	70
5.1.5.0	General.....	70
5.1.5.1	Subscription updating information flow.....	70
5.2	Application level registration procedures.....	70
5.2.0	General.....	70
5.2.1	Requirements considered for registration	70
5.2.1a	Implicit Registration	71
5.2.1a.0	General	71
5.2.1a.1	Implicit Registration for UE without ISIM or IMC.....	73
5.2.2	Registration flows.....	73
5.2.2.1	Requirements to consider for registration.....	73
5.2.2.2	Assumptions.....	73
5.2.2.3	Registration information flow – User not registered.....	74
5.2.2.4	Re-Registration information flow – User currently registered.....	75
5.2.2.5	Stored information.....	77
5.3	Application level de-registration procedures.....	78
5.3.1	Mobile initiated de-registration.....	78
5.3.2	Network initiated de-registration	79
5.3.2.0	General	79
5.3.2.1	Network Initiated Application (SIP) De-registration, Registration Timeout	80
5.3.2.2	Network Initiated Application (SIP) De-registration, Administrative.....	80
5.3.2.2.0	General	80
5.3.2.2.1	Network Initiated De-registration by HSS, administrative.....	81
5.3.2.2.2	Network Initiated De-registration by Service Platform.....	81
5.4	Procedures for IP multi-media sessions.....	83
5.4.0	General.....	83
5.4.1	Bearer interworking concepts	83
5.4.2	Interworking with Internet	83
5.4.2a	IP version interworking	83
5.4.3	Interworking with PSTN.....	84
5.4.4	Requirements for IP multi-media session control.....	85
5.4.5	Session Path Information.....	85
5.4.5.1	Session Path Information during Registration and Session Initiation	85
5.4.5.2	P-CSCF in the Session Path	85
5.4.5.3	S-CSCF in the Session Path	86
5.4.6	End-user preferences and terminal capabilities.....	86
5.4.6.0	General	86
5.4.6.1	Objectives.....	86
5.4.6.2	End-user expectations	86
5.4.6.3	Mechanism for bearer establishment.....	87
5.4.6.4	Session progress indication to the originating UE	89
5.4.7	Interaction between QoS and session signalling.....	89
5.4.7.0	General	89
5.4.7.1	Authorize QoS Resources	90
5.4.7.1a	Resource Reservation with Policy and Charging Control.....	90
5.4.7.2	Enabling of Media Flows.....	90
5.4.7.3	Disabling of Media Flows.....	91

5.4.7.4	Revoke Authorization for IP-Connectivity Access Network and IP Resources.....	91
5.4.7.5	Indication of IP-Connectivity Access Network bearer release.....	91
5.4.7.6	Authorization of IP-Connectivity Access Network bearer modification.....	91
5.4.7.7	Indication of IP-Connectivity Access Network bearer modification	91
5.4.7.8	Sharing of Resources for Network Detected Concurrent Sessions	92
5.4.7.8.1	Network Detected Concurrent Sessions	92
5.4.7.8.2	Initiating Resource Sharing for Network Detected Concurrent Sessions	92
5.4.7.8.3	Void.....	92
5.4.7.9	Priority sharing for concurrent sessions	92
5.4.8	QoS-Assured Preconditions	93
5.4.9	Event and information distribution	94
5.4.9.0	General	94
5.4.9.1	Subscription to event notifications	95
5.4.10	Void	96
5.4.11	Signalling Transport Interworking.....	96
5.4.12	Configuration and Routing principles for Public Service Identities	96
5.4.12.0	General	96
5.4.12.1	PSIs on the originating side.....	96
5.4.12.2	PSIs on the terminating side.....	96
5.4.12.3	Subdomain based PSIs	97
5.4.12.4	PSI configuration in the HSS	97
5.4.12.5	Requests originated by the AS hosting the PSI.....	98
5.4.13	Transcoding concepts	98
5.4a	Overview of session flow procedures.....	98
5.4a.1	End-to-End session flow procedures	98
5.4a.2	Transit network session flow procedures.....	101
5.5	Serving-CSCF/MGCF to serving-CSCF/MGCF procedures	103
5.5.0	General.....	103
5.5.1	(S-S#1) Different network operators performing origination and termination	103
5.5.2	(S-S#2) Single network operator performing origination and termination	105
5.5.3	(S-S#3) Session origination with PSTN termination in the same network as the S-CSCF.....	108
5.5.4	(S-S#4) Session origination with PSTN termination in a different network from the S-CSCF.....	110
5.6	Origination procedures	112
5.6.0	General.....	112
5.6.1	(MO#1) Mobile origination, roaming.....	112
5.6.2	(MO#2) Mobile origination, home	115
5.6.3	(PSTN-O) PSTN origination.....	117
5.6.4	(NI-O) Non-IMS Origination procedure from an external SIP client.....	118
5.6.5	Application Server Origination Procedure.....	120
5.6.5.1	(AS-O) Origination at Application Server	120
5.6.5.2	Void.....	122
5.6.5.3	S-CSCF selection by I-CSCF for AS Originating call procedures.....	122
5.7	Termination procedures.....	124
5.7.0	General.....	124
5.7.1	(MT#1) Mobile termination, roaming.....	124
5.7.2	(MT#2) Mobile termination, home	127
5.7.2a	(MT#3) Mobile termination, CS Domain roaming	129
5.7.3	(PSTN-T) PSTN termination	129
5.7.4	(NI-T) Non-IMS Termination to an external SIP client.....	131
5.7.5	(AS-T#1) PSI based Application Server termination – direct.....	133
5.7.6	(AS-T#2) PSI based Application Server termination – indirect.....	133
5.7.7	(AS-T#3) PSI based Application Server termination – DNS routing	134
5.7.8	(AST#4) Termination at Application Server based on service logic	135
5.7a	Procedures for the establishment of sessions without preconditions.....	136
5.7a.1	General.....	136
5.7a.2	Procedures for the establishment of sessions without preconditions - no resource reservation required before session becomes active	138
5.7a.3	Void	140
5.8	Procedures related to routing information interrogation.....	140
5.8.0	General.....	140
5.8.1	User identity to HSS resolution	140
5.8.2	SLF on register	141

5.8.3	SLF on UE invite	142
5.8.4	SLF on AS access to HSS	143
5.9	Routing of mid-session signalling	143
5.10	Session release procedures	144
5.10.0	General	144
5.10.1	Terminal initiated session release	144
5.10.2	PSTN initiated session release	146
5.10.3	Network initiated session release	147
5.10.3.0	Removal of IP-CAN bearers used to transport IMS SIP signalling	147
5.10.3.1	Network initiated session release - P-CSCF initiated	147
5.10.3.1.0	General	147
5.10.3.1.1	Network initiated session release - P-CSCF initiated – after removal of IP-Connectivity Access Network bearer	148
5.10.3.1.2	Void	149
5.10.3.2	Network initiated session release - S-CSCF Initiated	149
5.11	Procedures to enable enhanced multimedia services	150
5.11.1	Session Hold and Resume Procedures	150
5.11.1.0	General	150
5.11.1.1	Mobile-to-Mobile Session Hold and Resume Procedures	150
5.11.1.2	Mobile-initiated Hold and Resume of a Mobile-PSTN Session	152
5.11.1.3	PSTN-initiated Hold and Resume of a Mobile-PSTN Session	153
5.11.2	Procedures for anonymous session establishment	155
5.11.2.0	General	155
5.11.2.1	Signalling requirements for anonymous session establishment	155
5.11.2.2	Bearer path requirements for anonymous session establishment	155
5.11.3	Procedures for codec and media characteristics flow negotiations	155
5.11.3.0	General	155
5.11.3.1	Codec and media characteristics flow negotiation during initial session establishment	156
5.11.3.2	Codec or media characteristics flow change within the existing reservation	159
5.11.3.3	Codec or media characteristics flow change requiring new resources and/or authorization	160
5.11.3.4	Sample MM session flow - addition of another media	163
5.11.4	Procedures for providing or blocking identity	166
5.11.4.0	General	166
5.11.4.1	Procedures for providing the authenticated identity of the originating party	166
5.11.4.2	Procedures for blocking the identity of the originating party	168
5.11.4.3	Procedures for providing the authenticated identity of the originating party (PSTN origination)	169
5.11.4.4	Procedures for providing the authenticated identity of the originating party (PSTN termination)	169
5.11.5	Session Redirection Procedures	169
5.11.5.0	General	169
5.11.5.1	Session Redirection initiated by S-CSCF to IMS	169
5.11.5.2	Session Redirection to PSTN Termination (S-CSCF #2 forwards INVITE)	170
5.11.5.2a	Session Redirection to PSTN Termination (REDIRECT to originating UE#1)	171
5.11.5.3	Session Redirection initiated by S-CSCF to general endpoint (REDIRECT to originating UE#1)	173
5.11.5.4	Session Redirection initiated by P-CSCF	174
5.11.5.5	Session Redirection initiated by UE	175
5.11.5.6	Session Redirection initiated by originating UE#1 after Bearer Establishment (REDIRECT to originating UE#1)	176
5.11.6	Session Transfer Procedures	177
5.11.6.0	General	177
5.11.6.1	Refer operation	177
5.11.6.2	Application to Session Transfer Services	179
5.11.6.2.0	General	179
5.11.6.2.1	Blind Transfer and Assured Transfer	179
5.11.6.2.2	Consultative Transfer	180
5.11.6.2.3	Three-way Session	180
5.12	Mobile Terminating call procedures to unregistered Public User Identities	180
5.12.0	General	180
5.12.1	Mobile Terminating call procedures to unregistered Public User Identity that has services related to unregistered state	181
5.12.2	Mobile Terminating call procedures to unregistered Public User Identity that has no services related to unregistered state	182
5.13	IMS Emergency Sessions	183

5.14	Interactions involving the MRFC/MRFP	183
5.14.0	General.....	183
5.14.1	Interactions between the UE and the MRFC.....	183
5.14.2	Service control based interactions between the MRFC and the AS.....	183
5.14.3	Interactions for services using both the Ut interface and MRFC capabilities.....	183
5.14.4	Transcoding services involving the MRFC/MRFP.....	183
5.15	Mobile Terminating session procedure for unknown user	184
5.15.0	General.....	184
5.15.1	Unknown user determined in the HSS.....	184
5.15.2	Unknown user determined in the SLF	185
5.16	IMS messaging concepts and procedures.....	185
5.16.0	General.....	185
5.16.1	Immediate Messaging.....	186
5.16.1.0	General.....	186
5.16.1.1	Procedures to enable Immediate Messaging	186
5.16.1.1.0	General	186
5.16.1.1.1	Immediate messaging procedure to registered Public User Identity.....	186
5.16.1.1.2	Immediate messaging procedure to unregistered Public User Identity.....	187
5.16.1.2	Immediate messages with multiple recipients.....	188
5.16.2	Session-based Messaging	188
5.16.2.0	General	188
5.16.2.1	Architectural principles.....	188
5.16.2.2	Procedures to enable Session based Messaging	189
5.16.2.2.0	General	189
5.16.2.2.1	Session based messaging procedure to registered Public User Identity	189
5.16.2.2.2	Session based messaging procedure using multiple UEs	190
5.16.2.2.3	Session based messaging procedure with an intermediate node.....	193
5.16.2.2.4	Session based messaging release procedure	194
5.16.2.2.5	Session based messaging release procedure with an intermediate node.....	195
5.17	Refreshing sessions	195
5.18	Void.....	196
5.19	Support for Transit scenarios in IMS	196
5.19.1	General.....	196
5.19.2	Providing IMS application services in transit network scenarios	199
5.20	Procedures for Assigning, Using, and Processing GRUUs	199
5.20.1	UE.....	199
5.20.1.1	Obtaining a GRUU during registration	199
5.20.1.2	Using a GRUU	200
5.20.1.3	Using a GRUU while requesting Privacy.....	200
5.20.2	Serving-CSCF.....	200
5.20.2.1	Allocating a GRUU during registration	200
5.20.2.2	Using a GRUU	200
5.20.3	Interrogating-CSCF	201
5.20.3a	HSS.....	201
5.20.4	Elements other than UE acting as a UA.....	201
5.20.4.1	Using a GRUU	201
5.20.4.2	Assigning a GRUU	201
5.21	IMS Multimedia Priority Services Procedures.....	201
5.22	Support of Overload Control.....	202
5.22.1	Next-hop monitoring of overload	202
5.22.2	Filter based Overload Control.....	203
Annex A (Informative):	Information flow template	204
Annex B (Informative):	Void	206
Annex C (Informative):	Void	207
Annex D (Informative):	Void	208
Annex E (Normative):	IP-Connectivity Access Network specific concepts when using GPRS and/or EPS to access IMS	209

E.0	General	209
E.1	Mobility related concepts	209
E.1.0	General	209
E.1.1	Procedures for P-CSCF discovery	210
E.1.1.0	General	210
E.1.1.1	GPRS/EPS procedure for P-CSCF discovery	210
E.1.2	Support for Enhanced Coverage for data centric UEs	211
E.2	QoS related concepts	212
E.2.1	Application Level Signalling for IMS	212
E.2.1.0	General	212
E.2.1.1	QoS Requirements for Application Level Signalling	212
E.2.1.2	Requirements for IM CN subsystem signalling flag	212
E.2.1.3	Application Level Signalling support for IMS services	212
E.2.1a	PDP context/EPS Bearer procedures for IMS	213
E.2.1a.1	Establishing PDP Context/EPS bearer for IM CN Subsystem Related Signalling	213
E.2.1a.2	Deletion of PDP Context/EPS bearer used to transport IMS SIP signalling	214
E.2.2	The QoS requirements for an IM CN subsystem session	214
E.2.2.0	General	214
E.2.2.1	Relation of IMS media components and PDP contexts/EPS bearers carrying IMS media	215
E.2.3	Interaction between GPRS/EPS QoS and session signalling	215
E.2.3.0	General	215
E.2.3.1	Resource Reservation with Policy and Charging Control	216
E.2.4	Network initiated session release - P-CSCF initiated	216
E.2.4.0	General	216
E.2.4.1	Network initiated session release - P-CSCF initiated after loss of radio coverage	217
E.3	Address and identity management concepts	218
E.3.1	Deriving IMS identifiers from the USIM	218
E.4	Void	219
E.5	IP version interworking in IMS	219
E.6	Usage of NAT in GPRS/EPS	219
E.7	Retrieval of Network Provided Location Information in GPRS/EPS	219
E.8	Geographical Identifier	220
E.9	Support for Paging policy differentiation for IMS services	220
Annex F (Informative):	Routing subsequent requests through the S-CSCF	221
Annex G (Normative):	Reference Architecture and procedures when the NAT is invoked between the UE and the IMS domain	222
G.1	General	222
G.1.1	General requirements	222
G.2	Reference models	222
G.2.1	IMS-ALG and IMS Access Gateway model	222
G.2.2	ICE and Outbound reference model	223
G.3	Network elements for employing the IMS-ALG and IMS Access Gateway	224
G.3.1	Required functions of the P-CSCF	224
G.3.2	Required functions of the IMS Access Gateway	224
G.3.3	Iq reference point	225
G.4	Procedures for employing the IMS-ALG and IMS Access Gateway	225
G.4.1	General	225
G.4.2	NAT detection in P-CSCF	225
G.4.3	Session establishment procedure	225
G.4.4	Session release procedure	226
G.4.5	Session modification	226
G.4.6	Media forwarding in the IMS Access Gateway	227

G.5	Network elements for employing NAT Traversal for ICE and Outbound	228
G.5.1	General requirements	228
G.5.2	ICE	228
G.5.2.1	Overview	228
G.5.2.2	Required functions of the UE	228
G.5.2.3	Required functions of the STUN relay server	229
G.5.2.4	Required functions of the STUN server	229
G.5.3	Outbound	229
G.5.3.1	Overview	229
G.5.3.2	Required functions of the P-CSCF	229
G.5.3.3	Required functions of the S-CSCF	230
G.5.3.4	Required functions of the UE	230
G.6	Procedures for employing ICE and Outbound	230
G.6.1	Flow establishment procedures	230
G.6.2	Session establishment procedures	231
G.6.3	Session release procedures	233
G.6.4	Session modification procedures	234
G.6.5	Policy and Charging Control procedures	234
G.6.6	Detection of NAT Traversal support	235
G.6.7	Procedures at other IMS entities processing SDP	235
Annex H (Informative):	Example HSS deployment	236
Annex I (Normative):	Border Control Functions	237
I.1	General	237
I.2	Overall architecture	237
I.3	Border Control Functions	238
I.3.1	IP version interworking	238
I.3.1.1	Originating Session Flows towards IPv4 SIP network	238
I.3.1.2	Terminating Session Flows from IPv4 SIP network	240
I.3.2	Configuration independence between operator networks	241
I.3.3	Transcoding Support for Interworking	241
I.3.3.1	General	241
I.3.3.2	Session Flows	242
I.3.3.2.1	Proactive transcoding support	242
I.3.3.2.2	Reactive transcoding support	244
Annex J (Informative):	Dynamic User Allocation to the Application Servers	247
J.1	General	247
J.2	Representative AS	247
J.2.1	Concept of Representative AS	247
J.2.2	Procedures related to Representative AS	248
J.3	Dynamic assignment of AS by S-CSCF caching	248
J.3.1	Concept of Dynamic assignment of AS by S-CSCF caching	248
J.3.2	Procedures related to Dynamic assignment of AS by S-CSCF caching	248
Annex K (Normative):	Inter-IMS Network to Network Interface between two IM CN subsystem networks	250
K.1	General	250
K.2	Overall architecture	250
Annex L (Normative):	Aspects for use of Common IMS in 3GPP2 systems	251
L.1	General	251
L.2	Definitions	251
L.2.1	HSS	251

L.3	Mobility related concepts when using 3GPP2 Packet Data Subsystem	251
L.3.1	General	251
L.3.2	Procedures for P-CSCF discovery	252
L.4	QoS related concepts when using 3GPP2 Packet Data Subsystem	252
L.5	IP version support in IMS when using 3GPP2 Packet Data Subsystem	252
L.6	Address and identity management concepts	252
L.6.1	Deriving IMS identifiers	252
L.7	Relationship to 3GPP Generic User Profile (GUP)	253
Annex M (Informative): IMS Local Breakout		254
M.1	P-CSCF located in visited network	254
M.1.1	Description	254
M.1.1.0	General	254
M.1.1.1	Architecture	254
M.1.1.2	Flow for originating session	254
M.2	P-CSCF located in home network	256
M.2.1	Description	256
M.2.1.0	General	256
M.2.1.1	Architecture	256
M.2.1.2	Flow for originating session	256
M.2.2	Address assignment	257
M.2.3	IPv4 - IPv6 interworking	257
M.2.4	NAT traversal	258
M.3	P-CSCF located in visited network and with VPLMN loopback possibility	258
M.3.1	Description	258
M.3.1.1	General	258
M.3.1.2	Architecture	258
M.3.1.3	Flow for originating session with VPLMN routing	258
M.3.1.4	Flow for originating session with Home routing	260
M.3.2	Interaction with SRVCC and ICS	260
Annex N (Normative): Aspects for use of Common IMS in Fixed xDSL, Fiber and Ethernet based systems		261
N.1	Origination procedures	261
N.1.1	(FO#1) Fixed xDSL origination, home	261
N.2	Termination procedures	262
N.2.1	(FT#1) Fixed xDSL termination, home	262
N.3	Geographical Identifier	264
Annex P (Informative): Transcoding Support involving the MRFC/MRFP		265
P.1	General	265
P.1.1	Scope	265
P.1.2	Description	265
P.1.3	Session flows	265
P.1.3.1	General	265
P.1.3.2	Proactive transcoding invocation	265
P.1.3.3	Reactive transcoding invocation	267
Annex Q (Normative): Optimal media routing		270
Q.1	General	270
Q.2	Procedures and flows	271
Q.2.1	SDP extension	271
Q.2.2	General IMS-ALG procedures	271
Q.2.3	Common flows	273

Q.2.3.1	IMS-ALG allocates a TrGW.....	273
Q.2.3.2	IMS-ALG does not allocate a TrGW.....	273
Q.2.3.3	IMS-ALG bypasses its TrGW and one or more prior TrGWs.....	273
Q.2.3.4	IMS-ALG bypasses its TrGW using secondary realm from prior IMS.....	275
Q.2.3.5	IMS-ALG bypasses one or more prior TrGWs using a secondary realm.....	276
Q.2.3.6	IMS-ALG bypasses TrGWs performing NAT traversal.....	277
Q.2.5	Flows with transcoding.....	278
Q.2.5.1	Proactive transcoding where transcoding is required.....	278
Q.2.5.2	Proactive transcoding where transcoding not required.....	278
Q.2.5.3	IMS-ALG bypasses prior unrequired proactive transcoder.....	280
Q.2.5.4	IMS-ALG bypasses its TrGW and prior unrequired proactive transcoder.....	281
Q.2.5.5	IMS-ALG replaces prior proactive transcoder.....	283
Q.2.5.6	Proactive transcoding without resource reservation.....	284
Q.2.5.7	Reactive transcoding.....	284
Q.3	Charging.....	284
Annex R (Informative): Distribution of Network Provided Location Information within IMS.....		285
R.1	General.....	285
R.2	Session Establishment/Modification at Mobile Origination - Location Info in Request.....	285
R.3	Session Establishment/Modification at Mobile Origination - Location Info in Response.....	287
R.4	Session Establishment/Modification at Mobile Termination.....	288
R.5	Session Establishment/Modification - Location Information Distributed by IMS AS.....	289
R.6	Session Release.....	290
Annex S (Normative): Business Trunking.....		291
S.1	General.....	291
S.2	IP-PBXs using static mode Business Trunking.....	291
S.2.1	High level architecture.....	291
S.2.2	High level Flows.....	292
S.2.2.1	General.....	292
S.2.2.2	Originating procedures.....	292
S.2.2.2.1	Originating procedures using the S-CSCF.....	292
S.2.2.2.2	Originating procedures using the Transit Function.....	293
S.2.2.3	Terminating Procedures.....	294
S.2.2.3.1	Terminating procedures using the S-CSCF.....	294
S.2.2.3.2	Terminating procedures using the Transit Function.....	295
Annex T (Normative): IP-Connectivity Access Network specific concepts when using Trusted WLAN (TWAN) to access IMS.....		297
T.0	General.....	297
T.1	Retrieval of Network Provided Location Information in TWAN access.....	297
Annex U (Normative): WebRTC access to IMS - network-based architecture.....		298
U.1	Overview.....	298
U.1.0	General.....	298
U.1.1	Assumptions.....	298
U.1.2	Architecture and reference model.....	299
U.1.3	Functional entities.....	299
U.1.3.1	WIC (WebRTC IMS Client).....	299
U.1.3.2	WWSF (WebRTC Web Server Function).....	299
U.1.3.3	eP-CSCF (P-CSCF enhanced for WebRTC).....	300
U.1.3.4	eIMS-AGW (IMS Access GateWay enhanced for WebRTC).....	300
U.1.3.5	WAF (WebRTC Authorisation Function).....	301
U.1.4	Reference points.....	301
U.1.4.1	W1 (UE to WWSF).....	301