



Smart Cards;
Test specification for the Host Controller Interface (HCI);
Part 3: Host Controller features
(Release 13)

iTeh STANDARDS PREVIEW
(Standard: etsi:102695-3-v13.0.0-2019-04)
Full standards catalog: <https://standards.iteh.ai/catalog/standards/sls/bcd718e8-3def-4bc9-8863-76aa80b131db/etsi-ts-102695-3-v13.0.0-2019-04>

ReferenceRTS/SCP-00HCIHvd00

Keywordssmart card, terminal

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	9
Introduction	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definition of terms, symbols, abbreviations and formats.....	11
3.1 Terms.....	11
3.2 Symbols.....	11
3.3 Abbreviations	11
3.4 Formats.....	12
3.4.1 Format of the table of optional features	12
3.4.2 Format of the applicability table	12
3.4.3 Status and Notations	12
3.4.4 Format of the conformance requirements tables.....	13
4 Test environment.....	14
4.1 Table of optional features.....	14
4.2 Applicability table	15
4.3 Information to be provided by the device supplier	17
4.4 Test equipment	17
4.4.0 Base Requirements	17
4.4.1 Measurement / setting uncertainties.....	18
4.4.2 Default conditions for DUT operation.....	18
4.4.2.1 General	18
4.4.2.2 Status of UICC interfaces.....	18
4.4.3 Minimum/maximum conditions for DUT operation.....	18
4.4.4 Conventions	18
4.5 Test execution	18
4.5.1 Parameter variations	18
4.5.2 Execution requirements	18
4.6 Pass criterion	19
4.6.0 Principle.....	19
4.6.1 Unanticipated behaviour from the DUT	19
5 Test cases.....	19
5.1 HCI architecture	19
5.1.1 Overview	19
5.1.2 Hosts	20
5.1.3 Gates	20
5.1.3.1 Conformance requirements	20
5.1.4 Pipes.....	20
5.1.4.1 Conformance requirements	20
5.1.5 Registries	21
5.1.5.1 Conformance requirements	21
5.2 HCP.....	21
5.2.1 HCP packets.....	21
5.2.1.1 Conformance requirements	21
5.2.2 HCP message structure	22
5.2.2.1 Conformance requirements	22
5.2.3 Message fragmentation	22
5.2.3.1 Conformance requirements	22
5.3 Instructions	22

5.3.1	Commands	22
5.3.1.1	Overview	22
5.3.1.1.1	Conformance requirements	22
5.3.1.2	Generic commands	23
5.3.1.2.1	ANY_SET_PARAMETER	23
5.3.1.2.2	ANY_GET_PARAMETER	24
5.3.1.2.3	ANY_OPEN_PIPE	25
5.3.1.2.4	ANY_CLOSE_PIPE	26
5.3.1.3	Administration commands	26
5.3.1.3.1	ADM_CREATE_PIPE	26
5.3.1.3.2	ADM_NOTIFY_PIPE_CREATED	27
5.3.1.3.3	ADM_DELETE_PIPE	27
5.3.1.3.4	ADM_NOTIFY_PIPE_DELETED	27
5.3.1.3.5	ADM_CLEAR_ALL_PIPE	27
5.3.1.3.6	ADM_NOTIFY_ALL_PIPE_CLEARED	28
5.3.2	Responses	28
5.3.2.1	Conformance requirements	28
5.3.2.2	Test case 1: responses received out of order, previous commands sent by host	28
5.3.2.2.1	Test execution	28
5.3.2.2.2	Initial conditions	28
5.3.2.2.3	Test procedure	28
5.3.2.3	Test case 2: responses received out of order, previous commands sent by host controller	29
5.3.2.3.1	Test execution	29
5.3.2.3.2	Initial conditions	29
5.3.2.3.3	Test procedure	29
5.3.3	Events	29
5.3.3.1	Conformance requirements	29
5.4	GATES and subclauses	30
5.4.1	GATES	30
5.4.1.1	Conformance requirements	30
5.4.2	Management gates	30
5.4.2.1	Administration gates	30
5.4.2.1.1	Host controller administration gate	30
5.4.2.1.2	Host administration gate	31
5.4.2.2	Link management gate	31
5.4.2.2.1	Host controller link management gate	31
5.4.2.2.2	Host link management gate	32
5.4.2.3	Identity management gate	33
5.4.2.3.1	Local registry	33
5.4.2.3.2	Remote registry	34
5.4.2.4	Loop back gate	35
5.4.2.4.1	Conformance requirements	35
5.4.3	Generic gates	35
5.5	HCI procedures	35
5.5.1	Pipe management	35
5.5.1.1	Pipe creation	35
5.5.1.1.1	Conformance requirements	35
5.5.1.1.2	Test case 1: valid pipe creation from host simulator to another host	36
5.5.1.1.3	Test case 2: pipe creation from host simulator to another host, host simulator not in other host's WHITELIST	36
5.5.1.1.4	Test case 3: pipe creation from host simulator to another host, other host rejects pipe creation	37
5.5.1.1.5	Test case 4: valid pipe creation from host controller to host simulator	37
5.5.1.1.6	Test case 5: pipe creation from host simulator to host controller, pipe not supported by host controller	38
5.5.1.2	Pipe deletion	38
5.5.1.2.1	Conformance requirements	38
5.5.1.2.2	Test case 1: valid pipe deletion from host simulator to another host	39
5.5.1.3	Clear all Pipes	39
5.5.1.3.1	Conformance requirements	39
5.5.1.3.2	Test case 1: clear all pipes from host controller - static pipes, dynamic pipes to host	39
5.5.2	Registry access	40
5.5.3	Host and Gate discovery	40

5.5.4	Session initialization	40
5.5.4.1	Conformance requirements	40
5.5.5	Loop back testing	41
5.5.5.1	Conformance requirements	41
5.5.5.2	Test case 1: pipe creation	41
5.5.5.2.1	Test execution	41
5.5.5.2.2	Initial conditions	41
5.5.5.2.3	Test procedure	41
5.6	Contactless card emulation	41
5.6.1	Overview	41
5.6.1.1	Conformance requirements	41
5.6.2	Void	42
5.6.3	Gates	42
5.6.3.1	Void	42
5.6.3.2	Identity management gate	42
5.6.3.2.1	Conformance requirements	42
5.6.3.3	Card RF gates	42
5.6.3.3.1	Overview	42
5.6.3.3.2	Commands	42
5.6.3.3.3	Events and subclauses	42
5.6.3.3.4	Registry and subclauses	43
5.6.3.4	Card application gates	49
5.6.3.4.1	Overview	49
5.6.3.4.2	Commands	49
5.6.3.4.3	Events and subclauses	49
5.6.3.4.4	Registry	50
5.6.4	Procedures	51
5.6.4.1	Use of contactless card application	51
5.6.4.1.1	Conformance requirements	51
5.6.4.2	Non ISO/IEC 14443-4 type A applications	51
5.6.4.2.1	Conformance requirements	51
5.6.4.3	Type B' RF technology	52
5.6.4.3.1	Conformance requirements	52
5.6.4.4	Type F RF technology	52
5.6.4.4.1	Conformance requirements	52
5.6.4.4.2	Test case 1: NFCIP-1 command is not forwarded to UICC	53
5.6.4.5	Update RF technology settings	54
5.6.4.5.1	Conformance requirements	54
5.6.4.6	Identity check	54
5.6.4.6.1	Conformance requirements	54
5.7	Contactless reader	54
5.7.1	Overview	54
5.7.1.1	Conformance requirements	54
5.7.2	Reader RF gates	55
5.7.2.1	Overview	55
5.7.2.2	Command	55
5.7.2.2.1	WR_XCHG_DATA	55
5.7.2.3	Registries	56
5.7.2.3.1	Type A reader RF gate	56
5.7.2.3.2	Type B reader RF gate	57
5.7.2.4	Events and subclauses	57
5.7.2.4.1	Events	57
5.7.2.4.2	EVT_READER_REQUESTED	58
5.7.2.4.3	EVT_END_OPERATION	58
5.7.2.4.4	EVT_READER_STATUS	58
5.7.2.5	Responses	58
5.7.2.5.1	Conformance requirements	58
5.7.3	Reader application gates	59
5.7.3.1	Overview	59
5.7.3.2	Command	59
5.7.3.2.1	Conformance requirements	59
5.7.3.3	Registry	59

5.7.3.3.1	Conformance requirements.....	59
5.7.3.4	Events and subclauses.....	59
5.7.3.4.1	Events.....	59
5.7.3.4.2	EVT_TARGET_DISCOVERED.....	59
5.7.4	Procedures.....	60
5.7.4.1	Use of contactless reader application.....	60
5.7.4.1.1	Conformance requirements.....	60
5.7.4.2	Contactless reader not available.....	60
5.7.4.2.1	Conformance requirements.....	60
5.7.4.3	Error management.....	60
5.7.4.3.1	Conformance requirements.....	60
5.8	Connectivity.....	61
5.8.1	Overview.....	61
5.8.2	Connectivity gate and subclauses.....	61
5.8.2.1	Connectivity gate.....	61
5.8.2.2	Commands.....	61
5.8.2.2.1	PRO_HOST_REQUEST.....	61
5.8.2.3	Events and subclauses.....	61
5.8.2.3.1	Events.....	61
5.8.2.3.2	EVT_CONNECTIVITY.....	61
5.8.2.3.3	Void.....	61
5.8.2.3.4	EVT_OPERATION_ENDED.....	62
5.8.2.3.5	EVT_TRANSACTION.....	62
5.8.2.4	Registry.....	62
5.8.2.4.1	Conformance requirements.....	62
5.8.3	Connectivity application gate and subclauses.....	62
5.8.3.1	Connectivity application gate.....	62
5.8.3.1.1	Conformance requirements.....	62
5.8.3.2	Commands.....	63
5.8.3.2.1	Conformance requirements.....	63
5.8.3.3	Events and subclauses.....	63
5.8.3.3.1	Events.....	63
5.8.3.3.2	EVT_STANDBY.....	63
5.8.3.4	Registry.....	63
5.8.3.4.1	Conformance requirements.....	63
5.8.4	Procedures.....	63
5.8.4.1	Use of connectivity gate.....	63
5.9	APDU Transport.....	63
5.9.1	Server APDU host (APDU gate).....	63
5.9.1.1	General.....	63
5.9.1.1.1	Conformance requirements.....	63
5.9.1.2	Commands.....	64
5.9.1.3	Events.....	64
5.9.1.3.1	Conformance requirements.....	64
5.9.1.4	Registry.....	65
5.9.1.4.1	Conformance requirements.....	65
5.9.1.5	State diagram for the APDU gate.....	65
5.9.1.5.1	Conformance requirements.....	65
5.9.2	Client APDU host (APDU application gate).....	65
5.9.2.1	General.....	65
5.9.2.1.1	Conformance requirements.....	65
5.9.2.2	Commands.....	65
5.9.2.3	Events.....	65
5.9.2.3.1	Conformance requirements.....	65
5.9.2.3.2	Test case 1: initial activation of APDU gate – Client APDU host.....	66
5.9.2.3.3	Test case 2: APDU command processing after reboot.....	67
5.9.2.4	Registry.....	67
5.9.2.5	State diagram for the APDU gate.....	67
5.9.2.5.1	Conformance requirements.....	67
Annex A (informative):	Bibliography.....	68

Annex B (informative): Core specification version information.....69
Annex C (informative): Change history70
History71

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/bcd718e8-3def-4bc9-8863-76aa80b131db/etsi-ts-102-695-3-v13.0.0-2019-04>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Smart Card Platform (SCP).

The contents of the present document are subject to continuing work within TC SCP and may change following formal TC SCP approval. If TC SCP modifies the contents of the present document, it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 0 early working draft;
 - 1 presented to TC SCP for information;
 - 2 presented to TC SCP for approval;
 - 3 or greater indicates TC SCP approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

The present document is part 3 of a multi-part deliverable covering the Test specification for the Host Controller Interface (HCI), as identified below:

- Part 1: "Terminal features";
- Part 2: "UICC features";
- Part 3: "Host Controller features".**

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document defines test cases for the terminal relating to the Host Controller Interface (HCI) as specified in ETSI TS 102 622 [1].

The aim of the present document is to ensure interoperability between the terminal and the UICC independently of the respective manufacturer, card issuer or operator.

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/bcd718e8-3def-4bc9-8863-76aa80b131db/etsi-ts-102-695-3-v13.0.0-2019-04>

1 Scope

The present document covers additional test cases for the Host Controller to those specified in ETSI TS 102 695-1 [10].

The present document specifies the test cases for:

- the HCI core as described in the first part of ETSI TS 102 622 [1];
- the contactless platform as described in the second part of ETSI TS 102 622 [1].

Test cases for the UICC and terminal relating to ETSI TS 102 622 [1] and test cases for the Single Wire Protocol (SWP) covering both terminal and UICC are out of scope of the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- In the case of a reference to a TC SCP document, a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 102 622: "Smart Cards; UICC - Contactless Front-end (CLF) Interface; Host Controller Interface (HCI)".
- [2] ETSI TS 102 613: "Smart Cards; UICC - Contactless Front-end (CLF) Interface; Part 1: Physical and data link layer characteristics".
- [3] ETSI TS 102 223: "Smart Cards; Card Application Toolkit (CAT)".
- [4] ISO/IEC 18092: "Information technology -- Telecommunications and information exchange between systems -- Near Field Communication -- Interface and Protocol (NFCIP-1)".
- [5] ISO/IEC 14443-2: "Identification cards -- Contactless integrated circuit(s) cards -- Proximity cards -- Part 2: Radio frequency power and signal interface".
- [6] ISO/IEC 14443-3: "Cards and security devices for personal identification -- Contactless proximity objects -- Part 3: Initialization and anticollision".
- [7] ISO/IEC 14443-4: "Cards and security devices for personal identification -- Contactless proximity objects -- Part 4: Transmission protocol".
- [8] ISO/IEC 7816-4: "Information technology -- Identification cards -- Part 4: Organization, security and commands for interchange".
- [9] ISO/IEC 9646-7: "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 7: Implementation Conformance Statements".
- [10] ETSI TS 102 695-1: "Smart Cards; Test specification for the Host Controller Interface (HCI); Part 1: Terminal features".
- [11] ETSI TS 102 221: "Smart Cards; UICC-Terminal interface; Physical and logical characteristics".

- [12] ISO/IEC 7816-3: "Identification cards -- Integrated circuit cards -- Part 3: Cards with contacts -- Electrical interface and transmission protocols".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

3 Definition of terms, symbols, abbreviations and formats

3.1 Terms

For the purposes of the present document, the terms given in ETSI TS 102 622 [1] and the following apply:

allowed error response code: response code which is not ANY_OK and which is allowed for the referenced command as specified in ETSI TS 102 622 [1]

non-occurrence RQ: RQ which has been extracted from ETSI TS 102 622 [1], but which indicates a situation which should never occur

NOTE: The consequence is that such RQs cannot be explicitly tested.

user: any logical or physical entity which controls the test equipment in a way that it is able to trigger activities of the DUT

3.2 Symbols

For the purposes of the present document, the symbols given in ETSI TS 102 622 [1] and the following apply:

PIPE0 the static pipe connected to the link management gate of the device under test.
 PIPE1 the static pipe connected to the administration gate of the device under test.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI TS 102 622 [1] and the following apply:

AC Alternating Current
 DUT Device Under Test
 FFS For Further Study
 HCUT Host Controller Under Test
 HS Host Simulator
 ICR_x Initial Condition Requirement (where x is a number)

NOTE: As used in the applicability table; see clauses 4.2 and 4.5.2.

NAA Network Access Application
 PCD Proximity Coupling Device

PICC	Proximity Card
RFU	Reserved for Future Use
RO	Read-Only
RQ	Conformance requirement
RW	Read-Write
SRx	Static requirement (where x is a number)

NOTE: As used in the applicability table; see clauses 4.2 and 4.5.2.

TRx Trigger Requirement (where x is a number)

NOTE: As used in the applicability table; see clauses 4.2 and 4.5.2.

WO Write-Only

3.4 Formats

3.4.1 Format of the table of optional features

The columns in table 4.1 have the following meaning.

Column	Meaning
Option	The optional feature supported or not by the DUT.
Status	See clause 3.4.3.
Support	The support columns are to be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [9], are used for the support column in table 4.1. Y or y supported by the implementation. N or n not supported by the implementation. N/A, n/a or - no answer required (allowed only if the status is N/A, directly or after evaluation of a conditional status).
Mnemonic	The mnemonic column contains mnemonic identifiers for each item.

3.4.2 Format of the applicability table

The applicability of every test in table 4.2 is formally expressed by the use of Boolean expression defined in the following clause.

The columns in table 4.2 have the following meaning.

Column	Meaning
Clause	The "Clause" column identifies the clause containing the test case referenced in the "Test case number and description" column.
Test case number and description	The "Test case number and description" column gives a reference to the test case number (along with the corresponding description) detailed in the present document and required to validate the DUT.
Release	The "Release" column gives the Release applicable and onwards, for the corresponding test case.
Execution requirements	The usage of the "Execution requirements" column is described in clause 4.5.2.
Rel-x Terminal	For a given Release, the corresponding "Rel-x " column lists the tests required for a DUT to be declared compliant to this Release.
Support	The "Support" column is blank in the proforma, and is to be completed by the manufacturer in respect of each particular requirement to indicate the choices, which have been made in the implementation.

3.4.3 Status and Notations

The "Rel-x" columns show the status of the entries as follows:

The following notations, defined in ISO/IEC 9646-7 [9], are used for the status column:

M mandatory - the capability is required to be supported.

O	optional - the capability may be supported or not.
N/A	not applicable - in the given context, it is impossible to use the capability.
X	prohibited (excluded) - there is a requirement not to use this capability in the given context.
O.i	qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies an unique group of related optional items and the logic of their selection which is defined immediately following the table.
Ci	conditional - the requirement on the capability ("M", "O", "X" or "N/A") depends on the support of other optional or conditional items. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table. For nested conditional expressions, the syntax "IF ... THEN (IF ... THEN ... ELSE...) ELSE ..." is to be used to avoid ambiguities.

References to items

For each possible item answer (answer in the support column) there exists a unique reference, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table. If there is more than one support column in a table, the columns are to be discriminated by letters (a, b, etc.), respectively.

EXAMPLE: 4.1/4 is the reference to the answer of item 4 in table 4.1.

3.4.4 Format of the conformance requirements tables

The conformance requirements tables contained in the present document have the following format and meaning:

Column Status	Meaning										
Mandatory	This mandatory column contains the conformance requirement number (e.g. RQ3).										
Optional	This optional column is present when the containing clause sources conformance requirements from multiple clauses in the core specification. In this case, the cells in this column indicate the specific clause from the core specification from which the conformance requirement was sourced. If the conformance requirements are sourced from a single clause in the core specification, this column is not present.										
Optional	This optional column is present when the table contains conformance requirements which are applicable to only a subset of the releases which are covered by the present document. In this case, the content of the cells indicates the release(s) to which the conformance requirement is applicable. Additionally, a cell being empty indicates that the conformance requirement is applicable to every release which is covered by the present document. Examples of the content of cells in this column are given below: <table border="1" data-bbox="339 1451 1417 1597"> <thead> <tr> <th>Sample Content</th> <th>Applicability of conformance requirement</th> </tr> </thead> <tbody> <tr> <td></td> <td>All releases covered by the present document.</td> </tr> <tr> <td>Rel-7 to Rel-8</td> <td>Rel-7 to Rel-8 only.</td> </tr> <tr> <td>Rel-9 upwards</td> <td>Rel-9 up to the latest release which is covered by the present document.</td> </tr> <tr> <td>Rel-7</td> <td>Rel-7 only.</td> </tr> </tbody> </table>	Sample Content	Applicability of conformance requirement		All releases covered by the present document.	Rel-7 to Rel-8	Rel-7 to Rel-8 only.	Rel-9 upwards	Rel-9 up to the latest release which is covered by the present document.	Rel-7	Rel-7 only.
Sample Content	Applicability of conformance requirement										
	All releases covered by the present document.										
Rel-7 to Rel-8	Rel-7 to Rel-8 only.										
Rel-9 upwards	Rel-9 up to the latest release which is covered by the present document.										
Rel-7	Rel-7 only.										
	The absence of this column indicates that all conformance requirements are applicable to every release which is covered by the present document.										
Mandatory	This mandatory column contains the text of the conformance requirement.										