
**Road vehicles — Liquefied natural gas
(LNG) fuel system components —**

**Part 7:
Pressure relief valve**

*Véhicules routiers — Équipements pour véhicules utilisant le gaz
naturel liquéfié (GNL) comme combustible —
Partie 7: Soupape de sécurité à la pression*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 12614-7:2014

<https://standards.iteh.ai/catalog/standards/sist/9d56ecfd-bbd5-48f3-bfc6-d2e485402078/iso-12614-7-2014>



iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 12614-7:2014](https://standards.iteh.ai/catalog/standards/sist/9d56ecfd-bbd5-48f3-bfc6-d2e485402078/iso-12614-7-2014)

<https://standards.iteh.ai/catalog/standards/sist/9d56ecfd-bbd5-48f3-bfc6-d2e485402078/iso-12614-7-2014>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Marking	2
5 Construction and assembly	2
6 Test	2
6.1 Applicability	2
6.2 Hydrostatic strength	3
6.3 Leakage	3
6.4 Continued operation	3
6.5 Operational test	3

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 12614-7:2014](https://standards.iteh.ai/catalog/standards/sist/9d56ecfd-bbd5-48f3-bfc6-d2e485402078/iso-12614-7-2014)

<https://standards.iteh.ai/catalog/standards/sist/9d56ecfd-bbd5-48f3-bfc6-d2e485402078/iso-12614-7-2014>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 25, *Vehicles using gaseous fuels*.

ISO 12614 consists of the following parts, under the general title *Road vehicles — Liquefied natural gas (LNG) fuel system components*:

- *Part 1: General requirements and definitions*
- *Part 2: Performance and general test methods*
- *Part 3: Check valve*
- *Part 4: Manual valve*
- *Part 5: Tank pressure gauge*
- *Part 6: Overpressure regulator*
- *Part 7: Pressure relief valve*
- *Part 8: Excess flow valve*
- *Part 9: Gas-tight housing and ventilation hose*
- *Part 10: Rigid fuel line in stainless steel*
- *Part 11: Fittings*
- *Part 12: Rigid fuel line in material other than stainless steel*
- *Part 13: Pressure control regulator*
- *Part 14: Differential pressure fuel content gauge*
- *Part 15: Capacitance fuel content gauge*

- *Part 16: Heat exchanger - vaporizer*
- *Part 17: Natural gas detector*
- *Part 18: Gas temperature sensor*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 12614-7:2014](https://standards.iteh.ai/catalog/standards/sist/9d56ecfd-bbd5-48f3-bfc6-d2e485402078/iso-12614-7-2014)

<https://standards.iteh.ai/catalog/standards/sist/9d56ecfd-bbd5-48f3-bfc6-d2e485402078/iso-12614-7-2014>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 12614-7:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/9d56ecfd-bbd5-48f3-bfc6-d2e485402078/iso-12614-7-2014>

Road vehicles — Liquefied natural gas (LNG) fuel system components —

Part 7: Pressure relief valve

1 Scope

This part of ISO 12614 specifies tests and requirements for the pressure relief valve (PRV), a liquefied natural gas fuel system component intended for use on the types of motor vehicles defined in ISO 3833. This part of ISO 12614 is not applicable to the following:

- a) fuel containers;
- b) stationary gas engines;
- c) container mounting hardware;
- d) electronic fuel management;
- e) refueling receptacles.

NOTE 1 It is recognized that miscellaneous components not specifically covered herein can be examined to meet the criteria of this part of ISO 12614 and tested according to the appropriate functional tests.

NOTE 2 All references to pressure in this part of ISO 12614 are to be considered gauge pressures unless otherwise specified.

NOTE 3 This part of ISO 12614 is based upon a working pressure for natural gas as a fuel of 1,6 MPa [16 bar¹]. Other working pressures can be accommodated by adjusting the pressure by the appropriate factor (ratio). For example, 2 MPa (20 bar) working pressure system will require pressures to be multiplied by 1,25.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3833, *Road vehicles — Types — Terms and definitions*

ISO 12614-1, *Road vehicles — Liquefied natural gas (LNG) fuel system components — Part 1: General requirements and definitions*

ISO 12614-2, *Road vehicles — Liquefied natural gas (LNG) fuel system components — Part 2: Performance and general test methods*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12614-1 and the following apply.

1) 1 bar = 0,1 MPa = 105 Pa; 1 MPa = 1 N/mm².

3.1 set pressure

pressure at which it is intended that the PRV opens

4 Marking

Marking of the component shall provide sufficient information to allow the following to be traced:

- a) the manufacturer's or agent's name, trademark, or symbol;
- b) the model designation (part number);
- c) the working pressure or pressure and temperature range.

The following additional markings are recommended:

- a) the direction of flow (when necessary for correct installation);
- b) the type of fuel;
- c) electrical ratings (if applicable);
- d) the symbol of the certification agency;
- e) the type approval number;
- f) the serial number or date code;
- g) reference to this part of ISO 12614 (i.e. ISO 12614-7).

STANDARD PREVIEW
(standards.iteh.ai)

NOTE This information can be provided by a suitable identification code on at least one part of the component when it consists of more than one part.

<https://standards.iteh.ai/catalog/standards/sist/9d56ecfd-bbd5-48f3-bfc6-d2e485402078/iso-12614-7-2014>

5 Construction and assembly

The PRV shall comply with the applicable provisions of ISO 12614-1 and ISO 12614-2 and with the tests specified in [Clause 6](#) of this part of ISO 12614.

6 Test

6.1 Applicability

The tests required to be carried out are indicated in [Table 1](#).

Table 1 — Tests applicable

Test	Applicable	Test procedure as required by ISO 12614-2	Specific test requirements of this part of ISO 12614
Hydrostatic strength	X	X	X (see 6.2)
Leakage	X	X	X (see 6.3)
Excess torque resistance	X	X	
Bending moment	X	X	
Continued operation	X	X	X (see 6.4)
Operational	X		X (see 6.5)
Corrosion resistance	X	X	
Oxygen ageing	X	X	
Electrical over voltages			
Non-metallic synthetic immersion	X	X	
Vibration resistance	X	X	
Brass material compatibility	X	X	

6.2 Hydrostatic strength

Test the PRV according to the procedure for testing hydrostatic strength specified in ISO 12614-2, at 2,5 times its working pressure, specified by its manufacturer.

For the purposes of this test, the PRVs mechanism shall be removed and its orifice blocked.

6.3 Leakage

ISO 12614-7:2014

<https://standards.iteh.ai/catalog/standards/sist/9d56ecfd-bbd5-48f3-bfc6-9d4541628c0d/iso-12614-7-2014>

Test the PRV at temperatures less than +162 °C and 85 °C (if required by the operating conditions) at working pressure.

6.4 Continued operation

The PRV shall be capable of withstanding 600 cycles of operation when tested according to the provisions of the continued operation test procedure given in ISO 12614-2 and the following.

- a) A test cycle consists of, first, pressurizing the PRV to the set pressure. This action shall cause the PRV to open and vent. Once the valve is venting, reduce the inlet pressure. When the PRV re-seats, the cycle is finished.
- b) After 600 cycles, test the PRV for leakage at 20 °C ± 5 °C at its working pressure. Cycle time shall be within a period of 10s + 2s.

6.5 Operational test

6.5.1 General

Verify the opening and re-seating pressures of the PRV. The opening pressure shall be equal to the set pressure ±5 % at 20 °C, +5 % at less than -162 °C and +5 % at 85 °C or 120 °C (if required by the operating conditions).

6.5.2 Test procedure

Three randomly selected samples shall be subjected to the following test procedure. This test has three steps, which shall be conducted in the order given. Appropriate test media shall be chosen (i.e. air,