



**Universal Mobile Telecommunications System (UMTS);
LTE;
IP Multimedia Subsystem (IMS);
Multimedia telephony;
Media handling and interaction
(3GPP TS 26.114 version 13.8.0 Release 13)**

PRE-STD-126-114-13.8.0-2019-05
PRE-STD-126-114-13.8.0-2019-05
<https://standards.1e3.com/catalog/standards/sist/8511266d-390e-477b-8424-fb03a768d00c/sist-126-114-13.8.0-2019-05>



ReferenceRTS/TSGS-0426114vd80

KeywordsLTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	15
Introduction	15
1 Scope	16
2 References	16
3 Definitions and abbreviations.....	23
3.1 Definitions	23
3.2 Abbreviations	24
4 System description	26
4.1 System	26
4.2 Client	26
4.3 MRFP and MGW	28
5 Media codecs.....	28
5.1 Media components	28
5.2 Codecs for MTSI clients in terminals.....	29
5.2.1 Speech.....	29
5.2.1.1 General codec requirements	29
5.2.1.2 Detailed codec requirements, AMR.....	29
5.2.1.3 Detailed codec requirements, AMR-WB	29
5.2.1.4 Detailed codec requirements, EVS.....	30
5.2.1.5 Offering multiple audio bandwidths and multiple channels.....	30
5.2.1.6 Codec preference order.....	30
5.2.2 Video	30
5.2.3 Real-time text.....	32
6 Media configuration	32
6.1 General	32
6.2 Session setup procedures.....	33
6.2.1 General.....	33
6.2.1a RTP profile negotiation	33
6.2.1a.1 General.....	33
6.2.1a.2 Using SDPCapNeg in SDP offer.....	33
6.2.1a.3 Answering to an SDP offer using SDPCapNeg	34
6.2.2 Speech.....	34
6.2.2.1 General	34
6.2.2.2 Generating SDP offers	35
6.2.2.3 Generating SDP answer	38
6.2.3 Video	46
6.2.3.1 Introduction.....	46
6.2.3.2 Common Session Setup Procedures.....	47
6.2.3.3 Coordination of Video Orientation (CVO)	48
6.2.3.4 Video Region-of-Interest (ROI)	48
6.2.3.5 RTP Retransmission.....	51
6.2.3.6 Forward Error Correction (FEC).....	51
6.2.4 Text.....	51
6.2.5 Bandwidth negotiation.....	52
6.2.5.1 General	52
6.2.5.2 Speech	53
6.2.5.3 Video.....	55
6.2.6 The Synchronization Info attribute "3gpp_sync_info"	56
6.2.7 Negotiated QoS parameters	57

6.2.7.1	General	57
6.2.7.2	Alignment of negotiated QoS parameters and b=AS bandwidth modifier	57
6.2.7.3	Alignment of negotiated QoS parameters and a=bw-info attribute	58
6.3	Session control procedures	58
7	Data transport	59
7.1	General	59
7.2	RTP profiles	59
7.3	RTCP usage	59
7.3.1	General	59
7.3.2	Speech	60
7.3.3	Video	61
7.3.4	Real-time text	62
7.3.5	Void	62
7.3.6	Reduced-Size RTCP	62
7.3.7	Video Region-of-Interest (ROI) Signaling	63
7.4	RTP payload formats for MTSI clients	65
7.4.1	General	65
7.4.2	Speech	66
7.4.3	Video	67
7.4.4	Real-time text	67
7.4.5	Coordination of Video Orientation	67
7.4.6	RTP Retransmission	70
7.4.7	Forward Error Correction (FEC)	70
7.5	Media flow	70
7.5.1	General	70
7.5.2	Media specific	70
7.5.2.1	Speech	70
7.5.2.1.1	General	70
7.5.2.1.2	Default operation	70
7.5.2.1.2.1	General	70
7.5.2.1.2.2	Codec Mode Requests	71
7.5.2.1.2.3	Frame aggregation and redundancy	71
7.5.2.1.3	HSPA	71
7.5.2.1.4	EGPRS	71
7.5.2.1.5	GIP	72
7.5.2.1.6	Initial codec mode for AMR and AMR-WB	72
7.5.2.1.7	E-UTRAN	72
7.5.2.1.8	Initial codec mode for EVS	73
7.5.2.1.9	Dual-mono	73
7.5.2.2	Video	73
7.5.2.3	Text	73
7.5.3	Media synchronization	73
7.5.3.1	General	73
7.5.3.2	Text	74
7.5.4	ECN usage in RTP sessions	74
7.5.5	Handling of bit-rate variations	74
7.5.5.1	General	74
7.5.5.2	Video	74
7.5.5.3	Speech	75
8	Jitter buffer management in MTSI clients in terminals	75
8.1	General	75
8.2	Speech	75
8.2.1	Terminology	75
8.2.2	Functional requirements for jitter-buffer management	76
8.2.3	Minimum performance requirements for jitter-buffer management	76
8.2.3.1	General	76
8.2.3.2	Objective performance requirements	77
8.2.3.2.1	General	77
8.2.3.2.2	Jitter buffer delay criteria	77
8.2.3.2.3	Jitter induced concealment operations	78

8.2.3.3	Delay and error profiles	79
8.2.3.4	Speech material for JBM minimum performance evaluation.....	79
8.3	Video.....	79
8.4	Text	79
9	Packet-loss handling.....	80
9.1	General	80
9.2	Speech	80
9.2.1	General.....	80
9.2.2	Transmitting redundant frames	80
9.2.3	Receiving redundant frames	83
9.3	Video	84
9.3.1	General.....	84
9.3.2	Receiver behaviour	84
9.3.3	Sender behaviour	84
9.3.4	Recommendations for packet loss recovery mechanisms usage	85
9.4	Text	85
10	Adaptation	86
10.1	General	86
10.2	Speech	86
10.2.0	General.....	86
10.2.1	RTCP-APP with codec control requests	87
10.2.1.1	General	87
10.2.1.2	General Format of RTCP-APP packet with codec control requests	88
10.2.1.2a	Padding	89
10.2.1.3	Redundancy Request.....	89
10.2.1.4	Frame Aggregation Request.....	89
10.2.1.5	Codec Mode Request	90
10.2.1.6	Generation of RTP payloads for multiple codec control requests	91
10.2.1.7	EVS Primary Rate Request	92
10.2.1.8	EVS Bandwidth Request	93
10.2.1.9	EVS Channel Aware Request	93
10.2.1.10	EVS Primary mode to EVS AMR-WB IO mode Switching Request	94
10.2.1.11	EVS AMR-WB IO mode to EVS Primary mode Switching Request	95
10.2.2	Example use cases	95
10.2.3	SDP negotiation for RTCP-APP	97
10.3	Video	99
10.3.1	General.....	99
10.3.2	Signaling mechanisms	99
10.3.3	Adaptation triggers	100
10.3.4	Sender behavior, downswitching	100
10.3.4.1	Downswitching divided into phases.....	100
10.3.4.2	Rate reduction phase	101
10.3.4.3	Delay recovery phase	102
10.3.5	Sender behavior, up-switching.....	102
10.3.6	Receiver behavior, down-switching.....	102
10.3.7	Receiver behavior, up-switch.....	102
10.3.8	ECN triggered adaptation	102
10.4	Text	103
10.5	Explicit Congestion Notification.....	104
10.6	Using the a=bw-info attribute for adaptation	104
11	Front-end handling	104
11.1	General	104
12	Inter-working.....	105
12.1	General	105
12.2	3G-324M	106
12.2.1	General.....	106
12.2.2	Codec usage	106
12.2.2.1	General	106
12.2.2.2	Text	106

12.2.3	Payload format.....	106
12.2.4	MTSI media gateway trans-packetization.....	106
12.2.4.1	General.....	106
12.2.4.2	Speech de-jitter buffer.....	106
12.2.4.3	Video bitrate equalization	106
12.2.4.4	Data loss detection	107
12.2.4.5	Data integrity indication.....	107
12.2.4.6	Packet size considerations.....	107
12.2.4.6.0	General	107
12.2.4.6.1	The Maximum Receive SDU Size attribute “3gpp_MaxRecvSDUSize”.....	107
12.2.4.7	Setting RTP timestamps.....	108
12.2.4.8	Protocol termination.....	108
12.2.4.9	Media synchronization.....	108
12.2.5	Session control.....	108
12.3	GERAN/UTRAN CS inter-working.....	108
12.3.0	3G-324M	109
12.3.1	Codecs for MTSI media gateways.....	109
12.3.1.1	Speech interworking between 3GPP PS access and CS GERAN/UTRAN.....	109
12.3.1.1a	Speech inter-working between fixed access and CS GERAN/UTRAN.....	110
12.3.1.2	Text.....	110
12.3.2	RTP payload formats for MTSI media gateways.....	110
12.3.2.1	Speech.....	110
12.3.2.2	Text.....	111
12.3.3	Explicit Congestion Notification	111
12.3.4	Codec switching procedures with SRVCC	112
12.4	PSTN.....	112
12.4.1	3G-324M	112
12.4.2	Text.....	112
12.5	GIP inter-working.....	113
12.5.1	Text.....	113
12.5.2	Speech.....	113
12.6	Void.....	113
12.6.1	Void.....	113
12.6.2	Void.....	113
12.7	Inter-working with other IMS and non-IMS IP networks	113
12.7.1	General.....	113
12.7.2	Speech.....	113
12.7.2.1	General.....	113
12.7.2.2	Speech codecs and formats	114
12.7.2.2.1	MTSI MGW for interworking between MTSI client in terminal using 3GPP access and other IMS or non-IMS IP networks	114
12.7.2.2.2	MTSI MGW for interworking between MTSI client in terminal using fixed access and other IMS or non-IMS IP networks	114
12.7.2.2.3	Common procedures.....	114
12.7.2.3	Codec preference order for session negotiation	115
12.7.2.4	RTP profiles	115
12.7.2.5	RTP payload formats.....	115
12.7.2.6	Packetization	115
12.7.2.7	RTCP usage and adaptation	116
12.7.2.8	RTP usage	117
12.7.2.9	Session setup and session modification.....	117
12.7.2.10	Audio level alignment.....	117
12.7.3	Explicit Congestion Notification	117
12.7.4	Text.....	118
12.7.5	Inter-working IPv4 and IPv6 networks.....	118
13	Void.....	118
13a	Media types, codecs and formats used for MSRP transport.....	118
13a.1	General	118
13a.2	Difference relative to 3GPP TS 26.141	119
13a.2.1	Video	119

14	Supplementary services	119
14.1	General	119
14.2	Media formats and transport	119
14.3	Media handling in hold procedures	119
15	Network preference management object	119
15.1	General	119
15.2	Nodes Definition	120
15.3	Example Configuration of 3GPP MTSINP MO	132
16	Quality of Experience	134
16.1	General	134
16.2	Metrics Definition	134
16.2.1	Corruption duration metric	134
16.2.2	Successive loss of RTP packets	135
16.2.3	Frame rate	135
16.2.4	Jitter duration	135
16.2.5	Sync loss duration	136
16.2.6	Round-trip time	136
16.2.7	Average codec bitrate	136
16.2.8	Codec information	137
16.3	Metric Configuration	137
16.3.1	QoE metrics reporting management object	137
16.3.2	QoE metric reporting configuration	141
16.3.3	QoE reporting rule definition	142
16.4	Metrics Reporting	143
16.4.1	XML schema for QoE report message	144
16.4.2	Example XML for QoE report message	145
17	Management of Media Adaptation	145
17.1	General	145
17.2	Media adaptation management object	146
17.3	Management procedures	169
17.3.1	Management of speech adaptation	169
17.3.2	Management of video adaptation	171
18	MTSI client in terminal using fixed access	173
18.1	General	173
18.2	Media codecs	173
18.2.1	General	173
18.2.2	Speech	173
18.2.2.1	Speech codecs	173
18.2.2.2	Error concealment procedures	173
18.2.2.3	Source controlled rate operation	174
18.2.3	Video	174
18.2.4	Real-time text	175
18.3	Media configuration	175
18.3.1	General	175
18.3.2	Session setup procedures	175
18.3.2.1	General	175
18.3.2.2	Speech	175
18.3.2.3	Video	176
18.3.2.4	Text	176
18.3.2.5	Bandwidth negotiation	176
18.3.3	Session control procedures	176
18.4	Data transport	176
18.4.1	General	176
18.4.2	Packetization	177
18.4.3	RTP payload format	177
18.5	Jitter buffer management	177
18.6	Packet-loss handling	178
18.7	Adaptation	178
18.8	Front-end handling	178

18.9	Supplementary services	178
19	Additional bandwidth information	178
19.1	General	178
19.2	Bandwidth properties	179
19.2.1	General description	179
19.2.2	Maximum Supported Bandwidth	180
19.2.3	Maximum Desired Bandwidth	180
19.2.4	Minimum Desired Bandwidth	180
19.2.5	Minimum Supported Bandwidth	181
19.2.6	IP version	181
19.2.7	Maximum Packet Rate	181
19.2.8	Minimum Packet Rate	182
19.3	SDP attribute	182
19.3.1	Definition	182
19.3.2	SDP grammar	182
19.3.3	Declarative use	183
19.3.4	Usage in offer/answer	184
19.4	Modifications of the bandwidth information by intermediate network nodes	185
Annex A (informative): Examples of SDP offers and answers		186
A.1	SDP offers for speech sessions initiated by MTSI client in terminal	186
A.1.1	HSPA or unknown access technology	186
A.1.1.1	Only AMR-NB supported by MTSI client in terminal	186
A.1.1.2	AMR and AMR-WB are supported by MTSI client in terminal	187
A.1.1.2.1	One-phase approach	187
A.1.1.2.2	Two-phase approach	188
A.1.2	EGPRS	188
A.1.3	Generic Access	189
A.2	SDP offers for speech sessions initiated by media gateway	190
A.2.1	General	190
A.2.2	MGW between GERAN UE and MTSI	190
A.2.3	MGW between legacy UTRAN UE and MTSI	190
A.2.4	MGW between CS UE and MTSI	191
A.2.5	MGW between GERAN UE and MTSI when wideband speech is supported	191
A.3	SDP answers to SDP speech session offers	192
A.3.1	General	192
A.3.1a	SDP answer from an MTSI client in terminal when only narrowband speech was offered	192
A.3.2	SDP answer from an MTSI client in terminal	193
A.3.2a	SDP answer from a non-MTSI UE with AVP	194
A.3.3	SDP answer from an MTSI client in terminal supporting only AMR	194
A.3.4	SDP answer from an MTSI client in terminal using EGPRS access when both AMR and AMR-WB are supported	195
A.3.4a	SDP answer from an MTSI client in terminal using EGPRS access when only AMR is supported	196
A.3.4b	SDP answer from an MTSI client in terminal using WLAN	196
A.3.5	SDP answer from MTSI MGW supporting only one codec mode set for AMR and AMR-WB each	197
A.3.5a	SDP answer from MTSI MGW supporting only one codec mode set for AMR	199
A.3.6	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing UE on GERAN	199
A.3.7	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing legacy UE on UTRAN	200
A.4	SDP offers and answers for video sessions	201
A.4.1	Void	201
A.4.2	Void	201
A.4.2a	H.264/AVC	201
A.4.2b	High Granularity CVO example	203
A.4.2c	RTP Retransmission	203
A.4.2d	RTP Forward Error Correction (FEC)	204
A.4.2e	SDP Examples with ROI	205
A.4.3	Void	211

A.4.4	Void.....	211
A.4.4a	H.264/AVC with "imageattr" attribute.....	211
A.4.4a.1	H.264/AVC with "imageattr" attribute – different image sizes in SDP offer and answer.....	213
A.4.4a.2	H.264/AVC with "imageattr" attribute – different payload type numbers in offer and answer.....	214
A.4.4b	H.264/AVC with "imageattr" attribute with multiple rtpmaps.....	215
A.4.5	H.264 with asymmetric video streams.....	217
A.4.6	H.264/AVC with "imageattr" attribute for non-CVO operation.....	218
A.4.7	H.264 (AVC) and H.265 (HEVC).....	220
A.4.7.1	MTSI client with 848x480 resolution 5 inch display.....	220
A.4.7.2	MTSI client with 1280x720 resolution 5 inch display.....	221
A.4.7.3	MTSI client with 848x480 resolution 10 inch display.....	222
A.4.7.4	MTSI client with 1280x720 resolution 10 inch display.....	223
A.4.8	H.264 (AVC) and H.265 (HEVC) with asymmetric video streams.....	224
A.5	SDP offers for text.....	225
A.5.1	T.140 with and without redundancy.....	225
A.6	SDP example with bandwidth information.....	226
A.6.1	General.....	226
A.6.2	SDP examples with bandwidth information declared with bandwidth modifiers.....	226
A.6.3	SDP examples giving additional bandwidth information using the a=bw-info attribute.....	227
A.7	SDP examples with "3gpp_sync_info" attribute.....	230
A.7.1	Synchronized streams.....	230
A.7.2	Nonsynchronized streams.....	230
A.8	SDP example with QoS negotiation.....	231
A.9	Void.....	235
A.9a	SDP offer/answer regarding the use of Reduced-Size RTCP.....	235
A.10	Examples of SDP offers and answers for inter-working with other IMS or non-IMS IP networks.....	236
A.10.1	General.....	236
A.10.2	Session initiated by MTSI client in terminal.....	236
A.10.2.1	SDP offers from an MTSI client in terminal.....	236
A.10.2.2	SDP offers modified by MTSI MGW when pre-emptively adding inter-working formats.....	237
A.10.2.3	SDP modified by MGW when adding inter-working formats only when the original SDP offer was rejected.....	238
A.11	Adding or removing a video component to/from an on-going video call session.....	240
A.12	SDP examples when using ECN.....	244
A.12.1	SDP examples when using ECN for speech.....	244
A.12.1.1	With RTP/AVP and zero RTCP bandwidth.....	244
A.12.1.2	With RTP/AVPF and non-zero RTCP bandwidth.....	245
A.12.1.3	With RTCP ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients.....	246
A.12.2	SDP examples when using ECN for video in RTP.....	246
A.12.2.1	Without RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports.....	246
A.12.2.2	With RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients.....	247
A.13	SDP examples for MTSI client in terminal using fixed access.....	249
A.13.1	General.....	249
A.13.2	SDP examples for PCM.....	249
A.13.3	SDP example for G.722.....	250
A.13.4	SDP example for EVS, AMR-WB, G.722, AMR, PCM and DTMF.....	250
A.14	SDP offers and answers for speech sessions with EVS.....	251
A.14.1	SDP offers initiated by MTSI client in terminal.....	251
A.14.1.1	Unknown access technology.....	251
A.14.1.2	EGPRS.....	252
A.14.1.3	E-UTRAN/HSPA.....	252
A.14.1.4	Dual-mono.....	253
A.14.2	SDP offers initiated by media gateway.....	254

A.14.2.1	Network between MTSI using fixed access and MTSI modifying SDP offer to configure EVS AMR-WB IO mode	254
A.14.3	SDP answers from MTSI client in terminal	255
A.14.3.1	SDP answer from MTSI client in terminal when narrowband speech is negotiated	255
A.14.3.2	SDP answer from MTSI client in terminal when up to wideband speech is negotiated	255
A.14.3.3	SDP answer from MTSI client in terminal when only wideband speech is negotiated	256
A.14.3.4	SDP answer from MTSI client in terminal when up to super-wideband speech is negotiated	256
A.14.3.5	SDP answer from MTSI client in terminal when only super-wideband speech is negotiated	257
A.14.3.6	SDP answer from MTSI client in terminal using WLAN	257
A.14.3.7	SDP answer from MTSI client in terminal supporting dual-mono	257
A.14.3.8	SDP answer from MTSI client in terminal supporting dual-mono for send direction	258
A.14.3.9	SDP answer from MTSI client in terminal when SC-VBR is negotiated	258
A.14.4	SDP answers from MTSI client in terminal using fixed access.....	259
A.14.4.1	SDP answer from MTSI client in terminal using fixed access when narrowband speech is negotiated ...	259
A.14.4.2	SDP answer from MTSI client in terminal using fixed access when only wideband speech is negotiated.....	259
A.14.4.3	SDP answer from MTSI client in terminal using fixed access when only super-wideband speech is negotiated.....	259
Annex B (informative): Examples of adaptation scenarios		261
B.1	Video bitrate adaptation	261
Annex C (informative): Example adaptation mechanisms for speech.....		262
C.1	Example of feedback and adaptation for speech and video.....	262
C.1.1	Introduction	262
C.1.2	Signalling state considerations	263
C.1.3	Adaptation state machine implementations	265
C.1.3.1	General.....	265
C.1.3.2	Adaptation state machine with four states	267
C.1.3.3	Adaptation state machine with four states (simplified version without frame aggregation).....	270
C.1.3.4	Adaptation state machine with two states	272
C.1.3.5	Adaptation when using ECN	273
C.2	Example criteria for video bit rate feedback and adaptation.....	275
C.2.1	Introduction	275
C.2.2	Media sender side.....	276
C.2.3	Media receiver side	276
C.2.4	Video encoder bitrate adaptation, down-switch	276
C.2.5	Video encoder bitrate adaptation, receiver-driven up-switch.....	278
C.2.6	Video encoder bitrate adaptation, recovery phase.....	278
Annex D (informative): Reference delay computation algorithm.....		280
Annex E (informative): QoS profiles		282
E.1	General	282
E.2	Bi-directional speech (AMR12.2, IPv4, RTCP and MBR=GBR bearer).....	282
E.3	Void.....	283
E.4	Bi-directional real-time text (3 kbps, IPv4 or IPv6, RTCP and MBR=GBR bearer).....	284
E.5	Bi-directional speech (AMR-WB23.85, IPv4, RTCP and MBR=GBR bearer).....	286
E.6	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv4, RTCP and MBR=GBR bearer)	286
E.7	Bi-directional speech (AMR12.2, IPv6, RTCP and MBR=GBR bearer).....	287
E.8	Bi-directional speech (AMR-WB23.85, IPv6, RTCP and MBR=GBR bearer).....	288
E.9	Void.....	289
E.10	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv6, RTCP and MBR=GBR bearer)	289

E.11	Bi-directional speech (AMR, IPv4, RTCP and MBR>GBR bearer).....	290
E.12	Bi-directional speech (AMR-WB, IPv4, RTCP and MBR>GBR bearer).....	291
E.13	Void.....	292
E.14	Bi-directional video (H.264 AVC level 1.1, IPv4, RTCP and MBR>GBR bearer).....	292
E.15	Bi-directional speech (AMR, IPv6, RTCP and MBR>GBR bearer).....	293
E.16	Bi-directional speech (AMR-WB, IPv6, RTCP and MBR>GBR bearer).....	294
E.17	Void.....	295
E.18	Bi-directional video (H.264 AVC level 1.1, IPv6, RTCP and MBR>GBR bearer).....	295
E.19	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv4, RTCP and MBR=GBR bearer).....	296
E.20	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv6, RTCP and MBR=GBR bearer).....	297
E.21	Bi-directional video (H.264 AVC level 1.2, IPv4, RTCP and MBR>GBR bearer).....	299
E.22	Bi-directional video (H.264 AVC level 1.2, IPv6, RTCP and MBR>GBR bearer).....	302
E.23	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500 kbps, IPv6, RTCP and MBR=GBR bearer).....	303
E.24	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	304
E.25	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600 kbps, IPv6, RTCP and MBR=GBR bearer).....	305
E.26	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	306
E.27	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650 kbps, IPv6, RTCP and MBR=GBR bearer).....	307
E.28	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	308
E.29	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750 kbps, IPv6, RTCP and MBR=GBR bearer).....	309
E.30	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	310
E.31	Bi-directional speech (EVS 13.2, IPv4, RTCP and MBR=GBR bearer).....	311
E.32	Bi-directional speech (EVS 24.4, IPv4, RTCP and MBR=GBR bearer).....	312
E.33	Bi-directional speech (EVS 13.2, IPv6, RTCP and MBR=GBR bearer).....	313
E.34	Bi-directional speech (EVS 24.4, IPv6, RTCP and MBR=GBR bearer).....	314
Annex F (Normative):	Void.....	316
Annex G (Normative):	DTMF events.....	317
G.1	General.....	317
G.2	Encoding of DTMF signals.....	317
G.3	Session setup.....	317
G.4	Data transport.....	318
Annex H (informative):	Network Preference Management Object Device Description Framework.....	320

Annex I (informative):	QoE Reporting Management Object Device Description Framework ...	321
Annex J (informative):	Media Adaptation Management Object Device Description Framework	322
Annex K (informative):	Computation of b=AS for AMR and AMR-WB	323
K.1	General	323
K.2	Procedure for computing the bandwidth	323
K.3	Computation of RTP payload size.....	323
K.4	Detailed computation	324
Annex L (Normative):	Facsimile transmission	332
L.1	General	332
L.2	FoIP support in MTSI clients	332
L.2.1	FoIP support in MTSI client in terminal	332
L.2.2	FoIP support in MTSI MGW	332
L.2.3	Recommended configuration.....	332
L.3	Session setup	333
L.3.1	Session setup for any MTSI client supporting facsimile transmission	333
L.3.2	Session setup when the recommended profile is supported	333
L.4	Data transport using UDP/IP	334
L.5	CS GERAN inter-working	334
L.6	PSTN inter-working	334
L.7	SDP examples	335
L.7.1	Facsimile-only session	335
Annex M (informative):	IANA registration information for SDP attributes.....	337
M.1.	Introduction	337
M.2	3gpp_sync_info	337
M.3	3gpp_MaxRecvSDUSize.....	337
M.4	3gpp_mtsi_app_adapt.....	338
M.5	predefined_ROI.....	338
M.6	bw-info	339
Annex N (informative):	Computation of b=AS for Video Codec	341
N.1	General	341
N.2	Examples	341
Annex O (informative):	IANA registration information for RTP Header Extensions.....	342
O.1.	Introduction	342
O.2	urn:3gpp:video-orientation	342
O.3	urn:3gpp:video-orientation:6.....	342
O.4	urn:3gpp:roi-sent	342
O.5	urn:3gpp:predefined-roi-sent.....	343
Annex P (informative):	Video packet loss handling operation principles and examples	344
P.1	General	344