



**Universal Mobile Telecommunications System (UMTS);
LTE;
IP Multimedia Subsystem (IMS);
Multimedia telephony;
Media handling and interaction
(3GPP TS 26.114 version 15.5.0 Release 15)**



Reference

RTS/TSGS-0426114vf50

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	15
Introduction	15
1 Scope	16
2 References	16
3 Definitions and abbreviations.....	23
3.1 Definitions	23
3.2 Abbreviations	24
4 System description	26
4.1 System	26
4.2 Client	27
4.3 MRFP and MGW	28
5 Media codecs.....	28
5.1 Media components	28
5.2 Codecs for MTSI clients in terminals.....	29
5.2.1 Speech.....	29
5.2.1.1 General codec requirements.....	29
5.2.1.2 Detailed codec requirements, AMR.....	29
5.2.1.3 Detailed codec requirements, AMR-WB.....	29
5.2.1.4 Detailed codec requirements, EVS.....	29
5.2.1.5 Offering multiple audio bandwidths and multiple channels.....	30
5.2.1.6 Codec preference order.....	30
5.2.2 Video	30
5.2.3 Real-time text.....	32
6 Media configuration	32
6.1 General	32
6.2 Session setup procedures.....	33
6.2.1 General.....	33
6.2.1a RTP profile negotiation	33
6.2.1a.1 General.....	33
6.2.1a.2 Using SDPCapNeg in SDP offer.....	33
6.2.1a.3 Answering to an SDP offer using SDPCapNeg	34
6.2.2 Speech.....	34
6.2.2.1 General	34
6.2.2.2 Generating SDP offers	35
6.2.2.3 Generating SDP answer	38
6.2.3 Video	46
6.2.3.1 Introduction.....	46
6.2.3.2 Common Session Setup Procedures.....	47
6.2.3.3 Coordination of Video Orientation (CVO)	48
6.2.3.4 Video Region-of-Interest (ROI).....	48
6.2.3.5 RTP Retransmission.....	51
6.2.3.6 Forward Error Correction (FEC).....	51
6.2.4 Text.....	51
6.2.5 Bandwidth negotiation.....	52
6.2.5.1 General	52
6.2.5.2 Speech	54
6.2.5.3 Video.....	56
6.2.6 The Synchronization Info attribute "3gpp_sync_info"	57
6.2.7 Negotiated QoS parameters	58

6.2.7.1	General	58
6.2.7.2	Alignment of negotiated QoS parameters and b=AS bandwidth modifier	58
6.2.7.3	Alignment of negotiated QoS parameters and a=bw-info attribute	59
6.3	Session control procedures	59
7	Data transport	60
7.1	General	60
7.2	RTP profiles	60
7.3	RTCP usage	60
7.3.1	General	60
7.3.2	Speech	61
7.3.3	Video	62
7.3.4	Real-time text	63
7.3.5	Void	63
7.3.6	Reduced-Size RTCP	63
7.3.7	Video Region-of-Interest (ROI) Signaling	64
7.4	RTP payload formats for MTSI clients	67
7.4.1	General	67
7.4.2	Speech	67
7.4.3	Video	68
7.4.4	Real-time text	68
7.4.5	Coordination of Video Orientation	68
7.4.6	RTP Retransmission	71
7.4.7	Forward Error Correction (FEC)	71
7.5	Media flow	71
7.5.1	General	71
7.5.2	Media specific	71
7.5.2.1	Speech	71
7.5.2.1.1	General	71
7.5.2.1.2	Default operation	71
7.5.2.1.2.1	General	71
7.5.2.1.2.2	Codec Mode Requests	72
7.5.2.1.2.3	Frame aggregation and redundancy	72
7.5.2.1.3	HSPA	72
7.5.2.1.4	EGPRS	72
7.5.2.1.5	GIP	73
7.5.2.1.6	Initial codec mode for AMR and AMR-WB	73
7.5.2.1.7	E-UTRAN and NR	73
7.5.2.1.8	Initial codec mode for EVS	74
7.5.2.1.9	Dual-mono	74
7.5.2.2	Video	74
7.5.2.3	Text	74
7.5.3	Media synchronization	74
7.5.3.1	General	74
7.5.3.2	Text	75
7.5.4	ECN usage in RTP sessions	75
7.5.5	Handling of bit-rate variations	75
7.5.5.1	General	75
7.5.5.2	Video	75
7.5.5.3	Speech	76
8	Jitter buffer management in MTSI clients in terminals	76
8.1	General	76
8.2	Speech	76
8.2.1	Terminology	76
8.2.2	Functional requirements for jitter-buffer management	77
8.2.3	Minimum performance requirements for jitter-buffer management	77
8.2.3.1	General	77
8.2.3.2	Objective performance requirements	78
8.2.3.2.1	General	78
8.2.3.2.2	Jitter buffer delay criteria	78
8.2.3.2.3	Jitter induced concealment operations	79

8.2.3.3	Delay and error profiles	80
8.2.3.4	Speech material for JBM minimum performance evaluation.....	80
8.3	Video.....	80
8.4	Text	80
9	Packet-loss handling.....	81
9.1	General	81
9.2	Speech	81
9.2.1	General.....	81
9.2.2	Transmitting redundant frames	81
9.2.3	Receiving redundant frames	84
9.3	Video	85
9.3.1	General.....	85
9.3.2	Receiver behaviour	85
9.3.3	Sender behaviour	85
9.3.4	Recommendations for packet loss recovery mechanisms usage	86
9.4	Text	86
10	Adaptation	87
10.1	General	87
10.2	Speech	87
10.2.0	General.....	87
10.2.1	RTCP-APP with codec control requests	88
10.2.1.1	General	88
10.2.1.2	General Format of RTCP-APP packet with codec control requests	89
10.2.1.2a	Padding	90
10.2.1.3	Redundancy Request.....	90
10.2.1.4	Frame Aggregation Request.....	90
10.2.1.5	Codec Mode Request	91
10.2.1.6	Generation of RTP payloads for multiple codec control requests	92
10.2.1.7	EVS Primary Rate Request	93
10.2.1.8	EVS Bandwidth Request	94
10.2.1.9	EVS Channel Aware Request	94
10.2.1.10	EVS Primary mode to EVS AMR-WB IO mode Switching Request	95
10.2.1.11	EVS AMR-WB IO mode to EVS Primary mode Switching Request	96
10.2.2	Example use cases	96
10.2.3	SDP negotiation for RTCP-APP.....	98
10.3	Video	100
10.3.1	General.....	100
10.3.2	Signaling mechanisms	100
10.3.3	Adaptation triggers	101
10.3.4	Sender behavior, downswitching	102
10.3.4.1	Downswitching divided into phases.....	102
10.3.4.2	Rate reduction phase	102
10.3.4.3	Delay recovery phase	103
10.3.5	Sender behavior, up-switching.....	103
10.3.6	Receiver behavior, down-switching.....	103
10.3.7	Receiver behavior, up-switch.....	103
10.3.8	ECN triggered adaptation	104
10.4	Text	105
10.5	Explicit Congestion Notification.....	105
10.6	Using the a=bw-info attribute for adaptation	105
10.7	Access network bitrate recommendation.....	106
10.7.1	General.....	106
10.7.2	Relation to session signaling bitrate information.....	106
10.7.3	Use with dynamic bitrate adaptation.....	106
10.7.3.1	General	106
10.7.3.2	Adaptation of sent media	107
10.7.3.3	Adaptation of received media	110
10.7.4	Message mapping for LTE access	110
10.7.5	Message mapping for NR access	110
11	Front-end handling	111

11.1	General	111
12	Inter-working.....	112
12.1	General	112
12.2	3G-324M	112
12.2.1	General.....	112
12.2.2	Codec usage	112
12.2.2.1	General	112
12.2.2.2	Text	112
12.2.3	Payload format	112
12.2.4	MTSI media gateway trans-packetization.....	112
12.2.4.1	General	112
12.2.4.2	Speech de-jitter buffer.....	112
12.2.4.3	Video bitrate equalization	113
12.2.4.4	Data loss detection	113
12.2.4.5	Data integrity indication.....	113
12.2.4.6	Packet size considerations	113
12.2.4.6.0	General	113
12.2.4.6.1	The Maximum Receive SDU Size attribute "3gpp_MaxRecvSDUSize"	114
12.2.4.7	Setting RTP timestamps	114
12.2.4.8	Protocol termination.....	114
12.2.4.9	Media synchronization	114
12.2.5	Session control.....	115
12.3	GERAN/UTRAN CS inter-working.....	115
12.3.0	3G-324M	115
12.3.1	Codecs for MTSI media gateways.....	115
12.3.1.1	Speech interworking between 3GPP PS access and CS GERAN/UTRAN.....	115
12.3.1.1a	Speech inter-working between fixed access and CS GERAN/UTRAN.....	116
12.3.1.2	Text	116
12.3.2	RTP payload formats for MTSI media gateways.....	116
12.3.2.1	Speech.....	116
12.3.2.2	Text	118
12.3.3	Explicit Congestion Notification	118
12.3.4	Codec switching procedures with SRVCC.....	118
12.4	PSTN.....	118
12.4.1	3G-324M	118
12.4.2	Text.....	119
12.5	GIP inter-working.....	119
12.5.1	Text.....	119
12.5.2	Speech.....	119
12.6	Void.....	119
12.6.1	Void	119
12.6.2	Void	119
12.7	Inter-working with other IMS and non-IMS IP networks	119
12.7.1	General.....	119
12.7.2	Speech.....	120
12.7.2.1	General	120
12.7.2.2	Speech codecs and formats	120
12.7.2.2.1	MTSI MGW for interworking between MTSI client in terminal using 3GPP access and other IMS or non-IMS IP networks	120
12.7.2.2.2	MTSI MGW for interworking between MTSI client in terminal using fixed access and other IMS or non-IMS IP networks	120
12.7.2.2.3	Common procedures.....	121
12.7.2.3	Codec preference order for session negotiation	121
12.7.2.4	RTP profiles	121
12.7.2.5	RTP payload formats.....	121
12.7.2.6	Packetization	122
12.7.2.7	RTCP usage and adaptation	122
12.7.2.8	RTP usage	123
12.7.2.9	Session setup and session modification.....	123
12.7.2.10	Audio level alignment	123
12.7.3	Explicit Congestion Notification	124

12.7.4	Text.....	124
12.7.5	Inter-working IPv4 and IPv6 networks.....	124
12.8	MGW handling for NO_REQ interworking.....	124
13	Void.....	125
13a	Media types, codecs and formats used for MSRP transport.....	125
13a.1	General.....	125
13a.2	Difference relative to 3GPP TS 26.141.....	125
13a.2.1	Video.....	125
14	Supplementary services.....	125
14.1	General.....	125
14.2	Media formats and transport.....	126
14.3	Media handling in hold procedures.....	126
15	Network preference management object.....	126
15.1	General.....	126
15.2	Nodes Definition.....	127
15.3	Example Configuration of 3GPP MTSINP MO.....	138
16	Quality of Experience.....	140
16.1	General.....	140
16.2	Metrics Definition.....	140
16.2.1	Corruption duration metric.....	141
16.2.2	Successive loss of RTP packets.....	141
16.2.3	Frame rate.....	141
16.2.4	Jitter duration.....	142
16.2.5	Sync loss duration.....	142
16.2.6	Round-trip time.....	142
16.2.7	Average codec bitrate.....	143
16.2.8	Codec information.....	143
16.3	Metric Configuration.....	143
16.3.1	QoE metrics reporting management object.....	144
16.3.2	QoE metric reporting configuration.....	150
16.3.3	QoE reporting rule definition.....	150
16.4	Metrics Reporting.....	151
16.4.1	XML schema for QoE report message.....	152
16.4.2	Example XML for QoE report message.....	153
16.5	QoE Measurement Collection Functionalities.....	154
16.5.1	Configuration and reporting.....	154
16.5.2	XML configuration.....	155
17	Management of Media Adaptation.....	157
17.1	General.....	157
17.2	Media adaptation management object.....	157
17.3	Management procedures.....	180
17.3.1	Management of speech adaptation.....	180
17.3.2	Management of video adaptation.....	182
18	MTSI client in terminal using fixed access.....	184
18.1	General.....	184
18.2	Media codecs.....	184
18.2.1	General.....	184
18.2.2	Speech.....	184
18.2.2.1	Speech codecs.....	184
18.2.2.2	Error concealment procedures.....	184
18.2.2.3	Source controlled rate operation.....	185
18.2.3	Video.....	185
18.2.4	Real-time text.....	186
18.3	Media configuration.....	186
18.3.1	General.....	186
18.3.2	Session setup procedures.....	186
18.3.2.1	General.....	186

18.3.2.2	Speech	186
18.3.2.3	Video	187
18.3.2.4	Text	187
18.3.2.5	Bandwidth negotiation	187
18.3.3	Session control procedures	187
18.4	Data transport	187
18.4.1	General	187
18.4.2	Packetization	188
18.4.3	RTP payload format	188
18.5	Jitter buffer management	188
18.6	Packet-loss handling	189
18.7	Adaptation	189
18.8	Front-end handling	189
18.9	Supplementary services	189
19	Additional bandwidth information	189
19.1	General	189
19.2	Bandwidth properties	190
19.2.1	General description	190
19.2.2	Maximum Supported Bandwidth	191
19.2.3	Maximum Desired Bandwidth	191
19.2.4	Minimum Desired Bandwidth	191
19.2.5	Minimum Supported Bandwidth	192
19.2.6	IP version	192
19.2.7	Maximum Packet Rate	192
19.2.8	Minimum Packet Rate	193
19.3	SDP attribute	193
19.3.1	Definition	193
19.3.2	SDP grammar	193
19.3.3	Declarative use	194
19.3.4	Usage in offer/answer	195
19.4	Modifications of the bandwidth information by intermediate network nodes	196
Annex A (informative): Examples of SDP offers and answers		197
A.1	SDP offers for speech sessions initiated by MTSI client in terminal	197
A.1.1	HSPA or unknown access technology	197
A.1.1.1	Only AMR-NB supported by MTSI client in terminal	197
A.1.1.2	AMR and AMR-WB are supported by MTSI client in terminal	198
A.1.1.2.1	One-phase approach	198
A.1.1.2.2	Two-phase approach	199
A.1.2	EGPRS	199
A.1.3	Generic Access	200
A.2	SDP offers for speech sessions initiated by media gateway	201
A.2.1	General	201
A.2.2	MGW between GERAN UE and MTSI	201
A.2.3	MGW between legacy UTRAN UE and MTSI	201
A.2.4	MGW between CS UE and MTSI	202
A.2.5	MGW between GERAN UE and MTSI when wideband speech is supported	202
A.3	SDP answers to SDP speech session offers	203
A.3.1	General	203
A.3.1a	SDP answer from an MTSI client in terminal when only narrowband speech was offered	203
A.3.2	SDP answer from an MTSI client in terminal	204
A.3.2a	SDP answer from a non-MTSI UE with AVP	205
A.3.3	SDP answer from an MTSI client in terminal supporting only AMR	205
A.3.4	SDP answer from an MTSI client in terminal using EGPRS access when both AMR and AMR-WB are supported	206
A.3.4a	SDP answer from an MTSI client in terminal using EGPRS access when only AMR is supported	207
A.3.4b	SDP answer from an MTSI client in terminal using WLAN	207
A.3.5	SDP answer from MTSI MGW supporting only one codec mode set for AMR and AMR-WB each	208
A.3.5a	SDP answer from MTSI MGW supporting only one codec mode set for AMR	210

A.3.6	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing UE on GERAN.....	210
A.3.7	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing legacy UE on UTRAN	211
A.4	SDP offers and answers for video sessions	212
A.4.1	Void.....	212
A.4.2	Void.....	212
A.4.2a	H.264/AVC	212
A.4.2b	High Granularity CVO example.....	214
A.4.2c	RTP Retransmission.....	214
A.4.2d	RTP Forward Error Correction (FEC).....	215
A.4.2e	SDP Examples with ROI.....	216
A.4.3	Void.....	222
A.4.4	Void.....	222
A.4.4a	H.264/AVC with "imageattr" attribute.....	222
A.4.4a.1	H.264/AVC with "imageattr" attribute – different image sizes in SDP offer and answer	224
A.4.4a.2	H.264/AVC with "imageattr" attribute – different payload type numbers in offer and answer	225
A.4.4b	H.264/AVC with "imageattr" attribute with multiple rtpmaps.....	226
A.4.5	H.264 with asymmetric video streams	228
A.4.6	H.264/AVC with "imageattr" attribute for non-CVO operation.....	229
A.4.7	H.264 (AVC) and H.265 (HEVC).....	231
A.4.7.1	MTSI client with 848x480 resolution 5 inch display.....	231
A.4.7.2	MTSI client with 1280x720 resolution 5 inch display	232
A.4.7.3	MTSI client with 848x480 resolution 10 inch display.....	233
A.4.7.4	MTSI client with 1280x720 resolution 10 inch display.....	234
A.4.8	H.264 (AVC) and H.265 (HEVC) with asymmetric video streams.....	235
A.5	SDP offers for text.....	236
A.5.1	T.140 with and without redundancy	236
A.6	SDP example with bandwidth information.....	237
A.6.1	General	237
A.6.2	SDP examples with bandwidth information declared with bandwidth modifiers.....	237
A.6.3	SDP examples giving additional bandwidth information using the a=bw-info attribute.....	238
A.7	SDP examples with "3gpp_sync_info" attribute	241
A.7.1	Synchronized streams.....	241
A.7.2	Nonsynchronized streams.....	241
A.8	SDP example with QoS negotiation.....	242
A.9	Void.....	246
A.9a	SDP offer/answer regarding the use of Reduced-Size RTCP.....	246
A.10	Examples of SDP offers and answers for inter-working with other IMS or non-IMS IP networks	247
A.10.1	General	247
A.10.2	Session initiated by MTSI client in terminal	247
A.10.2.1	SDP offers from an MTSI client in terminal.....	247
A.10.2.2	SDP offers modified by MTSI MGW when pre-emptively adding inter-working formats	248
A.10.2.3	SDP modified by MGW when adding inter-working formats only when the original SDP offer was rejected.....	249
A.11	Adding or removing a video component to/from an on-going video call session.....	251
A.12	SDP examples when using ECN	255
A.12.1	SDP examples when using ECN for speech.....	255
A.12.1.1	With RTP/AVP and zero RTCP bandwidth.....	255
A.12.1.2	With RTP/AVPF and non-zero RTCP bandwidth	256
A.12.1.3	With RTCP ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients	257
A.12.2	SDP examples when using ECN for video in RTP.....	257
A.12.2.1	Without RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports	257

A.12.2.2	With RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients	258
A.13	SDP examples for MTSI client in terminal using fixed access	260
A.13.1	General	260
A.13.2	SDP examples for PCM	260
A.13.3	SDP example for G.722.....	261
A.13.4	SDP example for EVS, AMR-WB, G.722, AMR, PCM and DTMF	261
A.14	SDP offers and answers for speech sessions with EVS	262
A.14.1	SDP offers initiated by MTSI client in terminal.....	262
A.14.1.1	Unknown access technology.....	262
A.14.1.2	EGPRS.....	263
A.14.1.3	NR/E-UTRAN/HSPA.....	263
A.14.1.4	Dual-mono	264
A.14.2	SDP offers initiated by media gateway	265
A.14.2.1	Network between MTSI using fixed access and MTSI modifying SDP offer to configure EVS AMR-WB IO mode.....	265
A.14.3	SDP answers from MTSI client in terminal	266
A.14.3.1	SDP answer from MTSI client in terminal when narrowband speech is negotiated	266
A.14.3.2	SDP answer from MTSI client in terminal when up to wideband speech is negotiated	266
A.14.3.3	SDP answer from MTSI client in terminal when only wideband speech is negotiated	267
A.14.3.4	SDP answer from MTSI client in terminal when up to super-wideband speech is negotiated	267
A.14.3.5	SDP answer from MTSI client in terminal when only super-wideband speech is negotiated	268
A.14.3.6	SDP answer from MTSI client in terminal using WLAN.....	268
A.14.3.7	SDP answer from MTSI client in terminal supporting dual-mono	268
A.14.3.8	SDP answer from MTSI client in terminal supporting dual-mono for send direction	269
A.14.3.9	SDP answer from MTSI client in terminal when SC-VBR is negotiated	269
A.14.4	SDP answers from MTSI client in terminal using fixed access.....	270
A.14.4.1	SDP answer from MTSI client in terminal using fixed access when narrowband speech is negotiated	270
A.14.4.2	SDP answer from MTSI client in terminal using fixed access when only wideband speech is negotiated.....	270
A.14.4.3	SDP answer from MTSI client in terminal using fixed access when only super-wideband speech is negotiated.....	270
Annex B (informative):	Examples of adaptation scenarios	272
B.1	Video bitrate adaptation	272
Annex C (informative):	Example adaptation mechanisms for speech.....	273
C.1	Example of feedback and adaptation for speech and video.....	273
C.1.1	Introduction	273
C.1.2	Signalling state considerations	274
C.1.3	Adaptation state machine implementations.....	276
C.1.3.1	General.....	276
C.1.3.2	Adaptation state machine with four states	278
C.1.3.3	Adaptation state machine with four states (simplified version without frame aggregation).....	281
C.1.3.4	Adaptation state machine with two states	283
C.1.3.5	Adaptation when using ECN	284
C.2	Example criteria for video bit rate feedback and adaptation.....	286
C.2.1	Introduction	286
C.2.2	Media sender side.....	287
C.2.3	Media receiver side	287
C.2.4	Video encoder bitrate adaptation, down-switch	287
C.2.5	Video encoder bitrate adaptation, receiver-driven up-switch.....	289
C.2.6	Video encoder bitrate adaptation, recovery phase.....	289
Annex D (informative):	Reference delay computation algorithm.....	291
Annex E (informative):	QoS profiles	293
E.1	General	293

E.2	Bi-directional speech (AMR12.2, IPv4, RTCP and MBR=GBR bearer).....	293
E.3	Void.....	294
E.4	Bi-directional real-time text (3 kbps, IPv4 or IPv6, RTCP and MBR=GBR bearer).....	295
E.5	Bi-directional speech (AMR-WB23.85, IPv4, RTCP and MBR=GBR bearer).....	297
E.6	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv4, RTCP and MBR=GBR bearer).....	297
E.7	Bi-directional speech (AMR12.2, IPv6, RTCP and MBR=GBR bearer).....	298
E.8	Bi-directional speech (AMR-WB23.85, IPv6, RTCP and MBR=GBR bearer).....	299
E.9	Void.....	300
E.10	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv6, RTCP and MBR=GBR bearer).....	300
E.11	Bi-directional speech (AMR, IPv4, RTCP and MBR>GBR bearer).....	301
E.12	Bi-directional speech (AMR-WB, IPv4, RTCP and MBR>GBR bearer).....	302
E.13	Void.....	303
E.14	Bi-directional video (H.264 AVC level 1.1, IPv4, RTCP and MBR>GBR bearer).....	303
E.15	Bi-directional speech (AMR, IPv6, RTCP and MBR>GBR bearer).....	304
E.16	Bi-directional speech (AMR-WB, IPv6, RTCP and MBR>GBR bearer).....	305
E.17	Void.....	306
E.18	Bi-directional video (H.264 AVC level 1.1, IPv6, RTCP and MBR>GBR bearer).....	306
E.19	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv4, RTCP and MBR=GBR bearer).....	307
E.20	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv6, RTCP and MBR=GBR bearer).....	308
E.21	Bi-directional video (H.264 AVC level 1.2, IPv4, RTCP and MBR>GBR bearer).....	310
E.22	Bi-directional video (H.264 AVC level 1.2, IPv6, RTCP and MBR>GBR bearer).....	313
E.23	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500 kbps, IPv6, RTCP and MBR=GBR bearer).....	314
E.24	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	315
E.25	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600 kbps, IPv6, RTCP and MBR=GBR bearer).....	316
E.26	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	317
E.27	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650 kbps, IPv6, RTCP and MBR=GBR bearer).....	318
E.28	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	319
E.29	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750 kbps, IPv6, RTCP and MBR=GBR bearer).....	320
E.30	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	321
E.31	Bi-directional speech (EVS 13.2, IPv4, RTCP and MBR=GBR bearer).....	322
E.32	Bi-directional speech (EVS 24.4, IPv4, RTCP and MBR=GBR bearer).....	323
E.33	Bi-directional speech (EVS 13.2, IPv6, RTCP and MBR=GBR bearer).....	324
E.34	Bi-directional speech (EVS 24.4, IPv6, RTCP and MBR=GBR bearer).....	325

Annex F (Normative):	Void	327
Annex G (Normative):	DTMF events	328
G.1	General	328
G.2	Encoding of DTMF events	328
G.3	Session setup	328
G.4	Data transport for DTMF events	330
Annex H (informative):	Network Preference Management Object Device Description Framework	332
Annex I (informative):	QoE Reporting Management Object Device Description Framework ...	333
Annex J (informative):	Media Adaptation Management Object Device Description Framework	334
Annex K (informative):	Computation of b=AS for AMR and AMR-WB	335
K.1	General	335
K.2	Procedure for computing the bandwidth	335
K.3	Computation of RTP payload size	335
K.4	Detailed computation	336
Annex L (Normative):	Facsimile transmission	344
L.1	General	344
L.2	FoIP support in MTSI clients	344
L.2.1	FoIP support in MTSI client in terminal	344
L.2.2	FoIP support in MTSI MGW	344
L.2.3	Recommended configuration	344
L.3	Session setup	345
L.3.1	Session setup for any MTSI client supporting facsimile transmission	345
L.3.2	Session setup when the recommended profile is supported	345
L.4	Data transport using UDP/IP	346
L.5	CS GERAN inter-working	346
L.6	PSTN inter-working	346
L.7	SDP examples	347
L.7.1	Facsimile-only session	347
Annex M (informative):	IANA registration information for SDP attributes	349
M.1	Introduction	349
M.2	3gpp_sync_info	349
M.3	3gpp_MaxRecvSDUSize	349
M.4	3gpp_mtsi_app_adapt	350
M.5	predefined_ROI	350
M.6	bw-info	351
M.7	ccc_list	352
Annex N (informative):	Computation of b=AS for Video Codec	353
N.1	General	353