

ETSI TS 145 005 V14.6.0 (2019-05)



Digital cellular telecommunications system (Phase 2+) (GSM); GSM/EDGE Radio transmission and reception (3GPP TS 45.005 version 14.6.0 Release 14)

Standard Preview
(standards.iteh.ai)
Full standard: <https://standards.iteh.ai/catalog/standards/sist/etsi/etsi-ts-145-005/v14-6-0-2019-05>
43d3-a772-18ab98d76093/etsi-ts-145-005/v14-6-0-2019-05



ReferenceRTS/TSGR-0645005ve60

KeywordsGSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|---|----|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 10 |
| 1 Scope | 11 |
| 1.1 References | 12 |
| 1.2 Abbreviations | 13 |
| 1.3 Definitions | 14 |
| 2 Frequency bands and channel arrangement..... | 14 |
| 3 Reference configuration | 17 |
| 4 Transmitter characteristics | 18 |
| 4.1 Output power..... | 18 |
| 4.1.1 Mobile Station | 18 |
| 4.1.2 Base station | 23 |
| 4.1.2.1 Additional requirements for PCS 1 900 and MXM 1900 Base stations..... | 25 |
| 4.1.2.2 Additional requirements for GSM 850 and MXM 850 Base stations..... | 25 |
| 4.1.2.3 Additional requirements for GSM 700 Base stations..... | 25 |
| 4.1.2.4 Additional requirements for ER-GSM 900 Base stations | 25 |
| 4.1.2.4.1 Uncoordinated deployment | 26 |
| 4.1.2.4.2 Coordinated deployment | 26 |
| 4.2 Output RF spectrum | 26 |
| 4.2.1 Spectrum due to the modulation and wide band noise..... | 26 |
| 4.2.1.1 General requirements for all types of Base stations and MS..... | 26 |
| 4.2.1.2 Additional requirements for multicarrier BTS | 27 |
| 4.2.1.3 Tables for spectrum requirements due to modulation and wideband noise..... | 28 |
| 4.2.1.4 Exceptions for spectrum due to modulation and wideband noise | 32 |
| 4.2.1.4.1 Mobile Stations and Base Transceiver Stations except multicarrier BTS | 32 |
| 4.2.1.4.2 Multicarrier BTS | 33 |
| 4.2.2 Spectrum due to switching transients..... | 33 |
| 4.2.2.1 General requirements | 33 |
| 4.2.2.2 Mobile Station:..... | 34 |
| b) Base transceiver station: | 34 |
| 4.3 Spurious emissions | 35 |
| 4.3.1 Principle of the specification | 35 |
| 4.3.2 Base Transceiver Station | 37 |
| 4.3.2.1 General requirements | 37 |
| 4.3.2.2 Additional requirements for co-existence with GSM systems on other frequency bands..... | 38 |
| 4.3.2.3 Additional requirements for co-existence with 3 G | 39 |
| 4.3.3 Mobile Station | 40 |
| 4.3.3.1 Mobile Station GSM 400, T-GSM 810, GSM 900, ER-GSM 900 and DCS 1 800 | 40 |
| 4.3.3.2 Mobile Station GSM 700, GSM 850 and PCS 1 900..... | 41 |
| 4.4 Radio frequency tolerance..... | 42 |
| 4.5 Output level dynamic operation | 42 |
| 4.5.1 Base Transceiver Station | 42 |
| 4.5.2 Mobile Station | 42 |
| 4.6 Modulation accuracy | 43 |
| 4.6.1 GMSK modulation..... | 43 |
| 4.6.2 QPSK, AQPSK, 8-PSK, 16-QAM and 32-QAM modulations | 43 |
| 4.6.2.1 RMS EVM | 44 |
| 4.6.2.1.1 MS requirements | 44 |
| 4.6.2.1.2 Requirements for BTS..... | 44 |
| 4.6.2.2 Origin Offset Suppression..... | 45 |
| 4.6.2.3 Peak EVM..... | 45 |
| 4.6.2.4 95:th percentile..... | 45 |

| | | |
|-----------|---|----|
| 4.6.3 | Phase and amplitude coherency when using blind physical layer transmissions | 46 |
| 4.6.3.1 | General | 46 |
| 4.6.3.2 | EC-GSM-IoT MS | 46 |
| 4.6.3.3 | BTS supporting EC-GSM-IoT | 46 |
| 4.7 | Intermodulation attenuation | 46 |
| 4.7.1 | Base transceiver station | 46 |
| 4.7.2 | Intra BTS intermodulation attenuation | 46 |
| 4.7.2.1 | GSM 400, GSM 900, ER-GSM 900, DCS 1800 | 47 |
| 4.7.2.1.1 | Requirements for BTS except multicarrier BTS | 47 |
| 4.7.2.1.2 | Requirements for multicarrier BTS | 47 |
| 4.7.2.2 | MXM 850 and MXM 1900 | 47 |
| 4.7.2.3 | GSM 700, GSM 850 and PCS 1900 | 48 |
| a) | Requirements for BTS except multicarrier BTS | 48 |
| b) | Requirements for multicarrier BTS | 48 |
| c) | Additional requirements for all BTS | 48 |
| 4.7.3 | Void | 48 |
| 4.7.4 | Mobile PBX (GSM 900 only) | 48 |
| 5 | Receiver characteristics | 48 |
| 5.1 | Blocking characteristics | 49 |
| 5.1.1 | Definitions of applicable frequency ranges | 49 |
| 5.1.2 | Requirements for MS | 51 |
| 5.1.3 | Requirements for BTS | 53 |
| 5.1.4 | Signal levels of blocking signal | 54 |
| 5.1.5 | Micro- and pico-BTS | 59 |
| 5.2 | AM suppression characteristics | 59 |
| 5.2.1 | Requirements for MS | 59 |
| 5.2.2 | Requirements for BTS | 60 |
| 5.3 | Intermodulation characteristics | 61 |
| 5.3.1 | Requirements for MS | 61 |
| 5.3.2 | Requirements for BTS | 61 |
| 5.4 | Spurious emissions | 62 |
| 6 | Transmitter/receiver performance | 62 |
| 6.1a | MS conditions | 62 |
| 6.1b | BTS conditions | 63 |
| 6.1 | Nominal Error Rates (NER) | 65 |
| 6.1.1 | GMSK modulation | 65 |
| 6.1.1.1 | General performance requirements | 65 |
| 6.1.1.2 | Requirements for MS | 65 |
| 6.1.1.3 | Requirements for BTS | 65 |
| 6.1.2 | QPSK/8-PSK modulation | 66 |
| 6.1.2.1 | Requirements for MS | 66 |
| 6.1.2.2 | Requirements for BTS | 67 |
| 6.1.3 | 16-QAM/32-QAM modulation | 67 |
| 6.1.3.1 | Requirements for MS | 67 |
| 6.1.3.2 | Requirements for BTS | 68 |
| 6.2 | Reference sensitivity level | 68 |
| 6.2.1 | Circuit-switched channels | 68 |
| 6.2.1a | Reference performance in VAMOS mode | 71 |
| 6.2.2 | Packet-switched channels | 72 |
| 6.2.3 | Flexible Layer One | 74 |
| 6.2.4 | Repeated associated control channel performance | 74 |
| 6.2.4a | Extended Coverage control channel and data channel performance for EC-GSM-IoT | 75 |
| 6.2.5 | Enhanced MS receiver performance | 75 |
| 6.2.6 | Additional performance conditions | 75 |
| 6.3 | Reference interference level | 76 |
| 6.3.1 | GMSK modulated speech channels and associated control channels | 76 |
| 6.3.2 | Co-channel reference interference performance | 76 |
| 6.3.2.1 | MS requirements | 76 |
| 6.3.2.2 | BTS requirements | 77 |
| 6.3.3 | Adjacent channel reference interference performance | 77 |

| | | |
|--|--|------------|
| 6.3.3.1 | Normal symbol rate used | 77 |
| 6.3.3.1.1 | MS requirements | 78 |
| 6.3.3.1.2 | BTS requirements | 79 |
| 6.3.3.2 | Higher symbol rate used..... | 79 |
| 6.3.3.2.1 | MS requirements | 79 |
| 6.3.3.2.2 | BTS requirements..... | 80 |
| 6.3.4 | Reference interference performance – signal levels | 80 |
| 6.3.5 | Additional reference interference performance requirements and conditions..... | 81 |
| 6.4 | Erroneous frame indication performance | 83 |
| 6.5 | Random access and paging performance at high input levels | 84 |
| 6.6 | Frequency hopping performance under interference conditions | 85 |
| 6.7 | Incremental Redundancy Performance for EGPRS and EGPRS2 MS | 85 |
| Annex A (informative): Spectrum characteristics (spectrum due to the modulation)..... | | 199 |
| Annex B (normative): Transmitted power level versus time | | 207 |
| Annex C (normative): Propagation conditions..... | | 213 |
| C.1 | Simple wideband propagation model | 213 |
| C.2 | Doppler spectrum types..... | 213 |
| C.3 | Propagation models | 214 |
| C.3.1 | Typical case for rural area (Rax): (6 tap setting)..... | 214 |
| C.3.2 | Typical case for hilly terrain (HTx): (12 tap setting)..... | 214 |
| C.3.3 | Typical case for urban area (Tux): (12 tap setting)..... | 215 |
| C.3.4 | Profile for equalization test (Eqx): (6 tap setting) | 215 |
| C.3.5 | Typical case for very small cells (Tix): (2 tap setting)..... | 215 |
| Annex D (normative): Environmental conditions | | 216 |
| D.1 | General | 216 |
| D.2 | Environmental requirements for the MSs..... | 216 |
| D.2.1 | Temperature (GSM 400, GSM 900, ER-GSM 900 and DCS 1 800) | 216 |
| D.2.1.1 | Environmental Conditions (PCS 1 900, GSM 850 and GSM 700)..... | 216 |
| D.2.2 | Voltage | 216 |
| D.2.3 | Vibration (GSM 400, GSM 900, ER-GSM 900 and DCS 1 800)..... | 217 |
| D.2.3.1 | Vibration (PCS 1 900, GSM 850 and GSM 700)..... | 217 |
| D.3 | Environmental requirements for the BSS equipment | 217 |
| D.3.1 | Environmental requirements for the BSS equipment | 218 |
| Annex E (normative): Repeater characteristics | | 219 |
| E.1 | Introduction | 219 |
| E.2 | Spurious emissions | 219 |
| E.3 | Intermodulation products | 220 |
| E.4 | Out of band gain | 220 |
| E.5 | Frequency error and modulation accuracy | 220 |
| E.5.1 | Frequency error | 220 |
| E.5.2 | Modulation accuracy at GMSK modulation..... | 220 |
| E.5.3 | Modulation accuracy at 8-PSK, 16-QAM, 32-QAM, QPSK and AQPSK modulation..... | 220 |
| Annex F (normative): Antenna Feeder Loss Compensator Characteristics (GSM 400, GSM 900 and DCS 1800)..... | | 222 |
| F.1 | Introduction | 222 |
| F.2 | Transmitting path | 222 |
| F.2.1 | Maximum output power | 222 |
| F.2.2 | Gain | 223 |

| | | |
|-------------------------------|---|------------|
| F.2.3 | Burst transmission characteristics | 223 |
| F.2.4 | Phase error | 223 |
| F.2.5 | Frequency error | 224 |
| F.2.6 | Group delay | 224 |
| F.2.7 | Spurious emissions | 224 |
| F.2.8 | VSWR | 225 |
| F.2.9 | Stability | 225 |
| F.3 | Receiving path | 225 |
| F.3.1 | Gain | 225 |
| F.3.2 | Noise figure | 225 |
| F.3.3 | Group delay | 225 |
| F.3.4 | Intermodulation performance | 225 |
| F.3.5 | VSWR | 225 |
| F.3.6 | Stability | 225 |
| F.4 | Guidelines (informative) | 225 |
| Annex G (normative): | Calculation of Error Vector Magnitude | 227 |
| Annex H (normative): | Requirements on Location Measurement Unit | 229 |
| H.1 | TOA LMU Requirements | 229 |
| H.1.1 | Void | 229 |
| H.1.2 | LMU characteristics | 229 |
| H.1.2.1 | Blocking characteristics | 229 |
| H.1.2.2 | AM suppression characteristics | 229 |
| H.1.2.3 | Intermodulation characteristics | 230 |
| H.1.2.4 | Spurious emissions | 230 |
| H.1.3 | Time-of-Arrival Measurement Performance | 230 |
| H.1.3.1 | Sensitivity Performance | 230 |
| H.1.3.2 | Interference Performance | 231 |
| H.1.3.3 | Multipath Performance | 232 |
| H.1.4 | Radio Interface Timing Measurement Performance | 232 |
| H.2 | E-OTD LMU Requirements | 232 |
| H.2.1 | LMU Characteristics | 232 |
| H.2.1.1 | Blocking characteristics | 233 |
| H.2.1.2 | AM suppression characteristics | 233 |
| H.2.1.3 | Intermodulation characteristics | 233 |
| H.2.2 | Sensitivity and Interference Performance | 233 |
| H.2.2.1 | Sensitivity Performance | 233 |
| H.2.2.2 | Interference Performance | 234 |
| H.2.2.3 | Multipath Performance | 234 |
| Annex I (normative): | E-OTD Mobile Station Requirements | 236 |
| I.1 | Introduction | 236 |
| I.2 | Sensitivity and Interference Performance | 236 |
| I.2.1 | Sensitivity Performance | 236 |
| I.2.2 | Interference Performance | 237 |
| I.2.3 | Multipath Performance | 237 |
| Annex J (informative): | Guidance on the Usage of Dynamic ARFCN Mapping | 238 |
| J.1 | Introduction | 238 |
| J.2 | Dynamic allocation of GSM 400, GSM 800, GSM 900, ER-GSM 900, DCS 1800 and PCS 1900 ARFCNs | 238 |
| J.3 | Controlling changes in dynamic mapping | 238 |
| Annex K (normative): | Reference TFCs for FLO | 240 |
| Annex L (normative): | Reference Test Scenarios for DARP | 242 |

| | | |
|-----------------------------|--|------------|
| Annex M (normative): | Minimum Performance Requirements for Assisted Global Positioning System (A-GPS) | 244 |
| M.1 | General | 244 |
| M.1.1 | Abbreviations | 244 |
| M.1.2 | Measurement parameters | 244 |
| M.1.2.1 | MS based A-GPS measurement parameters | 244 |
| M.1.2.2 | MS assisted A-GPS measurement parameters | 244 |
| M.1.3 | Response time | 244 |
| M.1.4 | Time assistance | 244 |
| M.1.4.1 | Use of fine time assistance | 245 |
| M.1.4.2 | 2D position error | 245 |
| M.2 | A-GPS minimum performance requirements | 245 |
| M.2.1 | Sensitivity | 245 |
| M.2.1.1 | Coarse time assistance | 245 |
| M.2.1.1.1 | Minimum Requirements (Coarse time assistance) | 246 |
| M.2.1.2 | Fine time assistance | 246 |
| M.2.1.2.1 | Minimum Requirements (Fine time assistance) | 246 |
| M.2.2 | Nominal Accuracy | 246 |
| M.2.2.1 | Minimum requirements (nominal accuracy) | 247 |
| M.2.3 | Dynamic Range | 247 |
| M.2.3.1 | Minimum requirements (dynamic range) | 247 |
| M.2.4 | Multi-Path scenario | 247 |
| M.2.4.1 | Minimum Requirements (multi-path scenario) | 248 |
| M.2.5 | Moving scenario and periodic location | 248 |
| M.2.5.1 | Minimum Requirements (moving scenario and periodic location) | 249 |
| M.3 | Test conditions | 249 |
| M.3.1 | General | 249 |
| M.3.1.1 | Parameter values | 249 |
| M.3.1.2 | Time assistance | 250 |
| M.3.1.3 | GPS Reference Time | 250 |
| M.3.1.4 | Reference and MS locations | 250 |
| M.3.1.5 | Satellite constellation and assistance data | 250 |
| M.3.1.6 | Atmospheric delays | 250 |
| M.3.1.7 | GSM Frequency and frequency error | 251 |
| M.3.1.8 | Information elements | 251 |
| M.3.1.9 | GPS signals | 251 |
| M.3.1.10 | RESET MS POSITIONING STORED INFORMATION Message | 251 |
| M.4 | Propagation Conditions | 251 |
| M.4.1 | Static propagation conditions | 251 |
| M.4.2 | Multi-path Case G1 | 251 |
| M.5 | Measurement sequence chart | 252 |
| M.5.1 | General | 252 |
| M.5.2 | MS Based A-GPS Measurement Sequence Chart | 252 |
| M.5.3 | MS Assisted A-GPS Measurement Sequence Chart | 253 |
| M.6 | Assistance data required for testing | 254 |
| M.6.1 | Introduction | 254 |
| M.6.2 | Information elements required for MS-based | 254 |
| M.6.3 | Information elements available for MS-assisted | 255 |
| M.7 | Converting MS-assisted measurement reports into position estimates | 256 |
| M.7.1 | Introduction | 256 |
| M.7.2 | MS measurement reports | 256 |
| M.7.3 | Weighted Least Squares (WLS) position solution | 257 |
| Annex N (normative): | Reference Test Scenarios for DARP Phase II (MSRD) | 259 |
| N.1 | Interferer configurations | 259 |
| N.2 | Correlation and antenna gain imbalance | 260 |

| | | |
|-----------------------------|--|------------|
| N.3 | Testing MSRD terminal conformance to legacy requirements | 261 |
| Annex O (normative): | Minimum Performance Requirements for Assisted Galileo and Additional Navigation Satellite Systems (A-GANSS) | 263 |
| O.1 | General | 263 |
| O.1.1 | Abbreviations | 263 |
| O.1.2 | Measurement parameters..... | 263 |
| O.1.2.1 | MS based A-GANSS measurement parameters..... | 263 |
| O.1.2.2 | MS assisted A-GANSS measurement parameters | 263 |
| O.1.3 | Response time | 263 |
| O.1.4 | Time assistance | 264 |
| O.1.4.1 | Use of fine time assistance..... | 264 |
| O.1.5 | Error definitions | 264 |
| O.1.6 | Mobile stations supporting multiple constellations | 264 |
| O.1.7 | Mobile stations supporting multiple signals..... | 264 |
| O.2 | A-GANSS minimum performance requirements | 265 |
| O.2.1 | Sensitivity..... | 265 |
| O.2.1.1 | Coarse time assistance | 265 |
| O.2.1.1.1 | Minimum Requirements (Coarse time assistance)..... | 266 |
| O.2.1.2 | Fine time assistance | 266 |
| O.2.1.2.1 | Minimum Requirements (Fine time assistance)..... | 266 |
| O.2.2 | Nominal Accuracy..... | 267 |
| O.2.2.1 | Minimum requirements (nominal accuracy)..... | 267 |
| O.2.3 | Dynamic Range | 268 |
| O.2.3.1 | Minimum requirements (dynamic range) | 268 |
| O.2.4 | Multi-Path scenario | 268 |
| O.2.4.1 | Minimum Requirements (multi-path scenario)..... | 269 |
| O.2.5 | Moving scenario and periodic location | 269 |
| O.2.5.1 | Minimum Requirements (moving scenario and periodic location)..... | 270 |
| O.3 | Test conditions | 271 |
| O.3.1 | General | 271 |
| O.3.1.1 | Parameter values | 271 |
| O.3.1.2 | Time assistance | 271 |
| O.3.1.3 | GANSS Reference Time..... | 271 |
| O.3.1.4 | Reference and MS locations | 272 |
| O.3.1.5 | Satellite constellation and assistance data..... | 272 |
| O.3.1.6 | Atmospheric delays..... | 272 |
| O.3.1.7 | Sensors..... | 272 |
| O.3.1.8 | Information elements | 272 |
| O.3.1.9 | GNSS signals | 272 |
| O.3.1.10 | RESET MS POSITIONING STORED INFORMATION Message | 272 |
| O.3.2 | GNSS System Time Offsets | 273 |
| O.4 | Propagation Conditions | 273 |
| O.4.1 | Static propagation conditions | 273 |
| O.4.2 | Multi-path case | 273 |
| O.5 | Measurement sequence chart..... | 274 |
| O.5.1 | General | 274 |
| O.5.2 | TTFB Measurement Sequence Chart..... | 274 |
| O.6 | Assistance data required for testing..... | 276 |
| O.6.1 | GPS assistance data | 276 |
| O.6.2 | GANSS assistance data | 276 |
| O.7 | Converting MS-assisted measurement reports into position estimates | 279 |
| O.7.1 | Introduction | 279 |
| O.7.2 | MS measurement reports..... | 279 |
| O.7.3 | Weighted Least Squares (WLS) position solution..... | 280 |
| Annex P (normative): | Minimum receiver performance requirements for MSR BS | 283 |

| | | |
|-------------------------------|---|------------|
| P.1 | Reference Sensitivity and interference performance..... | 283 |
| P.2 | Other receiver characteristics | 283 |
| P.2.1 | Blocking characteristics | 283 |
| P.2.2 | Intermodulation characteristics | 283 |
| P.2.3 | AM suppression..... | 284 |
| Annex Q (normative): | Reference Test Scenarios for Voice services over Adaptive Multi-user channels on One Slot (VAMOS)..... | 285 |
| Q.1 | Interferer configurations in downlink..... | 285 |
| Q.2 | Interferer configurations in uplink | 286 |
| Q.3 | Sensitivity test configuration in downlink..... | 287 |
| Q.4 | Sensitivity test configuration in uplink..... | 287 |
| Q.5 | Time and frequency offset in uplink | 287 |
| Q.6 | VAMOS DTX scenario in downlink..... | 287 |
| Q.7 | Correlation and antenna gain imbalance for VAMOS III MS..... | 288 |
| Annex R (normative): | Reference Test Scenarios for Overlaid CDMA | 290 |
| R.1 | Frequency offset in uplink..... | 290 |
| Annex S (normative): | Normalized coherency error | 291 |
| Annex T (normative): | Calculation of the equivalent combined power | 293 |
| Annex U (informative): | Change history | 294 |
| History | | 303 |

iTeh STANDARD PREVIEW
 (standards.iteh.ai)
 Full standard:
<https://standards.iteh.ai/catalog/standards/sist/a772e3e-07b9-43d3-a772-18ab98d76093/etsi-ts-145-005-v14-6-0-2019-05>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

x the first digit:

- 1 presented to TSG for information;
- 2 presented to TSG for approval;
- 3 or greater indicates TSG approved document under change control.

Y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.

z the third digit is incremented when editorial only changes have been incorporated in the document.

PREVIEW
iTech STANDARD
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/43d3-a772-18ab98d76093/etsi-ts-145-005-v14.6.0-2019-05>

1 Scope

The present document defines the requirements for the transceiver of the pan-European digital cellular telecommunications systems GSM.

Requirements are defined for two categories of parameters:

- those that are required to provide compatibility between the radio channels, connected either to separate or common antennas, that are used in the system. This category also includes parameters providing compatibility with existing systems in the same or adjacent frequency bands;
- those that define the transmission quality of the system.

The present document defines RF characteristics for the Mobile Station (MS) and Base Station System (BSS). The BSS will contain Base Transceiver Stations (BTS), which can be normal BTS, micro-BTS or pico-BTS. The precise measurement methods are specified in 3GPP TS 51.010 and 3GPP TS 51.021.

Unless otherwise stated, the requirements defined in this EN apply to the full range of environmental conditions specified for the equipment (see annex D).

In the present document some relaxations are introduced for GSM 400 MSs, GSM 900 MSs, GSM 700 MSs and GSM 850 MSs which pertain to power class 4, 5 or 6 (see subclause 4.1.1). In the present document these Mobile Stations are referred to as "small MS".

In the present document some relaxations to receiver requirements are introduced for a MS indicating support for Downlink Multi Carrier (DLMC), see 3GPP TS 24.008, when in DLMC configuration. DLMC configurations are specified for only GSM 850, GSM 900, DCS 1800 and PCS 1900.

MSs may operate on more than one of the frequency bands specified in clause 2. These MSs are referred to as "Multi band MSs" in this EN. Multi band MSs shall meet all requirements for each of the bands supported. The relaxation on GSM 400 MSs, GSM 900 MSs, GSM 700 MSs and GSM 850 MSs for a "small MS" are also valid for a multi band MS if it complies with the definition of a small MS.

The RF characteristics of repeaters are defined in annex E of this EN. Annexes D and E are the only clauses of this EN applicable to repeaters. Annex E does not apply to the MS or BSS. The precise measurement methods for repeaters are specified in 3GPP TS 51.026 [35].

The present document also includes specification information for mixed mode operation at 850 MHz and 1900 MHz (MXM 850 and MXM 1900). 850 MHz and 1900 MHz mixed-mode is defined as a network that deploys both 30 kHz RF carriers and 200 kHz RF carriers in geographic regions where the Federal Communications Commission (FCC) regulations are applied or adopted.

The requirements for a MS in a mixed-mode system, MXM 850 and MXM 1900, correspond to the requirements for GSM 850 MS and PCS 1900 MS respectively.

Annex M defines the minimum performance requirements for A-GPS for MSs that support A-GPS. Annex M does not apply to the BSS.

The present document also includes specific requirements for multicarrier BTS, wherever explicitly stated in the text, that apply for all classes of multicarrier BTS (Wide Area, Medium Range and Local Area) if nothing else is stated. All other requirements designated for BTS and normal BTS apply if not otherwise stated. The multicarrier BTS classes have relaxed requirements in the areas of Tx spurious emissions, intermodulation attenuation and, when multicarrier receiver is included, Rx blocking. Usage of multicarrier BTSs in some geographical regions might be subject to regulatory restrictions to protect other radio systems operating in bands of adjacent frequency assignments, in particular for all safety related applications like railway applications. In areas where such systems coexist with multicarrier BTSs, the received interference power originating from multicarrier BTSs might have to be limited.

The document also includes entry points in some tables for the multicarrier BTS requirements to which TS 37.104 [33] for Multi-Standard Radio Base Stations (MSR BS) is referring to as specific GSM/EDGE single-RAT requirements not covered by the general requirements. These entry points are marked with ^{M)} and, as described in a note in each applicable table, identify the relevant column(s) that are applicable as MSR BS requirements. In general the requirements for multicarrier BTS equipped with multicarrier receiver also apply to Multi-Standard Radio Base Stations. The GSM requirements for Multi-Standard Radio Base Stations are defined for GSM 850, GSM 900, DCS 1800 and PCS 1900 only. Requirements for other frequency bands and MXM base stations are excluded. Annex P defines the minimum performance

for the receiver in MSR BS.

For equipment not declared as MSR BS the ^{M)} indications can be ignored.

The present document defines requirements for the usage of the ER-GSM band. The national implementation might be subject to regulatory coordination agreements to avoid system impacts (RF scenarios for ER-GSM introduction are given in 3GPP TR 45.050).

The present document defines requirements for supporting a low-complexity, low data throughput service in environments experiencing high propagation attenuation as indoors in basements etc. This service, based on EGPRS, with extended coverage is called EC-GSM-IoT. For EC-GSM-IoT, in case no specific requirement is explicitly stated, the requirements for EGPRS apply.

1.1 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [1A] 3GPP TS 25.144: "User Equipment (UE) and Mobile Station (MS) Over the Air Performance Requirements".
- [1B] 3GPP TS 34.114: "User Equipment (UE) / Mobile Station (MS) Over The Air (OTA) antenna performance; Conformance testing".
- [2] 3GPP TR 43.030: "Radio network planning aspects".
- [3] 3GPP TS 43.052: "GSM Cordless Telephony System (CTS); Lower layers of the CTS radio interface; Stage 2".
- [4] 3GPP TS 43.059: "Functional Stage 2 description of Location Services in GERAN".
- [5] 3GPP TS 43.064: "General Packet Radio Service (GPRS); GPRS Radio Interface Stage 2".
- [6] 3GPP TS 44.014: "Individual equipment type requirements and interworking; Special conformance testing functions".
- [7] 3GPP TS 44.018: "Mobile radio interface layer 3 specification; Radio Resource Control Protocol".
- [7A] 3GPP TS 44.031: "Mobile Station (MS) – Serving Mobile Location Centre (SMLC) Radio Resource LCS Protocol (RRLP)".
- [8] 3GPP TS 44.071: "Mobile radio interface layer 3 Location Services (LCS) specification".
- [9] 3GPP TS 45.001: "Physical layer on the radio path General description".
- [10] 3GPP TS 45.002: "Multiplexing and multiple access on the radio path".
- [11] 3GPP TS 45.003: "Channel coding".
- [12] 3GPP TS 45.004: "Modulation".
- [13] 3GPP TS 45.008: "Radio subsystem link control".
- [14] 3GPP TS 45.010: "Radio subsystem synchronization".
- [15] 3GPP TS 45.050: "Background for Radio Frequency (RF) requirements".