

Designation: C 10 - 07

# Standard Specification for Natural Cement<sup>1</sup>

This standard is issued under the fixed designation C 10; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon  $(\varepsilon)$  indicates an editorial change since the last revision or reapproval.

# 1. Scope\*

1.1 This specification covers natural cement.

Note 1—Examples of typical past uses of natural cement include unit masonry mortar, cement plaster, grout, whitewash, and concrete.

- 1.2 For properties where values are given in both SI and non-SI units, the values in SI units are to be regarded as the standard. Values in SI units shall be obtained by measurement in SI units or by appropriate conversion, using the Rules for Conversion and Rounding given in IEEE/ASTM SI 10, of measurements made in other units.
- 1.3 The text of this standard references notes and footnotes which provide explanatory material. These notes and footnotes (excluding those in tables and figures) shall not be considered as requirements of the standard.

#### 2. Referenced Documents

- 2.1 ASTM Standards:<sup>2</sup>
- C 109/C 109M Test Method for Compressive Strength of Hydraulic Cement Mortars (Using 2-in. or [50-mm] Cube Specimens)
- C 114 Test Methods for Chemical Analysis of Hydraulic Cement
- C 150 Specification for Portland Cement
- C 151 Test Method for Autoclave Expansion of Hydraulic Cement
- C 183 Practice for Sampling and the Amount of Testing of Hydraulic Cement
- C 185 Test Method for Air Content of Hydraulic Cement
- C 187 Test Method for Normal Consistency of Hydraulic Cement
- C 188 Test Method for Density of Hydraulic Cement
- <sup>1</sup> This test method is under the jurisdiction of ASTM Committee C01 on Cement and is the direct responsibility of Subcommittee C01.10 on Hydraulic Cements for General Concrete Construction.
- Current edition approved Dec. 1, 2007. Published December 2007. Originally approved in 1904. Last previous edition approved in 2006 as C 10 06.
- <sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

- C 191 Test Methods for Time of Setting of Hydraulic Cement by Vicat Needle
- C 204 Test Methods for Fineness of Hydraulic Cement by Air-Permeability Apparatus
- C 219 Terminology Relating to Hydraulic Cement
- C 305 Practice for Mechanical Mixing of Hydraulic Cement Pastes and Mortars of Plastic Consistency
- C 465 Specification for Processing Additions for Use in the Manufacture of Hydraulic Cements
- C 778 Specification for Standard Sand
- C 786 Test Method for Fineness of Hydraulic Cement and Raw Materials by the 300-μm (No. 50), 150-μm (No. 100), and 75-μm (No. 200) Sieves by Wet Methods
- IEEE/ASTM SI 10 Standard for Use of the International System of Units (SI): The Modern Metric System

## 3. Terminology

3.1 For definitions of terms related to this specification, see Terminology C 219.

#### 4. Ordering Information

- 4.1 Orders for material under this specification shall include the following:
  - 4.1.1 This specification number and date, and
  - 4.1.2 Optional physical requirements as given in 7.2.

#### 5. Additions

- 5.1 The cement covered by this specification shall contain no addition except as follows:
  - 5.1.1 Water, or calcium sulfate, or both.
- 5.1.2 Processing additions used in the manufacture of the cement shall have been shown to meet the requirements of Specification C 465 in the amounts used or greater.

## 6. Chemical Requirements

6.1 Natural cements shall conform to the standard chemical requirements in Table 1.

#### 7. Physical Requirements

7.1 Natural cements shall conform to the respective standard physical requirements prescribed in Table 1.