

ETSI TS 151 021 V14.7.0 (2019-05)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Base Station System (BSS) equipment specification;
Radio aspects
(3GPP TS 51.021 version 14.7.0 Release 14)**

*Full and complete review
https://standards.iteh.ai/catalog/standards/sist/15b-993-408a-8bac-8a59c66a6662/etsi-ts-151-021-v14-7-0-2019-05*



ReferenceRTS/TSGR-0651021ve70

KeywordsGSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|---|----|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 9 |
| 1 Scope | 10 |
| 2 References | 10 |
| 3 Definitions, abbreviations, frequency bands and channels..... | 12 |
| 3.1 Definitions | 12 |
| 3.2 Abbreviations | 14 |
| 3.3 Frequency bands and channels | 15 |
| 3.3.1 Frequency bands | 15 |
| 3.3.2 Channels and channel numbering | 15 |
| 4 General test conditions and declarations | 16 |
| 4.1 Output power and determination of power class | 16 |
| 4.2 Specified frequency range | 17 |
| 4.3 Frequency hopping | 17 |
| 4.4 RF power control..... | 18 |
| 4.5 Downlink discontinuous transmission (DTX) | 18 |
| 4.6 Test environments | 18 |
| 4.6.1 Normal test environment | 18 |
| 4.6.2 Extreme test environment | 19 |
| 4.6.2.1 Extreme temperature | 19 |
| 4.6.3 Vibration..... | 19 |
| 4.6.4 Power supply | 20 |
| 4.7 Acceptable uncertainty of measurement equipment | 20 |
| 4.8 Interpretation of measurement results | 24 |
| 4.9 Selection of configurations for testing..... | 24 |
| 4.10 BTS Configurations..... | 25 |
| 4.10.1 Receiver diversity | 25 |
| 4.10.2 Duplexers..... | 25 |
| 4.10.3 Power supply options..... | 26 |
| 4.10.4 Ancillary RF amplifiers | 26 |
| 4.10.5 BSS using antenna arrays | 26 |
| 4.10.6 BTS supporting 8-PSK modulation | 27 |
| 4.10.7 BTS supporting additional modulations in EGPRS2 | 28 |
| 4.10.8 Supported Symbol Rate..... | 28 |
| 4.10.9 Support of RTTI and/or FANR | 28 |
| 4.10.10 Multicarrier BTS..... | 28 |
| 4.10.11 Support of EC-GSM-IoT | 29 |
| 4.10.12 Support of Multilateration | 30 |
| 5 Format and interpretation of tests..... | 30 |
| 6 Transmitter | 31 |
| 6.1 Static Layer 1 functions..... | 31 |
| 6.1.1 Test purpose..... | 31 |
| 6.1.2 Test case | 31 |
| 6.1.3 Void | 32 |
| 6.1.4 Conformance requirement | 32 |
| 6.1.5 Requirement reference..... | 32 |
| 6.2 Modulation accuracy | 32 |
| 6.2.1 Test purpose..... | 32 |
| 6.2.2 Test case | 32 |
| 6.2.3 Void | 33 |

| | | |
|-----------|--|----|
| 6.2.4 | Conformance requirement | 33 |
| 6.2.5 | Requirement reference | 35 |
| 6.3 | Mean transmitted RF carrier power and equivalent combined power | 35 |
| 6.3.1 | Test purpose | 35 |
| 6.3.2 | Test case | 35 |
| 6.3.3 | Void | 36 |
| 6.3.4 | Conformance requirement | 36 |
| 6.3.5 | Requirement reference | 38 |
| 6.4 | Transmitted RF carrier power versus time | 38 |
| 6.4.1 | Test purpose | 38 |
| 6.4.2 | Test case | 38 |
| 6.4.3 | Void | 39 |
| 6.4.4 | Conformance requirement | 39 |
| 6.4.5 | Requirement reference | 43 |
| 6.5 | Adjacent channel power | 43 |
| 6.5.1 | Spectrum due to modulation and wideband noise | 43 |
| 6.5.1.1 | Test purpose | 43 |
| 6.5.1.2 | Test case | 43 |
| 6.5.1.3 | Void | 44 |
| 6.5.1.4 | Conformance requirement | 44 |
| 6.5.1.4.1 | Normal BTS Minimum requirement | 44 |
| 6.5.1.4.2 | Multicarrier BTS Minimum requirement | 45 |
| 6.5.1.4.3 | Micro and Pico-BTS Minimum requirement | 45 |
| 6.5.1.5 | Requirement reference | 47 |
| 6.5.2 | Switching transients spectrum | 47 |
| 6.5.2.1 | Test purpose | 47 |
| 6.5.2.2 | Test case | 47 |
| 6.5.2.3 | Void | 48 |
| 6.5.2.4 | Conformance requirement | 48 |
| 6.5.2.5 | Requirement reference | 49 |
| 6.6 | Spurious emissions from the transmitter antenna connector | 49 |
| 6.6.1 | Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band | 49 |
| 6.6.1.1 | Test Purpose | 49 |
| 6.6.1.2 | Test Case | 49 |
| 6.6.1.3 | Void | 50 |
| 6.6.1.4 | Conformance requirement | 50 |
| 6.6.1.5 | Requirement Reference | 50 |
| 6.6.2 | Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band | 50 |
| 6.6.2.1 | Applicability (Phase 2) | 50 |
| 6.6.2.1.1 | Test Purpose | 50 |
| 6.6.2.1.2 | Test Case | 50 |
| 6.6.2.1.3 | Void | 51 |
| 6.6.2.1.4 | Conformance requirement | 51 |
| 6.6.2.1.5 | Requirement Reference | 52 |
| 6.6.2.2 | Applicability (Phase 2+) | 52 |
| 6.6.2.2.1 | Test Purpose | 52 |
| 6.6.2.2.2 | Test Case | 52 |
| 6.6.2.2.3 | Void | 53 |
| 6.6.2.2.4 | Conformance requirement | 53 |
| 6.6.2.2.5 | Requirement Reference | 54 |
| 6.6.2.3 | Applicability (Release 1999 and later releases GSM 400, GSM 900 and DCS 1800) | 54 |
| 6.6.2.3.1 | Test Purpose | 54 |
| 6.6.2.3.2 | Test Case | 54 |
| 6.6.2.3.3 | Void | 55 |
| 6.6.2.3.4 | Conformance requirement | 55 |
| 6.6.2.3.5 | Requirement Reference | 55 |
| 6.6.2.4 | Applicability (Release 4 and later releases GSM 700, GSM 850 and PCS 1900) | 55 |
| 6.6.2.4.1 | Test Purpose | 55 |
| 6.6.2.4.2 | Test Case | 55 |
| 6.6.2.4.3 | Void | 56 |
| 6.6.2.4.4 | Conformance requirement | 56 |

| | | |
|------------|---|----|
| 6.6.2.4.5 | Requirement Reference | 56 |
| 6.6.2.5 | Applicability (Release 7 and later releases GSM 400, T-GSM 810, GSM 900 and DCS 1800)..... | 56 |
| 6.6.2.5.1 | Test Purpose | 56 |
| 6.6.2.5.2 | Test Case | 57 |
| 6.6.2.5.3 | Void | 58 |
| 6.6.2.5.4 | Conformance requirement | 58 |
| 6.6.2.5.5 | Requirement Reference | 59 |
| 6.6.2.5a | Applicability (Release 7 and later releases GSM 700, GSM 850 and PCS 1900) | 59 |
| 6.6.2.5a.1 | Test Purpose | 59 |
| 6.6.2.5a.2 | Test Case | 59 |
| 6.6.2.5a.3 | Void | 59 |
| 6.6.2.5a.4 | Conformance requirement | 59 |
| 6.6.2.5a.5 | Requirement Reference | 60 |
| 6.6.2.6 | Applicability (Release 8 and later releases GSM 400, T-GSM 810, GSM 900 and DCS 1800)..... | 60 |
| 6.6.2.6.1 | Test Purpose | 60 |
| 6.6.2.6.2 | Test Case | 60 |
| 6.6.2.6.3 | Void | 61 |
| 6.6.2.6.4 | Conformance requirement | 61 |
| 6.6.2.6.5 | Requirement Reference | 62 |
| 6.6.2.7 | Applicability (Release 8 and later releases GSM 700, GSM 850 and PCS 1900) | 62 |
| 6.6.2.7.1 | Test Purpose | 63 |
| 6.6.2.7.2 | Test Case | 63 |
| 6.6.2.7.3 | Void | 64 |
| 6.6.2.7.4 | Conformance requirement | 64 |
| 6.6.2.7.5 | Requirement Reference | 65 |
| 6.6.2.8 | Applicability (Release 8 and later releases GSM 400, GSM 900 and DCS 1800)..... | 65 |
| 6.6.2.8.1 | Test Purpose | 65 |
| 6.6.2.8.2 | Test Case | 66 |
| 6.6.2.8.3 | Void | 67 |
| 6.6.2.8.4 | Complete conformance | 67 |
| 6.6.2.8.5 | Requirement Reference | 67 |
| 6.6.2.9 | Applicability (Release 12 and later releases GSM 400, T-GSM 810, GSM 900, ER-GSM 900 and DCS 1800)..... | 67 |
| 6.6.2.9.1 | Test Purpose | 67 |
| 6.6.2.9.2 | Test Case | 67 |
| 6.6.2.9.3 | Void | 69 |
| 6.6.2.9.4 | Conformance requirement | 69 |
| 6.6.2.9.5 | Requirement Reference | 69 |
| 6.6.2.10 | Applicability (Release 12 and later releases GSM 400, T-GSM 810, GSM 900 and DCS 1800)..... | 69 |
| 6.6.2.10.1 | Test Purpose | 70 |
| 6.6.2.10.2 | Test Case | 70 |
| 6.6.2.10.3 | Void | 71 |
| 6.6.2.10.4 | Conformance requirement | 71 |
| 6.6.2.10.5 | Requirement Reference | 72 |
| 6.6.2.11 | Applicability (Release 12 and later releases GSM 400, GSM 900, ER-GSM 900 and DCS 1800)..... | 72 |
| 6.6.2.11.1 | Test Purpose | 72 |
| 6.6.2.11.2 | Test Case | 73 |
| 6.6.2.11.3 | Void | 74 |
| 6.6.2.11.4 | Conformance requirement | 74 |
| 6.6.2.11.5 | Requirement Reference | 74 |
| 6.7 | Intermodulation attenuation (GSM 400, GSM 900, ER-GSM 900 and DCS 1800)..... | 74 |
| 6.7.1 | Test purpose..... | 74 |
| 6.7.2 | Test case | 74 |
| 6.7.3 | Void | 76 |
| 6.7.4 | Conformance requirement | 76 |
| 6.7.5 | Requirement reference | 77 |
| 6.8 | Intra Base Station System intermodulation attenuation..... | 78 |
| 6.8.1 | Test purpose..... | 78 |
| 6.8.2 | Test case | 78 |
| 6.8.3 | Void | 79 |
| 6.8.4 | Conformance requirement | 79 |
| 6.8.5 | Requirement reference | 79 |

| | | |
|---------|---|-----|
| 6.9 | Intra Base Station System intermodulation attenuation, MXM 850 and MXM 1900 | 80 |
| 6.9.1 | Test purpose..... | 80 |
| 6.9.2 | Test cases | 80 |
| 6.9.2.1 | 200 kHz carriers-only..... | 80 |
| 6.9.2.2 | 200 kHz and ANSI-136 30 kHz carriers | 80 |
| 6.9.3 | Void | 80 |
| 6.9.4 | Conformance requirement | 80 |
| 6.9.5 | Requirement reference..... | 81 |
| 6.10 | Intra Base Station System intermodulation attenuation, PCS 1900, GSM 850 and GSM 700..... | 81 |
| 6.10.1 | Test purpose..... | 81 |
| 6.10.2 | Test case | 81 |
| 6.10.3 | Void | 82 |
| 6.10.4 | Conformance requirement | 82 |
| 6.10.5 | Requirement reference..... | 82 |
| 6.11 | Intermodulation attenuation (GSM 700, GSM 850, MXM 850, PCS 1900 and MXM 1900) | 82 |
| 6.11.1 | Test purpose..... | 82 |
| 6.11.2 | Test case | 83 |
| 6.11.3 | Void | 84 |
| 6.11.4 | Conformance requirement | 84 |
| 6.11.5 | Requirement reference..... | 85 |
| 6.12 | Wideband noise and intra BSS intermodulation attenuation in multicarrier operation | 86 |
| 6.12.1 | Test purpose..... | 86 |
| 6.12.2 | Test case | 86 |
| 6.12.3 | Void | 88 |
| 6.12.4 | Conformance requirement | 88 |
| 6.12.5 | Requirement reference..... | 90 |
| 7 | Receivers | 90 |
| 7.1 | Static Layer 1 receiver functions (nominal error ratios)..... | 90 |
| 7.1.1 | Test Purpose..... | 90 |
| 7.1.2 | Test Case..... | 91 |
| 7.1.3 | Void | 94 |
| 7.1.4 | Conformance requirement | 94 |
| 7.1.5 | Requirement Reference..... | 95 |
| 7.2 | Erroneous Frame Indication Performance..... | 95 |
| 7.2.1 | Test Purpose..... | 95 |
| 7.2.2 | Test Case..... | 95 |
| 7.2.3 | Void | 96 |
| 7.2.4 | Conformance requirement | 96 |
| 7.2.5 | Requirement reference | 96 |
| 7.3 | Static Reference Sensitivity Level..... | 97 |
| 7.3.1 | Test Purpose..... | 97 |
| 7.3.2 | Test Case..... | 97 |
| 7.3.3 | Void | 105 |
| 7.3.4 | Conformance requirement | 105 |
| 7.3.5 | Requirements Reference | 110 |
| 7.4 | Multipath Reference Sensitivity Level..... | 110 |
| 7.4.1 | Test Purpose..... | 110 |
| 7.4.2 | Test Case..... | 110 |
| 7.4.3 | Void | 127 |
| 7.4.4 | Conformance requirement | 127 |
| 7.4.5 | Requirement Reference..... | 137 |
| 7.5 | Reference interference level | 137 |
| 7.5.1 | Test Purpose..... | 137 |
| 7.5.2 | Test Case..... | 137 |
| 7.5.3 | Void | 161 |
| 7.5.4 | Conformance requirement | 161 |
| 7.5.5 | Requirements Reference | 178 |
| 7.6 | Blocking Characteristics..... | 178 |
| 7.6.1 | Test Purpose..... | 178 |
| 7.6.2 | Test Case..... | 178 |
| 7.6.3 | Void | 186 |

| | | |
|-----------|---|-----|
| 7.6.4 | Conformance requirement | 186 |
| 7.6.5 | Requirements reference | 188 |
| 7.7 | Intermodulation characteristics | 188 |
| 7.7.1 | Test Purpose..... | 188 |
| 7.7.2 | Test Case..... | 188 |
| 7.7.3 | Void | 190 |
| 7.7.4 | Conformance requirement | 190 |
| 7.7.5 | Requirement Reference..... | 190 |
| 7.8 | AM suppression..... | 191 |
| 7.8.1 | Test Purpose..... | 191 |
| 7.8.2 | Test Case..... | 191 |
| 7.8.3 | Void | 193 |
| 7.8.4 | Conformance requirement | 193 |
| 7.8.5 | Requirement Reference..... | 193 |
| 7.9 | Spurious emissions from the receiver antenna connector..... | 194 |
| 7.9.1 | Test Purpose..... | 194 |
| 7.9.2 | Test Case..... | 194 |
| 7.9.3 | Void | 195 |
| 7.9.4 | Conformance requirement | 195 |
| 7.9.5 | Requirement Reference..... | 195 |
| 8 | Radiated spurious emissions | 195 |
| 8.1 | Test Purpose | 195 |
| 8.2 | Test Case | 195 |
| 8.3 | Void..... | 197 |
| 8.4 | Conformance requirement | 197 |
| 8.5 | Requirement reference | 198 |
| 9 | Radio link management..... | 198 |
| 9.1 | General | 198 |
| 9.2 | Synchronization..... | 198 |
| 9.2.1 | Timing Tolerance..... | 198 |
| 9.2.1.1 | Test purpose | 198 |
| 9.2.1.2 | Test case..... | 199 |
| 9.2.1.3 | Void..... | 199 |
| 9.2.1.4 | Conformance requirement | 199 |
| 9.2.1.5 | Requirement reference | 199 |
| 9.3 | Frame structure..... | 199 |
| 9.3.1 | BCCH Multiframe | 200 |
| 9.3.1.1 | Test purpose | 200 |
| 9.3.1.2 | Test case..... | 200 |
| 9.3.1.2a | Test case for EC-GSM-IoT | 200 |
| 9.3.1.3 | Void..... | 200 |
| 9.3.1.4 | Conformance requirement..... | 200 |
| 9.3.1.5 | Requirement reference | 200 |
| 9.3.2 | TDMA-frame structure | 200 |
| 9.3.2.1 | Test purpose | 200 |
| 9.3.2.2 | Test case..... | 201 |
| 9.3.2.3 | Void..... | 201 |
| 9.3.2.4 | Conformance requirement..... | 201 |
| 9.3.2.5 | Requirement reference | 201 |
| 9.4 | Radio link measurements | 201 |
| 9.4.1 | Signal Strength..... | 202 |
| 9.4.1.1 | Measurement Accuracy..... | 202 |
| 9.4.1.1.1 | Test purpose | 202 |
| 9.4.1.1.2 | Test case | 202 |
| 9.4.1.1.3 | Void..... | 202 |
| 9.4.1.1.4 | Conformance requirement | 202 |
| 9.4.1.1.5 | Requirement reference..... | 204 |
| 9.4.1.2 | Selectivity of signal strength measurements | 204 |
| 9.4.1.2.1 | Test purpose | 204 |
| 9.4.1.2.2 | Test case | 204 |

| | | |
|---|--|------------|
| 9.4.1.2.3 | Void..... | 205 |
| 9.4.1.2.4 | Conformance requirement | 205 |
| 9.4.1.2.5 | Requirement reference..... | 205 |
| 9.4.2 | Signal quality | 205 |
| 9.4.2.1 | Test purpose | 205 |
| 9.4.2.2 | Test case..... | 205 |
| 9.4.2.3 | Void..... | 206 |
| 9.4.2.4 | Conformance requirement..... | 206 |
| 9.4.2.5 | Requirement reference | 207 |
| 9.4.3 | Idle channel signal level | 207 |
| 9.4.3.1 | Test purpose | 207 |
| 9.4.3.2 | Test case..... | 207 |
| 9.4.3.3 | Void..... | 207 |
| 9.4.3.4 | Conformance requirement..... | 208 |
| 9.4.3.5 | Requirement reference | 208 |
| 9.5 | Adaptive frame alignment | 208 |
| 9.5.1 | Test purpose..... | 208 |
| 9.5.2 | Test case | 208 |
| 9.5.3 | Void..... | 209 |
| 9.5.4 | Conformance requirement | 209 |
| 9.5.5 | Requirement reference..... | 210 |
| Annex A (informative): Testing of statistical parameters..... | | 211 |
| A.1 | General theoretical methodology | 211 |
| A.2 | Detailed theoretical methodology | 213 |
| A.3 | Limitations and corrections to the theoretical methodology | 214 |
| A.3.1 | Independent errors..... | 214 |
| A.3.2 | Gaussian distribution..... | 214 |
| A.3.3 | Stationary random processes | 214 |
| A.3.4 | Low error ratios..... | 215 |
| A.3.5 | Total corrections..... | 215 |
| A.4 | Alternative experimental methodology | 215 |
| A.5 | Detailed definition of error events..... | 216 |
| Annex B (informative): Description of special test equipment..... | | 217 |
| B.1 | Base Station System Test Equipment (BSSTE) | 217 |
| B.1.1 | Fading and multipath propagation simulator..... | 217 |
| B.2 | Measurement set ups for TX intermodulation..... | 217 |
| B.2.1 | Test set-up for Intermodulation Attenuation (6.7.)..... | 217 |
| B.2.1.1 | RX-Band..... | 218 |
| B.2.1.2 | Outside RX Band..... | 218 |
| B.2.2 | Test set-up for Intra BSS Intermodulation Attenuation (6.8.) | 219 |
| B.2.2.1 | RX-Band..... | 219 |
| B.2.2.2 | TX-Band | 219 |
| Annex C (informative): Number of samples needed for statistical testing..... | | 220 |
| C.1 | GSM 900; Number of samples for testing..... | 220 |
| C.2 | DCS 1800; Number of Samples for Testing..... | 240 |
| Annex D (informative): Change history | | 262 |
| History | | 270 |

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/4ab5c15b-9893-4d8a-8bac-8a59c66a6662/etsi-ts-151-021-v14.7.0-2019-05>

1 Scope

The present document specifies the Radio Frequency (RF) test methods and conformance requirements for GSM 400, GSM 700, T-GSM 810, GSM 900, ER-GSM 900 and DCS 1800, PCS 1900, GSM 850, MXM 850 and MXM 1900 Base Station Systems (BSS)s. These have been derived from, and are consistent with, the core GSM specifications specified in the requirements reference subclause of each test with the exception that requirements expressed as a reference to regulatory documents (e.g. FCC) have not been included in the present document.

The present document is applicable to BSS meeting the requirements of either GSM Phase 2 or GSM Phase 2+. Unless otherwise stated, all tests are applicable to BSS meeting Phase 2 and/or Phase 2+ GSM requirements, because the requirements of the Phase 2 and Phase 2+ core GSM specifications which are referenced in the test are consistent. Most differences between Phase 2 and Phase 2+ requirements represent Phase 2+ features which are optional for the BSS to support.

Conformance requirements may be tested to verify all aspects of the performance of a BSS. These minimum requirements are intended to be used by manufacturers and operators to allow conformance and acceptance testing to be performed in a consistent manner; the tests to be performed should be agreed between the parties.

In some tests there are separate requirements for micro-BTS and BTS. If there is no separate requirement for a micro-BTS, the requirements for the BTS apply to a micro-BTS.

In Rel-7, higher symbol rate is introduced for EGPRS2-B. EGPRS2-A and all other channels use normal symbol rate. For definition of normal and higher symbol rate see 3GPP TS 45.004. All tests and requirements apply to both symbol rates except otherwise stated in the test.

In some tests there are separate requirements for multicarrier BTS, that apply for all classes of multicarrier BTS (Wide Area, Medium Range and Local Area, cf. [22]) unless otherwise stated. If there is no separate requirement for a multicarrier BTS class, the requirement designated for BTS and normal BTS apply to that multicarrier BTS class.

In Rel-12, BTS operating in the ER-GSM 900 band is introduced. In some tests there are separate requirements for BTS operating in the ER-GSM 900 band. If there is no separate requirement, the requirements for normal BTS apply.

In Rel-13, BTS support of a low-complexity, low data throughput service in environments experiencing high propagation attenuation as indoors in basements etc. is introduced. This service, based on EGPRS, with extended coverage is called EC-GSM-IoT. The requirements for EGPRS apply in case no specific requirement is explicitly stated for EC-GSM-IoT.

In the present document, the reference point for RF connections (except for the measurement of mean transmitted RF carrier power) is the antenna connector, as defined by the manufacturer. The present document does not apply to repeaters or RF devices which may be connected to an antenna connector of a BSS, except as specified in subclause 4.10.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TR 21.905: " Vocabulary for 3GPP Specifications "

[2] GSM 04.22: "Digital cellular telecommunications system (Phase 2+); Radio Link Protocol (RLP) for data and telematic services on the Mobile Station - Base Station System (MS - BSS) interface and the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".

- [3] GSM 05.01: "Digital cellular telecommunications system (Phase 2); Physical layer on the radio path; General description".
- [4] GSM 05.02 (ETS 300 574): "Digital cellular telecommunications system (Phase 2); Multiplexing and multiple access on the radio path".
- [5] GSM 05.03 (ETS 300 575): "Digital cellular telecommunications system (Phase 2); Channel coding".
- [6] GSM 05.04 (ETS 300 576): "Digital cellular telecommunications system (Phase 2); Modulation".
- [7] GSM 05.05 (ETS 300 577): "Digital cellular telecommunications system (Phase 2); Radio transmission and reception".
- [8] GSM 05.08 (ETS 300 578): "Digital cellular telecommunications system (Phase 2); Radio subsystem link control".
- [9] GSM 05.10 (ETS 300 579): "Digital cellular telecommunications system (Phase 2); Radio subsystem synchronization".
- [10] 3GPP TS 08.20: "Digital cellular telecommunications system (Phase 2); Rate adaption on the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [11] ETSI EN 300 019-1: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment Part 1-0: Classification of environmental conditions Introduction".
- [12] IEC 60 068-2: "Basic environmental testing procedures; Part 2: Tests".
- [13] IEC 60 721: "Classification of environmental conditions".
- [14] ETSI ETR 027: "Radio and Equipment Systems; methods of measurement for mobile radio equipment".
- [15] ETSI ETR 028: "Radio and Equipment Systems; Uncertainties in the measurement of mobile radio equipment characteristics".
- [16] ITU-R Rec. SM.329-7: "Spurious emissions"
- [17] 3GPP TS 05.05: " Digital cellular telecommunications system (Phase 2+); Radio transmission and reception ".
- [18] 3GPP TS 45.001: "Physical layer on the radio path; General description".
- [19] 3GPP TS 45.002: "Multiplexing and multiple access on the radio path".
- [20] 3GPP TS 45.003: "Channel coding".
- [21] 3GPP TS 45.004: "Modulation".
- [22] 3GPP TS 45.005: "Radio transmission and reception".
- [23] 3GPP TS 45.008: "Radio subsystem link control".
- [24] 3GPP TS 45.010: "Radio subsystem synchronization".
- [25] TIA/EIA-136-C: "TDMA Third Generation Wireless".
- [26] EN 300 019-1-3: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment Part 1-3; Classification of environmental conditions, Stationary use at weather-protected locations".
- [27] EN 300 019-1-4: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment Part 1-4; Classification of environmental conditions, Stationary use at non-weather-protected locations".
- [28] IEC 60 721-3-3 "Stationary use at weather protected locations".

- [29] IEC 60 721-3-4 "Stationary use at non weather protected locations".
- [30] 3GPP TS 24.022 "Radio Link Protocol (RLP) for circuit switched bearer and teleservices".
- [31] 3GPP TS 48.020 "Rate adaption on the Base Station System - Mobile services Switching Centre (BSS - MSC) interface".
- [32] 3GPP TS 25.113 "Base Station (BS) and repeater ElectroMagnetic Compatibility (EMC)".
- [33] 3GPP TS 36.113 "E-UTRA - Base Station (BS) and repeater ElectroMagnetic Compatibility (EMC)".
- [34] 3GPP TS 43.059 "Functional stage 2 description of Location Services (LCS) in GERAN".
- [35] 3GPP TS 49.031 "Base Station System Application Part LCS Extension (BSSAP-LE)".
- [36] 3GPP TS 44.018 " Mobile radio interface layer 3 specification; GSM/EDGE Radio Resource Control (RRC) protocol".
- [37] 3GPP TS 45.010 "Radio subsystem synchronization".

3 Definitions, abbreviations, frequency bands and channels

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply.

8-PSK: modulation type as defined 3GPP TS 45.004 clause 3.

Carrier Frequency: centre of the ARFCN under test.

GMSK: modulation type as defined by 3GPP TS 45.004 clause 2.

GSM: unless otherwise specified, references to GSM include GSM 400, GSM 700, T-GSM 810, GSM 850, GSM 900, ER-GSM 900, DCS 1800, PCS 1900, MXM 850 and MXM 1900.

GSM 900: unless otherwise specified, references to GSM 900 include P-GSM, E-GSM and R-GSM.

BSS: in the present document, the term BSS (or base station subsystem) applies to both a BTS and integrated BSS. If a separate BSC is required to perform tests on a BTS, the BSC may be regarded as test equipment and the environmental conditions of the BSC need not be controlled.

pico-BTS: as defined in 3GPP TS 45.005. In the present document, this also includes a BSS which incorporates a pico-BTS.

micro-BTS: as defined in 3GPP TS 05.05 and 3GPP TS 45.005. In the present document, this also includes a BSS which incorporates a micro-BTS.

Multicarrier BTS: defined as BTS, characterized by the ability to, in addition to single carrier operation, process two or more carriers in common active components simultaneously.

Wide Area (WA) multicarrier BTS: defined as a class of multicarrier BTS, characterized by requirements derived from macro cell scenarios. The class has either multicarrier transmitter only, or both multicarrier transmitter and receiver.

Medium Range (MR) multicarrier BTS: defined as a class of multicarrier BTS, characterized by requirements derived from micro cell scenarios. The class has both multicarrier transmitter and multicarrier receiver.

Local Area (LA) multicarrier BTS: defined as a class of multicarrier BTS, characterized by requirements derived from pico cell scenarios. The class has both multicarrier transmitter and multicarrier receiver.