



Designation: D 4644 – 87 (Reapproved 1998)

Standard Test Method for Slake Durability of Shales and Similar Weak Rocks¹

This standard is issued under the fixed designation D 4644; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last approval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers the determination of the slake durability index of a shale or other similar rock after two drying and wetting cycles with abrasion.

1.2 The values stated in SI units are to be regarded as the standard. The values given in parentheses are provided for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*

E 11 Specification for Wire-Cloth Sieves for Testing Purposes²

3. Terminology

3.1 *Definitions of Terms Specific to This Standard:*

3.1.1 *slake durability index*—the percentage by dry mass retained of a collection of shale pieces on a 2.00 mm (No. 10) sieve after two cycles of oven drying and 10 min of soaking in water with a standard tumbling and abrasion action.

4. Significance and Use

4.1 The test method is used to estimate qualitatively the durability of weak rocks in the service environment.

4.2 This test method is used to assign quantitative durability values to weak rocks. A primary example is the Franklin Rating System (1).³

5. Apparatus

5.1 *Slake Durability Device*—The drum (Fig. 1) shall be made of 2.00 mm (No. 10) square-mesh, woven-wire cloth, conforming to the requirements of Specification E 11. It shall be cylindrical in shape, with a diameter of 140 mm (5.5 in.) and a length of 100 mm (3.9 in.). The ends shall be rigid plates, with one removable end. It must be sufficiently strong to retain its shape during use, but neither the exterior of the mesh nor the interior of the drum shall be obstructed by a support. The drum shall be able to withstand a temperature of $110 \pm 5^\circ\text{C}$ ($230 \pm 9^\circ\text{F}$). A trough shall support the drum in a horizontal manner such that the drum is free to rotate about its axis. The trough shall be capable of being filled with slaking fluid to 20 mm (0.8 in.) below the drum axis, and shall allow at least 40 mm (1.6 in.) unobstructed clearance between the trough and the bottom of the mesh. The drum shall be rotated by a motor capable of maintaining a speed of 20 rpm, constant to within 5 %, for a period of 10 min. Devices conforming to these requirements are commercially available.

5.2 *Drying Oven*, thermostatically controlled, capable of maintaining a temperature of $110 \pm 5^\circ\text{C}$ ($230 \pm 9^\circ\text{F}$).

5.3 *Balance*, sensitive to 1 g and having a 2000-g capacity.

5.4 *Miscellaneous Apparatus*, including a brush.

5.5 *Distilled Water*.

6. Test Specimen

6.1 The specimen shall consist of ten representative, intact, roughly equidimensional shale fragments weighing 40 g to 60 g each. These fragments may be naturally occurring or may be produced by breaking with a hammer. Such fragments may be obtained from rock cores or from test pits, and their sizes will vary with the method of sampling. Break off any sharp corners, if possible, and remove any dust by brushing the sample just prior to weighing. The total sample shall weigh 450 to 550 g.

6.2 Transport and store the sample in such a manner as to retain the natural water content.

¹ This test method is under the jurisdiction of ASTM Committee D-18 on Soil and Rock and is the direct responsibility of Subcommittee D18.12 on Rock Mechanics.

Current edition approved Feb. 2, 1987. Published April 1987.

² *Annual Book of ASTM Standards*, Vol 14.02.

³ The boldface numbers in parentheses refer to the list of references at the end of this standard.