

ETSI TS 102 223 V15.2.0 (2019-06)



Smart Cards; Card Application Toolkit (CAT) (Release 15)

iTeh STANDARDS PREVIEW
(standards.iteh.ai)
Full standard: https://standards.iteh.ai/catalog/standards/sis/4c0b-a79b-fa0ae3205e4b/etsi-ts-102-223-v15.2.0-2019-06

Reference

RTS/SCP-T003r08avf20

Keywords

smart card

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	12
Foreword.....	12
Modal verbs terminology.....	12
1 Scope	13
2 References	13
2.1 Normative references	13
2.2 Informative references.....	16
3 Definition of terms, symbols and abbreviations.....	17
3.1 Terms.....	17
3.2 Symbols.....	18
3.3 Abbreviations	18
4 Overview of CAT.....	20
4.0 Introduction	20
4.1 Profile download	20
4.2 Proactive UICC	20
4.3 Data download to UICC	21
4.4 Menu selection	21
4.5 Call control by network access application	21
4.6 Void.....	21
4.7 Event download.....	22
4.8 Security	22
4.9 Multiple card	22
4.10 Timer expiration.....	22
4.11 Bearer Independent Protocol	22
4.12 Description of the access technology indicator mechanism	22
4.13 Tag allocation guidelines.....	23
4.14 Description of the network search mode mechanism.....	23
4.15 CAT operation in reduced capability terminals.....	23
4.16 CAT over the modem interface	24
4.17 CAT facilities provided by eCAT clients.....	24
4.18 Negotiation of Poll Interval	25
4.19 eUICC operation	25
5 Profile download	25
5.1 Procedure.....	25
5.2 Structure and coding of TERMINAL PROFILE.....	25
5.3 Definition of display parameters in profile download	34
5.3.0 Overview	34
5.3.1 Number of characters supported down the terminal display.....	34
5.3.2 Number of characters supported across the terminal display.....	34
5.3.3 Display can be resized	34
5.3.4 Text wrapping.....	34
5.3.5 Text scrolling	34
5.3.6 Width reduction when in a menu	34
5.3.7 Text attributes	35
6 Proactive UICC	35
6.1 Introduction	35
6.2 Identification of terminal support.....	38
6.3 General procedure	38
6.4 Proactive UICC commands and procedures.....	38
6.4.1 DISPLAY TEXT	38
6.4.2 GET INKEY	40
6.4.3 GET INPUT.....	41
6.4.4 MORE TIME.....	43

6.4.5	PLAY TONE	43
6.4.6	POLL INTERVAL	44
6.4.7	REFRESH.....	44
6.4.8	SET UP MENU	46
6.4.9	SELECT ITEM.....	47
6.4.10	SEND SHORT MESSAGE	48
6.4.11	Void.....	49
6.4.12	Void.....	49
6.4.13	SET UP CALL.....	49
6.4.14	POLLING OFF	50
6.4.15	PROVIDE LOCAL INFORMATION.....	50
6.4.16	SET UP EVENT LIST.....	51
6.4.17	PERFORM CARD APDU.....	51
6.4.18	POWER OFF CARD.....	52
6.4.19	POWER ON CARD.....	52
6.4.20	GET READER STATUS.....	53
6.4.21	TIMER MANAGEMENT	53
6.4.22	SET UP IDLE MODE TEXT	54
6.4.23	RUN AT COMMAND	54
6.4.24	SEND DTMF.....	55
6.4.25	LANGUAGE NOTIFICATION	56
6.4.26	LAUNCH BROWSER	56
6.4.27	OPEN CHANNEL.....	57
6.4.27.1	OPEN CHANNEL related to CS bearer.....	57
6.4.27.2	OPEN CHANNEL related to packet data service bearer	59
6.4.27.3	OPEN CHANNEL related to local bearer.....	61
6.4.27.4	OPEN CHANNEL related to Default (network) Bearer.....	62
6.4.27.5	OPEN CHANNEL related to UICC Server Mode	63
6.4.27.6	OPEN CHANNEL related to Terminal Server Mode.....	64
6.4.28	CLOSE CHANNEL.....	65
6.4.29	RECEIVE DATA	66
6.4.30	SEND DATA.....	67
6.4.31	GET CHANNEL STATUS.....	69
6.4.32	SERVICE SEARCH.....	69
6.4.33	GET SERVICE INFORMATION.....	69
6.4.34	DECLARE SERVICE	70
6.4.35	SET FRAMES	70
6.4.36	GET FRAME STATUS.....	71
6.4.37	RETRIEVE MULTIMEDIA MESSAGE.....	72
6.4.38	SUBMIT MULTIMEDIA MESSAGE.....	72
6.4.39	DISPLAY MULTIMEDIA MESSAGE	73
6.4.40	ACTIVATE	74
6.4.41	CONTACTLESS STATE CHANGED	75
6.4.42	COMMAND CONTAINER	75
6.4.43	ENCAPSULATED SESSION CONTROL	75
6.4.44	eUICC OPERATION	75
6.5	Common elements in proactive UICC commands	76
6.5.1	Command number	76
6.5.2	Device identities	76
6.5.3	Alpha identifier	76
6.5.4	Icon identifiers.....	76
6.5.5	Text Attribute.....	76
6.5.6	Frame identifier	77
6.6	Structure of proactive UICC commands	77
6.6.0	Foreword.....	77
6.6.1	DISPLAY TEXT	77
6.6.2	GET INKEY	77
6.6.3	GET INPUT.....	78
6.6.4	MORE TIME.....	79
6.6.5	PLAY TONE	79
6.6.6	POLL INTERVAL	79
6.6.7	SET-UP MENU	80

6.6.8	SELECT ITEM.....	80
6.6.9	SEND SHORT MESSAGE.....	81
6.6.10	Void.....	81
6.6.11	Void.....	81
6.6.12	SET UP CALL.....	81
6.6.13	REFRESH.....	82
6.6.14	POLLING OFF.....	82
6.6.15	PROVIDE LOCAL INFORMATION.....	82
6.6.16	SET UP EVENT LIST.....	83
6.6.17	PERFORM CARD APDU.....	83
6.6.18	POWER OFF CARD.....	83
6.6.19	POWER ON CARD.....	83
6.6.20	GET READER STATUS.....	83
6.6.21	TIMER MANAGEMENT.....	83
6.6.22	SET UP IDLE MODE TEXT.....	84
6.6.23	RUN AT COMMAND.....	84
6.6.24	SEND DTMF COMMAND.....	84
6.6.25	LANGUAGE NOTIFICATION.....	85
6.6.26	LAUNCH BROWSER.....	85
6.6.27	OPEN CHANNEL.....	86
6.6.27.1	OPEN CHANNEL related to CS bearer.....	86
6.6.27.2	OPEN CHANNEL related to packet data service bearer.....	87
6.6.27.3	OPEN CHANNEL related to local bearer.....	88
6.6.27.4	OPEN CHANNEL related to Default (network) Bearer.....	89
6.6.27.5	OPEN CHANNEL related to UICC Server Mode.....	89
6.6.27.6	OPEN CHANNEL related to Terminal Server Mode.....	90
6.6.28	CLOSE CHANNEL.....	90
6.6.29	RECEIVE DATA.....	90
6.6.30	SEND DATA.....	91
6.6.31	GET CHANNEL STATUS.....	91
6.6.32	SERVICE SEARCH.....	91
6.6.33	GET SERVICE INFORMATION.....	91
6.6.34	DECLARE SERVICE.....	92
6.6.35	SET FRAMES.....	92
6.6.36	GET FRAMES STATUS.....	93
6.6.37	RETRIEVE MULTIMEDIA MESSAGE.....	93
6.6.38	SUBMIT MULTIMEDIA MESSAGE.....	93
6.6.39	DISPLAY MULTIMEDIA MESSAGE.....	94
6.6.40	ACTIVATE.....	94
6.6.41	CONTACTLESS STATE CHANGED.....	94
6.6.42	COMMAND CONTAINER.....	94
6.6.43	ENCAPSULATED SESSION CONTROL.....	95
6.6.44	eUICC OPERATION.....	95
6.7	Command results.....	95
6.8	Structure of TERMINAL RESPONSE.....	97
6.8.0	Overall coding.....	97
6.8.1	Command details.....	99
6.8.2	Device identities.....	99
6.8.3	Result.....	99
6.8.4	Duration.....	99
6.8.5	Text string.....	99
6.8.6	Item identifier.....	100
6.8.7	Local information.....	100
6.8.8	Call control requested action.....	101
6.8.9	Result data object 2.....	101
6.8.10	Card reader status.....	101
6.8.11	Card ATR.....	101
6.8.12	R-APDU.....	101
6.8.13	Timer identifier.....	101
6.8.14	Timer value.....	101
6.8.15	AT Response.....	102
6.8.16	Text string 2.....	102

6.8.17	Channel data	102
6.8.18	Channel status	102
6.8.19	Channel data length	102
6.8.20	Bearer description	102
6.8.21	Buffer size	102
6.8.22	Total display duration	102
6.8.23	Service Availability	103
6.8.24	Service Record	103
6.8.25	Other address (local address)	103
6.8.26	Frames Information	103
6.8.27	SA template	103
6.8.28	eCAT sequence number	103
6.8.29	Encrypted TLV list	103
6.8.30	MAC	103
6.8.31	DNS server address	104
6.9	Proactive UICC session and terminal display interaction	104
6.10	Handling of unknown, unforeseen and erroneous messages	104
6.10.1	General	104
6.10.2	Message too short	104
6.10.3	Missing minimum information	105
6.10.4	Unknown Tag value	105
6.10.5	Unexpected Tag value	105
6.10.6	Length errors	105
6.10.7	Contents not understood	105
6.10.8	Extended length data objects	105
6.11	Proactive commands versus possible terminal response	106
6.12	CAT session timeout	112
7	ENVELOPE commands	112
7.1	Void	112
7.2	Menu selection	112
7.2.0	Description	112
7.2.1	Procedure	112
7.2.2	Structure of ENVELOPE (MENU SELECTION)	112
7.3	Call Control by NAA	113
7.3.1	Call Control by NAA	113
7.3.1.1	Procedure for mobile originated calls	113
7.3.1.2	Void	113
7.3.1.3	Indication to be given to the user	114
7.3.1.4	Interaction with Fixed Dialling Number (FDN)	114
7.3.1.5	Support of Barred Dialling Number (BDN) service	115
7.3.1.6	Structure of ENVELOPE (CALL CONTROL)	115
7.4	Timer expiration	117
7.4.1	Description	117
7.4.2	Structure of ENVELOPE (TIMER EXPIRATION)	117
7.5	Event download	118
7.5.0	Overview	118
7.5.1	MT call event	118
7.5.1.1	Procedure	118
7.5.1.2	Structure of ENVELOPE (EVENT DOWNLOAD - MT call)	118
7.5.2	Call connected event	119
7.5.2.1	Procedure	119
7.5.2.2	Structure of ENVELOPE (EVENT DOWNLOAD - call connected)	119
7.5.3	Call disconnected event	120
7.5.3.1	Procedure	120
7.5.3.2	Structure of ENVELOPE (EVENT DOWNLOAD - call disconnected)	120
7.5.4	Location status event	121
7.5.4.1	Procedure	121
7.5.4.2	Structure of ENVELOPE (EVENT DOWNLOAD - Location status)	121
7.5.5	User activity event	122
7.5.5.1	Procedure	122
7.5.5.2	Structure of ENVELOPE (EVENT DOWNLOAD - User activity)	122

7.5.6	Idle screen available event	123
7.5.6.1	Procedure	123
7.5.6.2	Structure of ENVELOPE (EVENT DOWNLOAD - Idle screen available)	123
7.5.7	Card reader status event	124
7.5.7.1	Procedure	124
7.5.7.2	Structure of ENVELOPE (EVENT DOWNLOAD - Card reader status)	124
7.5.8	Language selection event	124
7.5.8.1	Procedure	124
7.5.8.2	Structure of ENVELOPE (EVENT DOWNLOAD - Language selection)	125
7.5.9	Browser termination event	125
7.5.9.1	Procedure	125
7.5.9.2	Structure of ENVELOPE (EVENT DOWNLOAD - Browser termination)	125
7.5.10	Data available event	126
7.5.10.1	Procedure	126
7.5.10.2	Structure of ENVELOPE (EVENT DOWNLOAD - Data available)	126
7.5.11	Channel status event	127
7.5.11.1	Procedure	127
7.5.11.2	Structure of ENVELOPE (EVENT DOWNLOAD - Channel status)	127
7.5.12	Access Technology Change Event	128
7.5.12.1	Procedure	128
7.5.12.2	Structure of ENVELOPE (EVENT DOWNLOAD - Access Technology Change)	128
7.5.13	Display parameters changed event	129
7.5.13.1	Procedure	129
7.5.13.2	Structure of ENVELOPE (EVENT DOWNLOAD - Display parameters changed)	129
7.5.14	Local Connection event	129
7.5.14.1	Procedure	129
7.5.14.2	Structure of ENVELOPE (EVENT DOWNLOAD - Local Connection)	130
7.5.15	Network Search Mode Change Event	130
7.5.15.1	Procedure	130
7.5.15.2	Structure of ENVELOPE (EVENT DOWNLOAD - Network Search Mode Change)	131
7.5.16	Browsing status event	131
7.5.16.1	Procedure	131
7.5.16.2	Structure of ENVELOPE (EVENT DOWNLOAD - Browsing status)	131
7.5.17	Frames Information changed event	132
7.5.17.1	Procedure	132
7.5.17.2	Structure of ENVELOPE (EVENT DOWNLOAD - Frames Information changed)	132
7.5.18	HCI connectivity event	133
7.5.18.1	Procedure	133
7.5.18.2	Structure of ENVELOPE (EVENT DOWNLOAD - HCI connectivity event)	133
7.5.19	Contactless state request	133
7.5.19.1	Procedure	133
7.5.19.2	Structure of ENVELOPE (EVENT DOWNLOAD - Contactless state request)	134
7.5.20	Profile Container	134
7.5.20.1	Procedure	134
7.5.20.2	Structure of ENVELOPE (EVENT DOWNLOAD - Profile Container)	135
7.5.21	Void	136
7.5.22	Poll Interval Negotiation	136
7.5.22.1	Procedure	136
7.5.22.2	Structure of ENVELOPE (EVENT DOWNLOAD - Poll Interval Negotiation)	137
7.6	MMS Transfer Status	137
7.6.1	Procedure	137
7.6.2	Structure of ENVELOPE (MMS Transfer Status)	138
7.7	MMS notification download	138
7.7.0	Introduction	138
7.7.1	Procedure	139
7.7.2	Structure of ENVELOPE (MMS notification download)	139
7.8	Terminal Applications	140
7.8.1	Description	140
7.8.2	Structure of ENVELOPE (TERMINAL APPLICATIONS)	140
7.9	Envelope Container	141
7.9.1	Description	141
7.9.2	Structure of ENVELOPE (ENVELOPE CONTAINER)	141

7.10	Service List Retrieval	142
7.10.1	Description.....	142
7.10.2	Structure of ENVELOPE (SERVICE LIST)	143
8	COMPREHENSION-TLV data objects	143
8.0	Introduction	143
8.1	Address.....	144
8.2	Alpha identifier	145
8.3	Subaddress.....	145
8.4	Capability configuration parameters	145
8.5	Void.....	145
8.6	Command details.....	145
8.7	Device identities	152
8.8	Duration.....	153
8.9	Item	153
8.10	Item identifier	154
8.11	Response length.....	154
8.12	Result.....	154
8.12.0	Overall structure and coding	154
8.12.1	Void	156
8.12.2	Additional information for terminal problem	156
8.12.3	Additional information for network problem.....	156
8.12.4	Void	157
8.12.5	Void	157
8.12.6	Void	157
8.12.7	Void	157
8.12.8	Additional information for interaction with call control	157
8.12.9	Additional information for MultipleCard commands	157
8.12.10	Additional information for launch browser problem	158
8.12.11	Additional information for Bearer Independent Protocol	158
8.12.12	Additional information for Frames commands.....	159
8.12.13	Additional information for SUBMIT and RETRIEVE MULTIMEDIA MESSAGE.....	159
8.13	3GPP- SMS TPDU	159
8.14	Void.....	159
8.15	Text string	159
8.15.0	Object structure.....	159
8.15.1	Coding of text in unpacked format	160
8.15.2	Coding of text in packed format	160
8.15.3	Coding of text in 16 bits UCS2 alphabet format.....	160
8.16	Tone.....	160
8.17	Void.....	162
8.18	File list.....	162
8.19	Location information.....	162
8.20	IMEI	162
8.21	Help request.....	163
8.22	Network measurement results	163
8.23	Default text.....	163
8.24	Items next action indicator	163
8.25	Event list.....	164
8.26	Cause	165
8.27	Location status.....	165
8.28	Transaction identifier	166
8.29	Void.....	166
8.30	Call control requested action	166
8.31	Icon identifier	166
8.32	Item icon identifier list	167
8.33	Card reader status	167
8.34	Card ATR	168
8.35	C-APDU	169
8.36	R-APDU	169
8.37	Timer identifier	169
8.38	Timer value	170

8.39	Date-time and time zone.....	170
8.40	AT command.....	171
8.41	AT response.....	171
8.42	BC repeat indicator.....	171
8.43	Immediate response.....	171
8.44	DTMF string.....	172
8.45	Language.....	172
8.46	Void.....	172
8.47	Browser identity.....	172
8.48	URL.....	172
8.49	Bearer.....	173
8.50	Provisioning file reference.....	173
8.51	Browser termination cause.....	173
8.52	Bearer description.....	174
8.53	Channel data.....	174
8.54	Channel data length.....	175
8.55	Buffer size.....	175
8.56	Channel status.....	175
8.57	Card reader identifier.....	176
8.58	Other Address.....	177
8.59	UICC/terminal interface transport level.....	177
8.60	AID.....	178
8.61	Access technology.....	178
8.62	Display parameters.....	178
8.63	Service record.....	179
8.64	Device filter.....	181
8.65	Service search.....	182
8.66	Attribute information.....	182
8.67	Service availability.....	183
8.68	Remote entity address.....	184
8.69	ESN.....	184
8.70	Network access name.....	184
8.71	CDMA-SMS TPDU.....	185
8.72	Text attribute.....	185
8.73	Item text attribute list.....	185
8.74	IMEISV.....	186
8.75	Network search mode.....	186
8.76	Battery State.....	186
8.77	Browsing status.....	187
8.78	Frame Layout.....	187
8.79	Frames Information.....	187
8.80	Frame identifier.....	188
8.81	MEID.....	188
8.82	Multimedia Message Reference.....	188
8.83	Multimedia Message Identifier.....	189
8.84	Multimedia Message Transfer status.....	189
8.85	MM Content Identifier.....	190
8.86	Multimedia Message Notification.....	190
8.87	Last Envelope.....	190
8.88	Registry application data.....	190
8.89	Activate descriptor.....	191
8.90	Broadcast Network information.....	191
8.91	Contactless state request.....	193
8.92	Contactless functionality state.....	194
8.93	Extended registry application data.....	194
8.94	eCAT client profile.....	195
8.95	eCAT client identity.....	195
8.96	Encapsulated envelope type.....	195
8.97	Call control/Poll Interval Negotiation result.....	195
8.98	eCAT sequence number.....	196
8.99	Encrypted TLV list.....	196
8.100	MAC.....	197

8.101	SA template	197
8.102	CAT service list.....	198
8.103	Refresh enforcement policy.....	200
8.104	DNS Server Address	201
8.105	Supported radio access technologies	201
8.106	Profile ID.....	202
8.107	Application specific refresh data	202
9	Tag values	202
9.0	Introduction	202
9.1	BER-TLV tags in terminal to UICC direction.....	202
9.2	BER-TLV tags in UICC to terminal direction.....	202
9.3	COMPREHENSION-TLV tags in both directions.....	203
9.4	Type of command and next action indicator	203
10	Allowed type of command and device identity combinations	204
11	Void.....	205
Annex A (normative):	Support of CAT by terminal equipment.....	206
Annex B (informative):	Example of DISPLAY TEXT proactive UICC command.....	208
Annex C (normative):	Structure of CAT communications	209
Annex D (informative):	Terminal display in proactive UICC session.....	210
Annex E (informative):	Help information feature processing.....	211
Annex F (informative):	Monitoring of events.....	212
Annex G (normative):	Support of multiple card operation.....	213
Annex H (informative):	Multiple card proactive command examples	214
Annex I (informative):	Bearer independent protocol proactive command examples.....	215
Annex J (informative):	WAP terminology	220
Annex K (informative):	Use of CAT bearer independent protocol for local links Bluetooth case	221
K.0	Foreword	221
K.1	Service search command.....	221
K.2	Get service information command	221
K.3	OPEN CHANNEL command.....	221
Annex L (informative):	Bluetooth service discovery protocol.....	224
L.0	Overview	224
L.1	Service attribute.....	225
Annex M (informative):	Use of CAT bearer independent protocol for local links, server case.....	226
Annex N (informative):	Browsing terminology.....	227
Annex O (informative):	Use of USAT Bearer independent protocol for local links IrDA case.....	228
O.0	Foreword	228
O.1	Service Search command	228
O.2	Get Service Information command	228

O.3 OPEN CHANNEL command.....228

Annex P (informative): IrDA Information Access Service.....230

Annex Q (informative): IrDA IAS class name and associated parameters231

Annex R (informative): Example of Frames usage.....232

Annex S (normative): Support of CAT by Terminals with reduced feature capabilities235

Annex T (normative): Default routing for CAT over the modem interface238

T.0 Supported facilities.....238

T.1 Default routing mechanism239

T.2 Combination rules for terminal profiles240

Annex U (informative): Example of eCAT usage241

Annex V (informative): Change history244

History249

iTeh STANDARD PREVIEW
 (standards.iteh.ai)
 Full standard:
<https://standards.iteh.ai/catalog/standards/sist/c0d53bd7-639e-4c0b-a79b-fa0ae3205e4b/etsi-ts-102-223-v15.2.0-2019-06>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Smart Card Platform (SCP).

It is based on work originally done in the 3GPP in TSG-terminals WG3.

The contents of the present document are subject to continuing work within TC SCP and may change following formal TC SCP approval. If TC SCP modifies the contents of the present document, it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 0 early working draft;
 - 1 presented to TC SCP for information;
 - 2 presented to TC SCP for approval;
 - 3 or greater indicates TC SCP approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document defines the interface between the UICC and the terminal, and mandatory terminal procedures, specifically for "NAA Card Application Toolkit".

The Card Application Toolkit (CAT) is a set of generic commands and procedures for use by the ICC, irrespective of the access technology of the network. Within the scope of the present document, the UICC refers here to an ICC which supports at least one application in order to access a network. This application is called here Network Access Application (NAA).

The ICC is considered as a platform, which is either based on ETSI TS 102 221 [1] or ETSI TS 102 600 [38], here called "3G platform" or ETSI TS 151 011 [8], here called "2G platform".

NAA can be:

- a USIM application, as defined in ETSI TS 131 102 [6], which can reside only on a 3G platform;
- a SIM application, as defined in ETSI TS 151 011 [8], which can reside either on a 3G or a 2G platform;
- a TSIM application, as defined in ETSI TS 100 812 [i.2], which can reside only on a 3G platform;
- a ISIM application, as defined in ETSI TS 131 103 [36], which can reside only on a 3G platform;
- a CSIM application, as defined in 3GPP2 C.S0065-B [53];
- an R-UIM application, as defined in 3GPP2 C.S0023-D [30]; or
- other applications residing on a 3G platform or a 2G platform. Specifying the interface is to ensure interoperability between an ICC and a terminal independently of the respective manufacturers and operators.

The present document specifies as well mechanisms in order to expand the generic set of commands and procedures by access technology specific ones.

The present document defines:

- the commands;
- the application protocol;
- the mandatory requirements on the ICC and terminal for each procedure.

The present document does not specify any aspects related to the administrative management phase. Any internal technical realization of either the ICC or the terminal are only specified where these reflect over the interface. The present document does not specify any of the security algorithms that may be used.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- In the case of a reference to a TC SCP document, a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.