

Designation: C449 - 07

## StandardSpecification for Mineral Fiber Hydraulic-Setting Thermal Insulating and Finishing Cement<sup>1</sup>

This standard is issued under the fixed designation C449; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon  $(\varepsilon)$  indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 This specification covers mineral fiber (rock or slag) insulating and finishing cement shipped in dry-mix form, including hydraulic-setting binder, which, when mixed with water and applied in accordance with the manufacturer's directions, affords a smooth surface as a final finish for heated surfaces up to 1200 °F (649 °C) for specific applications. The actual temperature limit shall be agreed upon between the purchaser and the manufacturer.

Note 1—Precautionary measures should be taken with this material as with other hydraulic-setting mixtures. This material should be used within the time period recommended by the manufacturer.

- 1.2 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.
- 1.3 The following safety hazards caveat pertains only to the test method (Section 10) described in this specification: This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.
- 1.4 When the installation or use of thermal insulation materials, accessories, and systems pose safety or health problems, the manufacturer shall provide the user with appropriate current information regarding any known problems associated with the recommended use of the company's products and shall also recommend protective measures to be employed in their safe utilization. The user shall establish appropriate safety and health practices and determine the applicability of regulatory requirements prior to use.

## 2. Referenced Documents

- 2.1 ASTM Standards:<sup>2</sup>
- C163 Practice for Mixing Thermal Insulating Cement Samples
- C166 Test Method for Covering Capacity and Volume Change Upon Drying of Thermal Insulating Cement
- C168 Terminology Relating to Thermal Insulation
- C177 Test Method for Steady-State Heat Flux Measurements and Thermal Transmission Properties by Means of the Guarded-Hot-Plate Apparatus
- C356 Test Method for Linear Shrinkage of Preformed High-Temperature Thermal Insulation Subjected to Soaking Heat
- C390 Practice for Sampling and Acceptance of Thermal Insulation Lots
- C411 Test Method for Hot-Surface Performance of High-Temperature Thermal Insulation
- C518 Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus
- C795 Specification for Thermal Insulation for Use in Contact with Austenitic Stainless Steel
- C1045 Practice for Calculating Thermal Transmission Properties Under Steady-State Conditions
- C1058 Practice for Selecting Temperatures for Evaluating and Reporting Thermal Properties of Thermal Insulation
- C1114 Test Method for Steady-State Thermal Transmission Properties by Means of the Thin-Heater Apparatus
- E136 Test Method for Behavior of Materials in a Vertical Tube Furnace at 750°C

## 3. Terminology

3.1 *Definitions*—Definitions found in Terminology C168 shall be considered as applying to the terms used in this specification.

<sup>&</sup>lt;sup>1</sup> This specification is under the jurisdiction of ASTM Committee C16 on Thermal Insulation and is the direct responsibility of Subcommittee C16.20 on Homogeneous Inorganic Thermal Insulations.

Current edition approved Nov. 15, 2007. Published December 2007. Originally approved in 1960. Last previous edition approved in 2000 as C449/C449M-00. DOI: 10.1520/C0449-07.

<sup>&</sup>lt;sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.