



DRAFT INTERNATIONAL STANDARD ISO/DIS 16908

ISO/TC 131/SC 6

Secretariat: BSI

Voting begins on
2013-07-19

Voting terminates on
2013-10-19

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Hydraulic filter element test methods — Thermal conditioning and cold start-up simulation

Méthodes d'essai des composants de filtre hydraulique — Conditionnement thermique et simulation de démarrage à froid

ICS 23.100.60

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<http://standards.iteh.ai/catalog/standards/sist/197d8123-4846-9498-5972b2a2ba97/iso-16908-2014>

To expedite distribution, this document is circulated as received from the committee secretariat. ISO Central Secretariat work of editing and text composition will be undertaken at publication stage.

Pour accélérer la distribution, le présent document est distribué tel qu'il est parvenu du secrétariat du comité. Le travail de rédaction et de composition de texte sera effectué au Secrétariat central de l'ISO au stade de publication.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/197d8123-9b7c-4946-9498-5972b2a2ba97/iso-16908-2014>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	1
4 Symbols	2
5 Test equipment and materials.....	2
6 Accuracy of measuring instruments and test conditions.....	3
7 Summary of information required prior to testing.....	3
8 Thermal conditioning test.....	3
9 Cold start test.....	4
9.1 Preliminary preparation	4
9.1.1 Housing.....	4
9.2 Procedure	5
10 Pass/fail criteria.....	6
11 Data reporting.....	6
12 Identification statement (reference to this International Standard).....	6
Annex A (informative) Cold start test equipment.....	7
A.1 Test circuit.....	7
A.2 Test circuit components.....	8
A.2.1 Hydraulic power circuit pump and drive.....	8
A.2.2 Hydraulic power circuit reservoir.....	8
A.2.3 System pressure relief valve.....	8
A.2.4 System pressure transducer or pressure gauge	8
A.2.5 Flowmeter.....	8
A.2.6 Three-port directional control valves	8
A.2.7 Clean-up filters.....	9
A.2.8 Transfer cylinder.....	9
A.2.9 Sampling valve	9
A.2.10 Temperature transducer	9
A.2.11 Differential pressure transducer	9
A.2.12 Cold circuit reservoir	9
A.2.13 Cold circuit pump	10
A.2.14 Piping	10
Annex B (informative) Test data reporting form	11

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 16908 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 6, *Contamination control*.

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/9b7c-4946-9498-5972b2a2ba97/iso-16908-2014>

Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within a closed circuit. Filter elements maintain fluid cleanliness by removing insoluble contaminants.

Filter elements, particularly those intended for mobile hydraulic applications, are designed to withstand a range of thermal stresses, such as low and high temperature extremes, and system demands at low temperature (cold starts) whereby hydraulic fluid passes through the element under test at a greatly increased viscosity. These cold starts test the ability of the filter element to withstand the high differential pressures without subsequent loss of integrity or performance.

Stresses due to cold starts can be encountered within the lifetime of a filter element fitted in a mobile hydraulic system. It is therefore necessary to check that having been subjected to such conditions; the filter element shall continue to provide adequate filtration, while also maintaining structural integrity.

This standard provides a procedure by which to introduce stresses due to cold start and to condition a filter element prior to any subsequent performance qualification testing, such as Multi-pass, collapse, flow fatigue, etc. This enables the purchaser of the filter element to be secure in the knowledge that the product can withstand cold starts and still maintain performance as intended.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1978113-9b7c-4946-9498-5972b2a2ba97/iso-16908-2014>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/f97d8123-9b7c-4946-9498-5972b2a2ba97/iso-16908-2014>

Hydraulic filter element test methods — Thermal conditioning and cold start-up simulation

1 Scope

This International Standard specifies a test procedure to thermally condition a hydraulic filter element and simulate cold start, such as that which can be encountered in mobile machinery applications. It is intended to provide a procedure that yields reproducible results and can be used prior to other filter element performance tests, such as those specified in ISO 11170.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1219-1, *Fluid power systems and components — Graphic symbols and circuit diagrams — Part 1: Graphic symbols for conventional use and data-processing applications*

ISO 2942, *Hydraulic fluid power — Filter elements — Verification of fabrication integrity and determination of the first bubble point*

ISO 2943, *Hydraulic fluid power — Filter elements — Verification of material compatibility with fluids*

ISO 3968, *Hydraulic fluid power — Filters — Evaluation of differential pressure versus flow characteristics*

ISO 4021, *Hydraulic fluid power — Particulate contamination analysis — Extraction of fluid samples from lines of an operating system*

ISO 4406, *Hydraulic fluid power — Fluids — Method for coding the level of contamination by solid particles*

ISO 5598, *Fluid power systems and components — Vocabulary*

ISO 11170, *Hydraulic fluid power — Sequence of tests for verifying performance characteristics of filter elements*

ISO 11500, *Hydraulic fluid power — Determination of the particulate contamination level of a liquid sample by automatic particle counting using the light-extinction principle*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5598 and the following apply.

3.1

cold soak

prolonged immersion of a component or part in stationary fluid at 5 °C below the stated minimum temperature of use

- 3.2 cold start**
application of a rapid increase in flow and differential pressure with cold fluid at a high viscosity
- 3.3 differential pressure, Δp**
difference between the tested component inlet and outlet pressure as measured under the specified conditions
- 3.4 hot soak**
prolonged immersion of a component or part in stationary fluid at a temperature 15 °C above the manufacturer's recommended operating temperature
- 3.6 material safety data sheet (MSDS)**
specification sheet defining physical aspects, characteristics and health and safety data for a substance

4 Symbols

The graphical symbols used in this International Standard are in accordance with ISO 1219-1.

5 Test equipment and materials

- 5.1 Soak test fluid**, which shall be either the same as the system operating fluid or another compatible fluid agreed between the supplier and purchaser.
- 5.2 Cold start test fluid**, which may be either the same as the soak test fluid or an alternative with a higher cold temperature viscosity to minimize the volume of fluid required to conduct the cold start test and to standardize the fluid required for testing of additional filters. If an alternative fluid is chosen, it shall be fully compatible with the filter element material.
- 5.3 Differential pressure transducer**, which shall be:
- positioned such that the upstream and downstream connections are close to the filter housing, with no bends or restrictions included in the measurement, and with pressure taps in accordance with ISO 3968; and
 - connected to a calibrated data recording system.
- 5.4 Temperature transducer**, which shall be:
- located so that the sensor part is located in the internal fluid volume;
 - positioned so that it measures the temperature of the test fluid as close as possible upstream of the test element;
 - connected to a calibrated data recording system; and
 - positioned so that the sensor part does not touch the filter element or any part of the filter element container.
- 5.5 Environmental chamber**, which shall be capable of achieving and maintaining the required temperature within the stated limits and capable of containing the test equipment (see 5.6). The chamber shall have suitable thermal controls with a calibrated feedback loop to allow precise control of the chamber temperature.
- 5.6 Cold start test equipment.** See Annex A for a list of typical equipment necessary to perform the cold start test.

6 Accuracy of measuring instruments and test conditions

Use and maintain measuring instrument accuracy and test condition variations within the limits given in Table 1.

Table 1 — Accuracy of measuring instruments and test conditions

Test parameter	SI unit	Instrument accuracy (± of actual value)	Permitted variations in test conditions (± of target value)
Differential pressure	kPa ^a	2%	+ 5 % / - 0 %
Gauge pressure	kPa ^a	2%	5%
Flow rate	L/min	2%	
Temperature	°C	0,1 °C	5 °C

^a 100 kPa = 1 bar

7 Summary of information required prior to testing

Prior to applying the requirements of this International Standard to a particular hydraulic filter element, establish the

- fabrication integrity test pressure (see ISO 2942),
- required maximum element differential pressure for the cold start test.

NOTE 1 For filter elements protected by a bypass valve within the filter housing, the maximum test differential pressure is generally set as the maximum differential pressure across the bypass valve at maximum flow rate and viscosity at the minimum expected temperature. For filter elements without such bypass, the maximum test differential pressure is generally set as the maximum operating system pressure.

NOTE 2 The maximum test differential pressure is normally limited to the maximum permissible collapse or burst pressure of the filter element. If this pressure is exceeded, it can result in damage to the test filter element.

8 Thermal conditioning test

8.1 Visually inspect the filter element for any damage. If it is damaged, reject the filter element, and start over with a new filter element.

8.2 Carry out a fabrication integrity test on the element in accordance with ISO 2942. Reject the filter element if it is damaged as a result testing or fails to meet the required minimum bubble point pressure. If either of these occurs, start over with a new filter element.

8.3 Drain fluid and thoroughly dry before proceeding to 8.4.

8.4 Conduct heat soak and cold soak tests as required in accordance with ISO 2943. The following requirements will enhance the safe conduct of these tests:

- a) If the material safety data sheet for the test fluid states that inhalation of its vapours is harmful, ensure that any vapour from the fluid be extracted external to the workplace when testing with the fluid at above ambient temperatures.
- b) If external extraction of the vapour is unavailable, the test shall be conducted in an enclosed vessel or housing with suitable pressure rating.