

SLOVENSKI STANDARD
SIST ETS 300 394-4-8 E1:2003
01-december-2003

**Prizemni snopovni radio (TETRA) - Specifikacija za preskušanje skladnosti - 4. del:
Specifikacija za preskušanje protokola za neposredno obratovanje (DMO) -- 8.
poddel: Zgradba preskušalnega niza in nameni preskušanja (TSS&TP) za
neposredni prehod (DM-GATE)**

Terrestrial Trunked Radio (TETRA); Conformance testing specification; Part 4: Protocol testing specification for Direct Mode Operation (DMO); Sub-part 8: Test Suite Structure and Test Purposes (TSS&TP) for Direct Mode Gateway (DM-GATE)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 394-4-8 E1:2003](https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003>

Ta slovenski standard je istoveten z: ETS 300 394-4-8 Edition 1

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	------------------------------------	--------------------------------------

SIST ETS 300 394-4-8 E1:2003 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 394-4-8 E1:2003](https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003>



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 394-4-8

June 1999

Source: TETRA

Reference: DE/TETRA-02009-4-8

ICS: 33.020

Key words: ICS, PICS, TETRA

**Terrestrial Trunked Radio (TETRA);
Conformance testing specification;
Part 4: Protocol testing specification for
Direct Mode Operation (DMO);
Sub-part 8: Test Suite Structure and Test Purposes (TSS&TP)
for Direct Mode Gateway (DM-GATE)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

Internet: secretariat@etsi.fr - <http://www.etsi.org>

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999. All rights reserved.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 394-4-8 E1:2003](https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003>

Contents

Foreword	5
1 Scope	7
2 References	7
3 Definitions and abbreviations	8
3.1 TETRA definitions	8
3.2 TETRA abbreviations	8
3.3 ISO 9646 definitions	8
3.4 ISO 9646 abbreviations	8
4 Test Suite Structure (TSS)	8
4.1 NWK layer or Layer 3 test groups	9
4.2 Layer 2 test groups	9
4.3 Test group description	9
5 Introduction to Test Purposes (TPs)	9
5.1 Test purpose definition conventions	10
5.1.1 Text and MSCs	10
5.1.2 Preamble descriptions	11
5.1.2.1 Preamble RegisterHome	11
5.1.2.2 Preamble Idle_To_TX_Active_IC: From Idle state to Call Active TX Occupation	12
5.1.2.3 Preamble Idle_To_RX_Active: From Idle state to Call Active RX Occupation	13
5.1.2.4 Preamble Idle_to_TXR_Active	13
5.1.3 Postamble descriptions	14
5.1.3.1 Postamble DisconnectCall: From Call Active to Idle	14
5.1.3.2 Postamble PST_RegisterHome_Visit: end registration procedure	14
5.1.3.3 Postamble SendRelease	15
5.2 Test purpose naming conventions	15
6 Test Purposes for the Call Control protocol of a DMO GATEWAY: GWCC	16
6.1 Circuit Mode (CM) Call Control test purposes	16
6.1.1 Call set up	16
6.1.2 Call disconnection	19
6.1.3 Call collision	19
6.1.4 Control of transmission	20
6.1.5 Timer tests	22
6.2 Short Data Service (SDS) test purposes	23
7 Test Purposes for the MM protocol of a DMO GATEWAY	24
7.1 Capability test purposes	24
7.2 Valid behaviour test purposes	25
7.2.1 MSGW initiated registration procedures	25
7.2.2 V+D initiated registration procedures	26
7.2.3 Forwarding DM-MS registration procedures to SwMI	26
8 Test Purposes for the MLE protocol of a DMO GATEWAY	27
9 Test Purposes for the LLC protocol of a DMO GATEWAY	27
10 Test Purposes for the MAC protocol of a DMO GATEWAY	27

Annex A (informative): Bibliography	28
History.....	29

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 394-4-8 E1:2003](https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003>

Foreword

This European Telecommunication Standard (ETS) has been produced by the Terrestrial Trunked Radio (TETRA) Project of the European Telecommunications Standards Institute (ETSI).

This ETS consists of 4 parts as follows:

- Part 1: "Radio";
- Part 2: "Protocol testing specification for Voice plus Data (V+D)";
- Part 4: "Protocol testing specification for Direct Mode Operation (DMO)";**
- Part 5: "Security".

Transposition dates	
Date of adoption of this ETS:	4 June 1999
Date of latest announcement of this ETS (doa):	30 September 1999
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	31 March 2000
Date of withdrawal of any conflicting National Standard (dow):	31 March 2000

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 394-4-8 E1:2003](https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 394-4-8 E1:2003](https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003>

1 Scope

This ETS contains the Test Specifications: Test Suite Structure and Test Purposes (TSS&TPs) and the Abstract Test Suites (ATSS) to test conformity of products to the TETRA Direct Mode Operation (DMO) protocols. This ETS is divided into several parts, each one dealing with one TSS&TP or one ATS for the test of a layer 2 or layer 3 protocol for DMO.

This present sub-part 8 deals with TSS&TP for a GateWay (GW) connecting the MS-GW to the Switching and Management Infrastructure (SwMI) of a V+D system.

NOTE: Sub-part 7 deals with TSS&TP for the other part of the DMO Gateway, which is a Mobile Station (MS) connected to a Gateway (MS-GW).

Testing of security features is outside the scope of this ETS.

The objective of this test specification is to provide a basis for approval tests for TETRA equipment giving a high probability of air interface inter-operability between different manufacturer's TETRA equipment.

The ISO standard for the methodology of conformance testing, ISO/IEC 9646-1 [6] and ISO/IEC 9646-2 [7], as well as the ETSI methodology for conformance testing, ETS 300 406 [8], are used as the basis for the test methodology.

2 References

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] Void.
- [2] ETS 300 396-5: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 5: Gateways".
- [3] ETS 300 396-8-3: "Terrestrial Trunked Radio (TETRA); Direct Mode Operation (DMO); Part 8: PICS proforma; Sub-part 3: Direct Mode Gateway (DM-GATE)".
- [4] ETS 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [5] ETS 300 394-2-1: "Terrestrial Trunked Radio (TETRA); Conformance testing specification; Part 2: Protocol testing specification for Voice plus Data (V+D); Sub-part 1: Test suite structure and test purposes".
- [6] ISO/IEC 9646-1 (1994): "Information technology; Open Systems Interconnection; Conformance Testing Methodology and Framework; Part 1: General Concepts". (See also ITU-T Recommendation X.290).
- [7] ISO/IEC 9646-2 (1994): "Information technology; Open Systems Interconnection; Conformance Testing Methodology and Framework; Part 2: Abstract Test Suite Specification". (See also ITU-T Recommendation X.291).
- [8] ETS 300 406 (1995): "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".

3 Definitions and abbreviations

3.1 TETRA definitions

For the purposes of this ETS, the definitions given in ETS 300 396-5 [2] apply.

3.2 TETRA abbreviations

For the purposes of this ETS the following TETRA abbreviations apply:

CM	Circuit Mode
DMCC	Direct Mode Call Control
DMO	Direct Mode of Operation
GCC	Gateway Call Control
GMM	Gateway Mobility Management
GW	Gateway
LLC	Logical Link Control
MAC	Medium Access Control
MLE	Mobile Link entity
MNI	Mobile Network Identity
MS	Mobile Station
MSC	Message Sequence Chart
NWK	NetWork. Layer 3 of the TETRA protocol stack
SDS	Short Data Services
TX	Transmit
RX	Receive

3.3 ISO 9646 definitions

For the purposes of this ETS the following ISO 9646-1 [6] definitions apply:

Implementation Conformance Statement (ICS)

Implementation Under Test (IUT)

Implementation eXtra Information for Testing (IXIT)

Protocol Implementation Conformance Statement (PICS)

Protocol Implementation eXtra Information for Testing (PIXIT)

3.4 ISO 9646 abbreviations

For the purposes of this ETS the following ISO 9646-1 [6] abbreviations apply:

IUT	Implementation Under Test
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
TP	Test Purpose
TSS	Test Suite Structure

4 Test Suite Structure (TSS)

This TSS contains several components, some are specific of the gateway functionality and are new, while others are derived or form a subset of other TETRA specifications. TPs are either included in the present document, or are referenced into another document.

Here is the list of the TSS components:

at layer 3 also named NTW layer:

Gateway Call Control (GCC):

CM: derived from V+D CMCE TPs in ETS 300 394-2-1 [5];

SDS: derived from V+D CMCE TPs in ETS 300 394-2-1 [5].

Gateway Mobility Management (GMM): derived from V+D MM TPs in ETS 300 394-2-1 [5];

Mobile Link Entity (MLE): subset of V+D MLE in ETS 300 394-2-1 [5].

at layer 2:

LLC: subset of V+D LLC in ETS 300 394-2-1 [5];

MAC: subset of V+D MLE in ETS 300 394-2-1 [5].

4.1 NWK layer or Layer 3 test groups

The first level separates the NWK layer (or layer 3) in different protocols (Circuit mode, Short Data Service). Next level splits protocol testing into functional test groups according to the type of testing: Capability test (CA), Valid Behaviour (BV) and Timer tests (TI). Further level classifies the possible operations in each protocol condition or state.

The following list defines the NWK layer test group names and identifiers used for those:

Gateway (DMO_GATE):

Gateway Call Control (GWCC):

Circuit mode (CM):

Call set-up (SU);

Call disconnection (CD);

Call collision (CC);

Control of Transmission (CT);

Timer Tests (TI);

Short Data Service (SDS);

Gateway Mobility Management (GWMM):

Capability tests (CA);

Valid Behaviour tests (BV);

Mobile link entity (MLE): derived from V+D MS-MLE

4.2 Layer 2 test groups

The first level of the Layer 2 test groups separates the test suite in functional test groups: CA, BV and TI. The second level of the test subgroups is used to form a division of protocol requirements.

In the case of a Gateway, the layer 2 contains the LLC and the MAC, and the TSS as well as the TPs of both protocols are derived from the V+D identical components. See ETS 300 394-2-1 [5].

4.3 Test group description

Capability (CA) tests provide limited testing that the observable capabilities of the IUT are in accordance with the conformance requirements and the additional capabilities claimed in the PICS/PIXIT.

The Valid Behaviour (BV) group tests an IUT in response to valid behaviour of the test system. "Valid" means that a test event is syntactically and contextually correct. All test cases in the valid behaviour group are intended to verify as thoroughly as possible the various functions of the protocol.

Different timers are defined to supervise the various state transitions. The Timer (TI) test group is intended to verify that the IUT is reacting properly to an expiry of one of the timers or to a counter mismatch.

5 Introduction to Test Purposes (TPs)

The test purposes for each test suite are defined in clause 6 of the present document for NWK layer and MAC layer.

5.1 Test purpose definition conventions

5.1.1 Text and MSCs

Each TP is described in a table that contains the following information:

Table 0

TP-Name The TP name is a unique identifier, specified according to the TP naming conventions defined in the subclause below. (it is also the name of the corresponding test case)	Reference: reference to the paragraph number of specification ETS 300 396-5 [2] stating this conformance requirement. For example: ETS 300 396-5 [2], 6.2.5.1
Purpose	purpose of the test itself, indicating for example the test performed against a requirement of the protocol, described by this test purpose. Example: test of changeover initiated from RX reservation state
Test description	body of the test
Pass criteria	visible action to be observed at PCO to declare that the IUT passes the test and conforms to the specifications
Selection	expression based on ETS 300 396-8-3 [3] PICS statements, used to select or deselect the corresponding test case according to the options of the implementation.
Preamble	"None" or name of the preamble procedure bringing the IUT from idle state to the state required to run the test. For example: <code>idle_to_RX_reservation</code>
Postamble	"None" or name of the postamble to bring the IUT back to idle state, for example: <code>RX_occupation_to_idle</code>

(standards.iteh.ai)

The preambles and postambles are described using MSCs and are shown in the following paragraphs.

[SIST ETS 300 394-4-8 E1:2003](https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003)

<https://standards.iteh.ai/catalog/standards/sist/9a775ced-9747-43d4-aa3b-4e67a19a8b1a/sist-ets-300-394-4-8-e1-2003>