

ETSI TS 131 111 V15.5.1 (2019-05)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
Universal Subscriber Identity Module (USIM)
Application Toolkit (USAT)
(3GPP TS 31.111 version 15.5.1 Release 15)**



ReferenceRTS/TSGC-0631111vf51

KeywordsGSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope	13
2 References	13
3 Definitions, abbreviations and symbols	16
3.1 Definitions	16
3.2 Abbreviations	16
3.3 Symbols.....	17
4 Overview of USAT	17
4.1 Profile Download	17
4.2 Proactive UICC	17
4.3 Data download to UICC	17
4.4 Menu selection	18
4.5 Call control by USIM	18
4.6 MO Short Message control by USIM.....	18
4.7 Event download.....	18
4.8 Security	18
4.9 Multiple card	18
4.10 Timer Expiration	18
4.11 Bearer Independent Protocol	18
4.12 Description of the access technology indicator mechanism	18
4.13 Description of the network search mode mechanism	19
4.14 Geographical location discovery	19
4.15 Operation in reduced USAT capable terminals.....	19
4.16 Tag allocation guidelines.....	19
4.17 USAT over the AT interface	19
4.18 USAT facilities provided by eCAT clients.....	19
4.19 Negotiation of Poll Interval	19
4.20 ProSe usage information reporting.....	19
5 Profile download	19
5.1 Procedure.....	19
5.2 Structure and coding of TERMINAL PROFILE.....	20
5.3 Definition of display parameters in Profile download.....	25
6 Proactive UICC	25
6.1 Introduction	25
6.2 Identification of ME support	25
6.3 General procedure	26
6.4 Proactive UICC commands and procedures	26
6.4.1 DISPLAY TEXT	26
6.4.2 GET INKEY	26
6.4.3 GET INPUT.....	26
6.4.4 MORE TIME.....	26
6.4.5 PLAY TONE	26
6.4.6 POLL INTERVAL	26
6.4.7 REFRESH.....	26
6.4.7.1 EF _{IMSI} changing procedure	26
6.4.7.2 Generic Bootstrapping Procedure Request.....	27
6.4.7.3 EF _{UICCIARI} changing procedure	27
6.4.7.4 Steering of roaming and steering of roaming for I-WLAN procedure	27
6.4.7.5 Steering of roaming via NAS messages	27
6.4.7.6 Routing ID Data update via NAS messages.....	27

6.4.8	SET UP MENU	27
6.4.9	SELECT ITEM	28
6.4.10	SEND SHORT MESSAGE	28
6.4.11	SEND SS	28
6.4.12	SEND USSD	29
6.4.12.1	MMI Mode	29
6.4.12.2	Application Mode	30
6.4.13	SET UP CALL	31
6.4.14	POLLING OFF	32
6.4.15	PROVIDE LOCAL INFORMATION	32
6.4.16	SET UP EVENT LIST	34
6.4.17	PERFORM CARD APDU	34
6.4.18	POWER OFF CARD	34
6.4.19	POWER ON CARD	34
6.4.20	GET READER STATUS	34
6.4.21	TIMER MANAGEMENT	34
6.4.22	SET UP IDLE MODE TEXT	34
6.4.23	RUN AT COMMAND	35
6.4.24	SEND DTMF	35
6.4.25	LANGUAGE NOTIFICATION	35
6.4.26	LAUNCH BROWSER	35
6.4.27	OPEN CHANNEL	35
6.4.27.1	OPEN CHANNEL related to CS bearer	35
6.4.27.2	OPEN CHANNEL related to GPRS/UTRAN packet service/E-UTRAN/NG-RAN	35
6.4.27.3	OPEN CHANNEL related to local bearer	36
6.4.27.4	OPEN CHANNEL related to Default (network) Bearer	36
6.4.27.5	OPEN CHANNEL related to (I-)WLAN bearer	36
6.4.27.6	OPEN CHANNEL related to Terminal Server Mode	37
6.4.27.7	OPEN CHANNEL related to UICC Server Mode	38
6.4.27.8	OPEN CHANNEL for IMS	38
6.4.28	CLOSE CHANNEL	38
6.4.29	RECEIVE DATA	38
6.4.30	SEND DATA	38
6.4.31	GET CHANNEL STATUS	38
6.4.32	SERVICE SEARCH	38
6.4.33	GET SERVICE INFORMATION	39
6.4.34	DECLARE SERVICE	39
6.4.35	RETRIEVE MULTIMEDIA MESSAGE	39
6.4.36	SUBMIT MULTIMEDIA MESSAGE	39
6.4.37	DISPLAY MULTIMEDIA MESSAGE	39
6.4.38	SET FRAMES	39
6.4.39	GET FRAME STATUS	39
6.4.40	Geographical Location Request	39
6.4.41	ACTIVATE	40
6.4.42	CONTACTLESS STATE CHANGED	40
6.4.43	COMMAND CONTAINER	40
6.4.44	ENCAPSULATED SESSION CONTROL	40
6.5	Common elements in proactive UICC commands	40
6.5.1	Command number	40
6.5.2	Device identities	40
6.5.3	Alpha identifier	40
6.5.4	Icon identifiers	40
6.5.5	Text attribute	41
6.5.6	Frame identifier	41
6.6	Structure of proactive UICC commands	41
6.6.1	DISPLAY TEXT	41
6.6.2	GET INKEY	41
6.6.3	GET INPUT	41
6.6.4	MORE TIME	41
6.6.5	PLAY TONE	41
6.6.6	POLL INTERVAL	41
6.6.7	SET-UP MENU	41

6.6.8	SELECT ITEM.....	41
6.6.9	SEND SHORT MESSAGE	41
6.6.10	SEND SS	42
6.6.11	SEND USSD.....	42
6.6.12	SET UP CALL.....	42
6.6.13	REFRESH.....	43
6.6.14	POLLING OFF.....	44
6.6.15	PROVIDE LOCAL INFORMATION.....	44
6.6.16	SET UP EVENT LIST.....	44
6.6.17	PERFORM CARD APDU	44
6.6.18	POWER OFF CARD	44
6.6.19	POWER ON CARD.....	44
6.6.20	GET READER STATUS.....	44
6.6.21	TIMER MANAGEMENT	44
6.6.22	SET UP IDLE MODE TEXT	44
6.6.23	RUN AT COMMAND	44
6.6.24	SEND DTMF COMMAND.....	44
6.6.25	LANGUAGE NOTIFICATION	44
6.6.26	LAUNCH BROWSER	45
6.6.27	OPEN CHANNEL.....	45
6.6.27.1	OPEN CHANNEL related to (I-)WLAN Bearer.....	45
6.6.27.2	OPEN CHANNEL for IMS.....	46
6.6.28	CLOSE CHANNEL.....	46
6.6.29	RECEIVE DATA	46
6.6.30	SEND DATA.....	46
6.6.31	GET CHANNEL STATUS	46
6.6.32	SERVICE SEARCH	46
6.6.33	GET SERVICE INFORMATION	46
6.6.34	DECLARE SERVICE	46
6.6.35	RETRIEVE MULTIMEDIA MESSAGE.....	46
6.6.36	SUBMIT MULTIMEDIA MESSAGE.....	46
6.6.37	DISPLAY MULTIMEDIA MESSAGE	46
6.6.38	SET FRAMES	46
6.6.39	GET FRAMES STATUS.....	46
6.6.40	Geographical Location Request.....	47
6.6.41	ACTIVATE	47
6.6.42	CONTACTLESS STATE CHANGED	47
6.6.43	COMMAND CONTAINER	47
6.6.44	ENCAPSULATED SESSION CONTROL	47
6.7	Command results.....	47
6.8	Structure of TERMINAL RESPONSE.....	48
6.8.0	Overall structure of TERMINAL RESPONSE.....	48
6.8.1	Command details	49
6.8.2	Device identities	50
6.8.3	Result	50
6.8.4	Duration	50
6.8.5	Text string.....	50
6.8.6	Item identifier	50
6.8.7	Local information	50
6.8.8	Call control requested action	51
6.8.9	Result data object 2.....	51
6.8.10	Card reader status	51
6.8.11	Card ATR	51
6.8.12	R-APDU	51
6.8.13	Timer identifier.....	51
6.8.14	Timer value.....	51
6.8.15	AT Response.....	51
6.8.16	Text string 2.....	51
6.8.17	Channel data	51
6.8.18	Channel status.....	51
6.8.19	Channel data length	51
6.8.20	Bearer description.....	52

6.8.21	Buffer size.....	52
6.8.22	Total Display Duration	52
6.8.23	Service Availability	52
6.8.24	Service Record.....	52
6.8.25	Other address (local address).....	52
6.8.26	Frames Information.....	52
6.9	Proactive UICC session and ME display interaction.....	52
6.10	Handling of unknown, unforeseen and erroneous messages	52
6.11	Proactive commands versus possible Terminal response	52
7	ENVELOPE Commands	54
7.1	Data download to UICC	54
7.1.1	SMS-PP data download	54
7.1.1.1	Procedure	54
7.1.1.1a	Procedure for SMS-PP data download via REGISTRATION ACCEPT or DL NAS TRANSPORT messages	54
7.1.1.2	Structure of ENVELOPE (SMS-PP DOWNLOAD)	55
7.1.2	Cell Broadcast data download	56
7.1.2.1	Procedure	56
7.1.2.2	Structure of ENVELOPE (CELL BROADCAST DOWNLOAD)	57
7.2	Menu Selection.....	57
7.3	Call Control and MO SMS control by USIM.....	57
7.3.1	Call Control by USIM.....	57
7.3.1.1	Procedure for mobile originated calls	57
7.3.1.2	Procedure for Supplementary Services and USSD	58
7.3.1.3	Indication to be given to the user	59
7.3.1.4	Interaction with Fixed Dialling Number	60
7.3.1.5	Support of Barred Dialling Number (BDN) service.....	60
7.3.1.6	Structure of ENVELOPE (CALL CONTROL)	60
7.3.1.7	Procedure for PDP Context Activation	64
7.3.1.8	Procedure for EPS PDN connection Activation.....	64
7.3.1.9	Procedure for IMS communications establishment.....	65
7.3.1.10	Procedure for PDU session establishment.....	65
7.3.2	MO Short Message Control by USIM	66
7.3.2.1	Description	66
7.3.2.2	Structure of ENVELOPE (MO SHORT MESSAGE CONTROL).....	66
7.3.2.3	Indication to be given to the user	68
7.3.2.4	Interaction with Fixed Dialling Number	68
7.4	Timer Expiration	68
7.5	Event download.....	68
7.5.1	(I-)WLAN Access status event.....	68
7.5.1.1	Procedure	68
7.5.1.2	Structure of ENVELOPE (EVENT DOWNLOAD – (I-)WLAN Access Status)	68
7.5.1A	MT Call event	69
7.5.1A.1	Procedure	69
7.5.1A.2	Structure of ENVELOPE (EVENT DOWNLOAD - MT call)	69
7.5.2	Network Rejection event	70
7.5.2.1	Procedure	70
7.5.2.2	Structure of ENVELOPE (EVENT DOWNLOAD – Network Rejection)	70
7.5.2A	Call connected event.....	71
7.5.2A.1	Procedure	71
7.5.2A.2	Structure of ENVELOPE (EVENT DOWNLOAD - call connected)	71
7.5.3	CSG Cell Selection event	72
7.5.3.1	Procedure	72
7.5.3.2	Structure of ENVELOPE (EVENT DOWNLOAD – CSG Cell Selection)	72
7.5.3A	Call disconnected event	73
7.5.3A.1	Procedure	73
7.5.3A.2	Structure of ENVELOPE (EVENT DOWNLOAD - call disconnected)	73
7.5.4	Location status event	74
7.5.5	User activity event	74
7.5.6	Idle screen available event.....	74
7.5.7	Card reader status event.....	74

7.5.8	Language selection event.....	74
7.5.9	Browser termination event.....	74
7.5.10	Data available event.....	74
7.5.11	Channel status event.....	74
7.5.12	Access Technology Change Event.....	74
7.5.13	Display parameters changed event.....	75
7.5.14	Local Connection event.....	75
7.5.15	Network Search Mode Change Event.....	75
7.5.16	Browsing status event.....	75
7.5.17	Frames Information changed event.....	75
7.5.18	HCI connectivity event.....	75
7.5.19	Contactless state request.....	75
7.5.20	Incoming IMS Data event.....	75
7.5.20.1	Procedure.....	75
7.5.20.2	Structure of ENVELOPE (EVENT DOWNLOAD – Incoming IMS Data).....	75
7.5.21	IMS Registration Event.....	76
7.5.21.1	Procedure.....	76
7.5.21.2	Structure of ENVELOPE (EVENT DOWNLOAD – IMS Registration).....	76
7.5.22	Profile Container.....	77
7.5.23	Envelope Container.....	77
7.5.24	Poll Interval Negotiation.....	77
7.5.25	Data Connection Status Change Event.....	77
7.5.25.1	Procedure.....	77
7.5.25.2	Structure of ENVELOPE (EVENT DOWNLOAD – Data Connection Status Change).....	77
7.6	USSD Data Download.....	78
7.6.1	Procedure.....	78
7.6.2	Structure of ENVELOPE (USSD Data Download).....	79
7.7	MMS Transfer Status.....	79
7.8	MMS notification download.....	79
7.9	Terminal Applications.....	79
7.10	Geographical Location Reporting.....	79
7.10.1	Procedure.....	79
7.10.2	Structure of ENVELOPE (Geographical Location Reporting).....	80
7.11	Void.....	81
7.12	ProSe usage information reporting.....	81
7.12.1	Procedure.....	81
7.12.2	Structure of ENVELOPE (ProSe Report).....	81
8	COMPREHENSION-TLV data objects.....	82
8.1	Address.....	82
8.2	Alpha identifier.....	82
8.3	Subaddress.....	82
8.4	Capability configuration parameters.....	82
8.5	Cell Broadcast Page.....	82
8.6	Command details.....	82
8.7	Device identities.....	83
8.8	Duration.....	83
8.9	Item.....	83
8.10	Item identifier.....	83
8.11	Response length.....	83
8.12	Result.....	84
8.12.1	Additional information for SEND SS.....	84
8.12.2	Additional information for ME problem.....	84
8.12.3	Additional information for network problem.....	84
8.12.4	Additional information for SS problem.....	85
8.12.5	Additional information for SMS problem.....	85
8.12.6	Not used.....	85
8.12.7	Additional information for USSD problem.....	85
8.12.8	Additional information for interaction with call control or MO SM control.....	85
8.12.9	Additional information for MultipleCard commands.....	85
8.12.10	Additional information for launch browser problem.....	85
8.12.11	Additional information for Bearer Independent Protocol.....	86

8.12.12	Additional information for Frames commands	86
8.12.13	Additional information for SUBMIT and RETRIEVE MULTIMEDIA MESSAGE	86
8.13	SMS TPDU	86
8.14	SS string	86
8.15	Text string	86
8.16	Tone	86
8.17	USSD string	87
8.18	File List	87
8.19	Location Information	87
8.19.1	Location Information for GERAN	87
8.19.2	Location Information for UTRAN	87
8.19.3	Location Information for E-UTRAN	88
8.19.4	Location Information for NG-RAN	88
8.19.5	Location Information when no surrounding macrocell is detected	88
8.20	IMEI	88
8.21	Help Request	89
8.22	Network Measurement Results	89
8.23	Default Text	90
8.24	Items Next Action Indicator	90
8.25	Event list	90
8.26	Cause	91
8.27	Location status	91
8.28	Transaction identifier	91
8.29	BCCH channel list	92
8.30	Call control requested action	93
8.31	Icon Identifier	93
8.32	Item Icon Identifier list	93
8.33	Card reader status	93
8.34	Card ATR	93
8.35	C-APDU	93
8.36	R-APDU	93
8.37	Timer identifier	93
8.38	Timer value	94
8.39	Date-Time and Time zone	94
8.40	AT Command	94
8.41	AT Response	94
8.42	BC Repeat indicator	94
8.43	Immediate response	94
8.44	DTMF string	94
8.45	Language	95
8.46	Timing Advance	95
8.47	Browser Identity	95
8.48	URL	95
8.49	Bearer	95
8.50	Provisioning File Reference	95
8.51	Browser Termination Cause	96
8.52	Bearer description	96
8.52.1	Bearer parameters for CSD	96
8.52.2	Bearer parameters for GPRS/UTRAN Packet Service/E-UTRAN	96
8.52.3	Bearer parameters for UTRAN Packet Service with extended parameters / HSDPA / E-UTRAN	97
8.52.4	Bearer parameters for (I-)WLAN	98
8.52.5	Bearer parameters for E-UTRAN / mapped UTRAN packet service	98
8.52.6	Bearer parameters for NG-RAN	99
8.53	Channel data	99
8.54	Channel data length	99
8.55	Buffer size	99
8.56	Channel status	99
8.57	Card reader identifier	100
8.58	Other Address	100
8.59	UICC/ME interface transport level	100
8.60	AID	100
8.61	Network Access Name	100

8.62	Access Technology.....	100
8.63	Display parameters	100
8.64	Service Record	100
8.65	Device Filter.....	100
8.66	Service Search	101
8.67	Attribute Information	101
8.68	Service Availability	101
8.69	Remote Entity Address.....	101
8.70	Text Attribute	101
8.71	Item Text Attribute List.....	101
8.72	PDP context Activation parameters.....	101
8.73	UTRAN/E-UTRAN Measurement Qualifier.....	101
8.74	Multimedia Message Reference	102
8.75	Multimedia Message Identifier.....	102
8.76	Multimedia Message Transfer status	102
8.77	MM Content Identifier	102
8.78	Multimedia Message Notification	102
8.79	Last Envelope.....	102
8.80	Frames Layout	102
8.81	Frames Information	102
8.82	Frames identifier	102
8.83	I-WLAN Identifier	102
8.84	(I-)WLAN Access Status.....	103
8.85	IMEISV	103
8.86	Network search mode.....	103
8.87	Battery State	103
8.88	Browsing status	103
8.89	Registry application data	103
8.90	PLMNwAcT List.....	103
8.91	Routing Area Identification	104
8.92	Update/Attach/Registration Type.....	104
8.93	Rejection Cause Code	105
8.94	Geographical Location Parameters.....	105
8.95	GAD shapes.....	107
8.96	NMEA sentence	108
8.97	PLMN List.....	108
8.98	EPS PDN connection activation parameters	109
8.99	Tracking Area Identification	109
8.100	CSG ID list identifier	109
8.101	CSG cell selection status	110
8.102	CSG ID.....	110
8.103	HNB name.....	111
8.104	Activate descriptor	111
8.105	Broadcast Network information	111
8.106	Contactless state request.....	111
8.107	Contactless functionality state.....	111
8.108	IMS URI.....	111
8.109	Extended registry application data	111
8.110	IARI.....	111
8.111	IMPU List.....	112
8.112	IMS status code	112
8.113	eCAT client profile.....	112
8.114	eCAT client identity	112
8.115	Encapsulated envelope type	112
8.116	Void.....	112
8.117	Void.....	112
8.118	PLMN ID.....	113
8.119	E-UTRAN Inter-frequency Network Measurement Results	113
8.120	Call control result	113
8.121	eCAT sequence number	113
8.122	Encrypted TLV list.....	113
8.123	MAC.....	113

8.124	SA template	113
8.125	CAT service list.....	114
8.126	Refresh enforcement policy.....	114
8.127	DNS Server Address	114
8.128	ProSe Report Data.....	114
8.129	SSID	114
8.130	BSSID	114
8.131	HESSID.....	114
8.132	Media Type	115
8.133	IMS call disconnection cause	115
8.134	E-UTRAN Primary Timing Advance Information.....	115
8.135	URI truncated	116
8.136	Extended Rejection Cause Code	116
8.137	Data connection status.....	116
8.138	Data connection type	116
8.139	(E/5G)SM cause	117
8.140	IP address list	118
8.141	Surrounding macrocells.....	118
8.142	PDP/PDN/PDU type.....	118
8.143	PDU Session Establishment parameters.....	119
9	Tag values	119
9.1	BER-TLV tags in ME to UICC direction.....	119
9.2	BER-TLV tags in UICC TO ME direction.....	119
9.3	COMPREHENSION-TLV tags in both directions.....	120
9.4	Type of Command and Next Action Indicator	122
10	Allowed Type of command and Device identity combinations.....	122
11	Security requirements.....	122
Annex A (normative):	Support of USAT by Mobile Equipment	123
Annex B (informative):	Example of DISPLAY TEXT Proactive UICC Command	125
Annex C (normative):	Structure of USAT communications	126
Annex D (informative):	ME display in proactive UICC session.....	127
Annex E (informative):	Help information feature processing.....	128
Annex F (informative):	Monitoring of events.....	129
Annex G (normative):	Support of Multiple Card Operation	130
Annex H (informative):	Multiple Card proactive command examples	131
Annex I (informative):	Bearer independent protocol proactive command examples.....	132
Annex J (informative):	WAP References	133
Annex K (informative):	Use of USAT Bearer independent protocol for local links Bluetooth case	134
Annex L (informative):	Bluetooth Service Discovery protocol	135
Annex M (informative):	Use of USAT Bearer independent protocol for local links, server case	136
Annex N (informative):	USSD information flow between the Network, the ME and the UICC.....	137
N.1	MMI Mode	137
N.2	Application Mode.....	139
N.3	USSD Data Download.....	141

Annex O (informative):	Geographical location information discovery information flow between the ME and the UICC.....	142
Annex P (normative):	Support of USAT by Terminals with reduced feature capabilities.....	143
Annex Q (normative):	Default routing for USAT over AT interface	144
Q.0	3GPP-specific facilities	144
Q.1	Default routing mechanism	144
Q.2	Combination rules for terminal profiles	145
Annex R (informative):	UICC access to IMS, command flow examples	146
R.1	Discovery of the UICC's IARI and IMS Registration	146
R.2	Notification of Incoming IMS data	147
R.3	UICC originating a SIP message	148
Annex S (normative):	3GPP PS data off and Bearer Independent Protocol.....	149
Annex T (informative):	Data Connection Status change event, command flow examples	150
T.1	Introduction	150
T.2	Success activation of PDP/PDN/PDU request flow example.....	150
T.3	Rejected activation of PDP/PDN/PDU request flow example	151
T.4	PDP/PDN/PDU Data connection deactivated flow example.....	152
Annex U (informative):	Change History	154
History		159

3GPP STANDARD PREVIEW
 (standards.iteh.ai)
 Full standard:
<https://standards.iteh.ai/catalog/standards/sist/8067a00e-1b5c-4b88-ada5-ca11dd0d7dae/etsi-ts-131-111-v15.5.1-2019-05>

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- Y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- Z the third digit is incremented when editorial only changes have been incorporated in the document.

ETSI STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/8067a00e-1b3c-4b88-ada5-ca11dd0d7dae/etsi-ts-131-111-v15.5.1-2019-05>