



**SLOVENSKI STANDARD**  
**oSIST prEN 303 687 V1.0.0:2022**  
**01-julij-2022**

---

**6 GHz WAS/RLAN - Harmonizirani standard za dostop do radijskega spektra**

6 GHz WAS/RLAN Harmonised Standard for access to radio spectrum

**iTeh STANDARD**  
**PREVIEW**

Ta slovenski standard je istoveten z: **ETSI EN 303 687 V1.0.0 (2022-04)**  
(standards.iteh.ai)

---

**ICS:**

33.060.01

Radijske komunikacije na  
splošno

Radiocommunications in  
general

**oSIST prEN 303 687 V1.0.0:2022**

**en**

**iTeh STANDARD  
PREVIEW  
(standards.iteh.ai)**

oSIST prEN 303 687 V1.0.0:2022

<https://standards.iteh.ai/catalog/standards/sist/66ea86af-d80b-4706-91de-942fe0cff4d5/osist-pren-303-687-v1-0-0-2022>

# Draft ETSI EN 303 687 V1.0.0 (2022-04)



**6 GHz WAS/RLAN;**  
**Harmonised Standard for access to radio spectrum**  
**(standards.iteh.ai)**

[oSIST prEN 303 687 V1.0.0:2022](https://standards.iteh.ai/catalog/standards/sist/66ea86af-d80b-4706-91de-942fe0cff4d5/osist-pren-303-687-v1-0-0-2022)  
<https://standards.iteh.ai/catalog/standards/sist/66ea86af-d80b-4706-91de-942fe0cff4d5/osist-pren-303-687-v1-0-0-2022>

---

**Reference**

DEN/BRAN-230021

---

**Keywords**

access, broadband, LAN, radio, regulation, testing

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.  
All rights reserved.

# Contents

Intellectual Property Rights .....	8
Foreword.....	8
Modal verbs terminology.....	9
Introduction .....	9
1 Scope .....	10
2 References .....	10
2.1 Normative references .....	10
2.2 Informative references.....	11
3 Definition of terms, symbols and abbreviations.....	12
3.1 Terms.....	12
3.2 Symbols.....	13
3.3 Abbreviations .....	14
4 Technical requirements specifications .....	15
4.1 Environmental profile.....	15
4.2 Equipment categories .....	15
4.2.1 Description of categories .....	15
4.2.2 LPI category.....	15
4.2.3 VLP category .....	15
4.3 Conformance requirements .....	16
4.3.1 Nominal centre frequencies and nominal bandwidth.....	16
4.3.1.1 General .....	16
4.3.1.2 Definition .....	16
4.3.1.3 Limits .....	16
4.3.1.4 Conformance.....	16
4.3.2 RF output power .....	16
4.3.2.1 Definition .....	16
4.3.2.2 Limits .....	17
4.3.2.3 Conformance.....	17
4.3.3 Power Spectral Density.....	17
4.3.3.1 Definition .....	17
4.3.3.2 Limits .....	17
4.3.3.3 VLP NB usage with a PSD above 1 dBm/MHz.....	17
4.3.3.4 Conformance.....	18
4.3.4 Transmitter unwanted emissions.....	18
4.3.4.1 Transmitter unwanted emissions in the out-of-band domain .....	18
4.3.4.1.1 Definition.....	18
4.3.4.1.2 Limits .....	18
4.3.4.1.3 Conformance .....	18
4.3.4.2 Transmitter unwanted emissions in the spurious domain.....	18
4.3.4.2.1 Definition.....	18
4.3.4.2.2 Limits .....	19
4.3.4.2.3 Conformance .....	19
4.3.4.3 Transmitter unwanted emissions within the 6 GHz WAS/RLAN band.....	19
4.3.4.3.1 Definition.....	19
4.3.4.3.2 Limits .....	19
4.3.4.3.3 Conformance .....	21
4.3.5 Receiver spurious emissions .....	22
4.3.5.1 Definition .....	22
4.3.5.2 Limits .....	22
4.3.5.3 Conformance.....	22
4.3.6 Channel access mechanism.....	22
4.3.6.1 Applicability.....	22
4.3.6.2 Definition .....	22
4.3.6.3 Requirements and limits.....	22

4.3.6.3.1	Channel access mechanism for Frame Based Equipment (FBE).....	22
4.3.6.3.2	Channel access mechanism for Load Based Equipment (LBE) .....	24
4.3.6.3.3	ED Threshold level (Energy Detection Threshold level, FBE and LBE).....	29
4.3.6.3.4	Short Control Signalling transmissions (FBE and LBE) .....	30
4.3.6.4	Conformance.....	30
4.3.7	Receiver blocking .....	30
4.3.7.1	Definition .....	30
4.3.7.2	Performance criteria .....	30
4.3.7.3	Limits .....	30
4.3.7.4	Conformance.....	31
4.3.8	Receiver selectivity.....	31
4.3.8.1	Definition .....	31
4.3.8.2	Performance criteria .....	32
4.3.8.3	Limits .....	32
4.3.8.4	Conformance.....	32
4.3.9	Mechanical and electrical design .....	32
4.3.9.1	Power feeding .....	32
4.3.9.1.1	Description of types of power supply .....	32
4.3.9.1.2	Wired power connection equipment.....	33
4.3.9.2	Antenna design.....	33
4.3.9.2.1	Description of types of antenna design.....	33
4.3.9.2.2	Integral antenna .....	33
4.3.9.3	Conformance.....	33
4.3.10	User Access Restrictions .....	33
4.3.10.1	Definition .....	33
4.3.10.2	Requirements .....	33
4.3.10.3	Conformance.....	33
5	Testing for compliance with technical requirements.....	34
5.1	Environmental conditions for testing .....	34
5.1.1	Introduction.....	34
5.1.2	Normal test conditions .....	34
5.1.2.1	Normal temperature and humidity .....	34
5.1.2.2	Normal power source .....	34
5.1.3	Extreme test conditions .....	34
5.2	Interpretation of the measurement results .....	34
5.3	Definition of other test conditions .....	34
5.3.1	Test sequences .....	34
5.3.2	Test channels .....	35
5.3.3	Antennas .....	36
5.3.3.1	Integrated and dedicated antennas.....	36
5.3.3.2	Transmit operating modes.....	36
5.3.3.2.1	Operating mode 1 (single antenna).....	36
5.3.3.2.2	Operating mode 2 (multiple antennas, no beamforming) .....	37
5.3.3.2.3	Operating mode 3 (multiple antennas, with beamforming).....	37
5.3.4	Presentation of equipment .....	37
5.3.5	Measurement methods .....	37
5.4	Essential radio test suites.....	38
5.4.1	Product information .....	38
5.4.2	Nominal centre frequencies .....	39
5.4.2.1	Test conditions .....	39
5.4.2.2	Test methods .....	39
5.4.2.2.1	Conducted measurement.....	39
5.4.2.2.2	Radiated measurement.....	40
5.4.2.2.3	Test fixture measurement .....	40
5.4.3	RF output power .....	40
5.4.3.1	Test conditions .....	40
5.4.3.2	Test methods .....	41
5.4.3.2.1	Conducted measurement.....	41
5.4.3.2.2	Radiated measurement.....	42
5.4.3.2.3	Test fixture measurement .....	43
5.4.4	Power Spectral Density.....	43

iTech STANDARD  
PREVIEW  
(standards.iteh.ai)

oSIST prEN 303 687 V1.0.0:2022

[standards.iteh.ai/catalog/standards/sist/66ea86af-](https://standards.iteh.ai/catalog/standards/sist/66ea86af-)

[2fe0-ff4d5/osist-pr-en-303-687-v1-](https://standards.iteh.ai/catalog/standards/sist/66ea86af-2fe0-ff4d5/osist-pr-en-303-687-v1-0-0-2022)

0-0-2022

5.4.4.1	Test conditions .....	43
5.4.4.2	Test methods .....	43
5.4.4.2.1	Conducted measurement.....	43
5.4.4.2.2	Radiated measurement.....	46
5.4.4.2.3	Test fixture measurement .....	46
5.4.5	Transmitter unwanted emissions outside the 6 GHz WAS/RLAN band .....	46
5.4.5.1	Test conditions .....	46
5.4.5.2	Test method.....	46
5.4.5.2.1	Conducted measurement.....	46
5.4.5.2.2	Radiated measurement.....	49
5.4.5.2.3	Test fixture measurement .....	49
5.4.6	Transmitter unwanted emissions within the 6 GHz WAS/RLAN band.....	49
5.4.6.1	Test conditions .....	49
5.4.6.2	Test method.....	49
5.4.6.2.1	Conducted measurement.....	49
5.4.6.2.2	Radiated measurement.....	51
5.4.6.2.3	Test fixture measurement .....	51
5.4.7	Receiver spurious emissions .....	51
5.4.7.1	Test conditions .....	51
5.4.7.2	Test methods .....	52
5.4.7.2.1	Conducted measurement.....	52
5.4.7.2.2	Radiated measurement.....	54
5.4.7.2.3	Test fixture measurement .....	54
5.4.8	Channel access mechanism.....	54
5.4.8.1	Test conditions .....	54
5.4.8.2	Test method for FBE.....	54
5.4.8.2.1	Additional test conditions .....	54
5.4.8.2.2	Conducted measurements.....	54
5.4.8.2.3	Generic test procedure for measuring channel/frequency usage .....	58
5.4.8.2.4	Radiated measurements .....	58
5.4.8.2.5	Test fixture measurement .....	59
5.4.8.3	Test method for LBE.....	59
5.4.8.3.1	Additional test conditions .....	59
5.4.8.3.2	Conducted measurements.....	59
5.4.8.3.3	Generic test procedure for measuring channel/frequency usage .....	67
5.4.8.3.4	Radiated measurements .....	67
5.4.8.3.5	Test fixture measurement .....	68
5.4.9	Receiver blocking .....	68
5.4.9.1	Test conditions .....	68
5.4.9.2	Test methods .....	68
5.4.9.2.1	Conducted measurement.....	68
5.4.9.2.2	Radiated measurement.....	69
5.4.9.2.3	Test fixture measurement .....	69
5.4.10	Receiver selectivity .....	70
5.4.10.1	Test conditions .....	70
5.4.10.2	Test methods .....	70
5.4.10.2.1	Conducted measurement.....	70
5.4.10.2.2	Radiated measurements .....	71
5.4.10.2.3	Test fixture measurement .....	71
5.4.11	Mechanical and electrical design .....	71
5.4.12	VLP NB operation with a PSD exceeding 1 dBm/MHz .....	72
5.4.12.1	Test conditions .....	72
5.4.12.2	Test methods .....	72
5.4.12.2.1	Conducted measurements .....	72
5.4.12.2.2	Radiated measurements .....	73
5.4.12.2.3	Test fixture measurement .....	73
5.4.13	Assessment procedure for UAR.....	73
5.4.13.1	Introduction.....	73
5.4.13.2	Test conditions .....	73
5.4.13.3	Test Method .....	74

iTech STANDARD  
PREVIEW  
(standards.itech.ai)

oSIST prEN 303 687 V1.0.0:2022

<https://standards.itech.ai/catalog/standards/sist/6bea86af-180e-4706-91de-942fe0cff4d5/osist-pren-303-687-v1-0-0-2022>

<b>Annex A (informative):</b>	<b>Relationship between the present document and the essential requirements of Directive 2014/53/EU .....</b>	<b>75</b>
<b>Annex B (normative):</b>	<b>Test sites and arrangements for radiated measurements.....</b>	<b>77</b>
B.1	Introduction .....	77
B.2	Radiation test sites.....	77
B.2.1	Open Area Test Site (OATS) .....	77
B.2.2	Semi Anechoic Room (SAR) .....	78
B.2.3	Fully Anechoic Room (FAR) .....	79
B.2.4	Measurement distance .....	80
B.3	Antennas.....	81
B.3.1	Introduction .....	81
B.3.2	Measurement antenna.....	81
B.3.3	Substitution antenna .....	81
B.4	Test fixture .....	81
B.4.1	Introduction .....	81
B.4.2	Description of the test fixture.....	82
B.4.3	Using the test fixture for relative measurements at the extremes of the temperature range .....	82
B.4.4	Using the test fixture for normalized measurements .....	82
B.4.5	Using the test fixture for level independent measurements.....	83
B.5	Guidance on the use of radiation test sites .....	83
B.5.1	Introduction .....	83
B.5.2	Power supplies for the battery powered UUT .....	83
B.5.3	Site preparation .....	83
B.6	Coupling of signals.....	84
B.6.1	General .....	84
B.6.2	Data signals .....	84
B.7	Interference signals used for channel access mechanism tests.....	84
B.7.1	Additive White Gaussian Noise (AWGN) test signal .....	84
B.7.2	OFDM test signal 1 .....	84
B.7.3	OFDM test signal 2 .....	85
B.7.4	Verification of interference signal characteristics .....	85
B.7.5	Waveforms for test signals .....	86
<b>Annex C (normative):</b>	<b>Procedures for radiated measurements.....</b>	<b>87</b>
C.1	Introduction .....	87
C.2	Radiated measurements in an OATS or SAR.....	87
C.3	Radiated measurements in a FAR .....	88
C.4	Substitution measurement .....	88
C.5	Guidance for testing technical requirements .....	88
C.5.1	Radio test suites and corresponding test sites.....	88
C.5.2	Guidance for testing channel access mechanism.....	89
C.5.2.1	Introduction.....	89
C.5.2.2	Measurement set up .....	89
C.5.2.3	Calibration of the measurement set up.....	89
C.5.2.4	Test method .....	90
C.5.3	Guidance for testing receiver blocking.....	90
C.5.3.1	Introduction.....	90
C.5.3.2	Measurement set up .....	90
C.5.3.3	Calibration of the measurement set up.....	90
C.5.3.4	Test method .....	91
C.5.4	Guidance for testing receiver selectivity .....	91
C.5.4.1	Introduction.....	91
C.5.4.2	Measurement set up .....	91



C.5.4.3	Calibration of the measurement set up.....	92
C.5.4.4	Test method .....	92
<b>Annex D (informative):</b>	<b>Maximum measurement uncertainties .....</b>	<b>93</b>
<b>Annex E (informative):</b>	<b>Examples of spectrum masks.....</b>	<b>94</b>
E.1	Introduction .....	94
E.2	Equipment configured for multi-channel operation in groups of four adjacent channels .....	94
E.2.1	Example 1.....	94
E.2.2	Example 2.....	94
E.2.3	Example 3.....	95
E.2.4	Example 4.....	95
E.3	Equipment configured for multi-channel operation in 8 adjacent channels.....	96
E.3.1	Example 5.....	96
E.3.2	Example 6.....	96
E.3.3	Example 7.....	97
E.3.4	Example 8.....	97
E.3.5	Example 9.....	98
<b>Annex F (informative):</b>	<b>Change history .....</b>	<b>99</b>
History .....		100

# iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 303 687 V1.0.0:2022](https://standards.iteh.ai/catalog/standards/sist/66ea86af-d80b-4706-91de-942fe0cff4d5/osist-pren-303-687-v1-0-0-2022)  
<https://standards.iteh.ai/catalog/standards/sist/66ea86af-d80b-4706-91de-942fe0cff4d5/osist-pren-303-687-v1-0-0-2022>

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

## Foreword

(standards.iteh.ai)

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Broadband Radio Access Networks (BRAN), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

---

## Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

6 GHz Wireless Access Systems (WAS) including RLAN equipment are used in wireless local area networks which provide high speed data communications in between devices connected to the wireless infrastructure. The present document also addresses ad-hoc networking where devices communicate directly with each other, without the use of a wireless infrastructure.

The spectrum usage conditions for equipment within the scope of the present document are set in the ECC Decision (20)01 [i.3] and Commission Implementing Decision (EU) 2021/1067 of 17.6.2021 [i.11].

# iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 303 687 V1.0.0:2022](https://standards.iteh.ai/catalog/standards/sist/66ea86af-d80b-4706-91de-942fe0cff4d5/osist-pren-303-687-v1-0-0-2022)  
<https://standards.iteh.ai/catalog/standards/sist/66ea86af-d80b-4706-91de-942fe0cff4d5/osist-pren-303-687-v1-0-0-2022>

# 1 Scope

The present document specifies technical characteristics and methods of measurements for 6 GHz Wireless Access Systems including Radio Local Area Network (WAS/RLAN) equipment.

6 GHz WAS/RLAN equipment within the scope of the present document are covered by ECC and EU regulation as follows:

- ECC Decision (20)01 on the harmonised use of frequency band 5 945 MHz to 6 425 MHz for WAS/RLAN [i.3].
- Commission Implementing Decision (EU) 2021/1067 on the harmonised use of radio spectrum in the 5 945 MHz to 6 425 MHz frequency band for the implementation of wireless access systems including radio local area networks (WAS/RLANs) [i.11].

NOTE 1: Descriptions of 6 GHz WAS/RLAN equipment categories and sub-categories are provided in clause 4.2.

This radio equipment is capable of operating in all or parts of the frequency bands given in table 1.

**Table 1: Service frequency band**

	Service frequency band
Transmit	5 945 MHz to 6 425 MHz
Receive	5 945 MHz to 6 425 MHz

The present document describes spectrum access requirements to facilitate spectrum sharing with other equipment.

NOTE 2: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.1] is given in annex A.

**iTeh STANDARD  
PREVIEW  
(standards.iteh.ai)**

## 2 References

[oSIST prEN 303 687 V1.0.0:2022](https://standards.iteh.ai/catalog/standards/sist/66ea86af-180b-4706-91de-942fe0cff4d5/osist-pren-303-687-v1-0-0-2022)

<https://standards.iteh.ai/catalog/standards/sist/66ea86af-180b-4706-91de-942fe0cff4d5/osist-pren-303-687-v1-0-0-2022>

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] IEEE 802.11™-2020: "IEEE Standard for Information Technology - Telecommunications and Information Exchange between Systems - Local and Metropolitan Area Networks - Specific Requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".
- [2] IEEE 802.11ax™-2021: "IEEE Standard for Information Technology - Telecommunications and Information Exchange between Systems - Local and Metropolitan Area Networks - Specific Requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications - Amendment 1: Enhancements for High-Efficiency WLAN".
- [3] ETSI TS 138 141-1 (V16.9.0) (10-2021): "5G; NR; Base Station (BS) conformance testing Part 1: Conducted conformance testing (3GPP TS 38.141-1 version 16.9.0 Release 16)".

- [4] ETSI TS 138 141-2 (V16.9.0) (10-2021): "5G; NR; Base Station (BS) conformance testing Part 2: Radiated conformance testing (3GPP TS 38.141-2 version 16.9.0 Release 16)".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.3] ECC/DEC/(20)01 (11-2020): "On the harmonised use of the frequency band 5945-6425 MHz for Wireless Access Systems including Radio Local Area Networks (WAS/RLAN)".
- [i.4] ETSI EG 203 367 (V1.1.1) (06-2016): "Guide to the application of harmonised standards covering articles 3.1b and 3.2 of the Directive 2014/53/EU (RED) to multi-radio and combined radio and non-radio equipment".
- [i.5] ETSI TR 100 028-1 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".
- [i.6] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.7] ETSI TR 102 273-2 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
- [i.8] ETSI TR 102 273-3 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 3: Anechoic chamber with a ground plane".
- [i.9] ETSI TR 102 273-4 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 4: Open area test site".
- [i.10] ERC Recommendation 74-01 (approved 1998, amended 29 May 2019, updated 1 October 2021): "Unwanted emissions in the spurious domain".
- [i.11] Commission Implementing Decision (EU) 2021/1067 of 17.6.2021 on the harmonised use of radio spectrum in the 5 945-6 425 MHz frequency band for the implementation of wireless access systems including radio local area networks (WAS/RLANs).
- [i.12] ETSI EN 301 893: "5 GHz RLAN; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU".

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in Directive 2014/53/EU [i.1] and the following apply:

**6 GHz WAS/RLAN band:** frequency range of 5 945 MHz to 6 425 MHz

**adjacent signal:** signal adjacent to the wanted signal

**alternate adjacent channels:** channel(s) offset from the wanted channel by twice the channel spacing

**antenna assembly:** combination of the antenna (integral or dedicated), its coaxial cable and if applicable, its antenna connector and associated switching components

NOTE 1: This term (antenna assembly) refers to an antenna connected to one transmit chain.

NOTE 2: The gain of an antenna assembly  $G$  in dBi, does not include the additional gain that may result out of beamforming.

**backoff procedure:** procedure that facilitates the sharing of the medium by randomizing the transmission attempts from multiple devices competing for access to a channel

**beamforming gain:** additional (antenna) gain realized by using beamforming techniques in smart antenna systems

NOTE: Beamforming gain as used in the present document does not include the gain of the antenna assembly.

**burst:** period during which radio waves are intentionally transmitted, preceded and succeeded by periods during which no intentional transmission is made

**channel:** continuous part of the radio-frequency spectrum used for transmission and reception by WAS/RLAN equipment and identified by a nominal centre frequency and a nominal bandwidth

NOTE: WAS/RLAN equipment is permitted to operate (transmit/receive) in one or more adjacent or non-adjacent channels simultaneously.

**channel access engine:** mechanism that determines when a transmission attempt is permitted

**channel plan:** list of channels with their centre frequencies and for each of the centre frequencies, the declared nominal bandwidth(s)

**Clear Channel Assessment (CCA):** mechanism used by an equipment to identify other transmissions in the channel

**Contention Window (CW):** main parameter that determines the duration of the backoff procedure

**dedicated antenna:** antenna external to the equipment, using an antenna connector with a cable or a wave-guide and which has been designed or developed for one or more specific types of equipment

**Energy Detect (ED):** mechanism used to determine the presence of transmissions in the channel based on detecting the signal energy of the transmission

**environmental profile:** range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

**Fixed Frame Period (FFP):** periodic timing of the transmit/receive structure for Frame Based Equipment (FBE)

**Frame Based Equipment (FBE):** equipment where the transmit/receive structure has a periodic timing with a periodicity equal to the Fixed Frame Period (FFP)

**initiating device:** device that initiates a sequence of one or more transmissions

**integral antenna:** antenna designed as a fixed part of the equipment (without the use of an external connector) which cannot be disconnected from the equipment by a user with the intent to connect another antenna

NOTE 1: The term integral antenna is equivalent to integrated antenna.

NOTE 2: An integral antenna may be fitted internally or externally. In the case where the antenna is external, a non-detachable cable or wave-guide can be used.

**Listen Before Talk (LBT):** mechanism by which an equipment applies Clear Channel Assessment (CCA) before using the channel

**Load Based Equipment (LBE):** equipment where the transmit/receive structure is not fixed in time but demand-driven

**Low Power Indoor Access Point (LPI AP):** LPI access point or LPI bridge

**NarrowBand (NB) device:** VLP device that operates with a bandwidth below 20 MHz

**observation slot:** period during which the channel is checked for the presence of other transmissions

**occupied channel:** channel on which the channel access mechanism detected transmissions

**post backoff :** backoff procedure that is applied after every successful transmission

**prioritization period:** period consisting of an initial deferral period followed by an observation period during which the channel is checked for the presence of other transmissions

**receive chain:** receiver circuit with an associated antenna

**responding device:** device that transmits in response to the actions of an initiating device

**smart antenna systems:** equipment that combines multiple transmit and/or receive chains with a signal processing function to increase the throughput and/or to optimize its radiation and/or reception capabilities

**stand-alone equipment:** equipment that is intended primarily as radio communications equipment and that is normally used on a stand-alone basis

**unoccupied channel:** channel on which the channel access mechanism did not detect transmissions

**WAS/RLAN:** broadband radio systems that allow wireless access for public and private applications regardless of the underlying network topology

**WAS/RLAN devices:** components or sub-assemblies which intentionally emit and/or receive radio waves for the purpose of radio communication and are intended for incorporation into WAS/RLAN equipment

NOTE: Categories and sub-categories are provided in clause 4.2.

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

A	measured power output
$CW_{\min}$	minimum Contention Window size
$CW_{\max}$	maximum Contention Window size
D	measured Power Spectral Density
dB	decibel
dBc	dB relative to the transmit power
dB <sub>i</sub>	dB relative to the gain of an isotropic antenna
dB <sub>m</sub>	dB relative to 1 mW
dB <sub>r</sub>	dB relative to the reference level
E	field strength
$E_0$	reference field strength
$f_c$	nominal centre frequency for 20 MHz channels
$f_{c\_offset}$	frequency offset from the nominal centre frequency
G	antenna Gain
GHz	Gigahertz
h	running index
Hz	Hertz
kHz	kiloHertz