

ETSI TS 133 180 V14.7.0 (2019-07)



LTE; Security of the mission critical service (3GPP TS 33.180 version 14.7.0 Release 14)

iTeh STANDARDS PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/etsi-ts-133-180-v14.7.0-2019-07>
4fb3-96e3-78acd5a1a57/etsi-ts-133-180-v14.7.0-2019-07/file-fc86



Reference

RTS/TSGS-0333180ve70

Keywords

LTE,SECURITY

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and

of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	9
1 Scope	10
2 References	10
3 Definitions and abbreviations.....	12
3.1 Definitions	12
3.2 Abbreviations	13
4 Overview of Mission Critical Security.....	13
4.1 General	13
4.2 Signalling plane security architecture.....	14
4.3 MC system security architecture	14
4.3.1 General.....	14
4.3.2 User authentication and authorisation.....	15
4.3.3 Identity keying of users and services	15
4.3.4 Protection of application plane signalling.....	16
4.3.5 Media security	17
4.3.5.1 General	17
4.3.5.2 Media security for group communications.....	17
4.3.5.3 Media security for private calls.....	19
5 Common mission critical security framework	20
5.1 User authentication and authorization	20
5.1.1 General.....	20
5.1.2 User authentication	21
5.1.2.1 Identity management functional model.....	21
5.1.2.2 User authentication framework	22
5.1.2.3 OpenID Connect (OIDC)	23
5.1.2.3.1 General	23
5.1.2.3.2 User authentication example using username/password.....	24
5.1.3 MCX user service authorisation.....	24
5.1.3.1 General	24
5.1.3.2 MCX user service authorization with MCX Server	27
5.1.3.2.1 General	27
5.1.3.2.2 Using SIP REGISTER.....	27
5.1.3.2.3 Using SIP PUBLISH	28
5.1.4 Inter-domain MCX user service authorization.....	28
5.1.4.1 General	28
5.1.4.2 Inter-domain identity management functional model	28
5.2 Key management common elements	30
5.2.1 Overview of key management	30
5.2.2 Common key distribution	31
5.2.3 Key distribution with end-point diversity	32
5.2.4 Key distribution with associated parameters	35
5.2.5 Key distribution with SAKKE-to-self payload	36
5.2.6 Key distribution with identity hiding	37
5.2.7 Key distribution across multiple security domains	38
5.2.7.1 General	38
5.2.7.2 Identification of External Security Domains	38
5.2.7.3 Using multiple security domains	39
5.3 User key management	39
5.3.1 General.....	39
5.3.2 Functional model for key management.....	39

5.3.3	Security procedures for key management.....	40
5.3.4	Provisioned key material to support end-to-end communication security	42
5.3.5	KMS Certificate.....	42
5.3.6	KMS provisioned Key Set	42
5.4	Key management from MC client to MC server (CSK upload)	43
5.5	Key management between MCX servers (SPK)	43
5.6	Key management for one-to-one (private) communications (PCK).....	43
5.7	Key management for group communications (GMK).....	44
5.7.1	General.....	44
5.7.2	Security procedures for GMK provisioning.....	44
5.7.3	Group member GMK management	45
5.8	Key management from MC server to MC client (Key download)	46
5.8.1	General.....	46
5.8.2	‘Key download’ procedure	46
5.9	Key management during MBMS bearer announcement	47
5.10	UE key storage and key persistence	47
5.10.1	Key storage	47
5.10.2	Key persistence	47
6	Supporting security mechanisms.....	48
6.1	HTTP.....	48
6.1.1	Authentication for HTTP-1 interface.....	48
6.1.2	HTTP-1 interface security	48
6.2	SIP	48
6.2.1	Authentication for SIP core access	48
6.2.2	SIP-1 interface security	48
6.3	Network domain security	49
6.3.1	LTE access authentication and security	49
6.3.2	Inter/Intra domain interface security	49
7	MCPTT and MCVideo.....	49
7.1	General	49
7.2	Private communications	49
7.2.1	Key management	49
7.2.2	Security procedures (on-network).....	49
7.2.3	Security procedures (off-network).....	51
7.2.4	First-to-answer security and key management.....	52
7.2.4.1	Overview	52
7.2.4.2	First-to-answer request and response	53
7.2.4.3	First-to-answer call setup with security.....	53
7.2.4.4	First-to-answer media protection	55
7.2.5	Ambient listening call	55
7.2.6	Ambient viewing call.....	55
7.2.7	Private video pull	56
7.2.7.1	One-to-one video pull	56
7.2.7.2	One-from-server video pull.....	56
7.2.8	Private video push.....	57
7.2.8.1	One-to-one video push	57
7.2.8.2	One-to-server video push	57
7.2.8.3	Remotely initiated video push.....	58
7.3	Group communications	60
7.3.1	General.....	60
7.3.2	Group creation security procedure	60
7.3.3	Dynamic group keying.....	60
7.3.3.1	General	60
7.3.3.2	Group regrouping security procedure (within a single MC domain)	61
7.3.3.3	Group regrouping security procedure (involving multiple MC domains).....	61
7.3.4	Broadcast group call	62
7.3.5	Group-broadcast group call.....	62
7.3.6	Emergency group call	62
7.3.7	Imminent peril group call	63
7.3.8	Emergency Alert	63

7.3.9	Remotely initiated video push to group	64
7.4	Key derivation for media.....	65
7.4.1	Derivation of SRTP master keys for private call	65
7.4.2	Derivation of SRTP master keys for group media.....	66
7.5	Media protection profile	67
7.5.1	General.....	67
7.5.2	Security procedures for media stream protection.....	68
8	MCData	69
8.1	Overview	69
8.2	Key Management	70
8.3	One-to-one communications	71
8.4	Group communications	72
8.5	MCData payload protection	72
8.5.1	General.....	72
8.5.2	Prerequisites.....	72
8.5.2.1	Prerequisites for protected payloads.....	72
8.5.2.2	Prerequisites for authenticated payloads	72
8.5.3	Key derivation for protected payloads	73
8.5.4	Payload protection	73
8.5.4.1	Format of protected payloads.....	73
8.5.4.2	Encryption of protected payloads.....	73
8.5.5	Payload authentication.....	74
9	Signalling protection	74
9.1	General	74
9.2	Key distribution for signalling protection	75
9.2.1	Client-Server Key (CSK).....	75
9.2.1.1	General.....	75
9.2.1.2	Creation of the CSK	75
9.2.1.3	Initial 'CSK Upload' Procedure	76
9.2.1.4	CSK update via 'key download'.....	76
9.2.2	Multicast Signalling Key (MuSiK)	77
9.2.3	Signalling Protection Key (SPK)	78
9.3	Application signalling security (XML protection).....	78
9.3.1	General.....	78
9.3.2	Protected content	78
9.3.3	Key agreement	79
9.3.4	Confidentiality protection using XML encryption (xmlenc)	79
9.3.4.1	General	79
9.3.4.2	XML content encryption	79
9.3.4.3	XML URI attribute encryption.....	80
9.3.5	Integrity protection using XML signature (xmlsig)	81
9.4	RTCP signalling protection (SRTCP)	82
9.4.1	General.....	82
9.4.2	Unicast RTCP protection between client and server.....	82
9.4.3	Multicast RTCP protection between client and server.....	83
9.4.4	Offline floor and transmission control protection.....	83
9.4.5	RTCP protection between servers.....	83
9.4.6	Key derivation for SRTCP	83
9.4.7	Security procedures for transmission of RTCP content	84
9.4.8	RTCP protection profile.....	84
9.5	MCData signalling protection	85
9.5.1	Key distribution for signalling protection.....	85
9.5.2	Protection of MCData application signalling payloads (XML)	85
9.5.3	Protection of MCData signalling payloads	85
Annex A (normative):	Security requirements	86
A.1	Introduction	86
A.2	Configuration & service access	86
A.3	Group key management.....	86
A.4	On-network operation.....	86
A.5	Ambient listening	87

A.6	Data communication between MCX network entities	87
A.7	Key stream re-use	87
A.8	Late entry to group communication	87
A.9	Private call confidentiality	87
A.10	Off-network operation	88
A.11	Privacy of MCX service identities	88
A.12	User authentication and authorization	88
A.13	Inter-domain	89
A.14	MCData	90
A.15	Multimedia Broadcast/Multicast Service	90

Annex B (normative): OpenID connect profile for MCX.....91

B.1	General	91
B.2	MCX tokens	91
B.2.1	ID token.....	91
B.2.1.1	General.....	91
B.2.1.2	Standard claims.....	91
B.2.1.3	MCX claims.....	91
B.2.2	Access token.....	92
B.2.2.1	Introduction.....	92
B.2.2.2	Standard claims.....	92
B.2.2.3	MCX claims.....	92
B.3	MCX client registration.....	92
B.4	Obtaining tokens	93
B.4.1	General	93
B.4.2	Native MCX client	93
B.4.2.1	General.....	93
B.4.2.2	Authentication request	93
B.4.2.3	Authentication response	95
B.4.2.4	Access token request.....	95
B.4.2.5	Access token response	96
B.5	Refreshing an access token.....	96
B.5.1	General	96
B.5.2	Access token request	97
B.5.3	Access token response	97
B.6	MCX client registration with partner IdM service	98
B.7	Obtaining an access token from a partner domain	98
B.7.1	Overview	98
B.7.2	Token Exchange Request	99
B.7.3	Token Exchange Response	100
B.7.4	Token Request	100
B.7.5	Token Response	102
B.8	Security tokens	102
B.9	Access tokens for partner services	103
B.10	Using the token to access MCX resource servers	103
B.11	Token validation.....	103
B.11.1	ID token validation.....	103
B.11.2	Access token validation.....	103
B.11.3	Security token validation.....	103
B.12	Token revocation.....	103
B.13	IdMS interface security	103
Annex C (informative): OpenID connect detailed flow.....	105	

C.1	Detailed flow for MC user authentication and registration using OpenID Connect	105
C.2	Detailed flow for inter-domain MC user service authorization using OpenID Connect token exchange.....	106

Annex D (Normative): KMS provisioning messages109

D.1	General aspects.....	109
D.2	KMS requests	109
D.3	KMS responses.....	110
D.3.1	General	110
D.3.2	KMS certificates.....	110
D.3.2.1	Description.....	110
D.3.2.2	Fields	111
D.3.2.3	User IDs.....	111
D.3.3	User Key Provision	111
D.3.3.1	Description.....	111
D.3.3.2	Fields	112
D.3.4	Example KMS response XML	112
D.3.4.1	Example KMSInit XML	112
D.3.4.2	Example KMSKeyProv XML.....	113
D.3.4.3	Example KMSCertCache XML.....	115
D.3.5	KMS response XML schema.....	117
D.3.5.1	Base XML schema.....	117
D.3.5.2	Security Extension to KMS response XML schema.....	120

Annex E (normative): MIKEY message formats for media security121

E.1	General aspects.....	121
E.1.1	Introduction	121
E.1.2	MIKEY common fields	121
E.1.3	Crypto Session Identifiers	121
E.2	MIKEY message structure for GMK distribution.....	122
E.2.1	General	122
E.2.2	Default SRTP security profile for GMK use.....	122
E.3	MIKEY message structure for PCK distribution.....	123
E.3.1	General.....	123
E.3.2	Default SRTP security profile for PCK	123
E.3.3	Providing a SRTP security profile for PCK use	124
E.4	MIKEY message structure for CSK and MuSiK distribution.....	124
E.4.1	General	124
E.4.2	Default SRTCP security profile for CSK and MuSiK	125
E.4.3	Providing a SRTCP security profile for CSK or MuSiK.....	125
E.5	MIKEY general extension payload to support 'SAKKE-to-self'	125
E.6	MIKEY general extension payload to encapsulate parameters associated with a key	126
E.6.1	General	126
E.6.2	Void.....	127
E.6.3	MC group IDs.....	127
E.6.4	Activation time	128
E.6.5	Text	128
E.6.6	Reserved.....	128
E.6.7	Void.....	128
E.6.8	Void.....	128
E.6.9	Status	128
E.6.10	Expiry time	128
E.6.11	Key Type	128
E.7	Hiding identities within MIKEY messages.....	129

Annex F (normative):	Key derivation and hash functions.....	130
F.1	KDF interface and input parameter construction	130
F.1.1	General	130
F.1.2	FC value allocations	130
F.1.3	Calculation of the User Salt for GUK-ID generation	130
F.1.4	Calculation of keys for application data protection.....	130
F.1.5	Calculation of keys for MCData payload protection	131
F.2	Hash functions.....	131
F.2.1	Generation of MIKEY-SAKKE UID	131
F.2.1.1	Overview	131
F.2.1.2	Example UID	132
Annex G (normative):	Key identifiers	134
Annex H (normative):	Support for legacy multicast key (MKFC) and for MSCCK.....	135
H.1	General	135
H.2	MKFC Receipt	135
H.3	MSCCK Distribution.....	135
H.4	Use of multicast signalling keys (MKFC and MSCCK)	135
Annex I (informative):	Change history	136
History	137

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/stardards/sist/c8aa5fle-fc87/4fb3-96e3-78acd5a1a57/etsi-ts-133-180-v14.7.0-2019-07>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/c8aa5file-fc864fb3-96e3-78acd5a1a57/etsi-ts-133-180-v14.7.0-2019-07>

1 Scope

The present document specifies the security architecture, procedures and information flows needed to protect the mission critical service (MCX). The architecture includes mechanisms to protect the Common Functional Architecture and security mechanisms for mission critical applications. This includes Push-To-Talk (MCPTT), Video (MCVideo) and Data (MCData). Additionally, security mechanisms relating to on-network use, off-network use, roaming, migration, interconnection, interworking and multiple security domains are described.

This specification complements the Common Functional Architecture defined in TS 23.280 [36], the functional architecture for MCPTT defined in 3GPP TS 23.379 [2], the functional architecture for MCVideo defined in 3GPP TS 23.281 [37] and the functional architecture for MCData defined in 3GPP TS 23.282 [38].

The MC service can be used for public safety applications and also for general commercial applications e.g. utility companies and railways. As the security model is based on the public safety environment, some MC security features may not be applicable for commercial purposes.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
 - For a specific reference, subsequent revisions do not apply.
 - For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.379: "Functional architecture and information flows to support Mission Critical Push To Talk (MCPTT); Stage 2".
- [3] 3GPP TS 22.179: "Mission Critical Push To Talk (MCPTT) over LTE; Stage 1".
- [4] 3GPP TS 33.210: "3G security; Network Domain Security (NDS); IP network layer security".
- [5] 3GPP TS 33.310: "Network Domain Security (NDS); Authentication Framework (AF)".
- [6] 3GPP TS 33.203: "3G security; Access security for IP-based services".
- [7] 3GPP TS 33.179 Release 13: "Security of Mission Critical Push To Talk (MCPTT) over LTE".
- [8] 3GPP TS 33.328: "IP Multimedia Subsystem (IMS) media plane security".
- [9] IETF RFC 6507: "Elliptic Curve-Based Certificateless Signatures for Identity-Based Encryption (ECCSI)".
- [10] IETF RFC 6508: "Sakai-Kasahara Key Encryption (SAKKE)".
- [11] IETF RFC 6509: "MIKEY-SAKKE: Sakai-Kasahara Key Encryption in Multimedia Internet KEYing (MIKEY)".
- [12] IETF RFC 3550: "RTP: A Transport Protocol for Real-Time Applications".
- [13] IETF RFC 3711: "The Secure Real-time Transport Protocol (SRTP)".
- [14] 3GPP TS 33.401: "3GPP System Architecture Evolution (SAE); Security architecture".
- [15] 3GPP TS 23.228: "IP Multimedia Subsystem (IMS); Stage 2".

- [16] 3GPP TS 33.222: "Generic Authentication Architecture (GAA); Access to network application functions using Hypertext Transfer Protocol over Transport Layer Security (HTTPS)".
- [17] 3GPP TS 33.220: "Generic Authentication Architecture (GAA); Generic Bootstrapping Architecture (GBA)".
- [18] NIST FIPS 180-4: "Secure Hash Standard (SHS)".
- [19] IETF RFC 6749: "The OAuth 2.0 Authorization Framework".
- [20] IETF RFC 6750: "The OAuth 2.0 Authorization Framework: Bearer Token Usage".
- [21] OpenID Connect 1.0: "OpenID Connect Core 1.0 incorporating errata set 1", http://openid.net/specs/openid-connect-core-1_0.html.
- [22] IETF RFC 3830: "MIKEY: Multimedia Internet KEYing".
- [23] IETF RFC 3602: "The AES-CBC Cipher Algorithm and Its Use with IPsec".
- [24] IETF RFC 4771: "Integrity Transform Carrying Roll-Over Counter for the Secure Real-time Transport Protocol (SRTP)".
- [25] IETF RFC 6043: "MIKEY-TICKET: Ticket-Based Modes of Key Distribution in Multimedia Internet KEYing (MIKEY)".
- [26] IETF RFC 7714: "AES-GCM Authenticated Encryption in the Secure Real-time Transport Protocol (SRTP)".
- [27] W3C: "XML Encryption Syntax and Processing Version 1.1", <https://www.w3.org/TR/xmlenc-core1/>.
- [28] W3C: "XML Signature Syntax and Processing (Second Edition)", <http://www.w3.org/TR/xmldsig-core2/>.
- [29] IETF RFC 5905: "Network Time Protocol Version 4: Protocol and Algorithms Specification".
- [30] IETF RFC 5480: "Elliptic Curve Cryptography Subject Public Key Information".
- [31] IETF RFC 6090: "Fundamental Elliptic Curve Cryptography Algorithms".
- [32] IETF RFC 7519: "JSON Web Token (JWT)".
- [33] IETF RFC 7662: "OAuth 2.0 Token Introspection".
- [34] IETF RFC 3394: "Advanced Encryption Standard (AES) Key Wrap Algorithm".
- [35] IETF RFC 7515: "JSON Web Signature (JWS)".
- [36] 3GPP TS 23.280: "Common functional architecture to support mission critical services; Stage 2".
- [37] 3GPP TS 23.281: "Functional architecture and information flows for mission critical video; Stage 2".
- [38] 3GPP TS 23.282: "Functional model and information flows for Mission Critical Data".
- [39] 3GPP TS 23.002: "Network Architecture".
- [40] IETF RFC 2045: "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies".
- [41] IETF RFC 2392: "Content-ID and Message-ID Uniform Resource Locators".
- [42] NIST Special Publication 800-38D: "Recommendation for Block Cipher Modes of Operation: Galois/Counter Mode (GCM) and GMAC".
- [43] IETF RFC 5116: "An Interface and Algorithms for Authenticated Encryption".

- [45] IETF RFC 7521: “Assertion Framework for OAuth 2.0 Client Authentication and Authorization Grants”.
- [46] IETF RFC 7523: “JSON Web Token (JWT) Profile for OAuth 2.0 Client Authentication and Authorization Grants”.
- [47] 3GPP TS 22.280: " Mission Critical Services Common Requirements; Stage 1".
- [48] Void.
- [49] 3GPP TS 24.379: "Mission Critical Push To Talk (MCPTT) call control; Protocol specification."
- [50] 3GPP TS 24.282: "Mission Critical Data (MCData) signalling control; Protocol specification. "
- [51] IETF RFC 3711 Errata ID 3712, <https://www.rfc-editor.org/errata/eid3712>.
- [52] IANA: "[Multimedia Internet KEYing \(MIKEY\) Payload Name Spaces](https://www.iana.org/assignments/mikey-payloads/mikey-payloads.xhtml)",
<https://www.iana.org/assignments/mikey-payloads/mikey-payloads.xhtml>.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

Authorised Identity: An application identity given to an authorised user or network entity (e.g. MC Service ID) containing authorisation information.

External KMS: The KMS which is the root of trust for a specific External Security Domain.

External Security Domain: A security domain that the user is not a member of, but with which the user may communicate.

Floor: Floor(x) is the largest integer smaller than or equal to x.

Home KMS: The KMS that is the root of trust of the Home Security Domain.

Home Security Domain: The MCX user's primary security domain.

Identity Management Domain: The MC clients and MC functions that share an Identity Management Server (IdMS). To be specific, the MC clients request access tokens from the same primary IdMS, and the MC functions accept access tokens from this IdMS.

KMS Certificate: A certificate containing the security parameters for a security domain. This is required to support identity-based cryptography and differs from X.509 certificates used for traditional PKI. See Annex D.3.1 for details.

KMS URI: A unique identifier for a security domain, or equivalently, a logical KMS.

MCX: Mission critical services where “MCX” may be substituted with the term “MCPTT”, “MCVideo”, “MCData”, or any combination thereof.

Partner domain: A secondary MC domain which may support MC services for MC users who are home to a different MC domain. See also External Security Domain.

Primary domain: The “home” MC domain where MC users receive their primary identity management and MC services. See also Home Security Domain.

Security Domain: A security domain is a group of MCX users who share common security requirements and policies for their communications. From a technical perspective, users within a security domain share a KMS and KMS certificate. MCX users may be members of one or more security domains.