ETSI EN 301 489-20 V2.2.1 (2021-11)



ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 20: Specific conditions for Mobile Earth Stations (MES) used in the Mobile Satellite Services (MSS); Harmonised Standard for ElectroMagnetic Compatibility 2

Reference

REN/ERM-EMC-405

Keywords

earth station, EMC, harmonised standard, MSS, radio, regulation, satellite, testing

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from: <u>http://www.etsi.org/standards-search</u>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <u>https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx</u>

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommitteeSupportStaff.aspx

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI. The copyright and the foregoing restriction extend to reproduction in all media.

> © ETSI 2021. All rights reserved.

Contents

Intell	ectual Property Rights		5
Forev	vord		5
Moda	ll verbs terminology		6
1	Scope		7
2			
2.1 2.2		es	
3	Definition of terms, s	ymbols and abbreviations	9
3.1			
3.2			
3.3	Abbreviations		10
4	Test conditions		11
4.1			
4.2		st signals	
4.2.0			
4.2.1 4.2.2		r test signals at the input of transmitters	
4.2.2		r test signals at the output of transmitters r test signals at the input of receivers	
4.2.4	Arrangements fo	r test signals at the output of receivers	
4.3	Exclusion bands	r test signals at the output of receivers	
4.3.0	General		12
4.3.1	Transmitter excl	usion band (standards.iteh.ai)	13
4.3.2	Receiver exclusi	on band	13
5	Performance assessme	ent	13
5.1		//standards.iteh.ai/catalog/standards/sist/64c7740a-03ba-4439-88e0-	
5.2		ost equipment:9a0/etsi-en-301-489-20-v2-2-1-2021-11	
5.2.0	General		13
5.2.1		ombined equipment	
5.2.2		se of a test jig	
5.3	• • •	t	
5.4	Equipment classifica	ation	13
6	Performance criteria.		14
6.1	General		14
6.2		for Continuous Phenomena	
6.3	Performance criteria	for Transient Phenomena	14
7	Requirements		14
7.1			
7.1.1	General		14
7.1.2	Special condition	1S	15
7.2	-		
7.2.1			
7.2.2	Special condition	ns	17
Anne	ex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	18
Anne	x B (informative):	Definitions of MES within the scope of the present document	20
B.0	General		20
B.1	MES operating within	n 1,6 GHz/2,4 GHz band	20
B.2	MES operating within the 1,5 GHz/1,6 GHz		20

Histor	у		23
Anne	x C (informative):	Change history	22
B.5	MES operating in the 1	1 GHz/12 GHz/14 GHz frequency bands	21
B.4	MES operating below 1 GHz		
B.3	MES operating within 2,0 GHz band		

4

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ETSI EN 301 489-20 V2.2.1 (2021-11)</u> https://standards.iteh.ai/catalog/standards/sist/64c7740a-03ba-4439-88e0-77f9532cc9a0/etsi-en-301-489-20-v2-2-1-2021-11

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECTTM, **PLUGTESTSTM**, **UMTSTM** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPPTM** and **LTETM** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2MTM** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**[®] and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

(stanual us.iten.al)

ETSI EN 301 489-20 V2.2.1 (2021-11) This Harmonised European Standard (EN) has been produced by ETSI/Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM)_{etsi-en-301-489-20-v2-2-1-2021-11}

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.2] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 20 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

National transposition dates	
Date of adoption of this EN:	19 November 2021
Date of latest announcement of this EN (doa):	28 February 2022
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 2022
Date of withdrawal of any conflicting National Standard (dow):	31 August 2023

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ETSI EN 301 489-20 V2.2.1 (2021-11) https://standards.iteh.ai/catalog/standards/sist/64c7740a-03ba-4439-88e0-77f9532cc9a0/etsi-en-301-489-20-v2-2-1-2021-11

1 Scope

The present document specifies technical characteristics and methods of measurement for Mobile Earth Stations (MES) operating in the Mobile Satellite Services (MSSs) as defined in annex B, and ancillary equipment in respect of ElectroMagnetic Compatibility (EMC).

Technical specifications related to the antenna port and emissions from the enclosure port of the equipment are not included in the present document. Such technical specifications are found in the relevant product standards for the effective use of the radio spectrum, see table 1.

Emissions requirements in the present document are only specified for frequencies above 9 kHz.

Technology	ETSI Standard
Low data rate Land Mobile satellite Earth Stations (LMES) and Maritime Mobile satellite Earth Stations (MMES) operating in the 1 518 MHz to 1 675 MHz frequency bands	ETSI EN 301 426 [i.3]
Low data rate Land Mobile satellite Earth Stations (LMES) operating in the 11/12/14 GHz frequency bands	ETSI EN 301 427 [i.4]
Mobile Earth Stations (MES), including handheld earth stations, for Satellite Personal Communications Networks (S-PCN) in the 1 610 MHz to 2 500 MHz frequency bands under the Mobile Satellite Service (MSS)	ETSI EN 301 441 [i.5]
Mobile Earth Stations (MES), including handheld earth stations, for Satellite Personal Communications Networks (S-PCN) in the 1 980 MHz to 2 200 MHz frequency bands under the Mobile Satellite Service (MSS)	ETSI EN 301 442 [i.6]
Land Mobile Earth Stations (LMES) and Maritime Mobile Earth Stations (MMES) operating in the 1 518 MHz to 1 675 MHz frequency bands providing voice and/or data communications	ETSI EN 301 444 [i.7]
Mobile Earth Stations (MES) providing Low Bit Rate Data Communications (LBRDC) using Low Earth Orbiting (LEO) satellites operating in the 137 MHz to 401 MHz frequency bands	ETSI EN 301 721 [i.8]
Land Mobile Earth Stations (LMES) and Maritime Mobile Earth Stations (MMES) of Geostationary mobile satellite systems, including handheld earth stations, for 44 Satellite Personal Communications Networks (S-PCN) under the Mobile Satellite Service (MSS), operating in the 1 518 MHz to 1 675 MHz frequency bands	ÊTSPÊN 301 681 [i.9]
Aircraft Earth Stations (AES) providing Aeronautical Mobile Satellite Service (AMSS)/Mobile Satellite Service (MSS) and/or the Aeronautical Mobile Satellite on Route Service (AMS(R)S)/Mobile Satellite Service (MSS), operating in the 1 518 MHz to 2 500 MHz frequency bands	ETSI EN 301 473 [i.10]

Table 1: Radio Technologies in the sco	ope of the present document
--	-----------------------------

The environmental classification used in the present document are as stated in ETSI EN 301 489-1 [1].

For a multimode radio station, the present document only applies to the radio station when operated in the Mobile Satellite Service mode.

NOTE: The relationship between the present document and essential requirements of article 3.1(b) of Directive 2014/53/EU [i.1] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at https://docbox.etsi.org/Reference/.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 489-1 (V2.2.3) (11-2019): "ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements; Harmonised Standard for ElectroMagnetic Compatibility".
- [2] Void.
- [3] Void.
- [4] ITU-R Radio Regulations (2020).

[5] Void.

[6] Void.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area standards.iteh.ai)

[i.1]	Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC40a-03ba-4439-88e0-
[i.2]	77(9532cc9a0/etsi-en-301-489-20-v2-2-1-2021-11 Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
[i.3]	ETSI EN 301 426: "Satellite Earth Stations and Systems (SES); Harmonised Standard for Low data rate Land Mobile satellite Earth Stations (LMES) and Maritime Mobile satellite Earth Stations (MMES) not intended for distress and safety communications operating in the 1,5 GHz/1,6 GHz frequency bands covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
[i.4]	ETSI EN 301 427: "Satellite Earth Stations and Systems (SES); Harmonised Standard for low data rate Mobile satellite Earth Stations (MES) except aeronautical mobile satellite earth stations, operating in the 11/12/14 GHz frequency bands covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
[i.5]	ETSI EN 301 441: "Satellite Earth Stations and Systems (SES); Harmonised Standard for Mobile Earth Stations (MES), including handheld earth stations, for Satellite Personal Communications Networks (S-PCN) operating in the 1,6 GHz/2,4 GHz frequency band under the Mobile Satellite Service (MSS) covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
[i.6]	ETSI EN 301 442: "Satellite Earth Stations and Systems (SES); Harmonised Standard for NGSO Mobile Earth Stations (MES) including handheld earth stations, for Satellite Personal Communications Networks (S-PCN) operating in the 1 980 MHz to 2 010 MHz (earth-to-space) and 2 170 MHz to 2 200 MHz (space-to-earth) frequency bands under the Mobile Satellite Service (MSS) covering the essential requirements of article 3.2 of the Directive 2014/53/EU".

- [i.8] ETSI EN 301 721: "Satellite Earth Stations and Systems (SES); Harmonised Standard for Mobile Earth Stations (MES) providing Low Bit Rate Data Communications (LBRDC) using Low Earth Orbiting (LEO) satellites operating below 1 GHz frequency band covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
- [i.9] ETSI EN 301 681: "Satellite Earth Stations and Systems (SES); Harmonised Standard for Mobile Earth Stations (MES) of Geostationary mobile satellite systems, including handheld earth stations, for Satellite Personal Communications Networks (S-PCN) under the Mobile Satellite Service (MSS), operating in the 1,5 GHz and 1,6 GHz frequency bands covering the essential requirements of article 3.2 of the Directive 2014/53/EU".
- [i.10] ETSI EN 301 473: "Satellite Earth Stations and Systems (SES); Harmonised Standard for Aircraft Earth Stations (AES) providing Aeronautical Mobile Satellite Service (AMSS)/Mobile Satellite Service (MSS) and/or the Aeronautical Mobile Satellite on Route Service (AMS(R)S)/Mobile Satellite Service (MSS), operating in the frequency band below 3 GHz covering the essential requirements of article 3.2 of the Directive 2014/53/EU".

3 Definition of terms, symbols and abbreviations

3.1 Terms iTeh STANDARD PREVIEW

For the purposes of the present document, the terms given in ETSI EN 301489-1 [1] and the following apply:

ancillary equipment: electrical or electronic equipment, that is intended to be used with a receiver or transmitter <u>ETSI EN 301 489-20 V2.2.1 (2021-11)</u>

NOTE 1: It is considered as an ancillary equipment affalards/sist/64c7740a-03ba-4439-88e0-77f9532cc9a0/etsi-en-301-489-20-v2-2-1-2021-11

- the equipment is intended for use with a receiver or transmitter to provide additional operational and/or control features to the radio equipment (e.g. to extend control to another position or location);
- the ancillary equipment cannot be used without being connected to radio equipment to provide user functions independently of a receiver or transmitter; and
- the receiver or transmitter, to which it is connected, is capable of providing some intended operation such as transmitting and/or receiving without the ancillary equipment (i.e. it is not a sub-unit of the main equipment essential to the main equipment basic functions).
- NOTE 2: An example of ancillary equipment would be a docking station for radio equipment whose interface is dedicated to a particular product or range of products.

carrier-off state (idle mode): state of an MES when it is powered-on but not transmitting a signal, i.e. not in a carrier-on state

carrier-on state (allocated a channel): state of an MES when it is transmitting a signal in a continuous or a non-continuous mode

critical stored data: data that is essential for an EUT to perform a primary function in accordance with that EUT's specification

NOTE: This may include data previously stored by the user.

drive equipment: equipment used to enable the EUT to operate as intended during the test process

Externally Mounted Equipment (EME): equipment consisting of those of the modules of the Installable Equipment (IE) which are intended to be mounted externally to the vehicle as stated by the manufacturer

host equipment: any equipment which has complete user functionality when not connected to the MES, and to which connection is necessary for the MES to offer additional functionality

Installable Equipment (IE): equipment which is intended to be fitted to a vehicle

An IE may consist of one or several interconnected modules. NOTE:

integral antenna: antenna designed for permanent connection to the equipment and considered part of the enclosure port

Internally Mounted Equipment (IME): IE modules which are not defined as EME

multimode MES: equipment that accommodates radio stations of different radio systems

occupied bandwidth: See ITU-R Radio Regulations [4], part A, chapter 1, Terminology RR 147.

Portable Equipment (PE): radio equipment intended for portable use and powered by integral batteries or battery

NOTE 1: A PE would normally consist of a single module, but may consist of several interconnected modules.

NOTE 2: More than one of the equipment classifications can apply to certain equipment, as described in clause 5.4, dependent upon the manufacturer's declaration of normal intended use.

transmission disabled state: state of an MES when it is not authorized to transmit by the Network Control Facilities (NCF)

Symbols 3.2

For the purposes of the present document, the following symbols apply: REVIEW

minimum power required to establish a communication link Pmin

ETSI EN 301 489-20 V2.2.1 (2021-11) Abbreviations .iteh.ai/catalog/standards/sist/64c7740a-03ba-4439-88e0-3.3

77f9532cc9a0/etsi-en-301-489-20-v2-2-1-2021-11 For the purposes of the present document, the following abbreviations apply:

AC	Alternating Current
AES	Aircraft Earth Stations
BER	Bit Error Ratio
DC	Direct Current
EFTA	European Free Trade Association
EMC	ElectroMagnetic Compatibility
EME	Externally Mounted Equipment
EUT	Equipment Under Test
F-MES	Fixed MES
IE	Installable Equipment
IME	Internally Mounted Equipment
LBRDC	Low Bit Rate Data Communications
LEO	Low Earth Orbit
LMES	Land Mobile Earth Stations
MES	Mobile Earth Stations
MMES	Maritime Mobile Earth Stations
MSS	Mobile Satellite Service
NCF	Network Control Facilities
PE	Portable Equipment
PEP	Peak Envelope Power
P-MES	Portable MES
QTMA	Quality of Transmission Measurement Apparatus
RF	Radio Frequency
S-PCN	Satellite Personal Communications Networks
V-MES	Vehicle mounted MES

4 Test conditions

4.1 General

For the purposes of the present document, the test conditions of ETSI EN 301 489-1 [1], clause 4, shall apply with the following additions. Further product related test conditions for MES are specified in the present document.

11

For MES with ancillary equipment and/or various ports, the selection of test configurations shall be determined. The assessment shall include sufficient representative configurations of the MES to adequately exercise the equipment. These configurations shall be recorded in the test report.

In clauses 4.2 and 4.3, the Equipment Under Test (EUT) is the MES with the selected configurations of ancillary equipment.

The EUT operational frequencies used during the test shall be recorded in the test report.

For testing, any physically separated voltage converter from the MES, shall form part of the EUT.

Where radio equipment is provided with an integral antenna, it shall be tested with the antenna fitted in a manner representative of intended use.

4.2 Arrangements for test signals

4.2.0 General **iTeh STANDARD PREVIEW**

The provisions of ETSI EN 301 489-1 [1], clause 4.2 shall apply with the following additions.

In order to measure the system emissions and electromagnetic immunity under operational conditions, the following arrangements shall be provided: ETSI EN 301 489-20 V2.2.1 (2021-11)

- a) a Drive Equipment to put the MES terminal in its normal operating mode, and providing the MES with a receive signal to emulate the operational conditions of reception. This equipment shall control the EUT, when it is capable of transmission, so that it switches between the transmission disabled, carrier-on and carrier-off states. This Equipment may also be used to achieve loop back mode operation;
- b) a Quality of Transmission Measurement Apparatus (QTMA).

EXAMPLE: The quality of transmission may concern:

- the audio signal;
- the BER;
- the message throughput;
- the continuity of the communication link; or
- a combination of them.

For the immunity tests of the EUT, a communications link shall be established between the EUT and the testing system. The EUT shall be placed in the normal operating mode.

4.2.1 Arrangements for test signals at the input of transmitters

The provisions of ETSI EN 301 489-1 [1], clause 4.2.1 shall apply.