



**Universal Mobile Telecommunications System (UMTS);
LTE;
5G;
Non-Access-Stratum (NAS)
protocol for Evolved Packet System (EPS);
Stage 3
(3GPP TS 24.301 version 15.7.0 Release 15)**



ReferenceRTS/TSGC-0124301vf70

Keywords

5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	19
1 Scope	20
2 References	20
3 Definitions and abbreviations.....	23
3.1 Definitions	23
3.2 Abbreviations	29
4 General	30
4.1 Overview	30
4.2 Linkage between the protocols for EPS mobility management and EPS session management	31
4.2.A Handling of NAS signalling low priority indication	31
4.3 UE mode of operation	32
4.3.1 General.....	32
4.3.2 Change of UE mode of operation	33
4.3.2.1 General.....	33
4.3.2.2 Change of UE's usage setting.....	35
4.3.2.3 Change of voice domain preference for E-UTRAN.....	36
4.3.2.4 Change or determination of IMS registration status.....	37
4.3.2.5 Change of configuration regarding the use of SMS.....	39
4.4 NAS security	40
4.4.1 General.....	40
4.4.2 Handling of EPS security contexts.....	40
4.4.2.1 General.....	40
4.4.2.2 Establishment of a mapped EPS security context during intersystem handover	41
4.4.2.3 Establishment of secure exchange of NAS messages	42
4.4.2.4 Change of security keys	44
4.4.2.5 Derivation of keys at CS to PS SRVCC handover from A/Gb mode to S1 mode or from Iu mode to S1 mode	44
4.4.3 Handling of NAS COUNT and NAS sequence number	45
4.4.3.1 General	45
4.4.3.2 Replay protection	46
4.4.3.3 Integrity protection and verification.....	46
4.4.3.4 Ciphering and deciphering.....	46
4.4.3.5 NAS COUNT wrap around	47
4.4.4 Integrity protection of NAS signalling messages.....	47
4.4.4.1 General	47
4.4.4.2 Integrity checking of NAS signalling messages in the UE	48
4.4.4.3 Integrity checking of NAS signalling messages in the MME	48
4.4.5 Ciphering of NAS signalling messages	50
4.5 Disabling and re-enabling of UE's E-UTRA capability	51
4.6 Applicability of procedures	53
4.6.1 Relay nodes.....	53
4.7 EPS mobility management and EPS session management in NB-S1 mode	53
4.8 EPS mobility management and EPS session management in WB-S1 mode for IoT.....	53
4.9 Disabling and re-enabling of UE's NB-IoT capability	54
5 Elementary procedures for EPS mobility management.....	55
5.1 Overview	55
5.1.1 General.....	55
5.1.2 Types of EMM procedures	55
5.1.3 EMM sublayer states	56
5.1.3.1 General.....	56

5.1.3.2	EMM sublayer states in the UE.....	56
5.1.3.2.1	General	56
5.1.3.2.2	Main states.....	56
5.1.3.2.2.1	EMM-NULL	56
5.1.3.2.2.2	EMM-DEREGISTERED.....	57
5.1.3.2.2.3	EMM-REGISTERED-INITIATED	57
5.1.3.2.2.4	EMM-REGISTERED	57
5.1.3.2.2.5	EMM-DEREGISTERED-INITIATED.....	57
5.1.3.2.2.6	EMM-TRACKING-AREA-UPDATING-INITIATED	57
5.1.3.2.2.7	EMM-SERVICE-REQUEST-INITIATED.....	57
5.1.3.2.3	Substates of state EMM-DEREGISTERED	58
5.1.3.2.3.1	General.....	58
5.1.3.2.3.2	EMM-DEREGISTERED.NORMAL-SERVICE	58
5.1.3.2.3.3	EMM-DEREGISTERED.LIMITED-SERVICE.....	58
5.1.3.2.3.4	EMM-DEREGISTERED.ATTEMPTING-TO-ATTACH.....	59
5.1.3.2.3.5	EMM-DEREGISTERED.PLMN-SEARCH.....	59
5.1.3.2.3.6	EMM-DEREGISTERED.NO-IMSI	59
5.1.3.2.3.7	EMM-DEREGISTERED.ATTACH-NEEDED.....	59
5.1.3.2.3.8	EMM-DEREGISTERED.NO-CELL-AVAILABLE	59
5.1.3.2.3.9	EMM-DEREGISTERED.eCALL-INACTIVE.....	59
5.1.3.2.4	Substates of state EMM-REGISTERED	59
5.1.3.2.4.1	General.....	59
5.1.3.2.4.2	EMM-REGISTERED.NORMAL-SERVICE	59
5.1.3.2.4.3	EMM-REGISTERED.ATTEMPTING-TO-UPDATE	59
5.1.3.2.4.4	EMM-REGISTERED.LIMITED-SERVICE	60
5.1.3.2.4.5	EMM-REGISTERED.PLMN-SEARCH	60
5.1.3.2.4.6	EMM-REGISTERED.UPDATE-NEEDED	60
5.1.3.2.4.7	EMM-REGISTERED.NO-CELL-AVAILABLE.....	60
5.1.3.2.4.8	EMM-REGISTERED.ATTEMPTING-TO-UPDATE-MM.....	60
5.1.3.2.4.9	EMM-REGISTERED.IMSI-DETACH-INITIATED	60
5.1.3.3	EPS update status	60
5.1.3.4	EMM sublayer states in the MME	61
5.1.3.4.1	EMM-DEREGISTERED.....	61
5.1.3.4.2	EMM-COMMON-PROCEDURE-INITIATED.....	61
5.1.3.4.3	EMM-REGISTERED.....	61
5.1.3.4.4	EMM-DEREGISTERED-INITIATED	61
5.1.4	Coordination between EMM and GMM.....	62
5.1.5	Coordination between EMM and MM.....	63
5.2	Behaviour of the UE in state EMM-DEREGISTERED and state EMM-REGISTERED	63
5.2.1	General.....	63
5.2.2	UE behaviour in state EMM-DEREGISTERED	63
5.2.2.1	General	63
5.2.2.2	Primary substate selection.....	64
5.2.2.2.1	Selection of the substate after power on.....	64
5.2.2.3	Detailed description of UE behaviour in state EMM-DEREGISTERED	64
5.2.2.3.1	NORMAL-SERVICE.....	64
5.2.2.3.2	LIMITED-SERVICE.....	64
5.2.2.3.3	ATTEMPTING-TO-ATTACH	64
5.2.2.3.4	PLMN-SEARCH.....	65
5.2.2.3.5	NO-IMSI	65
5.2.2.3.6	ATTACH-NEEDED.....	65
5.2.2.3.7	NO-CELL-AVAILABLE	65
5.2.2.3.8	eCALL-INACTIVE.....	65
5.2.2.4	Substate when back to state EMM-DEREGISTERED from another EMM state	66
5.2.3	UE behaviour in state EMM-REGISTERED.....	66
5.2.3.1	General	66
5.2.3.2	Detailed description of UE behaviour in state EMM-REGISTERED.....	66
5.2.3.2.1	NORMAL-SERVICE.....	66
5.2.3.2.2	ATTEMPTING-TO-UPDATE.....	67
5.2.3.2.3	LIMITED-SERVICE.....	67
5.2.3.2.4	PLMN-SEARCH.....	68
5.2.3.2.5	UPDATE-NEEDED	68

5.2.3.2.6	NO-CELL-AVAILABLE	68
5.2.3.2.7	ATTEMPTING-TO-UPDATE-MM	68
5.2.3.2.8	IMSI-DETACH-INITIATED	68
5.3	General on elementary EMM procedures	69
5.3.1	EMM modes and NAS signalling connection	69
5.3.1.1	Establishment of the NAS signalling connection	69
5.3.1.2	Release of the NAS signalling connection	70
5.3.1.2.1	General	70
5.3.1.2.2	UE is using EPS services with control plane CIoT EPS optimization	72
5.3.1.3	Suspend and resume of the NAS signalling connection	72
5.3.2	Lists of forbidden tracking areas	74
5.3.3	List of forbidden PLMNs for attach in S101 mode	74
5.3.3a	Forbidden PLMNs for EPS services	74
5.3.4	Equivalent PLMNs list	74
5.3.5	Handling of the periodic tracking area update timer and mobile reachable timer (S1 mode only)	74
5.3.6	Handling of timer T3402	76
5.3.7	Handling of the Local Emergency Numbers List and the Extended Local Emergency Numbers List	76
5.3.7a	Specific requirements for UE configured to use timer T3245	78
5.3.7b	Specific requirements for UE when receiving non-integrity protected reject messages	78
5.3.8	Abnormal cases in the UE	80
5.3.9	Handling of NAS level mobility management congestion control	81
5.3.9A	Handling of congestion control for transport of user data via the control plane	82
5.3.10	Access class control	82
5.3.11	Power saving mode	82
5.3.12	Extended idle-mode DRX cycle	83
5.3.13	Interaction between power saving mode and extended idle mode DRX cycle	84
5.3.14	Dedicated core network	84
5.3.15	CIoT EPS optimizations	84
5.3.16	Restriction on use of enhanced coverage	86
5.3.17	Service Gap Control	86
5.4	EMM common procedures	87
5.4.1	GUTI reallocation procedure	87
5.4.1.1	General	87
5.4.1.2	GUTI reallocation initiation by the network	88
5.4.1.3	GUTI reallocation completion by the UE	88
5.4.1.4	GUTI reallocation completion by the network	88
5.4.1.5	Abnormal cases in the UE	88
5.4.1.6	Abnormal cases on the network side	88
5.4.2	Authentication procedure	90
5.4.2.1	General	90
5.4.2.2	Authentication initiation by the network	90
5.4.2.3	Authentication response by the UE	91
5.4.2.4	Authentication completion by the network	92
5.4.2.5	Authentication not accepted by the network	92
5.4.2.6	Authentication not accepted by the UE	93
5.4.2.7	Abnormal cases	93
5.4.3	Security mode control procedure	97
5.4.3.1	General	97
5.4.3.2	NAS security mode control initiation by the network	98
5.4.3.3	NAS security mode command accepted by the UE	99
5.4.3.4	NAS security mode control completion by the network	101
5.4.3.5	NAS security mode command not accepted by the UE	101
5.4.3.6	Abnormal cases in the UE	101
5.4.3.7	Abnormal cases on the network side	101
5.4.4	Identification procedure	102
5.4.4.1	General	102
5.4.4.2	Identification initiation by the network	102
5.4.4.3	Identification response by the UE	103
5.4.4.4	Identification completion by the network	103
5.4.4.5	Abnormal cases in the UE	103
5.4.4.6	Abnormal cases on the network side	103
5.4.5	EMM information procedure	104

5.4.5.1	General	104
5.4.5.2	EMM information procedure initiation by the network	104
5.4.5.3	EMM information procedure in the UE	105
5.4.5.4	Abnormal cases on the network side	105
5.5	EMM specific procedures	105
5.5.1	Attach procedure	105
5.5.1.1	General	105
5.5.1.2	Attach procedure for EPS services	106
5.5.1.2.1	General	106
5.5.1.2.2	Attach procedure initiation	107
5.5.1.2.3	EMM common procedure initiation	110
5.5.1.2.4	Attach accepted by the network	110
5.5.1.2.4A	Attach successful for EPS services and not accepted for SMS services	115
5.5.1.2.5	Attach not accepted by the network	116
5.5.1.2.5A	Attach for emergency bearer services not accepted by the network	120
5.5.1.2.5B	Attach for initiating a PDN connection for emergency bearer services not accepted by the network	122
5.5.1.2.6	Abnormal cases in the UE	122
5.5.1.2.6A	Abnormal cases in the UE, SMS services not accepted	126
5.5.1.2.7	Abnormal cases on the network side	126
5.5.1.3	Combined attach procedure for EPS services and non-EPS services (S1 mode only)	128
5.5.1.3.1	General	128
5.5.1.3.2	Combined attach procedure initiation	128
5.5.1.3.3	EMM common procedure initiation	128
5.5.1.3.4	Combined attach accepted by the network	128
5.5.1.3.4.1	General	128
5.5.1.3.4.2	Combined attach successful	128
5.5.1.3.4.3	Combined attach successful for EPS services only	130
5.5.1.3.5	Combined attach not accepted by the network	131
5.5.1.3.6	Abnormal cases in the UE	135
5.5.1.3.7	Abnormal cases on the network side	136
5.5.2	Detach procedure	136
5.5.2.1	General	136
5.5.2.2	UE initiated detach procedure	137
5.5.2.2.1	UE initiated detach procedure initiation	137
5.5.2.2.2	UE initiated detach procedure completion for EPS services only	138
5.5.2.2.3	UE initiated combined detach procedure completion	138
5.5.2.2.4	Abnormal cases in the UE	139
5.5.2.2.5	Abnormal cases on the network side	141
5.5.2.3	Network initiated detach procedure	141
5.5.2.3.1	Network initiated detach procedure initiation	141
5.5.2.3.2	Network initiated detach procedure completion by the UE	142
5.5.2.3.3	Network initiated detach procedure completion by the network	146
5.5.2.3.4	Abnormal cases in the UE	146
5.5.2.3.5	Abnormal cases on the network side	146
5.5.3	Tracking area updating procedure (S1 mode only)	148
5.5.3.1	General	148
5.5.3.2	Normal and periodic tracking area updating procedure	149
5.5.3.2.1	General	149
5.5.3.2.2	Normal and periodic tracking area updating procedure initiation	149
5.5.3.2.3	EMM common procedure initiation	154
5.5.3.2.4	Normal and periodic tracking area updating procedure accepted by the network	155
5.5.3.2.4A	Tracking area updating successful for EPS services and not accepted for SMS services	163
5.5.3.2.5	Normal and periodic tracking area updating procedure not accepted by the network	164
5.5.3.2.5A	Tracking area updating procedure for initiating a PDN connection for emergency bearer services not accepted by the network	170
5.5.3.2.6	Abnormal cases in the UE	170
5.5.3.2.6A	Abnormal cases in the UE, SMS services not accepted	176
5.5.3.2.7	Abnormal cases on the network side	176
5.5.3.3	Combined tracking area updating procedure	177
5.5.3.3.1	General	177
5.5.3.3.2	Combined tracking area updating procedure initiation	178

5.5.3.3.3	EMM common procedure initiation	180
5.5.3.3.4	Combined tracking area updating procedure accepted by the network	180
5.5.3.3.4.1	General.....	180
5.5.3.3.4.2	Combined tracking area updating successful	180
5.5.3.3.4.3	Combined tracking area updating successful for EPS services only.....	181
5.5.3.3.5	Combined tracking area updating procedure not accepted by the network	182
5.5.3.3.6	Abnormal cases in the UE	189
5.5.3.3.7	Abnormal cases on the network side	190
5.5.4	eCall inactivity procedure.....	190
5.5.5	Tracking area update request message (for N1 mode only).....	190
5.6	EMM connection management procedures (S1 mode only)	191
5.6.1	Service request procedure.....	191
5.6.1.1	General	191
5.6.1.2	Service request procedure initiation.....	195
5.6.1.2.1	UE is not using EPS services with control plane CIoT EPS optimization.....	195
5.6.1.2.2	UE is using EPS services with control plane CIoT EPS optimization.....	195
5.6.1.3	EMM common procedure initiation.....	196
5.6.1.4	Service request procedure accepted by the network.....	196
5.6.1.4.1	UE is not using EPS services with control plane CIoT EPS optimization.....	196
5.6.1.4.2	UE is using EPS services with control plane CIoT EPS optimization.....	198
5.6.1.5	Service request procedure not accepted by the network.....	202
5.6.1.5A	Service request procedure for initiating a PDN connection for emergency bearer services not accepted by the network.....	209
5.6.1.6	Abnormal cases in the UE.....	210
5.6.1.7	Abnormal cases on the network side	217
5.6.2	Paging procedure	218
5.6.2.1	General	218
5.6.2.2	Paging for EPS services	218
5.6.2.2.1	Paging for EPS services through E-UTRAN using S-TMSI	218
5.6.2.2.1.1	General	218
5.6.2.2.1.2	Abnormal cases on the network side	219
5.6.2.2.2	Paging for EPS services through E-UTRAN using IMSI.....	220
5.6.2.3	Paging for CS fallback to A/Gb or Iu mode.....	221
5.6.2.3.1	General	221
5.6.2.3.2	Abnormal cases in the UE	221
5.6.2.3.3	Abnormal cases on the network side	221
5.6.2.4	Paging for SMS	222
5.6.3	Transport of NAS messages procedure.....	222
5.6.3.1	General	222
5.6.3.2	UE initiated transport of NAS messages.....	223
5.6.3.3	Network initiated transport of NAS messages	223
5.6.3.4	Abnormal cases in the UE.....	223
5.6.3.5	Abnormal cases on the network side.....	223
5.6.4	Generic transport of NAS messages procedure	223
5.6.4.1	General	223
5.6.4.2	UE initiated generic transport of NAS messages	224
5.6.4.3	Network initiated transport of NAS messages	224
5.6.4.4	Abnormal cases in the UE.....	224
5.6.4.5	Abnormal cases on the network side.....	224
5.7	Reception of an EMM STATUS message by an EMM entity	225
6	Elementary procedures for EPS session management.....	225
6.1	Overview	225
6.1.1	General.....	225
6.1.2	Types of ESM procedures.....	226
6.1.3	ESM sublayer states.....	227
6.1.3.1	General	227
6.1.3.2	ESM sublayer states in the UE	227
6.1.3.2.1	BEARER CONTEXT INACTIVE	227
6.1.3.2.2	BEARER CONTEXT ACTIVE	227
6.1.3.2.3	PROCEDURE TRANSACTION INACTIVE.....	227
6.1.3.2.4	PROCEDURE TRANSACTION PENDING	228

6.1.3.3	ESM sublayer states in the MME.....	228
6.1.3.3.1	BEARER CONTEXT INACTIVE	228
6.1.3.3.2	BEARER CONTEXT ACTIVE PENDING	228
6.1.3.3.3	BEARER CONTEXT ACTIVE	228
6.1.3.3.4	BEARER CONTEXT INACTIVE PENDING.....	228
6.1.3.3.5	BEARER CONTEXT MODIFY PENDING.....	228
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE.....	229
6.1.3.3.7	PROCEDURE TRANSACTION PENDING	229
6.1.4	Coordination between ESM and SM	229
6.1.4A	Coordination between ESM and 5GSM	230
6.1.5	Coordination between ESM and EMM for supporting ISR.....	230
6.2	IP address allocation.....	231
6.2.1	General.....	231
6.2.2	IP address allocation via NAS signalling.....	231
6.2A	IP header compression.....	233
6.3	General on elementary ESM procedures	233
6.3.1	Services provided by lower layers	233
6.3.2	Principles of address handling for ESM procedures	233
6.3.3	Abnormal cases in the UE	236
6.3.4	Abnormal cases in the network.....	236
6.3.5	Handling of APN based congestion control.....	237
6.3.5A	Handling of group specific session management congestion control	237
6.3.6	Handling of network rejection not due to APN based congestion control.....	237
6.3.7	Handling of WLAN offload control	238
6.3.8	Handling of serving PLMN rate control	238
6.3.9	Handling of APN rate control	238
6.3.10	Handling of 3GPP PS data off	239
6.3.11	Handling of Reliable Data Service	240
6.4	Network initiated ESM procedures	240
6.4.1	Default EPS bearer context activation procedure	240
6.4.1.1	General	240
6.4.1.2	Default EPS bearer context activation initiated by the network.....	240
6.4.1.3	Default EPS bearer context activation accepted by the UE.....	241
6.4.1.4	Default EPS bearer context activation not accepted by the UE.....	242
6.4.1.5	Abnormal cases in the UE.....	242
6.4.1.6	Abnormal cases on the network side.....	242
6.4.2	Dedicated EPS bearer context activation procedure	243
6.4.2.1	General	243
6.4.2.2	Dedicated EPS bearer context activation initiated by the network.....	243
6.4.2.3	Dedicated EPS bearer context activation accepted by the UE	244
6.4.2.4	Dedicated EPS bearer context activation not accepted by the UE	245
6.4.2.5	Abnormal cases in the UE.....	246
6.4.2.6	Abnormal cases on the network side.....	246
6.4.3	EPS bearer context modification procedure.....	247
6.4.3.1	General	247
6.4.3.2	EPS bearer context modification initiated by the network	247
6.4.3.3	EPS bearer context modification accepted by the UE	248
6.4.3.4	EPS bearer context modification not accepted by the UE.....	249
6.4.3.5	Abnormal cases in the UE.....	251
6.4.3.6	Abnormal cases on the network side.....	251
6.4.4	EPS bearer context deactivation procedure.....	251
6.4.4.1	General	251
6.4.4.2	EPS bearer context deactivation initiated by the network.....	252
6.4.4.3	EPS bearer context deactivation accepted by the UE.....	253
6.4.4.4	Abnormal cases in the UE.....	255
6.4.4.5	Abnormal cases on the network side.....	255
6.4.4.6	Local EPS bearer context deactivation without NAS signalling.....	255
6.5	UE requested ESM procedures.....	257
6.5.0	General.....	257
6.5.1	UE requested PDN connectivity procedure	257
6.5.1.1	General	257
6.5.1.2	UE requested PDN connectivity procedure initiation	258

6.5.1.3	UE requested PDN connectivity procedure accepted by the network	259
6.5.1.4	UE requested PDN connectivity procedure not accepted by the network.....	261
6.5.1.4.1	General	261
6.5.1.4.2	Handling of network rejection due to ESM cause #26	262
6.5.1.4.3	Handling of network rejection due to ESM cause other than ESM cause #26	265
6.5.1.4A	Handling the maximum number of active EPS bearer contexts	270
6.5.1.4B	Void.....	270
6.5.1.5	Abnormal cases in the UE	270
6.5.1.6	Abnormal cases on the network side	271
6.5.1.7	Handling PDN connectivity request for UE configured for dual priority	272
6.5.2	UE requested PDN disconnect procedure	272
6.5.2.1	General	272
6.5.2.2	UE requested PDN disconnection procedure initiation	273
6.5.2.3	UE requested PDN disconnection procedure accepted by the network.....	273
6.5.2.4	UE requested PDN disconnection procedure not accepted by the network	273
6.5.2.5	Abnormal cases in the UE	274
6.5.2.6	Abnormal cases on the network side	274
6.5.3	UE requested bearer resource allocation procedure	274
6.5.3.1	General	274
6.5.3.2	UE requested bearer resource allocation procedure initiation	275
6.5.3.3	UE requested bearer resource allocation procedure accepted by the network	275
6.5.3.4	UE requested bearer resource allocation procedure not accepted by the network	276
6.5.3.4.1	General	276
6.5.3.4.2	Handling of network rejection due to ESM cause #26	278
6.5.3.4.3	Handling of network rejection due to ESM cause other than ESM cause #26	279
6.5.3.4A	Handling the maximum number of active EPS bearer contexts	281
6.5.3.5	Abnormal cases in the UE	281
6.5.3.6	Abnormal cases on the network side	281
6.5.4	UE requested bearer resource modification procedure	282
6.5.4.1	General	282
6.5.4.2	UE requested bearer resource modification procedure initiation	282
6.5.4.3	UE requested bearer resource modification procedure accepted by the network	284
6.5.4.4	UE requested bearer resource modification procedure not accepted by the network	284
6.5.4.4.1	General	284
6.5.4.4.2	Handling of network rejection due to ESM cause #26	287
6.5.4.4.3	Handling of network rejection due to ESM cause other than ESM cause #26	288
6.5.4.5	Abnormal cases in the UE	290
6.5.4.6	Abnormal cases on the network side	290
6.5.5	Handling session management request for UE configured for dual priority	291
6.6	Miscellaneous procedures	292
6.6.1	Exchange of protocol configuration options	292
6.6.1.1	General	292
6.6.1.2	ESM information request procedure	292
6.6.1.2.1	General	292
6.6.1.2.2	ESM information request initiated by the network	293
6.6.1.2.3	ESM information request completion by the UE	293
6.6.1.2.4	ESM information request completion by the network	293
6.6.1.2.5	Abnormal cases in the UE	293
6.6.1.2.6	Abnormal cases on the network side	293
6.6.1.3	Exchange of protocol configuration options in other messages	293
6.6.2	Notification procedure	294
6.6.2.1	General	294
6.6.2.2	Notification procedure initiation by the network	294
6.6.2.3	Notification procedure in the UE	294
6.6.2.4	Abnormal cases on the network side	294
6.6.3	Remote UE Report procedure	295
6.6.3.1	General	295
6.6.3.2	Remote UE Report initiated by the UE	295
6.6.3.3	Remote UE Report completion by the network	295
6.6.3.4	Remote UE Report completion by the UE	295
6.6.3.5	Abnormal cases in the UE	295
6.6.3.6	Abnormal cases on the network side	296

6.6.4	Transport of user data via the control plane	296
6.6.4.1	General	296
6.6.4.2	UE initiated transport of user data via the control plane	296
6.6.4.3	Network initiated transport of user data via the control plane	297
6.6.4.4	Abnormal cases in the UE	297
6.6.4.5	Abnormal cases on the network side	298
6.7	Reception of an ESM STATUS message by an ESM entity	298
7	Handling of unknown, unforeseen, and erroneous protocol data	299
7.1	General	299
7.2	Message too short	299
7.3	Unknown or unforeseen procedure transaction identity or EPS bearer identity	299
7.3.1	Procedure transaction identity	299
7.3.2	EPS bearer identity	301
7.4	Unknown or unforeseen message type	302
7.5	Non-semantical mandatory information element errors	303
7.5.1	Common procedures	303
7.5.2	EPS mobility management	303
7.5.3	EPS session management	303
7.6	Unknown and unforeseen IEs in the non-imperative message part	304
7.6.1	IEs unknown in the message	304
7.6.2	Out of sequence IEs	304
7.6.3	Repeated IEs	304
7.7	Non-imperative message part errors	304
7.7.1	Syntactically incorrect optional IEs	304
7.7.2	Conditional IE errors	305
7.8	Messages with semantically incorrect contents	305
8	Message functional definitions and contents	305
8.1	Overview	305
8.2	EPS mobility management messages	306
8.2.1	Attach accept	306
8.2.1.1	Message definition	306
8.2.1.2	GUTI	308
8.2.1.3	Location area identification	308
8.2.1.4	MS identity	308
8.2.1.5	EMM cause	308
8.2.1.6	T3402 value	308
8.2.1.7	T3423 value	308
8.2.1.8	Equivalent PLMNs	308
8.2.1.9	Emergency number list	308
8.2.1.9A	Extended emergency number list	308
8.2.1.10	EPS network feature support	308
8.2.1.11	Additional update result	308
8.2.1.12	T3412 extended value	309
8.2.1.13	T3324 value	309
8.2.1.14	Extended DRX parameters	309
8.2.1.15	DCN-ID	309
8.2.1.16	SMS services status	309
8.2.1.17	Non-3GPP NW provided policies	309
8.2.1.18	T3448 value	309
8.2.1.19	Network policy	309
8.2.1.20	T3447 value	309
8.2.1.21	Ciphering key data	309
8.2.2	Attach complete	309
8.2.3	Attach reject	310
8.2.3.1	Message definition	310
8.2.3.2	ESM message container	310
8.2.3.3	T3346 value	310
8.2.3.4	T3402 value	311
8.2.3.5	Extended EMM cause	311
8.2.4	Attach request	311

8.2.4.1	Message definition	311
8.2.4.2	Old P-TMSI signature	313
8.2.4.3	Additional GUTI	313
8.2.4.4	Last visited registered TAI	313
8.2.4.5	DRX parameter	313
8.2.4.6	MS network capability	313
8.2.4.7	Old location area identification	313
8.2.4.8	TMSI status	313
8.2.4.9	Mobile station classmark 2	313
8.2.4.10	Mobile station classmark 3	313
8.2.4.11	Supported Codecs	313
8.2.4.12	Additional update type	313
8.2.4.13	Voice domain preference and UE's usage setting	313
8.2.4.14	Device properties	314
8.2.4.15	Old GUTI type	314
8.2.4.16	MS network feature support	314
8.2.4.17	TMSI based NRI container	314
8.2.4.18	T3324 value	314
8.2.4.19	T3412 extended value	314
8.2.4.20	Extended DRX parameters	314
8.2.4.21	UE additional security capability	314
8.2.4.22	UE status	314
8.2.4.23	Additional information requested	314
8.2.5	Authentication failure	314
8.2.5.1	Message definition	314
8.2.5.2	Authentication failure parameter	315
8.2.6	Authentication reject	315
8.2.7	Authentication request	315
8.2.8	Authentication response	316
8.2.9	CS service notification	316
8.2.9.1	Message definition	316
8.2.9.2	CLI	317
8.2.9.3	SS Code	317
8.2.9.4	LCS indicator	317
8.2.9.5	LCS client identity	317
8.2.10	Detach accept	317
8.2.10.1	Detach accept (UE originating detach)	317
8.2.10.2	Detach accept (UE terminated detach)	318
8.2.11	Detach request	318
8.2.11.1	Detach request (UE originating detach)	318
8.2.11.2	Detach request (UE terminated detach)	319
8.2.11.2.1	Message definition	319
8.2.11.2.2	EMM cause	319
8.2.12	Downlink NAS Transport	319
8.2.13	EMM information	319
8.2.13.1	Message definition	319
8.2.13.2	Full name for network	320
8.2.13.3	Short name for network	320
8.2.13.4	Local time zone	320
8.2.13.5	Universal time and local time zone	320
8.2.13.6	Network daylight saving time	321
8.2.14	EMM status	321
8.2.15	Extended service request	321
8.2.15.1	Message definition	321
8.2.15.2	CSFB response	322
8.2.15.3	EPS bearer context status	322
8.2.15.4	Device properties	322
8.2.16	GUTI reallocation command	322
8.2.16.1	Message definition	322
8.2.16.2	TAI list	323
8.2.16.3	DCN-ID	323
8.2.17	GUTI reallocation complete	323

8.2.18	Identity request	323
8.2.19	Identity response	324
8.2.20	Security mode command	324
8.2.20.1	Message definition	324
8.2.20.2	IMEISV request	325
8.2.20.3	Replayed nonce _{UE}	325
8.2.20.4	Nonce _{MME}	325
8.2.20.5	Hash _{MME}	325
8.2.20.6	Replayed UE additional security capability	325
8.2.21	Security mode complete	325
8.2.21.1	Message definition	325
8.2.21.2	IMEISV	326
8.2.21.3	Replayed NAS message container	326
8.2.22	Security mode reject	326
8.2.23	Security protected NAS message	326
8.2.24	Service reject	327
8.2.24.1	Message definition	327
8.2.24.2	T3442 value	327
8.2.24.3	T3346 value	327
8.2.24.4	T3448 value	327
8.2.25	Service request	328
8.2.26	Tracking area update accept	328
8.2.26.1	Message definition	328
8.2.26.2	T3412 value	330
8.2.26.3	GUTI	330
8.2.26.4	TAI list	330
8.2.26.5	EPS bearer context status	330
8.2.26.6	Location area identification	330
8.2.26.7	MS identity	330
8.2.26.8	EMM cause	330
8.2.26.9	T3402 value	330
8.2.26.10	T3423 value	330
8.2.26.11	Equivalent PLMNs	330
8.2.26.12	Emergency number list	330
8.2.26.12A	Extended emergency number list	330
8.2.26.13	EPS network feature support	331
8.2.26.14	Additional update result	331
8.2.26.15	T3412 extended value	331
8.2.26.16	T3324 value	331
8.2.26.17	Extended DRX parameters	331
8.2.26.18	DCN-ID	331
8.2.26.19	SMS services status	331
8.2.26.20	Non-3GPP NW provided policies	331
8.2.26.21	T3448 value	331
8.2.26.22	Network policy	332
8.2.26.23	T3447 value	332
8.2.26.24	Ciphering key data	332
8.2.27	Tracking area update complete	332
8.2.28	Tracking area update reject	332
8.2.28.1	Message definition	332
8.2.28.2	T3346 value	333
8.2.28.3	Extended EMM cause	333
8.2.29	Tracking area update request	333
8.2.29.1	Message definition	333
8.2.29.2	Non-current native NAS key set identifier	336
8.2.29.3	GPRS ciphering key sequence number	336
8.2.29.4	Old P-TMSI signature	336
8.2.29.5	Additional GUTI	336
8.2.29.6	Nonce _{UE}	336
8.2.29.7	UE network capability	336
8.2.29.8	Last visited registered TAI	336
8.2.29.9	DRX parameter	336